Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Abb Automation

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Abb Automation Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Abb Automation Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
R 25 %7 - 189hz 25kvar	
R 50 %7 - 189hz 50kvar	
R 100 %7 - 189hz 100kvar	
1sda038302r0001	Zub. f. Leistungsschalter E1-E6 Einschaltauslöser
1sda038292r0001	A-Ausl. E1-E6 220-240V AC/DC Zub. f. Leistungsschalter E1-E6
1sda038312r0001	U-Ausl.E1-E6 220-230V AC/DC Zub. f. Leistungsschalter E1-E6
Rpba-01	Profibus Adapter Module
Rdcu-12c	Control Unit
Acs800-104-0580+c126+e250	Driver Module
Gae75-10	24VDC
Cas-22m	24VDC
Raio-01	Analogue I/O Extension Module
Rdio-01 /	Digital I/O Extension Module
1SDA067428R0001	XT1N 160 TMD 160-1600 4P FF IN = 100% Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	160 firmly Front connections 4-pin TMD 10xIth R160 InN = 100% ZNR: 85362090 Origin: IT Weight: 4,200 KG; Gross weight: 4,200 KG
1SDA067424R0001	XT1N 160 TMD 100-1000 4P FF Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N 160 firmly Front connections 4-pin TMD 10xIth R100 ZNR: 85362090 Origin: IT Weight: 2.800 KG; Gross weight: 2.800 KG
1SDA068059R0001	XT3N 250 TMD 250-2500 3P FF Compact circuit breaker Tmax XT3 with front. Connections With the following configuration: XT3 N 250 firmly Front connections 3-pin TMD 10xIth R250 ZNR: 85362090 Origin: IT Weight: 6,800 KG; Gross weight: 6,800 KG
1SDA067418R0001	XT1N 160 TMD 160-1600 3P FF Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N 160 firmly Front connections 3-pin TMD 10xIth R160

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	ZNR: 85362090 Origin: IT Weight: 4,400 KG; Gross weight: 4,400 KG
1SDA067417R0001	XT1N 160 TMD 125-1250 3P FF Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N 160 firmly Front connections 3-pin TMD 10xIth R125 ZNR: 85362090 Origin: IT Weight: 6,600 KG; Gross weight: 6,600 KG
TB-B/PG21-PG11/R	EXPANSION / REDUCTION TYPE R AG = PG 21 / IG = PG 11
Typ PFRL 101B	Radial force transducer type PFRL 101B, Nominal force 1 kN, for z. B. Self-aligning ball bearing 2205, D2 = 52 mm, axle journal d = 25mm continuous, without bearings and spacer rings, Net weight 2 kg Order number: 3BSE 002 958 R15 Consists: 1 pc. 3BSE 023 315 R5 PFRL 101B load cell 1kN 2 pcs. 3BSE 023 155 R4 cover with hole D1 = D1 = 33 mm
PFEA111-65 Loadcel card	Cable connector, without cable For connection of the force transducer type PFRL 101 Order number: 3BSC 860 067 R1
V18345.10.1.0.2.2.1.00.1	// TZIDC DIGITAL POSITIONER ABB TYPE: V18345-1010221001 TZIDC digital positioner, intelligent, parameterizable, with display and control panel V18345 - Housing / assembly 10 Housing made of aluminum, painted, for Attachment to linear actuators according to DIN / IEC 534 / NAMUR or on rotary actuators according to VDI / VDE 3845 - control input / 1 control input 4 ... 20 mA, two-wire technology, Communication connection with plug connection for LKS adapter - Explosion protection 0 Without

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Control output / safety position (with 2 single-acting, actuator is blocked Failure of the electrical power supply) - Connections 2 cables: thread 1 / 2-14 NPT, air line: 1 / 4-18 NPT thread - Optional extension with plug-in module 1 plug-in module for analogue feedback, for analog / digital feedback signal range 4 ... 20 mA, two-wire technology - Optional extension with 00 Without mechanical kit for digital feedback - Design (painting / marking) 1 standard Pos. 100: Statistical goods no .: 90328900 / country of origin: DE
3BSE 050 090 R65	Central unit type PFEA 111, for wall mounting, IP 65 Supply voltage: 24 V DC or 230 V AC Signal output: 0 - 10 V or 0 (4) - 20 mA Net weight 2 kg User manual, multilingual, on CD-ROM, Order number: 3BSE 050 090 R65
FEP311.025.A.1.D.1.D4.B.0.A.1.A.0.A.1.A.2.C.	1.B-..H2.....M1 FEP311 Nominal size 025 DN 25 (1 in.) - Lining material A PTFE - Electrode version 1 standard - Measuring electrode material D Hastelloy C-4 (2.4610) - Earthing accessories 1 standard - Process connection D4 flange DIN PN 40 - Process connection material B steel - Certificates 0 measuring tube with PED approval - Calibration A standard accuracy - Temperature range transducer / 1 standard transducer design / -20 ... 60 ° C Ambient temperature range (-4 ... 140 ° F) - Type plate A adhesive label - Signal cable length 0 Without cable - Explosion protection A Without - Degree of protection transmitter / sensor 1 IP 67 (NEMA 4X) / IP 67 (NEMA 4X) - Cable gland A M20 x 1.5 - Power supply 2 24 V AC / DC, 50 Hz - Signal inputs and outputs C HART + 20 mA active + pulses + Contact input / output - Presets / Diagnosis 1 parameters have factory settings / Standard diagnostic functions activated - Construction stand B Construction stand B DN3 - 150 / not PN16, PN40 and ASME CL150 - Housing design H2 two-chamber housing - Language of the documentation M1 German

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Pos. 100: Statistical goods no .: 9026900000 / country of origin: GB
ACS800-U4-0205-5+P901	
3BSE002959R0005	
216DB61 HESG324063R100/J	
NO T19039111- T190039112	CEWE ELITE447 PS:H,CL:0.5S, MOD:NNN CE447H05NNN
RMIO-01 PCB KIT : NO:6220434	
1SVR011700R0000	24 VDC, CC-E/STD
ES2000-9725	Ipn 2000A VA +-15...+-24V Np/Ns:1/5000 Rs25 Ω
CIRCUIT BREAKER DS 201A-C 6/0,03 1-POLE ABB	2CSR255140R1064
A-TRIGGER E1-E6-T8 220-240V AC/DC ABB	1SDA038292R0001
E-TRIGGER E1-E6-T8 220-240V AC/DC ABB	1SDA038302R0001
UNDERVOLTAGE RELEASE 220-230V AC/DC E1-E ABB	1SDA038312R0001
Protection Trip Units and Curves SACE	PR 122/P LSIG power supply auxiliary power supply : 24v dc +/- 20% maximum ripple 5% inrush current@24v -10A for 5ms rated power @ 24v -3W
Protection Trip Units and Curves SACE	PR 122/P LSI power supply auxiliary power supply : 24v dc +/- 20% maximum ripple 5% inrush current@24v -10A for 5ms rated power @ 24v -3W
LMS100.A2.Y0.Y0.A1	- Mounting A2 Switch rod mount up to 350 °F (176.6 °C) max process temperatures. When used with

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	chamber insulation option, 800 °F (426.7 °C) max process temperatures - High Temperature Processes Insulation Y0 Standard, without insulation pad (standard Options gear clamp mounting) - Approvals Y0 General Purpose, (not for hazardous locations) - Electrical Cable Connection A1 Standard, 0.50 in. NPT-Female - Operating Temperature 30 °C - Chamber Insulation No
1SAP250600R0001	
V18345.20.2.0.4.6.1.00.1	TZIDC Digital positioner, intelligent, configurable, with display and control panel V18345 - Housing / assembly 20 aluminum housing, painted, with mechanical position indicator, for attachment to thrust drives according to DIN / IEC 534 / NAMUR or to part-turn actuators VDI / VDE 3845 - Control input / 2 control inputs 4 ... 20 mA, two-wire technology, Communication port with plug-in connection for LKS adapter and FSK module for HART communication - Explosion protection 0 None - Actuating output / safety position (with 4 double-acting, actuator is vented Failure of the electrical power supply) - Connections 6 cables: thread M20 x 1.5, air line: Thread G 1/4 - Optional expansion with plug-in module 1 plug-in module for analogue feedback, for analogue / digital feedback, signal range 4 ... 20 mA, two-wire technology - Optional extension with 00 without mechanical kit for digital return message - Design (painting / marking) 1 standard Pos. 100: Statistical goods no.: 90328100 / country of origin: DE
266GST.F.K.B.N.A.1-.E2..L1.B7	266GST Gauge Pressure Transmitter, Basic Accuracy 0.04% 266GST - Sensor measuring range limits / F 0.4 and 40 kPa (4 and 400 mbar, 1.6 and Overload limit 160 in. H2O) / 1 MPa (10 bar, 145 psi) - Diaphragm material / filling liquid K Hastelloy C-276 / silicone oil - Process connection Material / Type B Stainless steel AISI 316L (1.4404) / 1/2-14 NPT female thread - Gasket Material N None - Body Material / Electrical A Aluminum Alloy (Barrel Type) /

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	1/2-14 Connection NPT - Output 1 HART digital communication and 4 ... 20 mA - Explosion protection E2 ATEX II category 1/2 GD, flameproof Encapsulation Ex d - Integrated digital display (LCD) L1 With integrated LCD display - Fastening accessories / material B7 For horizontal or vertical pipe and Wall mounting /AISI 316 (1.4401) [1] Measuring Range -150 ... 0 inH2O@4C [1] Scale -150 ... 0 inH2O@4C [2] Measuring Range -150 ... 0 inH2O@4C [2] Scale -150 ... 0 inH2O@4C
2TLA020051R5100	7350024480306 ADAM DYN-INFO Security sensor IP69K, M12-5 pin
266HSH.Q.S.B.A.1-.VA...L1..B6....I2	266HSH gauge pressure transmitter, basic accuracy 0.075%, Overload limit up to 90 MPa / 900 bar / 13050 psi 266HSH - Sensor measuring range limits / Q 80 and 8000 kPa (0.8 and 80 bar, 11.6 and Overload Limit / Basic Accuracy 1160 psi) / 21 MPa (210 bar, 3045 psi) / Basic accuracy 0.06% - Diaphragm material / Filling liquid S Stainless steel (AISI 316L SST) / Silicone Oil (NACE) - Process Connection Material / Type B Stainless steel AISI 316L/ 1/2 in. -14 NPT-f (NACE) - Body Material / Electrical A Aluminum Alloy (Barrel Type) / 1/2-14 Connection NPT - Output 1 HART digital communication and 4 ... 20 mA - Ventilation / VA stainless steel AISI 316L (1.4404) Drain valve material (NACE) (wetted) - Integrated digital display (LCD) L1 Integrated LCD display with integrated Keys - Mounting accessories / material B6 For horizontal or vertical mounting on Pipe and Wall / Carbon Steel - Additional identification plate I2 measuring point and certification plate stainless steel, laser printing Pos. 100: Country of origin: IT
CR-M2LS	SERİ NO: 1SVR405651R1100

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
CM11A1	
(27-08-01-05-25) 87 T 550-E / R1214	COUPLING MODULE ETHER NET INTERFACE ON THE STATION BUS 87 T 550-E / R1214
(27-08-01-05-26) 81ET03-E/R1210	INPUT MODULE FOR TEMPERATURE SENSOR 16-FOLD, 81ET03-E/R1210
(27-08-01-05-27) 81EU01-E/R1210	UNIVERSAL INPUT MODULE FOT BINARY ANALOG TRANSMITTER TYPE:81EU01-E/R1210
(Motor Axis 5 Irb 6640) (Old 3hac17484-10)	
V68853 (Elektronik Contrac Ebn 853)	
3hac2493-1	
Motor Axis 4 Irb 6640) (Old 3hac033209-001)	
3gaa062312-Asc	M3AA63B-4
Mba 800 / Mba820xhn1_A00187_D_Xx	
3 Hac 17484 - 6/ 00	
Abb 12	
Sicherung Je 3 Stück	FCF1,FCF2,FCF3 2A
Filterelement For Acid Filter	8018013
Adp-Al34/Fl/90 - Adaptaflex - Flexible Leitungssysteme	
Tzid-C (V18345-2020121001)	
Niin_12f213948 P/N_101c701	
Es2000-9725 / Ipn:2000a / Va:-+15 - +24v / Akim Sensörü	
242383554/X002/031234	
2rca025340a0001	
Feeder Proction Relay	MIF11P 100 ER H10
(Motor Axis 2-3 Irb 6600) (Old	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
3hac15882-2)	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.