



Abo Valves

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Abo Valves Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Abo Valves T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
924 T Dn100	BARE SHAFT
924 T Dn125	INDUCTIVE SENSOR AND HANDLE.
924 T Dn150	BARE SHAFT
924 T Dn200	BARE SHAFT
924 T Dn250	BARE SHAFT
924 T Dn300	BARE SHAFT
924 T Dn350	BARE SHAFT
924 T Dn40	BARE SHAFT
924 T Dn400	BARE SHAFT
924 T Dn500	BARE SHAFT
924 T Dn600	GEARBOX AND INDUCTIVE SENSOR
924 T Dn80	BARE SHAFT

924 U Pn10 Dn700	GEARBOX AND INDUCTIVE SENSOR
924 U Pn10 Dn800	GEARBOX AND INDUCTIVE SENSOR
924b	BUTTERFLY VALVE
SRBE-CA3-YR90-MW-22A-1W-C2M20-EX	DN 300 with pneumatic Actuator complete mounted with double acting actuator incl. Limit swicht Box FESTO PTFE lined flap Flange version (LUG) for installation between flanges according to ASME cl. 150 or EN1092-1 PN10/16 Design: EN 593 Overall length according to EN558-1 basic series 20 / API609 Sealing test according to EN 12 266-1, leak rate A Housing: ductile iron GGG40.3 with 80µm epoxy coating RAL 2002 Disc: Duplex 1.4469, PTFE coated Sleeve: PTFE / silicone elastomer insert Shaft: Duplex 1.4469 Temperature range: -40°C to 200°C Maximum pressure: 10 bar
Gate Valve	GGG40-15 DN 150 PN 16
Dismantling Part	GGG40-15 DN 150 PN 16
Compensator	GGG40-15-EPDM DN 150 PN 16
4M310-08	
5590B	