Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Actaris

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Actaris Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Actaris Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
G40 Dn 50	H3581 Rotary lobe gas meter DELTA Silver Edition no HTB version Nominal size: DN 50 Pressure rating: PN20 Connection: flange according to ANSI 150 Overall length: 171 mm Material: aluminum Gas type: according to DVGW worksheet G260 Reading direction: frontal reading Flow direction: freely selectable ** prepared for 2 immersion sleeves L4 (** please indicate flow direction when equipping with immersion sleeves) Measuring range: 1:20 (max. possible measuring range 1:50 - available for an additional charge) Pulse generator: 2x NF pulse generator + anti-manipulation contact Pulse value: 0.1 cbm Connector: Binder male 2x PR sockets Ermeto EO 6S Operating temperature: -25 ° C to + 55 ° C (according to MID) Paintwork: without
Hf3	G0464 HF pulse tap v. DKZ I = 0.0583 dm3 / imp
-RBE 1732 1"	kit
RBE 1732 1,5"	kit
RBE1732 3/4 "	KIT
RBE1831-1832 DN40	KIT

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
RBE1832 DN50	KIT
RBE4731-4732 DN25	KIT
RBE4731-4732 DN25	KIT
RBE4731-4732 DN50	KIT
Repair kit for gas pressure regulator	Typ RR16-50-54-12N-033 DN50 PN/ANSI 16/5
Repair kit for gas pressure regulato	Typ RR16-50-42-8N-033 DN50 PN/ANSI 16/5
SN: 000038	
Quantity gas meter MZ80 DN 80 PN16	Nominal width: DN 80 Pressure rating: PN16 Connection: intermediate construction Overall length: 120 mm Material: ductile iron Aluminum turbine wheel Type of gas: according to DVGW worksheet G260 Direction of reading: reading from the front Flow direction: freely selectable** Qmax: 250 m^3/h Q min: 10 m^3/h 2x NF pulse generator + anti-tampering contact Pulse value: 1 cbm Connector: Binder male Permanently lubricated bearings: yes Oil pump: without Operating temperature: -30°C to +60°C Painting: KTL coating EC Type Examination Certificate: CE-0085BS5061 No. ** for measurements not subject to legal control **
Turbine wheel gas meter G100 DN 80	Fluxi 2000 Nominal width: DN 80 Pressure rating: PN16 Connection: Flange according to DIN Overall length: 240 mm Material: ductile iron Type of gas: according to DVGW worksheet G260 Direction of reading: reading from the front Flow direction: freely selectable** prepared for 2 immersion sleeves (**please specify flow direction if equipped with immersion sleeves) Measuring range: 1:20 Pulse generator: 2x NF pulse generator + anti-manipulation contact Pulse value: 1.0 cbm/pulse Connector: Binder male

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	2x PR nozzle Ermeto EO 6S Type of lubrication: permanently lubricated (Oil pump available at extra cost) Operating temperature: -25°C to +55°C (according to MID) Painting: water-based paint similar to RAL7035 PTB approval no. DE-10-MI002-PTB001 Revision number: 2 No MID tested ** for measurements subject to legal control **
RBE 1732 DN:1 inç	
RBE 4022 DN:40	
1822 DN:40 PN 16	
1822 DN:50 PN16	
Gas pressure regulator RBE 3212 DN25	H5832 Nominal width: DN 25 Pressure rating: PN5 Connection type: internal thread 1" x 1 1/2" Medium: inert gases according to DVGW G260 Overall length: 130 mm Inlet pressure Pu max.: 5000 mbar Inlet pressure Pu min.: 2000 mbar Outlet pressure Pds: 55 mbar Spring control range: 28-70 mbar Flow rate: ** Nm^3/h SAV upper shutdown: yes Pdso: 100 mbar Leadership range: 70 - 130 SAV lower shutdown: yes Psu: 10 mbar Lead range: 5 - 28 Flow direction: ** Ambient temperature: -30°C to +60°C Paint finish: primed
RBE 1732	
H5950	Gas pressure regulator RBE 4732-D DN80 SAV 8632 Nominal diameter: DN 80 Pressure rating: PN20 Connection type: Flange according to DIN PN25 Medium: inert gases according to DVGW G260 Length: 298 mm Inlet pressure Pu max.: 19.2 bar Inlet pressure Pu min.: ** mbar Output pressure Pds: 3.0 bar

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Spring guide range: 1.5 - 5.5 bar Flow rate: ** Nm^3/h Silencer: no SAV type: 8632 SAV upper cut-off: yes PDSO: 4.6 bar Spring guide range: 3.9 - 4.6 bar SAV lower cutoff: yes Pdsu: 0.90 bar Spring guide range: 0.32 - 1.0 bar Flow direction: left to right Ambient temperature: -30°C to +60°C Paint finish: primed Permissible pressure: 19.2 bar EC type examination certificate: CE-0085CN0360 No.
RR16 DN50-31-8N-033	
RR16 DN50-31-8N-033	
RBE4022 DN80	
DELTA 2050-G65	Totalizator- Flow max. 100 m^3/h – Pressure 60 mbar – DN50 – PN16 – HF – Body for measure N2/H2 – Approvation CEE
Fluxi 2000	Turbine wheel gas meter G160 DN 80 Nominal diameter: DN 80 Pressure level: PN50 Connection: Flange according to ANSI300 Overall length: 240 mm Material: steel Gas type: according to DVGW worksheet G260 Reading direction: frontal reading Flow direction: freely selectable** prepared for 2 immersion sleeves (**when equipped with immersion sleeves, flow direction please specify) Measuring range: 1:20 (max. possible measuring range 1:30 (ND) or 1:50 (HD) available for an additional charge) Pulse generator: 2x LF pulse generator + anti-tamper contact Pulse value: 1 cbm/pulse Connector: Binder male 2x PR nozzles Ermeto EO 6S Type of lubrication: permanently lubricated (Oil pump available at extra cost) Operating temperature: -25°C to +55°C (according to MID) Paint: Water-based paint similar to RAL7035 PTB Approval No. DE-10-MI002-PTB001

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Revision number: 2
G0475	Oil pump for TRZ in conjunction with new device DN50 - DN150 - mounted on the meter -
H3749	Acceptance test certificate B according to EN 10204 DIN 50049-3.1B on strength, Leakage and functional testing (Sent as a PDF via email.)
12N Series + RV-MD Pilot	Connection and Pressure: DN 50, PN 16 (Body Pi max capacity 40 bar) Inlet/Outlet Range: Pi: 4-16 bar / Pout (Set): 100 mbar (Spring range 10-225 mbar) Orifice: 42 mm Serial Number: 9499203001 NOTE: All information on the regulator is as follows: BRAND: Actaris typ:RV-MD DN 1/4 PN 40 Pi min/max 40.0 spring range Wh: 0.4-3.0 DIN-DVGW: 9606E056 Orifice Size: 3.0 Serial No: 9499203001 Setting Point: 0.4 REGULATOR din-dvgw :AN 0420 Pmax 16,0 bar DN 50 PN 16 serial number: 9499203001 REGULATOR device type:12N DN50 Pi min/max 4.0 bar serial number: 9499203001 Pmax 16.0 bar
233-12-5-72 (Ex. 233-12-4-72)	
142-620-00	
Rr1680428h-Dn80-Pn16	
133-5-72	
Dattus-Fm2-Etc-L	GAS FLOW METER
Fluxi2200/Tz	
Rb4731 Dn80	
Rr16-25-31-8h-Ohne Sav	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
155-D	
Rr16-50-31-12n+rv-Md	
Rr1680828hdn80p	
Rbe4731 Dn80	
Rr16-25-31-8h-Sl-Izn.1	
111e300-13	
233-12-5-72	
Rr16-80-42-12n-Sl-Izn1	
Zg-Nr: 39906310	WEAR SET FOR TYPE RBE 1731-1732 DN 25
Rr1680548hdn80pn16	
Rr16-50-42-8n-033	
233-12-5-72 Dn50	
Acd G1.6-Arg	3604700
Rbe 4732 Acc	
Ssv Type 033	
12p-Mm-Sl-Izm.1	
Regulatordn50	
Rr16-80-42-12n	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.