

## Additel

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Additel** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Additel T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">ADT680-25-GP60K-BAR-AM</a>	Digitalmanometer Pressure range: 0 to 4200 bar Accuracy: 0.25% of the final value Connection: Autoclave 1 / 4HP outside
<a href="#">DAkKS initial pressure calibration, including cert</a>	including certificate
<a href="#">ADT927-N2-SET</a>	Hydraulic calibration hand pump Range: 85% vacuum to 700 bar Medium: hydraulic oil Connections: 1/2 "NPT including transport case Country of origin: China
<a href="#">ADT 681</a>	14 to 122°F (-10 to 50°C) operating temp Up to eleven selectable pressure units Large back lit display with 5-digit resolution ATEX certified intrinsically safe is optional Up to 0.02% accuracy IP67 rated, can submerge in 1m of water Panel mount versions available Data logging option NIST traceable certificate included CE mark
<a href="#">ADT 681</a>	
<a href="#">ADT680-25-GP40K-BAR-B2</a>	Pressure range: 0 to 2800 bar Accuracy: 0.25% of final value Connection: G1/2" inside
<a href="#">ADT680-10-GP10K-BAR-N2 Digitalmanometer</a>	Pressure range: 0 to 700 bar Accuracy: 0.1% of final value Connection: 1/2"NPT
<a href="#">ADT927W-N2-SET Hydraulic calibration hand pump</a>	Range: 85% vacuum to 700 bar Medium: deionized water Connections: 1/2" NPT female incl. transport case
<a href="#">ADT946A Hydraulic High Pressure Calibration Pump</a>	Range: up to 1000 bar Medium: oil Connections: G1/2" inside
<a href="#">ADT946A SET Hydraulic high pressure</a>	pump set Range: up to 1000 bar Medium: oil Connections: G1/2" inside

<a href="#">calibration</a>	incl. transport case
<a href="#">DT686 Digitamanometer</a>	Pressure range: 0 to 200 bar Accuracy: 0.02% FS Connection: G1/2" outside
<a href="#">ADT920HV-B2 Pneumatic calibration hand pump</a>	Range: from 95% vacuum to 200 bar Medium: Air Connections: G1/2" inside
<a href="#">927 Ek High Pressure Test Pump</a>	
<a href="#">ADT875-155</a>	ADT875-155 Dry Block Calibrator including insert sleeve H Measuring range: -40°C to 155°C Display accuracy ±0.18°C across the entire measuring range Stability: 0.01°C across the entire measuring range German user manual You can access these online via the QR code on the device. call up.
<a href="#">DAkKS calibration temperature block calibrator</a>	Calibration according to DAkKS-DKD-R5-4 including certificate
<a href="#">ADT681A</a>	Digital manometer Pressure range: ±2.5 mbar Differential pressure Accuracy: ±0.05% FS
<a href="#">ADT158Ex</a>	ADT158Ex Digital Pressure Module Measuring range: 0 to 200 bar (positive/negative pressure) Accuracy: ±0.02% FS Connection: G1/2" external German operating manual (available online via QR code on the device)
<a href="#">ADT673</a>	ADT673 Digital Manometer Pressure range: 0 to 700 bar Relative pressure Accuracy: ±0.02% FS Connection: G1/2" external German operating manual (available online via QR code on the device)
<a href="#">ADT673</a>	ADT673 Digital Manometer Pressure range: 0 to 200 bar Relative pressure Accuracy: ±0.02% FS Connection: G1/2" external German operating manual (available online via QR code on the device)
<a href="#">ADT920HV-B2</a>	ADT920HV-B2 Pneumatic High Pressure Calibration Pump Range: from 95% vacuum up to 200 bar Medium: Air Connection: G1/2" internal German operating manual (via QR code)
<a href="#">ADT946A</a>	ADT946A Hydraulic High Pressure Calibration Pump Up to 1000 bar Medium: Oil Connection: G1/2" internal German operating manual (via QR code)
<a href="#">Adt 680 (Druckbereich: 2800 Bar)</a>	
<a href="#">Adt912-Mk</a>	
<a href="#">Modell Adt 918</a>	
<a href="#">Adt 927</a>	
<a href="#">Adt680w</a>	
<a href="#">209/210</a>	
<a href="#">Automatic Pressure Controller -1 / 25 Barg</a>	
<a href="#">Adt912-N</a>	
<a href="#">Adt 223a</a>	
<a href="#">Additel-Adapter-Und-Anschl3;Sse-Set-Adt103--Istanbul-Turkiye</a>	
<a href="#">Modell Adt 919 A</a>	
<a href="#">Adt681-20-Gp1k</a>	Digital pressure gauge ADT681-20-GP1K Pressure range: 0 to 70 bar Accuracy: 0.2% of the final value Pressure connection: G1 / 4 "(others on request)
<a href="#">Adt102-Npt</a>	

<a href="#">Adt 761-M</a>	
<a href="#">Adt 959</a>	
<a href="#">Adt100-Bspm4-Bspf4q</a>	
<a href="#">Adt 936</a>	
<a href="#">Adt681-20-Gp2k</a>	Digital pressure gauge ADT681-20-GP2K Pressure range: 0 to 140 bar Accuracy: 0.2% of the final value - G1 / 4 "
<a href="#">Adt100-Nptm4-Nptf4rq</a>	
<a href="#">Adt912-Kit</a>	
<a href="#">Pnömatik Pressure Pump 0/700 Bar</a>	
<a href="#">Adt919-B</a>	
<a href="#">104</a>	
<a href="#">Adt938-N</a>	
<a href="#">Optional: Dakks Initial Calibration With 33 Measuring Points</a>	(Procedure B), including certificate per area
<a href="#">Pnömatik Pressure Pump -1/40 Bar</a>	
<a href="#">Adt 210</a>	
<a href="#">Adt 680</a>	
<a href="#">Adt 672</a>	Pressure Range: 60,000 psi (4200 bar) Up to ±0.02% FS accuracy Electrical Measurement Ranges: ±30.0000 V with ±(0.01% + 1.5mV) accuracy ±30.0000 mA with ±(0.01% + 1.5µA) accuracy 14 to 122°F (-10 to 50°C) operating temp NIST traceable certificate included CE mark
<a href="#">Modell Adt 920</a>	
<a href="#">Adt100-Nptm4-Bspm4</a>	
<a href="#">Adt938-Mk</a>	
<a href="#">Adt100-Bspm4-Bspf2q</a>	
<a href="#">Adt100-Htk-4</a>	
<a href="#">Adt949</a>	
<a href="#">Adt 916</a>	
<a href="#">Adt221a</a>	
<a href="#">Adt 209</a>	
<a href="#">Adt103-Npt</a>	
<a href="#">103</a>	
<a href="#">Adt681-20-Gp3k</a>	Digital pressure gauge ADT681-20-GP3K Pressure range: 0 to 200 bar Accuracy: 0.2% of the final value - G1 / 4 "