

Adz Nagano – Sensortechnik

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i
kapı teslim fiyat ve
teslim s¼resi i¼eren
teklifimizi almak i¼in
info@yursat.com.tr e-
posta adresine baŐvuru
yapabilir ya da ayrıntılı
bilgi i¼in +90 224 240
03 04 numaralı
telefonumuzdan bizlere
ulaŐabilirsiniz.
**Adz Nagano –
Sensortechnik** Markası,
tedarik s¼resi i¼in l¼tfen
bizimle iletiŐime
ge¼iniz.

*Firmamız Adz Nagano –
Sensortechnik T¼rkiye
Distrib¼t¼r¼ veya temsilcisi
deĐildir. Firmamız sipariŐ
durumunda, belirtilen ¼r¼nlerde
sadece Orjinal ve yeni ¼r¼n teklifi
sunmaktadır. Bu sitede
g¼sterilen ¼zel marka adları ve
ticari markalar ilgili sahiplerinin
m¼lkiyetindedir, talep
durumunda kaldırılmaktadır.*





rn	Aıklama
Sil 10.0,0	SIL 10.0,0.. -100 mbar, G1/4"E, SW22, MVS/A 1+, 2- Pressure transmitter with silicon membrane Adz no. 806414 Output: 4 ... 20 mA, 2-wire Measuring range: 0 ... -100 mbar, relative pressure Process connection: G 1/4 "E, SW 22 Angle connector DİN EN 175301-803 BF A MVS / A 4-pin, PIN assignment: 1+, 2- Accuracy class 1%
SML-10.0/160	4-20MA
SML ADZ Nr. 803258-C	803258 Pressure transmitter 0..400 bar (sealed reference); 20.0 (0..10) V, industrial G1/4A Form E; HEX22; Angle socket, DIN 175301-803 A /ISO4400 Assignment: PIN 1 = V+; PIN 3 = Iout/Vout; PIN 2 = GND
ADZ-SME-40,O-(O-160bar)(rel)	M8x1-O.5..4.5V-(10..32V)-Im-I(+)2(-)3(out)
ADZ-SML-31,O-	(O-200bar)(reI)-M12xIA(DIN 3852)-O,5..4,5V-(10..30V)- 1m-rd(+)bk(-)wh(out)
ADZ-SME-40,O-(O-200bar)(rel)	M8xI-O,5..4,5V-(10..30V)-1m-rd(+)bk(-)wh(out)
ADZ-SML-37,O-(O-200bar)(rel)	M12xIA(DIN 3852)-O,5..4,5V-(10..30V)- 1m-rd(+)bk(-)wh(out)
ADZ-SME-40,O-(O-160bar)(rel)	M8x1-O.5..4.5V-(10..30V)-Im-I(+)2(-)3(out)
813585	pressure transducer SIL, ItemNo.: 813585 0...40 mbar (gauge); 10.0 (4...20) mA/2- wire G1/4A Form E; HEX22; socket connector M12x1 (S763), 4 PIN configuration: PIN 1 = V+; PIN 3 = GND/Signal - accuracy class: 1%
0111060240	Pressure transmitter SML ADZ 0...-1bar relative 10.0 (4...20) Ma/2-wire G1/4A Form E HEX22: angle socket, DIN 175301-803 C Assignment PIN 3 = V+ PIN2 GND/Signal Accuracy class: 08%
1100682	TST 10.0, 0...-1 bar, G1/4" E, SW22, MVS/ C, 3+ 2- Pressure transmitter with stainless steel membrane Supply voltage: 10 ... 32 V DC Output: 4 ... 20 mA, 2-wire Measuring range: 0 ... -1 bar, relative pressure Process connection: G 1/4" E, SW 22 Seal: FKM (Viton) Angled plug DIN EN 175301-803 BF C MVS/C 4-pin, PIN assignment: 3+, 2-
806393	Pressure transmitter SML, ADZ Item no.: 806393 0...40 bar (relative); 16.0 (4...20) mA / railway 7/16-20 UNF 2B female; Schrader Opener; HEX22; Flange connector M12x1 (S763), 4-pin Assignment: PIN 1 = V+; PIN 3 = GND/Signal - Surge protection
801086	Pressure transmitter SML, ADZ Art.No.: 801086-G 0...25 bar (relative); 10.0 (4...20) mA/2- wire G1/4A Form E; HEX22; Angle socket, DIN 175301-803 C Assignment: PIN 3 = V+; PIN 2 = GND/Signal -
PRESSURE TRANSMITTER-ADZ-SIL 10.0	
9900001	ADZ SML 20.0, 10 bar, G1/4"E, SW22, MVS/C 0.25% Pressure transmitter with stainless steel diaphragm Increased accuracy, measurement deviation: 0.25% FS at RT Supply voltage: 12 ... 32 V DC Output: 0 ... 10 V DC, 3-wire Measuring range: 0 ... +10 bar, relative pressure Process connection: G 1/4" E, SW 22 Seal: FKM (Viton) Angled plug DIN EN 175301-803 BF C MVS/C 4-pin, PIN occupancy: 3+, 2-, 1=Sig
800789-M	Pressure transmitter SML, ADZ ArtNr .: 800789-M 0 ... 400 bar (sealed reference); 10.0 (4 ... 20) mA / 2-wire G1 / 4A form E; HEX22; Angle box, DIN 175301-803 C Assignment: PIN 3 = V +; PIN 2 = GND / signal -

Customs number: 90262020

[Sil – 10.0 / P13 180 3024](#)