Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Afriso

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Afriso Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Afriso Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
DIFF. PRESS GAUGES DIAL SIZE: 80 MM.	ONN.1/2" NPTF, MAG80DFI, DUAL SCALE CARK: PN100, D-74363, 2*1/4" NPT - D312 26 - REF. AFRISO 0 TO 2.5 BAR, 0 TO 36 PSI PART NO:86654312
RANGE: 0 TO 1 BAR,	CONN.: 2*1/4 NPT, WITH WALL MOUNT PLATE(38001) PART NO:88005312
0085AQ0985	
1110041184	
1110041185	
1110041186	
11500	
1211090	
141001	
16500	MT profile G1 1/2 mechanical level gauge with float filled with water/H2O) Measuring range adjustable from 0 to 250 cm by rotating the scale. - Reversible scale 0 to 150 cm and 0 to 250 cm - Connection thread G 1 1/2
20445	
20463	
20480	
20482	
207105	

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
230107FDG	
28040	
31235	
315008	
31556	
31824	
32257	
39615	
40539	
40540	
40630	
40642	
413204	
413214	
42300 (WASSERMANGELSICHERUNG WMS WP-6)	
42305	
42311	
43410	
43500	
52125	
52130	
53 015 41	
53204	
542470	
569581	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
5920008029	
64502	
66147302	
67401X	
67407X, GTT / 7RG	
77623	
77643	
78246	
85001211	
85051711	
85121701 RF 63	
85122701S	
85214201	
85216831	
85219831	
85315301 (0-16 bar)	
85316301	
88037312S	
999999	
AN11500	
AN32301S	
AN35120301	
AN35123301	
AN42300	
AN42415	
AN43646	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
AN43750	
AN63651	
AN67405	
AN67407X	
AN86625711	
AN86924701	
AN88027312	
AN88029312	
Anschluss-Set ASS-DP	
Art. Nr. 500237	
Art.-Nr.: 40731	
DMU 01 ST	
DMU 01 VM 0 / 40 bar, 32026	
DMU 01 VM 0/25bar G1/2B	
DMU 600/10	
EFM 752	
EUROLYZER STx	
FZM 15	
GTK/7RD	
GTK/7RD 0/90°C	
GTT / 7RG, Art.-Nr.: 67407X	
GTT/7RG 0/90 C 200 мм AN67408BX	
IT-D17 150 MM	
IT-D17 63 MM	
KP 100 D201	
KP 160 CH, D402	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
L-10 m AN44503	
LAG-13K	
LAG13KR	
43410	LAG-14 ER mit Relais Application For double-walled containers with liquid in the interstitial space. To Monitoring of flammable liquids stored above ground Danger classes A I, A II, A III, B (according to the former classification VbF) and non-flammable water-polluting liquids. The LAG container can within hazardous areas of Zones I and II (e.g. cathedral shaft near petrol tanks). Approved for tanks according to EN 12285-1, EN 12285-2, DIN 6618-3, DIN 6619, DIN 6623 and DIN 6624 under atmospheric conditions. The leak detector LAG-14 may be used for underground double- walled containers since July 2003 through the reclassification of water-polluting substances Germany is only used to replace existing systems become! Description Class II leak detector (EN 13160-1/-3) with intrinsically safe Probe circuit. Consisting of signal part, Leak detection liquid container (LAG container black) and probe. Signal part with operating and alarm displays, visual/acoustic alarm, Test button and increased interference protection. The audible alarm can be activated with the the acknowledgment button can be ended. Via the potential-free relay contact In the event of an alarm, additional external signaling devices (e.g. horns) or a Additional alarm device ZAG 01 can be switched. With fail-safe mode: Acoustic alarm if the probe fails. Using a mounting frame for Suitable for panel installation, for harsh operating conditions Seal set (IP 54) available. The LAG container is a control container and at the same time expansion vessel. This is allowed for above- ground containers Maximum ratio of useful content to total amount of leak detection fluid 1:35. If the volume of the monitoring space is larger Use additional container. Technical data Temperature range: Environment: -20/+50°C Storage: -20/+60°C

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Supply voltage: AC 230V Signal part: Wall-mounted housing made of impact-resistant plastic (ABS) W x H x D: 100 x 188 x 65 mm Protection class: IP 30 (EN 60529) Relay output: 1 potential-free changer Contact load: AC 250V, 2A Container: Antistatic plastic, black W x H x D: 300 x 325 x 145 mm Usable content / total content: 4.5 l / 10 l Outlet: G¾ IG Protection class: IP20 (EN 60529) Conformity: CE marking according to EU Construction Products Regulation 305/2011, EU 574/2014, EN 13160-1/-3 and ÜHP ATEX approval: TPS 22 ATEX 015639 0019 x Ex II (1) G [Ex ia] Ga IIC scope of delivery Signal part, leak detection fluid container and probe
LAG-14 ER, Art. N: 43410	
LAG-14E	
PF100E D402	
Pneumofix Typ 2 (20142)	
RF 100 85225802	
RF 100 D201, Art. N: 85214201	
S2601 (FZM 30)	
TRAGBARER RAUCHGAS-/ ABGASANALYSEGERAT	
UFS 01	
UFS 01 AN53202	
WMS-WP6 R2 42319	
WMS-WP6, R2	
WMS-WP6, R2 AN42319	
WMS-WP6-R2	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
WP 6 315007	
WP6	
DMU 01 0/25bar G1/2B	Measuring principle: piezoresistive thick-film ceramic measuring cell Measuring range: 0/25 bar (relative) Measuring accuracy: 0.5% FSO according to IEC 60770 medium range. Parts : stainless steel 304 (1.4301) / ceramic / FKM Connection : G 1/2 B according to EN 837 Supply voltage: DC 8-32 V Output signal : 4-20 mA / 2-wire Electrical connection : plug and cable socket according to ISO 4400 (DIN 43650-A)
S4650 ST 0-5000mbar 2xD8	M066030116
S2610 0/1000mbar 2xD8	for measuring overpressure, underpressure and differential pressure / for gaseous, dry, non-aggressive media Measuring range (mbar): -50 / +1,000 max. overpressure (bar): 3 resolution (mbar): 0.1 (<(><<)>199.9) or 1.0 (>200) accuracy (% from measured value): 1.0 +/- 1 digit (<(><<)>1,000 mbar) Scope of delivery: - measuring device with batteries - calibration protocol - protective cover with magnet
Connection set ASS-DP for differential pressure	measurement
77924	
Mt-profil g1/2	
ETB LS 1/961 E1 90/110°C 1000mm	67619 ETB LS 1/961 E1 90/110°C 1000 mm Switching point: 90...110°C Switching point tolerance: +0/-6°C Sensor element: Tmax = 125°C Capillary line: 1000 mm (Cu) Contact type: single contact (normally closed) Contact load: C-2 16(2.5)A 250V~ According to Imit data sheet: 541510/B
AN 16500 -MT-Profil G1 1/2	level indicator filled with water float mechanical level meter/H2O) Measurement range from 0 to 250 cm by bending the scale adjustable. - Turning scale 0 to 150 cm and 0 to 250 cm - G 1 1/2 connection thread
MT-Profil G1 1/2	16500 mechanical level measuring device with float filled with water/

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	H2O) Measuring range adjustable from 0 to 250 cm by turning the scale. - Reversible scale 0 to 150 cm and 0 to 250 cm - Connection thread G 1 1/2
Fuel Gauge 1-1/2” NPT	Fuel Gauge 1-1/2” NPT Vertical 55”
Fuel Gauge	Therma Level Gauge | Tank Depth 44 | 2NPT
Stainless steel sieve 100µm	20032
Two-line filter Z 500 i/a Si 50µm 20429	Filter housing made of brass, filter cup made of transparent, impact-resistant plastic. With shut-off valve in the flow line, check valve in the return line. Supplied with universal clamp ring fittings for pipes with 8, 10 and 12 mm outside diameter. Tested according to the rules of the German Institute for Building Technology and with Ü mark. Connection thread: Tank 2 x 3/8"i Burner 2 x 3/8"a Filter insert: Siku sieve 50-70 µm
Single-strand filter V 500 i/i Si 50µm 20309	
KP63Ch -60/0mbar 1/4 ax D452	35006452 Case diameter: 63 mm Connection: G 1/4 B axial, centric Display range: -60/0 mbar Case: Stainless steel 304 (1.4301) with bayonet ring 304 (1.4301) with 3-edge front ring 304, polished and bracket attachment Parts in contact with the medium: Stainless steel 316Ti/316L (1.4571/1.4404) Seal: FKM (Viton) Lens: plastic (PMMA) Accuracy class: 1.6 Options : none
KP100Ch -60/0mbar 1/2 ax D452	35106452 Case diameter: 100 mm Connection: G 1/2 B axial, centric Display range: -60/0 mbar Case: Stainless steel 304 (1.4301) with bayonet ring 304 (1.4301) with 3-edge front ring 304, polished and bracket attachment Parts in contact with the medium: Stainless steel 316Ti/316L (1.4571/1.4404) Seal: FKM (Viton)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Lens: plastic (PMMA) Accuracy class: 1.6 Options : none
64190	VMTh200 0/120°C 100mm G1/2B MS W90°
85266201	RF160 0/16bar 1/2 rad D201 Case diameter: 160 mm Connection: G 1/2 B radial downwards Display range: 0/16 bar Dial: with adjustable red marker hand Housing: sheet steel, black with over-ring, black sheet steel Parts in contact with the medium: brass, copper alloy viewing window: instrument glass Accuracy class: 1.6 Options : none
85216201	RF100 0/16bar 1/2 rad D201 Case diameter: 100 mm Connection: G 1/2 B radial downwards Display range: 0/16 bar Housing: sheet steel, black Parts in contact with the medium: brass, copper alloy Viewing window: plastic, clipped in with adjustable red marker pointer Accuracy class: 1.6 Options : none
63191	
63031	
63193	
63235	
LAG-14 ER (43410)	
RF 100 I MK2.21 -1/ 1,5 BAR 1/2 AX KL. 1,0 D431	
569581 Pump Rsp-L	
69239	
Kp100	
70075	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
86924701 Manometer 160 Bar	
An40540	
An 16500 Bspp	
63651	
0-Gt;60;C ; Cl.1	
43500 / Lag-13 K	
Gtk/7rd Thermostat Mit Kapillar Rohr	
An 43684	
141001 Tankinhaltsanzeiger Unimes 90-200 Cm 1 1/2"+2"	
413214 Manometer 0-16 Bar 1/2" Radial 100mm Gly	
69240	
Gsp1	
69241	
77643 Gerade Die Gruppe Primotherm 180-1 Dn 25, Ohne Pumpe	
An 40731	
Wms-Wp6	
Filter Paper For Soot Pumps 568400	
An43645	
An85114111	
55034	
42300 Water Shortage Protection Device Type Wms-Wp6 With Unlocking	
69243	
Wms 3-1	
Ath 63m/80m	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
413214 Manometer 0-16 Bar 1/2" Radial100mm Gly.	
An63031	
Gtt/7rg	
An 69236	
42368	
0t89c-59230078	
An 85122701	
An 69226	
An 43790	
77623 Ventil	
70072	
Stm500	
42300 Waterproofing Device Wms-Wp6a	
D201 An35120201 Pressure Gauge Kp100 0/160 Mbar G1 / 2 Rad Kl 1,6	
An 69391 Eurosoft	
63653	
69242	
42310	
Wp6 Level Sensor	
An20463 Ventilation Cowl G 2, Metal An20463	
42319	
85122732	
16500 Universal Mechanical Level Meter Mt-Profil R-1 1/2 16500	
An67421x	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
70074	
An 16500	
999999 Manometer 0-200 Bar 1/2" Radial100mm Gly.	
Soot Comparison Scale 568300	
It-D14 63 Mm	
67407x	
77615	
67401? Temperaturregler Gat/7rs	
56171	
Afriso.0-Gt;60;C ; Cl.1	
42300 Water Shortage Protection Devicemozh-Wp6	
L-10 M An44503 Sonde Optoelektronnyj	
56164	
An85113101	
It-D17 100 Mm	
Wms - Wp6 - R2 An42319	
53503	
31127g2	
69244	
86625711 Manometer Rf 63 Gly 0-250bar 1/4 Ax D711	
43410 Lag-14 Er	
Om5 An44502	
An 43688	
413204 Manometer 1-5 Bar 1/2" Radial100mm Gly.	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
42300 (Wassermangelsicherung Wms Wp-6)	
Afriso 0-4bar	Mess- / Einstellgerät
An20445 G2 X 2 1/2 Inch Reinforced Filler Cap For An20445 Diesel Fuel.	
An 43691	
An 43410	
An85122701	
It-D14 150 Mm	
42300	
85122701	
315007 Wassermangelsicherung Wp 6	
64115	
63031	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.