

Ahg Armaturen

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Ahg Armaturen Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Ahg Armaturen T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
ASKDN400PN16GGGDVGW	Butterfly valve DN400 PN16 including manual gearbox, DVGW U-shaped flange housing, Flange bore according to DIN 2501 PN16 Suitable for VS flanges according to DIN 2633-C Construction length EN 558-1 Series 20 (DIN 3202-3, K1) Shift shaft mounted in bushing, replaceable housing lining with molded edges on both sides Flange gaskets, EPDM centrally mounted flap disc with a spherically shaped seat surface Housing made of grey cast iron GG-25 with all-around epoxy powder coating Damper plate spheroidal graphite cast iron GGG-40 with Epoxy powder coating Shift shaft: Stainless steel AISI 420 Bearing bushing: Delrin Housing lining: EPDM - DVGW Nominal pressure: max. 12 bar Temperature: -20°C to max. +110°C including manual transmission DVGW Drinking Water Blue RAL 5015
FG(F) - 3	DN 250, PN 16, Seat: E
Butterfly valve DN 250 PN 16	U-shaped flange housing For installation between flanges PN 16 Head flange according to ISO 5211 Tightly closing, centrally mounted DVGW drinking water approval Installation length: 68 mm Housing: GGG40 + Epoxy 120µm, RAL 5005 Flap disc: GGG40 + epoxy min. 150µm Shaft: AISI 420

Nominal pressure: max 12 bar Seat ring: EPDM Temperature:
-20° / +110°C Operation: Manual gear