Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Aira Valve Automation

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Aira Valve Automation Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Aira Valve Automation Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Aira Valve Automation	
Aira Valve Automation	
AEP-1000-LSN	SPECIFICATIONS: - (A) INPUT SIGNAL : 4~20 MA DC (NOTE 1) (B) INPUT RESISTANCE : 235+15 (C) SUPPLY AIR PRESSURE : 20~100PSI (7.0 KG/CM²) (D) STANDARD STROKE : 10~80MM (NOTE 2) (E) AIR PIPING CONNECTION : 1/4 NPT (F) (F)CONDUIT CONNECTION : 1/2 NPT (F) (G)EXPLOSION-PROOF CLASSIFICATION : EXIA II BT6, EXDM II BT6, EXDM II CT6 (H) DEGREE PROTECTION : IP66 (I) AMBIENT TEMPERATURE : -20°C TO 70°C (J) PRESSURE GAUGE : STAINLESS STEEL 0-2 KG/CM² 0-4 KG/CM² 0-10 KG/CM² (K) OUTPUT CHARACTERISTICS : LINEAR (L) LINEARITY : WITHIN + 1.0% F.S. (M) SENSITIVITY : WITHIN + 0.2% F.S. (N) HYSTERESIS : WITHIN + 0.75% F.S. (O) REPEATABILITY : WITHIN + 0.5% F.S. (P)AIR CONSUMPTION : 5.0 LPM (1.4 KG/CM²) SUPPLY (Q) FLOW CAPACITY : 80 LPM (1.4 KG/CM²) SUPPLY (R)MATERIAL : ALLUMINIUM DIECAST BODY (S)WEIGHT : 2.8 KG. WITH A TERMINAL BOX
2” (50 MM)	HAND LEVER OPERATED SS 316 BODY & SS 316 BALL 2 WAY 3 PIECE BALL VALVE FLANGED END 150#. BALL VALVE DETAILS: - BODY : ASTM A351 Gr. CF8M (S.S.316) BALL : ASTM A351 Gr. CF8M (S.S.316) SEALS : PTFE LEAKAGE CLASS : CLASS VI WORKING PRESSURE : UP TO 10 KG/CM2

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	TEMPERATURE : UP TO 180°C END CONNECTION : FLANGED 150#
1” (25 MM)	HAND LEVER OPERATED SS 316 BODY & SS 316 BALL 2 WAY 3 PIECE BALL VALVE FLANGED END 150#. BALL VALVE DETAILS: - BODY : ASTM A351 Gr. CF8M (S.S.316) BALL : ASTM A351 Gr. CF8M (S.S.316) SEALS : PTFE LEAKAGE CLASS : CLASS VI WORKING PRESSURE : UP TO 10 KG/CM2 TEMPERATURE : UP TO 180°C END CONNECTION : FLANGED 150#
1/2” (15 MM)	HAND LEVER OPERATED SS 316 BODY & SS 316 BALL 2 WAY 3 PIECE BALL VALVE FLANGED END 150#. BALL VALVE DETAILS: - BODY : ASTM A351 Gr. CF8M (S.S.316) BALL : ASTM A351 Gr. CF8M (S.S.316) SEALS : PTFE LEAKAGE CLASS : CLASS VI WORKING PRESSURE : UP TO 10 KG/CM2 TEMPERATURE : UP TO 180°C END CONNECTION : FLANGED 150#
2” (50 MM) EN 1092-1	HAND LEVER OPERATED SS 316 BODY & SS 316 BALL 2 WAY 3 PIECE BALL VALVE FLANGED END 150#. BALL VALVE DETAILS: - BODY : ASTM A351 Gr. CF8M (S.S.316) BALL : ASTM A351 Gr. CF8M (S.S.316) SEALS : PTFE LEAKAGE CLASS : CLASS VI WORKING PRESSURE : UP TO 10 KG/CM2 TEMPERATURE : UP TO 180°C END CONNECTION : FLANGED 150# (FLANGE DRILLING AS PER BS EN 1092-1)
1” (25 MM) EN 1092-1	HAND LEVER OPERATED SS 316 BODY & SS 316 BALL 2 WAY 3 PIECE BALL VALVE FLANGED END 150#. BALL VALVE DETAILS: - BODY : ASTM A351 Gr. CF8M (S.S.316) BALL : ASTM A351 Gr. CF8M (S.S.316) SEALS : PTFE

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	LEAKAGE CLASS : CLASS VI WORKING PRESSURE : UP TO 10 KG/CM2 TEMPERATURE : UP TO 180°C END CONNECTION : FLANGED 150# (FLANGE DRILLING AS PER BS EN 1092-1)
1/2” (15 MM) EN 1092-1	HAND LEVER OPERATED SS 316 BODY & SS 316 BALL 2 WAY 3 PIECE BALL VALVE FLANGED END 150#. BALL VALVE DETAILS: - BODY : ASTM A351 Gr. CF8M (S.S.316) BALL : ASTM A351 Gr. CF8M (S.S.316) SEALS : PTFE LEAKAGE CLASS : CLASS VI WORKING PRESSURE : UP TO 10 KG/CM2 TEMPERATURE : UP TO 180°C END CONNECTION : FLANGED 150#

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.