

Ako Armaturen

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Ako Armaturen Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Ako Armaturen T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
15623P	
227.0705-125-35	
AE83210A07	
D10123	
D14123	
D14213	
D14223	
D14610	
DN100.	
DN80.	
KAM80007	
M015.03XK	

M040.03LF
M040.04HTEC
M040.05
M050.04HTEC
M050.05
M125.03X
M125.04HTEC
M150.02X
MP.50G
OV050.03.30M
OV100.0330PA2
STR.IP8000.030-X14-DN100
UG 54 DN 32 / DIN 2501 / PN 16 CT05321RA042E00
VF040.03X.33.30GLA
VF050.03X.33.30LA
VF065.03X.33.30LA
VF100.02X.33.30LA
VF100.03X.31.30LA
VF100.03X.35.30LA
VF100.03X31.30LA-VF100
VF125.03X.31.30LA
VF150.03X.31.30LA
VF80.03X31.30LA-VF80
VMC32.03X.50G.30LX
VMP025.04HTECK.71/NPT
VMP050.03X.71
VMP050.03X.72
VMPO.040.7
M 100. 03X
M0100.03X

M040.03X	
M050.03X	
M080.03X	
M080.03X	
M100.02X	
M100.03X	
M100.30X	
M1000.3X	
M150.03X	
M050.05	
VF150.03X.31.30LA,	AKO pinch valve series VF, directly actuated, with compressed air, neutral gases or water. Equipped with interchangeable cuff: Natural rubber abrasion-resistant with increased resilience Double fabric reinforced Nominal diameter DN: 150 Valve connection: Flange DIN EN 1092-1 PN10/16 Connection material: aluminum with wetted steel bushing Housing material: aluminum Paint finish: Powder coating pure white (similar to RAL 9010) Control air connection: internal thread G 1/4" Max. operating/control pressure in bar: 6.00 / 8.00 Min. differential pressure in bar: 2.00 Min./Max. operating temperature in °C: -10.00 / 80.00
VMP015.03XK.72	AKO VMP series pinch valve, directly actuated, with compressed air, neutral gases or water. Equipped with an interchangeable cuff: Natural rubber, abrasion-resistant with increased resilience single-layer fabric reinforced 15 Nominal diameter DN: Valve connection: Internal thread type "G" (DIN ISO 228-1) Connection material: POM-C injection molded black (polyoxymethylene) Housing material: POM-C injection molded black Control air connection: Internal thread G 1/8" Max. operating/control pressure in bar: 5.00 / 8.00 Minimum differential pressure in bar: 2.50 Minimum/Maximum operating temperature in °C: -10.00 / 80.00
237.0120-020-0	Expansion thermostat Temperature range: 20 - 30 °C Permissible tolerance ± 1.5 °C
140.0121-001K-840	NBR gasket set consisting of: 1 seal 7445-0024-500 Al 1 O-ring 7440-0069-840 NBR 1 O-ring 7440-0030-840 NBR 1 O-ring 7440-0061-840 NBR 1 seal 7441-0111-845 NBR For 3-way control valves with Emergency manual adjustment DN40 - DN150
FF100.31LA	Flange for VF series pneumatic pinch valve Nominal diameter DN: Valve connection: Flange DIN EN 1092-1 PN10/16 Connection material: Aluminum with medium-contacting steel bushing Paint finish: Powder coating pure white (similar to RAL 9010)

V065.03x.37/17 Ventil	
15640 Proplus-1f	
Vf040.03x.31.30la	
14323	
Vf200.3h.3la	
?015.03 ?? Pressure Valve	
27-6dh2-5232/5300	
Vf100.03x.31.30la Pneum.Quetschventil Typ Vf, Dn 100	
Vmp040.03x.71	
Vf100.03x.33.30la	
WF100	Mounting set DN 100, for VF valves Consisting of: mounting tube, paste, screws
237.0120-082-0	
?100.30?	
5312	
Vmp020.04hteck.72	
M100.03x Elastische Stutzen	
?150.03?	
Vf200.03h.35.30la	
Vmc15.03xk.50g.50	
Om200.03	
Ako-D14123	
Vmp020.07lwk.71	
?080.03?	
Vmc32.03x.50g.50	
Vmp040.03x.72	
Vmc50.03x.50g.30lx	
?06503?	
Vf150.03x.331.30ala	
Vf-80 Pneumatisches Ventil	

Zt6141002078
Vmc25.03x.50g.50
Vmp032.07lw.71 Pressure Valve
?040.03? Hub
Vf100.03x31.30la-Vf100 Ventil Pneum.Quetschventil Typ Vf, Dn 100
?1000 ??
Vf100.03x.31.30.La Ventil
Vf150.03x.33.30lc
Vf200.3h.35.3la Ventil Komplett Mit Manschetteako M200 03h 20/13
Rva35014114
Vmp040.03x.72 Ventil
Vf080.03x.31.30 La Pneumatisches Quetschventil
Ov100.0330pa2 Gate Valve With Positionerinner Diameter 100 Mm
Das Ventil Dn100 3.5 L 6 Bar Vf100.03x.31.30 La Ako
Vmc15.03xk.50g.71
Vmc50.03xk.50g.30lx
Vmp020.07lwk.71 Pressure Valve
Vf065.02x.33.30la
Vmp020.07lwk.71 Quetschventil
5560410
Vf80.03x31.30la-Vf80 Pneum.Quetschventil Typ Vf, Dn 80
M150.03x Kettenpanzer
Ako Vfo150.03x.31.30la Valve
Vmc40.03xk.50g.30lx
Vmf040.03x.50.30lx
M200.03h
Vf065.03x.31.30la
Vmc40.03x.50g.50

Vf080.03x.33.30la
237.0120-057-0
Vf100.03x31.30la-Vf100 Pneum.Quetschventil Typ Vf, Dn 100
M040.02x
237.0520-041-0
? 100. 03x
Ako Quetschventil Vm020.07x.70.80, Dn20/Pn10 Betriebsdruck Bar
Vf 065.03x.31.30la Ventil Pinch
Vf080.03x.31.30la Pneum.Quetschventil Typ Vf, Dn 80
M80.03x Manschette
Vmp020.07xk.72
M200.03x
5577020l
M100.04htec
For Vt100 Pressure Valve Collar
5530057
Vf 040.03x.31.30la Ventil Pinch
Vf80.03x31.30la-Vf80 Ventil Pneum.Quetschventil Typ Vf, Dn 80
M050.03x
Vf080.03x.31.30gla
Vmp020.03xk.71
060 065478
M040.03x
Vm020.07x.70.80
Vmc10.03xk.50g.50
Vf200.03x.33.30la Ventil
M080.03x
Vf-100 Pneumatisches Ventil

Vf200.03x.33.30la	
Mpl,50g	
060_065476 Entladeventil Vf Dn100 2000000031859	
Vmc20.03xk.50g.30lx	
Zt6140001778	
?100.02?	
O1254f5050pag	
?0100.03?	
226.0121-100-057	
?12504htec Manschette	
Ov-M Dn50 Schlauchschieber	
Vmce65.04htece.50rm.50	
Vmp20.03xk.71on?	
Vmc25.03xk.50ta.30lx	
M065.03x Manschette	
M100.04/03x	
Vmc32.03xk.50g.30lx	
Vf080.03x.31.30la	
VF150.03X.33.30LA	AKO pinch valve series VF, directly actuated, with compressed air, neutral gases or water. Equipped with interchangeable cuff: Natural rubber abrasion-resistant with increased resilience Double fabric reinforced Nominal diameter DN: 150 Valve connection: Flange DIN EN 1092-1 PN10/16 Connection material: aluminum Housing material: aluminum Paint finish: Powder coating pure white (similar to RAL 9010) Control air connection: internal thread G 1/4" Max. operating/control pressure in bar: 6.00 / 8.00 Min. differential pressure in bar: 2.00 Min./Max. operating temperature in °C: -10.00 / 80.00
Vmp020.03xk.71on	
Vmp020.03xk.72	
?04003?	
?10004htec	
226.0121-050-102	
Vmc20.03xk.50g.50	

Vmp032.07lw.71	
M025.03xk	
M065.02x	
Vmc25.03xk.50g.30lx	
Ov-M Dn-50	
20040.001.000	
Vf050.03x.31.30la	
Ako53124	
M150.03x	
140.0121-001k-840	
M100.03x Nozzle	
?10004htec Manschette	
Vf0100.03x.31.30la	
Vf100.03x31.30la	
227.0521-050-041	
319002593	
M025.02x	
Vmp050.03x.71 Pinch Valves Vmp /Socket Type Vmp Dn50	
?200 03? 20/13 Manschette	
M065.03x	
M100.03X	Cuff for pneumatic pinch valve, Suitable for valve series: VF(X), VMC(X), VA(X), VMCE(X) Natural rubber, abrasion-resistant with increased resilience double fabric reinforced Nominal diameter DN: Minimum/Maximum operating temperature in °C: -10.00 / 80.00
Ako 14903	
Screen (For 15640 Proplus-1f)	
Vmp025.03xk.71	