

Alfa Valvole



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin

info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Alfa Valvole Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Alfa Valvole Trkiye Distribtr veya temsilcisi deŐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Dga092a F05/F07 Sw17	Double acting pneum. drive with NAMUR connection G 1/4 " , Connection according to ISO 5211-F05 / F07, width across flats Z = 17mm, required control air 5-6 bar, max. 10 bar *** WITHOUT mounting kits *** Customs tariff number: 84123100 // Country of origin: Italy
Alfa10n Dn65, Pn16, Va, Fire-Safe	ALFA COMPACT BALL VALVE full bore, made of stainless steel ASTM A479 316 (L) / ASTM A351 CF8M, Parts made of carbon steel that are not in contact with the medium, Sealing elements TFM 1600 / PTFE, Overall length L = 107 mm, Connection according to DIN ISO 5211-F07, Approval according to TA-Luft *** Version DN65 PN16 with 4-hole flange ***
Alfa10nf Dn65, Pn16, Va, Fire-Safe (Alternativ)	Alternativ ALFA COMPACT BALL VALVE full bore, made of stainless steel ASTM A351 CF8M / ASTM A351 CF8M, Parts made of carbon steel that are not in contact with the medium, Sealing elements TFM 1600, Overall length L = 107 mm, Connection according to DIN ISO 5211-F07, Approval according to TA-Luft *** Version with 4-hole flange ***
S16319	Complete kit of seats and gaskets for ball valve ALFA 54 (not ALFA AP54) DN 4", as per dwg. S16319
S16322	Complete kit of seats and gaskets for ball valve ALFA 54 (not ALFA AP54) DN 6", as per dwg. S16322
H13500-DPL	Spare kit of 2 seats for ball valve ALFA AP DN 2", as per dwg. H13500-DPL

H13500-DPL gaskets	Spare kit of gaskets for ball valve ALFA AP DN 2", as per dwg. H13500-DPL
Complete kit of seats and gaskets	for ball valve ALFA 506 DN 4" seats in PTFE+AM, gaskets in PTFE+Graphite / Viton *** WITHOUT actuator as not specified in detail ***
SNA127**5** F07/F10 SW22	Single acting pneum. drive with NAMUR connection G 1/4 ", Connection according to ISO 5211-F07 / F10, width across flats Z = 22mm, required control air 5-6 bar, max. 10 bar *** WITHOUT assembly kits ***
KEE80107	Seal kit for pneumatic Drive type DNA110 / SNA110 Customs tariff number: 84123100 // Country of origin: Italy
SGA0754 F05/F07 SW17	Single acting pneum. drive with NAMUR connection G 1/4 ", Connection according to ISO 5211-F05 / F07, width across flats Z = 17mm, required control air 5-6 bar, max. 10 bar *** WITHOUT assembly kits ***
ART10002	Seal kit for pneumatic Drive type DNA160 / SNA160 Customs tariff number: 84123100 // Country of origin: Italy
SGA0634 F05/F07 SW14	Single acting pneum. drive with NAMUR connection G 1/4 ", Connection according to ISO 5211-F05 / F07, width across flats Z = 14mm, required control air 5-6 bar, max. 10 bar *** WITHOUT assembly kits ***
SNA118**3** F07/F10 SW22	Single acting pneum. drive with NAMUR connection G 1/4 ", Connection according to ISO 5211-F07 / F10, width across flats Z = 22mm, required control air 5-6 bar, max. 10 bar *** WITHOUT assembly kits ***
DN150 (6 ") DIAPHRAGM (MEBRANLI) VALVE	Valve Type: Type "KB" (Straight Through) Pressure Class: Class 150 Body Material: GGG40 - Butyl Coated Diaphragm Material: XA Grade Ultimate Diaphragm (EPDM -40 +130 ° C) Connection: Manual Metal Hand Control Flange Norm: ASME B16.5 Class 150 Length Norm: DIN3202 Series F1 (L: 480 mm, Hole Axis: 241.3 mm, Number of Holes: 8) Operation: By Hand Control, MANUAL
DN 150 (6 "), DIAPHRAGM	Diaphragm Material: XA Grade Ultimate Diaphragm (EPDM -40 +130 ° C)
DN100 (4` `), BALL ARM VALVE	It is a steam jacketed valve. ANSI 150 P Max: 20 bar L Length: 150 mm Note: Liquid sulfur passes through. Sulfur temperature is between 145-155 ° C
ALFA60P DN 8", ANSI 300lbs RF,	ALFA FLANGE BALL VALVE Trunnion Mounted trunnion mounted execution, 2 pcs. body, full bore, material *** Body: ASTM A216 WCB / Ball: ASTM A105 + ENP *** *** Stem: AISI 4140 ENP *** Seats: ASTM A105 + R.P.T.F.E. *** face to face dim. L = 502 mm, with drilling DIN ISO 5211-F14 *** with Gearbox *** Weight: approx 175kg Customs tariff number: 84818081 Country of origin Italy
10 BALL VALVE DN100 0069560043	
10 BALL VALVE DN50 0069560044	

BALL VALVE ALFA 24 DN.15 1/2" PN.25	Note: PN 64 is accepted too
Wafer type ball valve, ALFA11N	DN 3/4" ANSI 300lbs RF, UNC, Fire-Safe full bore, body material ASTM A105, seats in TFM, face to face dim. L = 39 mm, flanges ANSI 300 with UNC threaded holes, with drilling DIN ISO 5211-F03, heating jacket in carbon steel with heating threaded connections DN 1/2" NPT female, with hand lever Zolltarifnummer: 84818081 / Ursprungsland: Italien
SPARE PARTS FOR PNEUMATIC ACTUATOR	21-PISTON O-RING 8 EA 16-PISTON GUIDE-RING 8 EA 23-PINO. UPPER O-RING 8 EA 11-PINO. UPPER GUIDE 8 EA 12-PINO. BOTTOM GUIDE 8 EA 24- PINO. BOTTOM O-RING 8 EA
64 SB" 1/ 2" 3/4" ANSI 150	RF+PNUM. ACTUATOR + BOX
64 SB "1/2" 3" ANSI 150 RF +PNUM. ACTUATOR +	
64 SB "1.1/2" ANSI 300 RF +PNUM. ACTUATOR +	
ALFA 606 SB	ART11001 Flanged ball valve type ALFA 606 SB DN 1/2", ANSI 600lbs RF, Fire-Safe 2 pcs. body, full bore, material ASTM A105N / ASTM A351 CF8, seats in TFM, face to face dim. L = 165 mm, with drilling DIN ISO 5211-F03, FIRE-SAFE certified, with hand lever
ART10000	Wafer type ball valve, ALFA11N DN 1" ANSI 300lbs RF, UNC, Fire-Safe full bore, body material ASTM A105, seats in TFM, face to face dim. L = 43 mm, flanges ANSI 300 with UNC threaded holes, with drilling DIN ISO 5211-F03, heating jacket in carbon steel with heating threaded connections DN 1/2" NPT female, with hand leve A1J25A2C5-0001-M0010 (Q)
BALL FOR VALVE ALFA 11HP, SIZE: DN 15, 1/2" ANSI	600 LG, POS. 05
SEATS FOR VALVE ALFA 11HP, SIZE: DN 15, 1/2" ANSI	600 LG, POS. 06
PISTON, MODEL NO.: GTKN.75X90.ND17A	PENUMATIC ACTUATOR SERIES: GTKN.75X90.ND17A
PISTON PAT, MODEL NO.: GTKN.75X90.ND17A	PENUMATIC ACTUATOR SERIES: GTKN.75X90.ND17A
PISTON GUIDE RING, MODEL NO.: GTKN.75X90.ND17A	PENUMATIC ACTUATOR SERIES: GTKN.75X90.ND17A
PISTON ORING, MODEL NO.: GTKN.75X90.ND17A	PENUMATIC ACTUATOR SERIES: GTKN.75X90.ND17A
PISTON, MODEL NO.: GTKN.63X90.ND14A	PENUMATIC ACTUATOR SERIES: GTKN.63X90.ND14A
PISTON PAT, MODEL NO.: GTKN.63X90.ND14A	PENUMATIC ACTUATOR SERIES: GTKN.63X90.ND14A
PISTON GUIDE RING, MODEL NO.:	PENUMATIC ACTUATOR SERIES: GTKN.63X90.ND14A

GTKN.63X90.ND14A	
PISTON ORING, MODEL NO.: GTKN.63X90.ND14A	PENUMATIC ACTUATOR SERIES: GTKN.63X90.ND14A
BALL VALVE	FLANGED BALL VALVE ALFA 11HP, SIZE: DN 15, 1/2" ANSI 600 LG, P/N: 11HP
TYPE: A11NF	DN50 RAT: ANSI150 Pmax: 20Bar PT: 30Bar T/min T/Max - 29/200°C
BALL VALVES,3/4"ANSI300,A11N (Wafer type ball valv	ALFA VALVOLE Wafer type ball valve, ALFA11N DN 3/4" ANSI 300lbs RF, UNC, Fire-Safe full bore, body material ASTM A105, seats TFM 1600, face to face dim. L = 39 mm, flanges ANSI 300 with UNC threaded holes, with drilling DIN ISO 5211-F03, heating jacket in carbon steel with heating threaded connections DN 1/2" NPT female, with hand lever Customs tariff number: 84818081
VANA, DN50, ANSI 150 ,	TYPE: A11NF , DN50 , RAT: ANSI150 Pmax: 20Bar PT: 30Bar T/min T/Max -29/200°C
VALVE REPAIR KIT, 20-503V1, FOR VALVES WITH HEATIN	JACKETS DN20, MODEL: A11NF, POS: 6-7
VALVE REPAIR KIT, 20-503V1, FOR VALVES	WITH HEATING JACKETS DN25, MODEL: A11NF, POS: 6-7
VALVE REPAIR KIT, 20-503V1, FOR VALVES	WITH HEATING JACKETS DN80, MODEL: A11NF, POS: 6-7
VALVE REPAIR KIT, 20-503V1, FOR VALVES	WITH HEATING JACKETS DN150, MODEL: A11NF, POS: 6-7
VALVE REPAIR KIT, 20-503V1, FOR VALVES	WITH HEATING JACKETS DN200, MODEL: A11NF, POS: 6-7
DN 100 TYPE A 103 RAT PN 10-16	
ALFA10H.P. DN 2" ANSI600 RF, VA UNC	ALFA COMPACT BALL VALVE full bore, made of stainless steel ASTM A479 316(L) / ASTM A351 CF8M, PTFE sealing elements with metal core, Length L = 100 mm, ANSI 600 drilled, thread 5/8"-11 UNC
A10NF Wafer type ball valve DN:15	
Pneumatic Actuator	
KA610000	ALFA10NF DN50, PN10-40, VA, Fire-Safe ALFA COMPACT BALL VALVE full bore, made of stainless steel ASTM A351 CF8M / ASTM A351 CF8M, parts not in contact with the medium made of carbon steel, Seat rings made of TFM, Length L = 83 mm, Connection according to DIN ISO 5211-F05
KA625000	ALFA10NF DN125, PN10-16, VA, Fire-Safe full bore, made of stainless steel ASTM A351 CF8M / ASTM A351 CF8M, parts not in contact with the medium made of carbon steel, Seat rings made of TFM, Length L = 180 mm, Connection according to DIN ISO 5211-F10

HEAT JACKETED BALL VALVE, 4", ANSI300, A11N	Wafer type ball valve ALFA11N DN 4" ANSI 300lbs RF, UNC, Fire-Safe full bore, body material ASTM A105, seats TFM 1600, face to face dim. L = 150 mm, flanges ANSI 300 with UNC threaded holes, with drilling DIN ISO 5211-F03, heatingjacket in carbon steel with heating threaded connections DN 1" NPT female, with hand lever Customs
ART11001---ALFA T2 FB DN 3", ANSI600, CS	ALFA T2 FB DN 3", ANSI600, CS ALFA ball valve with flanged connection - RF - 125-250 AARH (STD) 2 pieces. body, trunnion mounted, material: ASTM A105 / A105N/A350 LF2 seats: ASTM A105N/A350 LF2+SINVEX Manual with std lever AT280A4CN-XXXX-M0010
GTXN 110x90.TP22A	
GTXN 118x90 TP22A	
GTXN 127x90 TP22A	
GTVN 63x90 TP14A	
GTVN 75x90 TP17A	
GTXN 160x90 TP27A	
10N CS GT127SE	BALL VALVE WITH PNEUMATIC ACTUATOR
KDAF0104	Sealing elements for ALFA10N/NF PN 10-40 DN 20, mat. TFM / Graphoil, Fire-Safe Kit Code: KGA1N20A1-001
KDAF0105	Sealing elements for ALFA10N/NF PN 10-40 DN 25, mat. TFM / Graphoil, Fire-Safe Kit Code: KGA1N25A1-001
KDAF0116	Sealing elements for ALFA10N/NF PN 10-40 DN 80, mat. TFM / Graphoil, Fire-Safe Kit Code: KGA1N80A1-001
KDAF0120	Sealing elements for ALFA10N/NF PN 10-40 DN 100, mat. TFM / Graphoil, Fire-Safe Kit Code: KGA1NA0A1-002
KDAF0130	Sealing elements for ALFA10NF PN 10-16 DN 150, mat. TFM / Graphoil, Fire-Safe Kit Code: KGA64A5A1-001
KDAF0140	Sealing elements for ALFA10NF PN 10-16 DN 200, mat. TFM / Graphoil, Fire-Safe Kit Code: KGA64B0A1-001
HEAT JACKETED BALL VALVE, 4", ANSI 150	Flanged ball valve, type ALFA 11N DN 4" ANSI 150 lbs RF - 125-250 AARH, flanges with UNC threaded holes, full bore, body material ASTM A105 from bar stock, ball material ASTM A351 CF8, stem material ASTM A479 F316(L), seats in TFM, face to face dimension L = 152 mm, heating jacket in carbon steel A105, heating connections screwed 1" NPT female, with drillings DIN ISO 5211, Fire-Safe certified, with standard hand lever
HEAT JACKETED BALL VALVE, 8", ANSI 150	Flanged ball valve, type ALFA 11NF DN 8" ANSI 150 lbs RF - 125-250 AARH, flanges with UNC threaded holes, full bore, body material ASTM A216 WCB (casting material) *** not available in ASTM A105 bar stock material ***, ball material ASTM A351 CF8, stem material ASTM A479 F316(L), seats in TFM, face to face dimension L = 314 mm, heating jacket in carbon steel A105, heating connections screwed 1" NPT

	female, with drillings DIN ISO 5211, Fire-Safe certified, with manual gear box type 242-45
A10n Pn10-40	40 bar
A60P	
DN15-304-A10N PN	
16810, Sealing Kit For Alfa 60/64/68, Dn 50	
Ka304640	
A10n Pn10-40 40bar	
Ka308000 + Ke800104	
16804, Sealing Kit For Alfa 60/64/68, Dn 20	
A10n 661-681-643	
23a 15 (1/2quot;)	
365736 Repair Kit For 35- Xv-4701	
10nf Dn40 Pn16	
Ke800203,Sga0634 F05/F07 Sw14	
23a 40 (1quot;1/2)	
A11 Nf / Dn 100	
365725 Repair Kit For Xv-4713	
1321-3	
Ke800206 Sga0924 F05/F07 Sw17	
Ka316600	
365731 Repair Kit For 35-Xv-4706 /35-Xv-4707	
Alfa 10hp Pn64-Pn100	
Rba 901 V013	
11005	
Kv11.16	Ballestra part number KV11.16 ON-OFF BALL VALVE (DN 50) ALFA VALVOLE x 3 pc. S.R.L.Actuator
64s.B.Ansi150 3	
6060895 - 100hp Astm A105	
Ka303218	

A11 Nf / Dn 200
Ke800213,Sna2104 F14 Sw36
A60 Ansi300
2-1/16quot;, 5000psi, Api-6a (Edition 19th)flanged, Rtj, Pr1, Psl2, M.C: Dd-60k, T.C:U According To Nac
Ka304000 Wafer Type Ball Valve, Alfa 10nf, Dn20, Pn16/40, Fire-Safe
Ka303209
A 103 Dn 100 Rat Pn 10-16 P Max 16 Bar Tmin-Tmax -29 / 160 C
A10n-11
18108 Alfa 60/64/68
894049
A10n-12
Ka603209
A10n-07
Valvola Dn 1.1/2
Ka320606
A10n-15
Ka320043
11008 Sealing Kit For Alfa 10n/Nf
A6040a2sd-0001-M00
Qtf 90
Vs2v1acbi06-Mg30t
A11 Nf / Dn 150
Vs2v1acbi05-Mg30t
16820, Sealing Kit For Alfa 60/64/68, Dn 100
Ke800109 Dna127a F07/F10 Sw22
Ka603218
3/4 300a352lcbredborele
Wafer type ball valve, ALFA11N DN 3/4" ANSI 300lbs RF,

Art11001	UNC, Fire-Safe full bore, body material ASTM A105, seats TFM 1600, face to face dim. L = 39 mm, flanges ANSI 300 with UNC threaded holes, with drilling DIN ISO 5211-F03, heating jacket in carbon steel with heating threaded connections DN 1/2" NPT female, with hand lever Customs tariff number: 84818081 Country of origin: Italy
Gt S.E. 83 K4	
Ka330021	
365730 Repair Kit For 35-Xv-4703 /35-Xv-4705	
Kas24303 (Completed With Ke800203 Pneumatic Actuator)	
Ka310043	
Kv11.17	Ballestra part number KV11.17 ON-OFF BALL VALVE (DN 80) ALFA VALVOLE x 3 pc. S.R.L.Actuato
Ka610801	
Ke800213 Sna2103 F14 Sw36	
16816 Sealing Kit For Alfa 60/64/68, Dn80, Material Tfm1600, Fire-Safe	
Gt S.E 75 K4	
Ka308000	
Kv11.18	Ballestra part number KV11.18 ON-OFF BALL VALVE (DN 25) ALFA VALVOLE x 3 pc. S.R.L.Actuator
Alfa 103I	
Ka305000	
Ke800204,Sga0754 F05/F07 Sw17	
Ke800209 Sna1274 F07/F10 Sw22	
2-1/16quot;, 5000psi, Api-6a (Edittion 19th), Fb, Pr1, Psl2, M.C: Ee-45k, T.C:U, Nace Mr-0175/Iso 15156	
Gtkn 75x90	
A10n-14	
Ka302211	
A10n-09	
Kv11.5	Ballestra part number KV11.5 ON-OFF BALL VALVE (DN 40) ALFA VALVOLE x 3 pc. S.R.L.Actuator
Gtxn.110 X 90.Np22a K4	

[365726 Repair Kit For Xv-4714-A /35-
Xv-4714-B](#)

[A10n-08](#)

[Alfa 10nf](#)

[Ka608000](#)

[893217](#)

[Ke800207,Sna1104 F07/F10 Sw22](#)

[Ke800106](#)

[892261](#)

[Gtkn75x90-Tp17a Lower](#)

[Kda20016](#)

[16803, Sealing Kit For Alfa 60/64/68, Dn
15](#)

[Alfa 10hp - Not Enough Information.](#)