Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Althen

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Althen Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Althen Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
DSA3217-PTP/16APx-30psiA 16-channel	Pressure Module with Absolute sensors with Precision Time Protocol (SET)
12HPS-5	Multi-Turn Potentiometer
KD – 1925 and KD 1950	For the first region: Ambient temperature of 150 – 170 °C, · The same temperature values are valid for the sensor cables, · The material to be measured is Ti6-4, · Extremely small sensor sizes are required as they will be positioned in tight spaces. For the second region: Ambient temperature of 150 – 170 °C, Ambient temperature of approximately 600 – 700 °C for sensor cables, · The material to be measured is Inco 718, · Small sensor dimensions.
SAK. 13FLP100A /POTENTİOMETRE	
LCF-300-LP-30	1010564

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Precision inclinometer - Measuring range / number of axes: ±30° / 1-axial (Code: 30) - Accuracy: 0.02% FSO - Output signal: 4 - 20 mA, 3-wire technology (code: L) - Supply voltage: 20 - 30 VDC - Service temperature: -40°C to +80°C - Electrical connection: Solder pins (code: P) Further specifications according to data sheet Dual use listed. Identification number: 7A101
H30JH 3-Axis Finger Joystick	
NM1-M1-IP-24E-420-B20-GFM	Industrial inclinometer system - Measuring range / number of axes / direction of rotation: ±20° / 1-axial / bi-directional (Code: B20) - Output signal: 4 - 20 mA, 2-wire (code: 420) - Supply voltage: 10 - 30 VDC (Code: 24E) - Electrical connection: 3 m connection cable 2 x 2 x 0.25 mm² PUR - Degree of protection: IP66 - Execution: base mounting (code: GFM) Further specifications according to data sheet
NM1-IP-2L-24-420-B20	Industrial inclinometer system - Measuring range / number of axes / direction of rotation: ±20° / 1-axial / bidirectional (code B20) - Output signal: 4 - 20 mA, 2-wire (code: 420) - Supply voltage: 18 - 28 VDC - Electrical connection: 3 m connection cable 2 x 0.25mm² (AWG20) - Degree of protection: IP68 - Electronics to protect against moisture and shedding vibrations Further specifications according to data sheet
LMP-35-2L-50kN-Z4933	Load measuring pin special design - Measuring range / type of force: 50 kN / compressive force - Accuracy: ±1.0% of full scale - Output signal: 4 - 20 mA, 2-wire technology - Supply voltage: 7.5 VDC to 28 VDC - Service / nominal temperature: -25°C to +80°C / -10°C to +50°C - Electrical connection: Souriau connector with Connection cable set, cable length 5 m - Mechanical connection: according to drawing - Degree of protection: IP67 Further specifications according to data sheet
TOG-2L-15to-Z4935	Customized strain gauge tension transducer - Measuring range / type of force: 15 t / weight

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Output signal: 4 - 20 mA, 2-wire - Supply voltage: 24 VDC - Electrical connection: Souriau connector with Connection cable set, cable length 3 m - Material: stainless steel Further specifications according to data sheet and drawing (will be created again)
TTL-20t-Z4936	Tension gauge special design - Measuring range / type of force: 20 t / tensile force - Accuracy: ±0.25% of final value - Output signal: 4 - 20 mA, 2-wire technology - Supply voltage: 7.5 VDC to 28 VDC - Service / nominal temperature: -20°C to +70°C / -10°C to +50°C - Electrical connection: plug connector with Connection cable set, cable length 5 m - Mechanical connection: according to drawing - Degree of protection: IP66 Further specifications according to data sheet
TTL-25t-Z4962	Tension gauge special design - Measuring range / type of force: 25 t / tensile force - Accuracy: ±0.25% of final value - Output signal: 4 - 20 mA, 2-wire technology - Supply voltage: 7.5 VDC to 28 VDC - Service / nominal temperature: -20°C to +70°C / -10°C to +50°C - Electrical connection: plug connector with Connection cable set, cable length 5 m - Mechanical connection: according to drawing - Degree of protection: IP66 Further specifications according to data sheet
LSOP-30	Analog Inclinometer Range: +-30 Degree, +-15 mA, Us: 10-24VDC, Output: 4-20mA
LSOP-30-ROHS	1011192 Precision inclinometer - Measuring range / number of axes: ±30° / 1-axis (Code: 30) - Accuracy: (NLH) <±0.02% of full scale - Resolution/response threshold: 1 µrad - Output signal: ±5V proportional to the sine of the tilt angle - Supply voltage: ±12 to ±18 VDC - Temperature of use: -20°C to +70°C - Electrical connection: Solder terminal (Code: P) Further specifications according to data sheet

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1011200	13FLP100A-5K-M-0.7 linear potentiometer - Measuring range: 101.6 mm ±0.5 mm (code: 100) - Non-linearity: ±0.7% (code: 0.7) - Resistance: 5 kOhm (Code: 5K) - Resistance Deviation: ±20% (Code: M) - Rated power: 1.2 watts - Mech. Connection: 4x through-holes on the housing Further specifications according to data sheet
Project	we need a joystick with 2 axis data from the "Althen" brand and a button on the Z axis. Communication protocols such as USB, RS232, RS485 will be suitable. Is it possible for you to suggest a product and price offer according to these requirements? If there is no model that you can suggest, can you submit an offer for the following products? HE1 Multi-Axis Finger Joystick HE2 Multi-Axis Finger Joystick HE3 Multi-Axis Finger Joystick
DC-EC 050	
1012386	SGR510-EC-KE-40Nm Rotating torque transducer with integrated electronics, self-diagnosis and active temperature compensation - Measuring range: ±40 Nm - Rotation speed: maximum 15,000 rpm - Accuracy: ±0.20% of final value - Output signal: 4 - 20 mA (Option: E) - Supply voltage: 12-32 VDC (nom. 24V DC) - Operating / nominal temperature: -10°C to +90°C / 0°C to +90°C - Electrical connection: plug connection, Lumberg 12-pin - Mechanical connection: shaft diameter: 20 mm (option: EC), smooth shaft with key (option: K) - Protection class: IP54 Further specifications according to data sheet
1005665	ACC-3 Connection cable for analog port suitable for SGR510/SGR520 - 12-pin Lumberg connector (female) to 15-pin Sub-D (female) - Length: 2.5 m
SGR510-EC-K-E-40Nm	Rotating torque transducer with integrated electronics, self-diagnosis and active temperature compensation - Measuring range: ±40 Nm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	- Rotation speed: maximum 15,000 rpm - Accuracy: ±0.20% of final value - Output signal: 4 - 20 mA (option: E) - Supply voltage: 12-32 VDC (nom. 24V DC) - Operating / nominal temperature: -10°C to +90°C / 0°C to +90°C - Electrical connection: plug connection, Lumberg 12-pin - Mech. connection: shaft diameter: 20 mm (option: EC), smooth shaft with key (option: K) - Protection class: IP54
S50JCK-X1-10R16	
LAU1000-3	
Pptr40gp5vbef	
Sg-Kp-24e-010	
Pptr100gp5vbef	
850904-D003	
40 07 Y19	
Althen-Dichtring-F3;R-Xpc10-M-10ba-L3mz02-Istanbul-Turkiye	
Nm2-4l-24-B10-15-E-T	
Dichtringe Zjoibs003	
Ags4003-350-G	
M/N:Kd2300-5su S/N:S0305282-02-10	
Sg-Ks	
Aaa223-0001-Xxg	
Nm2-4l-24-020-15-E	
Ags4003-100-G	
76066753040103	
M/N:Kd2300-5su S/N:S0305282-02-10 Kaman	
P981-0107-06m0	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
125hcd-006	
Nss1-1p-24e-5-2gw	
F306-Cfr0h0-005	
Xpc10-M-10ba-/L3m/Z02	
Nss-1-Ip-24e-B5-2gw	
Nss-1-Ip-24e-5-2gw	
Rd298hpt	
Hi2010e024-Sg-2k-E0112	
Paxp001b	
Ags4003-M-0400-Ab	
A-K-1k	
X103.10ajnrtz329	
Hi2013-0350-Ab-E054	
P500.120ej	
Sg-Ip-3l-24-420-2p	
Aosbka-500	
Sg-Ip-24e-420	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.