

Ametek



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Ametek Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Ametek Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Rebuild Kit For Gauge Calxp	4138
Backup Ring	3151
Rod Seal	3434
7/16-20 Mp Male Connector	MPM-MPM
STEP M.MAE HN200 3438 0600 AG04 90V6.0A	
151167-21 (NEW FLYER 606462)	
151167-11	
DG-200	Mechanical hand force measuring device Model DG-200 Capacity 200 x 1.0 lbf Measurement accuracy 0.5% of full scale Including carrying case and test accessories including calibration certificate
DPPH-150	min. 150 lbs %0.05 FS
MODEL: 71780KE GASKET	
Windjammer 119153-54	

NAUTILAIR BLOWER (150145-50)	
XG 300 28 300 V 28 A USB	
Supervac 3200 IKD 7.0 Mobil	(700-1202-021
MWIR-B 640	T47-1100179665 3.1. Land.No: 811290, NIB-b 3' Water Cooled Housing HT Cables,
850139.000000	Lamb Electric 240 V / 1100 W BP S2 suction motor 169 GH / TBH 69 / D 144 mm self-switching carbon brushes
122326-00	
122508-00	
Advanced Signal Calibrators Model ASC300	SIGNAL CALIBRATOR ADVANCED, AMETEK ASC300 W/NIST CERT
850334.000000 SML00039	Lamb Electric 240 V / 975 W BP S2 naturally aspirated engine 179 GH / TBH 72 / D 144 mm suitable for naturally aspirated engines, all Manufacturer, Lamb naturally aspirated engines Ametek 11642013
CMFA-P2000	Operating temperature: 1600°C Internal pressure: 1-2 mmSS Values we want to measure: O2, CO, NOx
System B / T-975 (P-015)	Pump system type BHX / Crystal system Pump system for Crystal pressure reference devices with pneumatic gripper pump Version: System B / T-975 (P-015) -0.91 ... 40 bar Connections: 1x test item CPF/F,1/4"NPT/F 1x reference 3/8"BSP/F, CPF/M included: Fine adjustment pressure, vent valve Changeover valve positive/negative overpressure (only with system B) Hose approx. 1m for test object connection CPF blanking plug for unused DUT connection CPF fitting connection for Crystal reference devices Gaskets, set of O-rings, Teflon tape Aluminum frame case
Ametek Pneumatic Hand Pumps – T-900 Series	Handpump: -0,91 – 40 bar Part Number: T-975-CPF
305122901S	
305010908S	
305010901S 50 hour/million	
30540090 IS	
30500790 IS	
30500890 IS	
30544890IS 7 micron	
USG (160 psi-11 bar)	
Pressure reference device for a pressure (with full temperature compensation in the range -10...+50°C) Version:	

CRYSTAL XP2i Gauge	see listing below Range: 1x overpressure optionally 1 - 2 - 7 - 20 - 30 - 70 - 140 - 200 - 300 - 700 - 1000 bar Connections: pressure CPF special connection up to 700 bar; at 1000 bar NPT or BSP without CPF adapter Functions: current value, max/min, average, PSV mode Zeroing at target pressure (display deviation) included: Batteries 2xAA Adapter standard CPF - 1/4"NPT/a (PN° MPM-1/4MPT) ISO/IEC 17025 Calibration Certificate (A2LA Accreditation) Specification: see XP2i Data Sheet N° 4611.Q - not recommended for oxygen service - continuous measurement: minimum -0.98 bar, maximum above range Accuracy: S2 - 0.02% of F.S Example order designation: 5 x 1KBAR-XP2I-S2-3696
Ametek Pressure Comparators - Type T Series	Hydraulic Hand Pump (System F) 0 - 1000 bar / 15.000 psi Medium: Water / Viton Pumps are delivered without oil or water Part Number: T-1-CPF Part Number: FOV
75160211	
Digital indicator model DFS2-R-ND	(without replaceable load cell) including RS232 & USB connections including ForceTest software including test accessories and carrying case incl. battery adapter/charger including calibration certificate
external force transducer series SLC	Model SLC-0025 Capacity 100N including calibration certificate
HUNTER HS70050R;	REEL CABLE STATIC GROUNDING MEDIUM DUTY SPRING RETURN 0.093IN DIA 50FT LG GALVANIZED STEEL CABLE POWDER COATED HOUSING RED ALLIGATOR CLAMP TRAILER MOUNTING; .
CE 140SE RS232	
A436147JI	
U SHAPED TUBING AND 24-25-26-27 PARTS	They are spare parts of AMETEK Brand T Model Hydraulic Deadwight Tester.
PISTON UNIT AND CYLINDER CARRIER	They are spare parts of AMETEK Brand T Model Hydraulic Deadwight Tester.
JOFRA dry block temperature calibrator RTC-156 B	AD-RTC-156B Temperature range: Maximum : 155 °C minimum @ Ambient 0°C : -46°C minimum @ Ambient 23°C : -30°C minimum @ Ambient 40°C : -15°C Temperature Stability : +/- 0.005°C Accuracy related to internal reference : +/- 0.10 °C external reference : +/- 0.04 °C (using ex. reference sensor) Display resolution : 0.001, 0.01 °C; 0.1°C or 1°C Immersion depth : 160 mm Bore diameter : 30 mm Auto step function : up to 20 steps Connection voltage: 230 V/45-65 Hz (other connection voltage possible) Connected load max.: 400 W Protection class : IP10 Dimensions without case : (L x W x H) 362 x 171 x 363 mm Dimensions with case : (L x W x H) 650 x 380 x 500 mm Weight without case : 10.5 kg weight with opt. Suitcase : approx. 15.5 kg Various features: Two-zone heating/cooling block Easy handling Color display (5.7") stabilization indicator "Calibrator is stable" output (SYNC) USB interface and calibration software LAN connection, input for SD card Input for RTD, TC, V, mA 4 - 20

	<p>mA transmitter input incl. 24 VDC encoder power supply Input for external reference sensor Input for DLC sensor Download work orders from PC the scope of delivery includes: Dry block temperature calibrator JOFRA RTC Traceable calibration certificate to international standards for temperature Traceable calibration certificate according to international standards for the input variables Tool for insert sleeve power cord 1 set of rubber plugs for insulating plugs User Guide USB interface cable Calibration software JOFRACAL Test cable set (2x red and 2x black)</p>
STS-200 reference sensor - 4mm diameter, 161mm len	(B & C models only), STS200A915EH Item No.: R2
Aluminum carrying case with trolley	Item no.: CT
Insert sleeves, undrilled (5 pieces)	Item No.: AD-127301 with hole for DLC sensor and reference sensor Material: aluminum
Insert sleeve drilled with a standard bore:	You can choose between holes for the following sensors: per sleeve 3mm, 4mm, 5mm, 6mm, 7mm, 8mm, 9mm, 10mm, 11mm, 12mm, 13mm, 14mm, 15mm and 16mm All inserts come with an additional hole for the reference sensor and an additional hole for the DLC sensor delivered)
PF3-400- 180-NC-01 324SCR	
WDG 1210	
116420-13 CH18	MOTOR AMETEK 116420-13 CH18 CUTTING BLOWER MOTOR 0,96 KW 220/240V AC
CheckPoint 3S, O2/CO2	O2/CO2 hand-held measuring device for checking protective gas packaging - Robust housing - New ceramic solid O2 sensor - CO2 sensor (infrared technology) - 3.5" color touch screen - Built-in sample gas pump - Monitoring of the sample gas flow, with alarm - 1 adjustable limit alarm per gas - Li-Ion battery for approx. 2,000 measurements Supplied in a plastic case with: - CheckPoint 3 meter - Power adapter with USB charging cable - Spare consumables (10 needles, 10 filters, 100 septa) - Factory calibration certificate
Consumable set CheckPoint 3	1x sample set, 1000 gray septa, 10 filters, 10 needles 0.8 x 16 mm
Protective rubber for side parts on the right and left	left CheckPoint 3
Surcharge for increased production costs	CheckPoint 3
O-RING METAL 42244JE	
MODEL:71780KE GASKET	
71785SE CELL, ZIRCONIA ELECTROCHEMICAL	(FOR WDG-1210 MODEL)
MODEL:80585SE DISPLAY PCB	
115950	

DFE3-050	
61208 90049	
STS-200A TEMPERATURE REFERENCE PROBE	ATC-156 + B STS 200A 915
886661	
117636	
117415	
STS-200A	Probe
119656-00	
063200082 1200W 230V (128mmX130mm)	
AX2HL 028MCD S 3705SF	
117634-01	BLOWER
DX-FLEX	PML11014A1BZ Model: (P) RF Admittance Measurement Type / Frequency and Phasing: (M) Manual Calibration Std. Sens. (Mode 7) Input: (L) Universal Power Supply Output: (1) DPDT Relay Housing: (1) No Approval 3/4"NPT Integral/Remote Options: (0) Integral Sensing Element Code: (14) 700-0202-002 316SS 50 PSI@ 300° F/20 PSI@ 450°F Mounting: (A1B) 3/4" NPT 316 SS Dimensions: (Z) Other (Specify After Model#) Insertion Length: 457 (mm) Cote Shield Length: 100 (mm) Country Approvals: Not Required
JOFRA Superior Temperature Reference Sensor	STS150 Pt100 reference probe, solid, with intelligence A Overall diameter 4 mm 915 90° Angled probe,Type 915 for PTC-155 Series,Range -25°C - 155°C A Cable 0,5 m with LEMO / LEMO connectors B Cable 2,0 m with LEMO / LEMO connectors C Cable 2,0 m with LEMO / Banana connectors D Cable 2,0 m with LEMO / Redel connector for DTI050 E Cable 0,5 m with LEMO / Redel connector for Calibrator H Accredited Certificate – ISO17025
122508-00	
122508-00	
977149-EU-3	
Dew Point Analyzer	
850573.000000	Lamb Electric suction motor 220 V / 1300 W TG S2 175 GH / TBH 64 / D 183 mm
95384WE	CELL LEAD KİTS FOR 36" PROBE
73052TE	75W, 115V, HEATER/THERMOCOUPLE ASSEMBLY FOR 36" PROBE

71785SE	CELL, ZIRCONIA ELECTROCHEMICAL
71922SE	
72346SE	FILTER INSITU 20 MICRON SS,316
71715KE	WASHER, CERAMIC
71848KE	WASHER, CERAMIC - NOTCHED
71782KE	INSULATING TUBE, MULLITE
305540901S	3050 SLR,DO,TE/5830 1 ppmv Nominal Moisture Generator
305400901S	OLV/SLR/DO/TE Reference Dryer
122508-00	
BU-2581-AQ	2.5 inch 0-4000 PSI ¼ inch NPT
069203001	1000W 240V WET DRY VACCUM MOTOR
119625-00	
ETC-400A-21	<p>Item no.: AD-ETC-400A Fixed insert sleeve with holes: 1x 6 mm, 2x 4 mm, 1x 3 mm and 1x 2 mm Technical specifications for all models: Temperature range: 28 °C to 400 °C Temperature stability: □ 0.15 °C Accuracy (int. reference): □ 0.5 °C Display resolution: 0.1 °C or 1 °C Automatic step function: up to 9 steps Immersion depth: 110 mm Supply voltage: 115 VAC or 230 VAC/45-65 Hz Power requirement: 350 W Protection class: IP10 Dimensions: without protective box: (L x W x H) 172 x 72 x 182 mm with protective box: (L x W x H) 350 x 235 x 135 mm Weight without protective box: 1.6 kg Weight with protective box: 2.8 kg Various features: Fast heating/cooling Small size and low weight Stabilization indicator RS232 interface and calibration software The scope of delivery includes: Dry block temperature calibrator JOFRA ETC Traceable certificate according to international standards for temperature stuck insert sleeve in the block Operator's and Reference Manual Calibration software JOFRACAL Power cable RS232 interface cable shoulder strap</p>
AD-124094	Aluminum carrying case
SBDST10302	
TJ310	Turbo-Mass Flowmeter with Digital Output
	<p>AMETEK JOFRA Dry Block Temperature Calibrator RTC-156 B Temperature range: Maximum: 155 °C Minimum @ ambient temperature 0°C: -46°C Minimum @ ambient temperature 23 °C: -30 °C Minimum @ ambient temperature 40 °C: -15 °C Temperature stability: +/- 0.005 °C Accuracy relative to Internal reference: +/- 0.10 °C External reference: +/- 0.04 °C (using external reference sensor) Display resolution: 0.001, 0.01 °C; 0.1°C or 1°C Immersion depth: 160 mm Bore diameter: 30 mm Automatic step function: up to 20 steps Connection voltage: 230 V/45-65 Hz (other connection</p>

AD-RTC-156B	voltages possible) Maximum power consumption: 400W Protection class: IP10 Dimensions without case: (L x W x H) 362 x 171 x 363 mm Dimensions with case: (L x W x H) 650 x 380 x 500 mm Weight without case: 10.5 kg Weight with optional case: approx. 15.5kg Various features: Dual-zone heating/cooling unit Easy to use Color display (5.7") Stabilization indicator "Calibrator is stable" output (SYNC) USB interface and calibration software LAN port, SD card slot Input for RTD, TC, V, mA 4 – 20 mA transmitter input incl. 24 VDC sensor power supply Input for external reference sensor Input for DLC sensor Downloading work orders from the PC Included in the delivery are: JOFRA RTC dry block temperature calibrator DANAK calibration certificate – Accredited Certificate – ISO17025 Tool for insert sleeve power cord 1 set of rubber stoppers for insulating plugs User manual USB interface cable JOFRACAL calibration software Test cable set (2x red and 2x black)
DLC	DLC – Dynamic Load Compensation Sensor (nur B & C Modelle)
R1	STS-102 Reference Sensor – 4 mm diameter, 30 mm length (B & C models only), STS102A030EH
R2	STS-200 reference sensor – 4 mm diameter, 161 mm length (B & C models only), STS200A915EH
CT	Aluminum carrying case with trolley
AD-127301	Insert sleeves, undrilled (5 pieces) with bore for DLC sensor and reference sensor Material: Aluminum
Parts	Insert sleeve, drilled with a standard bore: The following sensor holes are available: 3mm, 4mm, 5mm, 6mm, 7mm, 8mm, 9mm, 10 mm, 11 mm, 12 mm, 13 mm, 14 mm, 15 mm and 16 mm All inserts come with an additional hole for the (Reference sensor and an additional bore for the DLC sensor are supplied)
AD-RTCt-157B	AMETEK JOFRA Dry Block Temperature Calibrator RTCt-157 B Item No.: AD-RTCt-157B Temperature range: Maximum: 155 °C Minimum @ ambient 0°C: -57°C Minimum @ ambient temperature 23 °C: -45 °C Minimum @ ambient temperature 40 °C: -31 °C Temperature stability: +/- 0.005 °C Accuracy relative to Internal reference: +/- 0.11°C External reference: +/- 0.040 – 0.065 °C (using external reference sensor) Display resolution: 0.001, 0.01 °C; 0.1°C or 1°C Immersion depth: 160 mm Bore diameter: 30 mm Automatic step function: up to 20 steps Connection voltage: 230 V/45-65 Hz (other connection voltages possible) Maximum power consumption: 400W Protection class: IP10 Dimensions without case: (L x W x H) 362 x 171 x 363 mm Dimensions with case: (L x W x H) 650 x 380 x 500 mm Weight without case: 10.5 kg Weight with optional case: approx. 15.5kg Various features: Dual zone heating/cooling unit Easy to use Touch Screen Our Interface - Color Display Stabilization indicator "Calibrator is stable" output (SYNC) Wi-Fi, Ethernet & USB interface Input for RTD, TC, V, mA 4 – 20 mA transmitter input incl. 24 VDC sensor power supply Input for external reference sensor Input for DLC sensor Downloading

	work orders from the PC Included in the delivery are: JOFRA RTCT dry block temperature calibrator DANAK calibration certificate – Accredited Certificate – ISO17025 Tool for insert sleeve power cord 1 set of rubber stoppers for insulating plugs User manual USB interface cable Wi-Fi dongle JOFRACAL calibration software Test cable set (2x red and 2x black)
Insert sleeve, drilled with a standard bore:	The following sensor holes are available: 3mm, 4mm, 5mm, 6mm, 7mm, 8mm, 9mm, 10 mm, 11 mm, 12 mm, 13 mm, 14 mm, 15 mm and 16 mm (all inserts come with an additional hole for the Reference sensor and an additional bore for the DLC (Sensor supplied)
M01 – M02 – M04 – M05 – M06 – M07 – M08 – M09 – M10	Insert sleeve, multiple bore
M03	Insert sleeve, multiple bore
08393665	Brushless WNJ 5.7" 240VAC 268CFM 45 in.H BP E CL possible replacement for 151706-02
CTC-155 A	AMETEK JOFRA Dry Block Temperature Calibrator Temperature range: maximum 155°C : minimum -25°C @ 23°C (-39°C @ 0°C, -7°C @ 50°C) Temperature stability: ± 0.04°C Accuracy: ± 0.3°C (relative to internal reference) Radial homogeneity: ± 0.03°C Display resolution: 0.01°C, 0.1°C or 1°C Immersion depth: 120 mm Shaft diameter: 26 mm Temperature setting: manual, either directly or via 3 predefined values : automatically up to 12 checkpoints with holding time Heating: 13 min from 23°C to 155°C Cooling: 12 min at 155°C to 23°C, 16 min at 23°C to -25°C Switch test: Automatic / open, closed, hysteresis : up to 3 automatic repetitions Connection voltage: 180...254 VAC / 47-53 Hz (others on request) Maximum power consumption: 100 VA Protection class: IP10 Operating range: 0 ... 50°C, 5...90% RH non-condensing Dimensions: (L x W x H) 248 x 148 x 305 mm Weight: 5.5 kg (without case) / 9 kg (with case) Other features: large color display, easy operation IRI – intelligent status information for recalibration : Quiet mode selectable MVI - Temperature stability during grid fluctuations USB interface : online firmware update including: power cord User manual (English) USB interface cable JOFRACAL calibration software Calibration certificate traceable to international standards for temperature
129489	Insert sleeve (drilled) – Multihole type 1 D 26 mm, length 100 mm, 75 g, aluminum five holes D 3-4-5-6-9 mm Code M01
Drexelbrook 402-3300	Level Transmitter module and a 60-65cm long probe.
	AMETEK JOFRA Dry Block Temperature Calibrator RTCT-156 A Temperature range: Maximum: 155 °C Minimum @ ambient temperature 0 °C: -46 °C Minimum @ ambient temperature 23 °C : -32 °C Minimum @ ambient temperature 40 °C: -17 °C Temperature stability: +/- 0.005 °C Accuracy relative to Internal reference: +/- 0.10 °C Display resolution: 0.001, 0.01 °C; 0.1 °C or 1 °C Immersion depth: 160 mm Bore

[AD-RTCt-156A](#)

diameter: 30 mm Automatic step function: up to 20 steps
Connection voltage: 230 V/50-60 Hz (other connection voltages possible) Maximum power consumption: 350 VA
Dimensions without case: (L x W x H) 362 x 171 x 363 mm
Dimensions with case: (L x W x H) 650 x 440 x 610 mm
Weight without case: 10.3 kg Weight with optional case: approx. 20.5 kg
Various features: Dual-zone heating/cooling unit Easy to use Touch Screen Our Interface - Color Display Stabilization indicator "Calibrator is stable" output (SYNC) Wi-Fi, Ethernet & USB interface Downloading work orders from the PC Included in the delivery are: JOFRA RTCt dry block temperature calibrator DANAK calibration certificate - Accredited Certificate - ISO17025 Tool for insert sleeve power cord 1 set of rubber stoppers for insulating plugs User manual USB interface cable Wi-Fi dongle JOFRACAL calibration software

[AD-RTCt-156B](#)

AMETEK JOFRA Dry Block Temperature Calibrator RTCt-156 B
Temperature range: Maximum: 155 °C Minimum @ ambient temperature 0 °C: -46 °C Minimum @ ambient temperature 23 °C : -32 °C Minimum @ ambient temperature 40 °C: -17 °C
Temperature stability: +/- 0.005 °C Accuracy relative to Internal reference: +/- 0.10 °C External reference: +/- 0.04 °C (using external reference sensor) Display resolution: 0.001, 0.01 °C; 0.1 °C or 1 °C Immersion depth: 160 mm
Bore diameter: 30 mm Automatic step function: up to 20 steps
Connection voltage: 230 V/50-60 Hz (other connection voltages possible) Maximum power consumption: 350 VA
Dimensions without case: (L x W x H) 362 x 171 x 363 mm
Dimensions with case: (L x W x H) 650 x 440 x 610 mm
Weight without case: 10.3 kg Weight with optional case: approx. 20.5 kg
Various features: Dual-zone heating/cooling unit Easy to use Touch Screen Our Interface - Color Display Stabilization indicator "Calibrator is stable" output (SYNC) Wi-Fi, Ethernet & USB interface Input for RTD, TC, V, mA 4 - 20 mA transmitter input incl. 24 VDC sensor power supply Input for external reference sensor Input for DLC sensor
Downloading work orders from the PC Included in the delivery are: JOFRA RTCt dry block temperature calibrator DANAK calibration certificate - Accredited Certificate - ISO17025 Tool for insert sleeve power cord 1 set of rubber stoppers for insulating plugs User manual USB interface cable Wi-Fi dongle JOFRACAL calibration software Test cable set (2x red and 2x black)

[AD-RTCt-156C](#)

AMETEK JOFRA Dry Block Temperature Calibrator RTCt-156 C
Temperature range: Maximum: 155 °C Minimum @ ambient temperature 0 °C: -46 °C Minimum @ ambient temperature 23 °C : -32 °C Minimum @ ambient temperature 40 °C: -17 °C
Temperature stability: +/- 0.005 °C Accuracy relative to Internal reference: +/- 0.10 °C External reference: +/- 0.04 °C (using external reference sensor) Display resolution: 0.001, 0.01 °C; 0.1 °C or 1 °C Immersion depth: 160 mm
Bore diameter: 30 mm Automatic step function: up to 20 steps
Connection voltage: 230 V/50-60 Hz (other connection voltages possible) Maximum power consumption: 350 VA
Dimensions without case: (L x W x H) 362 x 171 x 363 mm
Dimensions with case: (L x W x H) 650 x 440 x 610 mm
Weight without case: 10.3 kg Weight with optional case: approx. 20.5 kg
Various features: Dual-zone heating/cooling

unit Easy to use Touch Screen Our Interface - Color Display
Stabilization indicator "Calibrator is stable" output (SYNC)
Wi-Fi, Ethernet & USB interface Input for external reference
sensor Input for DLC sensor Downloading work orders from
the PC Included in the delivery are: JOFRA RTCT dry block
temperature calibrator DANAK calibration certificate -
Accredited Certificate - ISO17025 Tool for insert sleeve
power cord 1 set of rubber stoppers for insulating plugs User
manual USB interface cable Wi-Fi dongle JOFRACAL
calibration software

SR	Mounting kit for sensors
321.006	
5362500-033	
5360726-02	
027656000 Ax3l 200ac N 473jh	
608920 4036	
750257-1	
M01 Multihole	
700-0201-058	
R8486	
880138902	
Sbc 4401c	
5360801-02	
803567	
061000062 230v 50/60hz	
801346	
50-Dcf3 24v Dc	24V DC Relay Module
090-0006-3-01-B	Power Supply Board
Lsp Hd 10	
80307se	PC DRIVER BOARD
M 280 T4 X 10	
Å008 O-Ring; 300-6241 For 241ce Hydrocarbon Dew Point Analyzer	
00 106772	
806027	

Dcs8-125e	
50-F1-120/50	
#008 O-Ring; 300-6241 For 241ce Hydrocarbon Dew Point Analyzer	
5360726-03	
027656000 Ax3I 200ac N 473jh	
5362462-020	
80549se	
03-J754601-05	
Dcs40-25e	
T9234c321-R8	
100-1848	
Nvs 146 200	
1060-752	ISM-LPS Logic Power Supply ISM-LPS
100.1788	
951a-C1-0040-Xx-E	LINEAR TRANSDUCER
Ctc660a230bnonxxfxx	
951a-V-0390-N2-D5-E	LINEAR TRANSDUCER ANALOG 39IN
1057-634	IRIG-B Cable
1000688 S/N:Vw-900-8556-1	
Dcs10-120e	
1000w	
00-107037	
910ac120kc120h1	ANNUNCIATOR 10ALARM 120VAC 50/60HZ 0.2AMP
Dcs600-1.7e	
5362500-150	
801387	
805037	
5362500-050	
Am-Mgaaa/Qt	
952qd-0600-Xxe-1270-C-F6m1-Ndx	LINER DISPLACEMENT TRANSDUCER 64-INCH

869989828	
Dcs80-15e	
43f4a-05-068	C1737 Please see attached photo
091.580	
470115	
100-1578 Uom:Ea Ae-241-0347-0	
5362462-033	
Dcs600-2e	
100-1207	
5362500-040	
95384we	
5362500-100	
Acs-8	
5362500-010	
5360726-04	
1064-760	IOM IOM
Dcs20-60e	
1064-768	IOM Local IOM
Xsc-1326-89093c	Isolated Millivolt Transmitter
00-106772	
5362462-040	
Dcs100-10e	
099.392-Autocal-	
801405	
XI-3-1k5p-A7-B	PROCESS CONTROL W TRANSDUCER 3PH -1000/0/1000W
100b-2f Obsolete, Replaced By Li-809560	
80-214014-90	CHARGER CONTROL BOARD
801402	
117502-12	
Macal	

880138901	
R7446-05	
1060-751	ISM-LPS Logic Power Supply ISM-LPS
Db-35l	BLOCK CALIBRATOR W/CASE THERMOCOUPLE/RTD
321.005	
Dcs80-13e	
100,1203	
P/N 880118901	
1074-124	ISM-FCV Field Contact Voltage Power Supply ISM-FCV
R7518p	
011041	
Sc-1302	4-20mA Isolated Voltage/Current Transmitter 1302
306.054	
470142	
Dcs300-4e	
119918-12	
Xl3-1k5-A4-4	TRANSDUCER 2.5AMP 120VAC 60HZ 500WATT
(E56617) 116480-00 Obsolete, No Replacement	
880019902	
5362462-150	
(921980) Ax 5.0 S Induktiver Messtaster (Lvdt)	
11kf7305-Agbl	CONTROLLER MODEL 40 GAUGE RANGE -5/-35H2O 15PSI
100-1219	
Z01-205-Ac	
091-643	
5362462-100	
1986a1rx Sd0284200	
Wdg210	
5362462-050	

100-1 579	
50-F1-125vdc	
811129	
100-1202 Windows Housing Assembly C/W Windows	
0.9m(36) Probe For Wdg 1210	
100,0666	
50-A1	
1060-798	120 VAC Input Module
1986a1xrx	2500 PROGRAMMABLE LIMIT SWITCH RESOLVERS, INDUSTRIAL DUTY FOOT MOUNT RESOLVER
M6 0/300c-V	
801401	
5362462-008	
802665	
Ims-Its	IMS-ITS Input Termination Shelf
Tm-2480	TEMPERATURE MONITOR
R2658p	
061300524 Alternative 850106.000000	
317.553	
1066830-008	
Wdg 210-71863se	
750264	
5362462-080	
5362500-020	
Ppce-System-3	
117459-04 4 A	
Ctc -1200 A İin Tasima Cantasi	
804.977	
1066830-100	
Qm280t-4-7	
5362500-080	

Am-Mgaaa/GI	
03-756103-25	
Dxuc01031030-R09-G	
100-1759 (Pwb Micro Interface 933)	
Dcs33-36e	
099.392	
03-J759501-10	
5362500-300	
Nsk 187 387 388	
M83-50679-001-2	PNEUMATIC TRANSMITTER SK MODEL NT
Mod. 2000	
Dcs60-20e	
Dcs150-8e	
M1 600 ? 1600°C; Cod.091.580	
100-1207-J	
Hyn-5003 24v	Ametek prestolite motor
100-2045	
1989-0-115-A-E	OUTPUT MODULE 16 CIRCUIT HIGH POWERED 115V
Sc-1302-I	4-20mA Isolated Voltage/Current Transmitter 1302
90p17x125dc1c24	DC Power Supply
1061-895	ISM-ECU Event Capture Unit ISM-ECU
998115366	
1986-1664	RESOLVER 30:1 INTERNAL GEAR REDUCER 10/1 FOOT MNT
Dcs100-12e	
Csc100	
Acs F1	
03-J750201-20	
1989-I/O-Bcd-3227-R-12-S-E-A-1	CONTROLLER QUICKSET 3
0.9m(36?) Probe For Wdg 1210	
#006 O-Ring; 300-6244 For 241ce	

Hydrocarbon Dew Point Analyzer Uz20721	ECU ECU
Usr-111-0025-0000	
T-975	
1/1x Series 2ac/Dc Power Supply	
Acs-124	
Å006 O-Ring; 300-6244 For 241ce Hydrocarbon Dew Point Analyzer	
100-1911	
Ka21-009-300g	PRESSURE TRANSDUCER
70986te	MEASURING CELL FOR FUEL COMPONENTS (HOT WIRE)
Nilfisk Gm 83 S¼p¼rge Motoru - S¼p¼rgemarket	NILFISK GM 83 S¼p¼rge Motoru - Belirtilen modele uygun muadil s¼p¼rge motorudur - İthal Ametek markası ¼r¼n¼d¼r - 220 V
5360726-01	
1989i/Obcd4022r12-Sea1	CONTROLLER QUICKSET 3
Has	
317.552	
041192f7 90-09020-001 Rev. A Oia (E56617) 116150-02 50 V Dc Nominal Motor	
280465001	
5362500-600	
Dcs8-140e	
1989-A16r12scm	CONTROLLER
00 107037	
100-1845	
5362462-600	
M280t-4-10	
750257	
Jha-4003-A	CONTACTOR 1200AMP
Dcs50-20e	
100lbf Chatillon	

1066830-080	
090-11782100	
Dcs150-7e	
5362462-060	
317.476	
1066830-01	
1061-888	ISM-CIU Communications Interface Unit ISM-CIU, ISM-1 CIU. 1061-685
Dpp Series Mechanical Force Gauge	P/N: DPP-50 Range: 0-50lb increments: 0.5lb
1989-Ca-16-R-12-S-C-X	CONTROLLER QUICKSET 3
951vp-1992-12	LINEAR DISTANCE TRANSDUCER QUICK-STIK 2
R8487	
90-Ax1 24v Dc	24V DC Relay Module
5362500-008	
061000062 230v 50 60hz	
470120	
00106772	
801691	
100,1578	
1066830-020	
Dcs300-3.5e	
M920127af50-03	
91562	
R7447	
80-219324-90	INVERTER CONTROL BOARD
03-J755201-00	
Jca 4673 MI00 – Fm / Prestolite Switch	
Model 5000	
1989-0-115-M-S	MECHANICAL RELAY OUTPUT MODULE 10AMP SPDT
5360801-01	
N1-194n	

100-1849	
1746-R1	SINGLE AXIS RESOLVER INTERFACE, ONE RESOLVER INPUT
2500ea0a4dx	240 VAC, 50/60 HZ, 0 AC RELAYS, 4 DC RELAYS, NO OPTIONS
117459-55	
3483 Me 4933 R	MFG CODE 0152 Please see attached photo
1989-Kp	REPLACEMENT KEYPAD WITH FLAT RIBBON CABLE, 18 INCHES LONG
1060-763	ISM-LPS LOGIC POWER SUPPLY
Dcs20-50e	
Dcs50-24e	
Dcs10-100e	
090 11782100	
3501d74h01	
M 280	
5362462-300	
T-620h	
90p17x6d1c4d	Panalarm Power Supply
1989-M-16-R-12-S-C-X	PROGRAMMABLE LIMIT SWITCH
Cut Monitor Cm2	
R1527p	
O700	
Wdg1200	
T-965	
5362500-060	
Dcs60-18e	