

Amot



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Amot Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Amot T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
4bodf11001-00-Del	Amot 3-way temperature control valve type B Nominal size: 4 "(100mm) Valve type: BO with flanges Housing material: Ductile iron BS 2789 grade 420/12 Connections: ANSI 150lbs RF flanges Element Code: 1096X110 / 43 ° C (38-47 ° C) No element with leakage Speccode DEL: element leak test mandatory, has to be ordered separately, flanges ANSI B16.5 150 lbs RF, stainless steel tag (please advise engraving when ordering)
Temperature Control Valve	
Temperature Switch-TS1, Type: 4140, 83-104/Set	Point 103 deg C,
Temperature Switch-TS2, Type: 4140, 83-104/Set	Point 95 deg C
3BRDF11507-00-BLX	AMOT 3- Way Thermostatic valve type B Nominal Bore: 3" (80 mm) Valve type: BR with Flange and Manual Override Housing material: Ductile Iron BS 2789 Grade 420/12 Connection: Flanged ANSI 150lbs RF Sealings: Nitrile Element Code: 2433X115/46° C (40-50° C) Type approval Bureau Veritas - details accord. to BV type approval certificate Speccode BLX: Foundry cert. 3.1 mandatory according to specification, 1 cert per valve in need, has to be ordered separately, Flange ANSI 150 lbs RF
	AMOT 3- Way Thermostatic valve type B Nominal Bore: 2" (50 mm) Valve type: BR with Flange and Manual Override Housing material: Ductile Iron BS 2789 Grade 420/12

2BRDF11507-00-BLX	Connection: Flanged ANSI 150lbs RF Sealings: Nitrile Element Code: 2433X115/46° C (40-50° C) Type approval Bureau Veritas - details accord. to BV type approval certificate Speccode BLX: Foundry cert. 3.1 mandatory according to specification, 1 cert per valve in need, has to be ordered separately, Flange ANSI 150 lbs RF
3BOCB18501-E2-AA	AMOT 3-way Temperature control valve type B
2 1/2BOCB16001-E2-AA	AMOT 3-way Temperature control valve type B Valve nominal bore: 2 1/2" (65 mm) Valve type : BO with flanges Housing material: cast iron Port connection: Flanged ND 10 Element Code: 1096E160/71° C (68-78° C) 2 elements with leak hole 1.6 mm Bureau Veritas type approved - details accord. to BV type approval certificate
4BRCB17007-00-AZA	Amot 3-way Type BR temperature controller Nominal size: 4 " (100mm) Valve type: BR (with emergency manual adjustment) with flanges Housing material: gray cast iron Connections: Flanges ND 10 Item Code: 2433X170 / 77 ° C (74-83 ° C) No elements with leakage holes Bureau Veritas type-examination - details according to BV type-examination certificate AZA = incl. Foundry certificate 3.1
CERT-UK-1005-FOUNDRY 3.1	
4140CK1E12AA0-EE	AMOT single stage Pressure switch type 4140C Set point: unset bar - if the free of charge presetting of the set point ex factory is requested, please advise set point when ordering. , Microswitch type K Standard finish Conduit Thread: PG 13,5 Pressure connection: 1/8" BSPT _r Pressure Range: 0,28-3,45 bar falling 0,48-3,72 bar rising
4140CK1E12AA0-EE	AMOT single stage Pressure switch type 4140C Set point: unset bar - if the free of charge presetting of the set point ex factory is requested, please advise set point when ordering. , Microswitch type K Standard finish Cable Bonnet PG 13.5 Pressure connection: 1/8 "BSPT _r Pressure Range 2: 3.45 - 6.89 bar falling 3.66 - 8.34 bar rising
EA10017S220A-BMF	For AMOT temperature control valve Model GEF Electric actuator Model : EA Size/ Nominal torque: 100/ 100Nm Shaft connection: 17mm square Operating voltage: 220V Extras: 4-20mA electronic positioner with position feedback
46770X151-BMF	Housing for 4G valve, viton and bronze
06GGHDBS12P10200-AA	
1 1/2EFCB11001-0-AA	
1 1/2ELCT11001-0-AA	
1 1/2ELCU11001-0-AA	
1 1/2EMCF11007-0-AA	
1/2CMCU10001-0-AA	
1092	

1096E130	
1096X057-SPR	
1096X100-SPR (x100)	
1096X105-SPR (X105)	
1096X105-SPR, 105F	
1096X165-SPR	
1096X175-SPR	For AMOT Temperature controller Type B Thermostat element 1096X175 Average control temperature: 79°C (77-85°)
1096X175	
1096x175SPR	
11007L001	
11009L001	
1182	
12GEFDBA032-AA	
1CMAU15001-0-AA	
1CMCU11001-0-AA	
2 1/2BOCB09501-E2-AA	
2 1/2BOCB11001-00-AA	
2 1/2BOCB12001-E2-AA	
2 1/2BOCB17001-00-AA	
2.580CB130-00-AA	
20124X601	
207L001	
21/2BOCB10501-00-AA	
21338X001	
2400D16J3-AA	
2433P110	
2433X095-SPR	SPARE ELEMENT ASSEMBLY 95F (35C) CONTROL TEMP.
2433X115-SPR	
2433X170	
26101AIN-AA	

2BCSJ17001-00-AA
2BFBB12005-00-AA
2BRCB 17007 - OO-AA
2BRDC10007-00-AA
3/4CMAU11082-D-AA
33BRCB17507-00-AA
3555I001
380CB16501-00-AA
3BOCB16001-00-AA
3BOSH13003
3BRCB17007-00-AA
3GEFCBA032-CBL
4140CK1011AA0-EE
4140CK1011AA0-E
4140CK1D11AA0-EE
4140CR1F11AA0-EE
4140D R3P00CE3-EE
4140DH1E00EE5-AEA
4140DK1D00CE3-EE
4140DK1D00CE4-EE
4140DK1E00CB3-EE
4140DK1E00CE3-EE
4140DK1E00CM1-EE
4140DK1H00CE1-EE
4140DR1V00CG5-EE
4140E-H1C00CB3-EE
4140EH1E00CC4-EE
4140EK3P00CD4EE
4140TK1E00E4-EE
4155A120D-ACW

41773X006	
41788 ASM	
4254M01R6AA00N-AA	
4261D,3"	
4261D,4"	
4261M05A172-AA	
43406L035	
44039L002	
4418F-6-E-8-X-G-04-AA	
4418FBE4XR00-CXI	
45317X	
46342X151	
46342X205	
46342X251	
46342X252	
46342X401	
46342X404	SEAL KIT - 4BRB, 4BRC, 4BRD, NITRILE Inculde: 1183 ORING - BUNA - BLACK EA 4 358 O RING Nitrile EA 4 OMMB00096 SEAL KIT INFO SHEET EA 1 46943L002 GASKET - 4B - NITRILE EA 1 761 O RING BUNA N EA 4
46342X505	Viton seal kit for AMOT 3-way regulator Type BM/BR Viton seal kit 5", consisting of: 6 x O-ring 1183L002 6 x O-ring 358L001 1 x housing seal 47132L002 (for valves up to approx. I/2010) 6 x O-ring 761L001 as housing seal (for valves from approx. II/2010)
46342X604	
46342X404	
47961X106	
47981L014	
48713X002	
49818L225	
4BOCB13001-00-AA	
4BRCB12007-00-AA	

53709L001	
5736	
5BRCB16507-00-AA	
5BRDC1100700BWY	
5BRDC11507-00-AA	
66280X2	
676L125	
6BRCB09507-00-AA	
6GEFCBA023-AA	
6GEFCBA031-AA	
80318X062	
80319X062	
8071D000D-AA	Type 8071D000DAA Panel Montage Inputs : 1= PT100 2= not fitted Outputs: 1= SSR 2= not fitted Communication: Comms not fitted Direction: Direct action
8071D120D-AA	
81964X201	
81964X205	
82046X210	
82334X101	
82382X006	
8253M131AK-AA	
8412114	
8412114	
9585L001	
9778C110D	
99708891206	
99708891207	
99708891218	
CLD-100	
D121S-AP	
EA 100	

EA20017S2200-BMF	
ES0200.MID04A.22NO	
ESD AMOT-4057	
MODEL B , ILC5H50286400107	
PN: 43406L040,MODEL: 6GPDCBF O M-AA SN: E50760-001, REF: 20	
PN: 43615L001, MODEL: 6GPDCBF O M-AA SN: E50760-001, REF: 10	
PN: 46457L220, MODEL: 6GPDCBF O M-AA SN: E50760-001, REF: 8	
RO50S-120 01	
Ser No: 4231/10	
TYA432-45 50A	
82046X210	ACTUATOR, PNEUMATIC FS200, SPARE Spare Pneumatic Actuator incl. Positioner suitable for mode of operation anticlockwise reverse acting or clockwise direct acting
226.0147-150-039	3-way temperature controller DN 150 with 3 round flange connections and 8 interchangeable tube slides with expansion thermostat 237.0122-039- 507 (nickel plated) Temperature range 39 - 50°C Seal set NBR Housing made of EN-GJL 250 Flange connection according to EN 1092-2 Shape B dimensioned and drilled according to: PN 16 Nominal width: 150 mm Any installation position With emergency manual adjustment to mechanical adjustment of tube slider to any Position in case of failure of the thermostat
SVX394	X-VALVE SOLENOID 24V 3" MICROSWITCH MANUAL RESET / CLOSE Orifice: 3" (76mm) Version with electric solenoid 24 V DC with micro switch + manual shutdown Energized when switched off
HAX-314	
HAX-309	hose connector 3" for 3" X-valve
HAX-523	Chalwyn hose connection Type HAX-523 from 5" (127mm) to 6" (152mm)
4140CK1E12AA0-EE	AMOT single stage Pressure monitor Type 4140C Set: 4.2 bar (F) Micro switch type K standard design Cable entry PG 13.5 Pressure connection: 1/8" BSPT Pressure range 2: 3.45 - 6.89 bar falling 3.66 - 8.34 bar increasing
SVX594	
3BRCB17007-00-AA	AMOT 3-way Type B temperature control valve Orifice: 3" (80mm) Valve type: BR (with manual override) with flanges Housing material: cast iron Connections: Flanges ND 10 Item

	Code: 2433X170/77°C(74-83°C) No elements with leak holes Bureau Veritas type-approved
8060A12-AA	For AMOT Thermostatic Valve Type G 3-wire PT 100 Temperature Sensor Conduit connection M20 Installation Thread: 1/2" BSP TR
SVX394	X-VALVE SOLENOID 24V 3" MICROSWITCH MANUAL RESET / CLOSE Orifice: 3" (76mm) Version with electric solenoid 24 V DC with micro switch + manual shutdown Energized when switched off
HAX-319	For valves with 76mm (3") diameter Transition piece from 76 mm (3") to 102 mm (4") outer diameter
8BOCB13501-00-AA	AMOT 3-way temperature controller type B.
SVX594	Air inlet shut-off valve Type SVX-594 Orifice: 5" (127mm) Version with electric solenoid 24 V DC with micro switch + manual shutdown Energized when switched off
SVX394	X-VALVE SOLENOID 24V 3" MICROSWITCH MANUAL RESET / CLOSE Orifice: 3" (76mm) Version with electric solenoid 24 V DC with micro switch + manual shutdown Energized when switched off
SVX384-	X-VALVE SOLENOID 12V 3" MICROSWITCH MANUAL RESET / CLOSE
HAX-513	For 127 mm (5") valves diameter
HAX-314	Transition piece from 76 mm (3") to 89mm (3.5")
HAX-319	For valves with 76mm (3") diameter Transition piece from 76 mm (3") to 102 mm (4") outer diameter
CSD-400	Chalwyn tow rope D valve model D29, D30 and D41- 400mm long
CSD-300	Chalwyn pull cord to D valve 300cm long
RTD-200	RTD-200 T-pull handle
SERVIS KIT 46342X8 L/O 8BO NITRILW	
SERVIS KIT 46342X8 L/O 8BO NITRILW	
VALVE 3mm 90-100°C GASKET HT/OI	
4140CK3P41AA0-EE	Type 4140C single stage unset Micro switch type K Corrosion protected Cable entry PG 13.5 Pressure connection: 1/8" BSPTTr Pressure range 1: 0.28-3.45 bar falling 0.48-3.72 bar increasing
4140CK1E11AA0-EE	AMOT single stage Pressure monitor Type 4140C ***Upon receipt of the order, we need the end point in increasing or decreasing, alternatively this will be sent unadjusted*** Micro switch type K standard design Cable entry PG 13.5 Pressure connection: 1/8" BSPTTr Pressure range 1: 0.28-3.45 bar falling 0.48-3.72 bar increasing

1096X160-SPR	Type B temperature controller Thermostatic element 1096X160 Control temperature: 71°C (68-78°)
4BRCB17007-00-AZA	Amot 3-way Temperature controller type BR Orifice: 4" (100mm) Valve type: BR (with manual override) with flanges Housing material: cast iron Connections: Flanges ND 10 Item Code: 2433X170/77°C(74-83°C) No elements with leak holes Bureau Veritas type-approved - details according to BV type-approval certificate AZA = incl. foundry certificate 3.1
CERT-UK-1005-FOUNDRY	Foundry certificate BSEN 10204-3.1 per valve is 1 Foundry Certificate necessary
Ultrasonic level switch COMPAGNIA TECNICA MOTORI	SPA 2433X195 Thermostatic Control Valve Temperature Element Block 6BRRJ1950700DDB Material: Brass/Steel Drawing_Product: APPENDIX N. 6_N.A. SPIR:3000-CTMS41230001-P11-00001-00_01_2
6BRRJ19507-00-DDB	Thermostatic control valve Manufacturer: AMOT Model: 6BRRJ19507-00-DDB Size: 6 = 6" Type: BR = manual override Material: R = 316 stainless steel outer parts Connection: J = ASME 150 lb Control temperature: 195 = 195°F Thermocouple Type: 07 = Buna N/Nitrile Orifice Dimensions: 0 = None Number of Holes: 0 = None Customer Specific Requirements: DDB
6BRRJ12007-00-DDB	Thermostatic control valve Manufacturer: AMOT Model: 6BRRJ12007-00-DDB Size: 6 = 6" Type: BR = manual override Material: R = 316 stainless steel outer parts Connection: J = ASME 150 lb Control temperature: 120 = 120°F Thermocouple Type: 07 = Buna N/Nitrile Orifice Dimensions: 0 = None Number of Holes: 0 = None Customer Specific Requirements: DDB
Ring set COMPAGNIA TECNICA MOTORI SPA 46342X604	Service Ring KIT Material:NITRILE Drawing_item:Appendix N. 7_7,9,17 SPIR:3000-CTMS41230001-P11-00001-00_01_2
6BRRJ11507-00-DDB	Thermostatic control valve Manufacturer: AMOT Model: 6BRRJ11507-00-DDB Size: 6 = 6" Type: BR = manual override Material: R = 316 stainless steel outer parts Connection: J = ASME 150 lb Control temperature: 115 = 115°F Thermocouple Type: 07 = Buna N/Nitrile Orifice Dimensions: 0 = None Number of Holes: 0 = None Customer Specific Requirements: DDB
4BP1J1104800-FFS	Thermostatic control valve Manufacturer: AMOT Model: 4BP1J11048-0-0-FFS Size: 4 = 4" Type: BP = Stainless steel B series special valve with manual override Material: 1 = 316 stainless steel outer parts Connection: J = ANSI B16 .34 Class 150 Control Temperature: 110 = 110°F Heater Type: 48 Port Dimensions: 0 = N/A Number of Ports: 0 = N/A Customer Specific Requirements: FFS
4BOCF14002-D4-AA	AMOT 3-way Type B temperature control valve As an alternative to the complete control valve, we offer you the corresponding thermostat elements and the sealing kit in items 2 1 and 2 2. . Orifice: 4" (100mm) Valve type: BF with flanges Housing material: cast iron Connections: Flanges ANSI 125lbs Element Code: 1096P140/60°C (57-66°C) Nickel

	plated elements Gasket material: Viton 4 elements with leak hole 3.2 mm Type-approved by Bureau Veritas - detail according to BV type-approval certificate
1096P140D	For AMOT temperature controller type B Thermostatic element 1096P140 Plated version Average control temperature: 60°C (57-66°C) with 3.2 mm leak hole
46342X402	Gasket set Viton complete for AMOT controller Type 4BO consisting of: 1 x housing seal No. 46943L002 (for valves up to approx. 1/2010) 4 x O-Ring #1183L002 Viton 4 x O-ring No. 761L001 as housing seal for valves from approx. II/2010)
SVX-594	Chalwyn air inlet shutoff valve Type SVX-594 Orifice: 5" (127mm) Version with electric solenoid 24 V DC with micro switch + manual shutdown Energized when switched off
SVX384	X-VALVE SOLENOID 12V 3" MICROSWITCH MANUAL RESET / CLOS Orifice: 3" (76mm) Version with electric solenoid 12 V DC with micro switch + manual shutdown Energized when switched off
HAX-314	Transition piece from 76 mm (3") to 89mm (3.5")
HAX-513	For 127 mm (5") valves diameter
HAX-304	hose connector 2.3/8" (60mm)
4BOCB09501-00-AA	AMOT 3-way temperature control valve type B Orifice: 4" (100mm) Valve type: BO with flanges Housing material: cast iron Connections: Flanges ND 10 Element Code: 1096X095/35°C (29-41°C) No element with leak hole Bureau Veritas type-approved - details according to BV type-approval certificate
1096X095-SPR	For AMOT Type B temperature controller As an alternative to the complete valve in item 1 1, we offer you the usual spare parts in items 2 1 - 2 4. . Thermostatic element 1096X095 Average control temperature: 35°C (29-41°)
46342X401	Seal kit nitrile complete for AMOT controller Type 4BO consisting of: 1 x housing seal No. 46943L002 (for valves up to approx. 1/2010) 4 x O-ring #1183 4 x O-ring No. 761 as housing seal (for valves from approx. 2/2010)
9585L002	For AMOT temperature controller type BR/BM as well as BO,BF (current design, made in UK)
44039L002	For AMOT Type B temperature controller Flange gasket 4" MET 2/3 Part No.: 44039L002
4BRCB09507-00-AA	AMOT 3- Way Thermostatic valve Type B Valve nominal bore: 4" (100mm) Valve type : BR (Manual Override) with flanges Housing material: cast iron Port connection: Flanged ND 10 Element Code: 2433X095/ 35°C(29-41°C) No elements with leak hole Bureau Veritas type approved - details accord. to BV type approval certificate
1096X160-SPR	Thermostat element 1096X160 Control temperature: 71°C

	(68-78°) (Cummins QSK50)
7002 Swing Gate Air Shut Off	
7002 Swing Gate Air Shut Off (Cummins QSK50)	
F1421000228413 FUEHLER4102J04 79	4102J04-04174-AMU (79°FUEHLER4102J04 79 4102J04-04174-AMU (79°C) MANUFACTURER PART NO: 4102J04-04174-AMU
F1320000185129 AMOT TEMP. WITH VALVE M14X2	FUSEROD 323MAMOT TEMP. VALVE M14X2 WITH FUSEROD 323M MANUFACTURER PART NO: 4103DA20A-174-BLF
F1421000228412 TEMPERATURE SENSOR TYP	4102J18-18174-AMUTEMPERATURE SENSOR TYP 4102J18-18174-AMU S.A. MANUFACTURER PART NO: 4102J18-18174-AMU
4BRCB09007-00-AA	AMOT 3-way Temperature control valve type B Nominal width: 4" (100mm) Valve type: BR (with emergency manual adjustment) with flanges Housing material: gray cast iron Connections: flanges ND 10 Element Code: 2433X090/32°C (27-35°C) No elements with leakage holes Bureau Veritas type-tested
4BRCB17007-00-AZA	Amot 3-way Temperature controller type BR Nominal width: 4" (100mm) Valve type: BR (with emergency manual adjustment) with flanges Housing material: gray cast iron Connections: flanges ND 10 Element Code: 2433X170/77°C(74-83°C) No elements with leakage holes Bureau Veritas type tested - details according to BV type certificate AZA = incl. foundry certificate 3.1
2433X195-SPR	Temperature controller type BM/BR Thermostat element 2433X195 Average control temperature: 91°C (87-98°)
1096X145-SPR	Temperature controller type B Thermostat element 1096X145 Control temperature: 63°C (60-69°)
3BOCF13001-B2-AA	THERMOSTATIC VALVE
LO THERMOSTATIC VALVE DN150	AMOT(with thermostatic element) (SAE 40) (Code:130 Control Temp: 54 °C) DN150
LO THERMOSTATIC VALVE DN200	AMOT(with thermostatic element) (SAE 40) (Code:130 Control Temp: 54 °C) DN200
HT THERMOSTATIC VALVE DN150	AMOT(with thermostatic element) (Code: 180 Control Temp: 82 °C) DN 150
LT THERMOSTATIC VALVE DN150	AMOT(with thermostatic element) (Code: 100 Control Temp: 38 °C) DN 150
SVX594 SHUT-OFF VALVE	Nominal width: 5" (127 mm) Version with electric solenoid 24 V DC with micro switch + manual shutdown Live when switched off
SVX394 SHUT-OFF VALVE	X-VALVE SOLENOID 24V 3" MICROSWITCH MANUAL RESET / CLOSE Nominal width: 3" (76 mm) Version with electric solenoid 24 V DC with micro switch + manual shutdown Live when switched off

47961X103	Service Kit fr AMOT 3-Way Temperaturregler Type 3GEF, 3GPD Service kit consisting of: 1 piece 43419L002 pin 2 pieces 43635L002 Viton O-ring 1 piece 43636L002 Viton O-ring 2 pieces 46457L016 bearings
1096X160-SPR	For AMOT temperature controller type B Thermostat element 1096X160 Control temperature: 71°C (68-78°)
1096X130-SPR	For AMOT temperature controller type B Thermostat element 1096X130 Control temperature: 54°C (51-60°)
Thermostat Valve No.	3363E160, 160 Deg F (Thermostat Valve No. AMOT 3363E160, 160 Deg F)
46342X604	Nitrile seal kit complete for AMOT regulator type 6BR/BM consisting of: 9 x O-ring 1183 9 x O-ring 358 1 x housing seal 47733 for valves up to approx. end of 2010 9 x O-ring 761 as housing seal for valves from approx. 2011
2433X110-SPR	For AMOT Temperature controller type BM/BR Thermostat element 2433X110 Average control temperature: 43°C (38-47°)
ASP001-180-00	Wax thermostat 79-88°C Wax thermostat 79-88°C Third party spare part Replaces: AMOT 1096X180 AMOT 47536X180 and Thermoreg/MVA 2001A-180 Setpoint: 180°F/82°C Temperature range/Working range: 79-88°C Allowed tolerance: ± 1.5 °C
1096X180-SPR	For AMOT Temperature controller Type B Thermostat element 1096X180 Control temperature: 82°C (79-88°)
2433X100-SPR	Thermostat element 2433X100 Average control temperature: 38°C (34-42°)
THERMOSTATIC VALVE	SEAL KIT, PN: 46342X505, SN: E00084876-1
HAX-314	Transition piece from 76 mm (3") to 89mm (3.5")
HAX-319	For valves with 76mm (3") diameter Adapter from 76 mm (3") to 102 mm (4") outer diameter
SVX594 SHUT-OFF VALVE	
3BOCF13001-B2-AA	THERMOSTATIC VALVE
1096X115-SPR	For AMOT Temperature controller Type B Thermostat element 1096X115 Control temperature: 46°C (40-50°)
5435X130	Temperature controller Type E thermostat element 5435X130 Middle Control temperature: 54°C (49-60°C)
4140CR3S41AA0-EE	QUOTE PART NUMBER AMOT Single-stage pressure switch Type 4140C Microswitch Type R Micro switch: High Vibration/Shock resistant with gold plated contacts Corrosion-protected cable entry PG 13.5 Pressure connection: 1/8" BSPPL Pressure range 1: 0.34 - 4.27 bar

2800D002-AA	AMOT Safety and shut-off device type 2800 Housing: Aluminium, black anodized, front shaft Pressure connection: 1/4" NPT With reset lock Set to 0.7 bar (f)
47224X	GP valve Pneumatic positioner F10 No 47224X
4140CK1V11AA0-EE /	AMOT Single-stage pressure switch type 4140C SET: 2BAR (F) Microswitch Type K standard version cable entry PG 9 Pressure connection: 1/8" BSPT Pressure range 1: 0.28-3.45 bar falling 0.48-3.72 bar increasing
EA100	Regulator temp. AMOT EA100
4475B031-AA	
4457A011K1DAB	
4110B2U20F-AA	
2800D002-AA	AMOT Safety and Storage device type 2800 Housing: aluminum, black anodized, front shaft Pressure connection: 1/4" NPT With reset lock Set to 0.7 bar (f)
3BOCF18001-E2-AA	
08GGHD2S12FBAAA-AA	
4475B031-RBN	
4457A011K1-DAB	
4110B2220F-AA	AMOT speed Monitoring valve type 4110
3BOCF18001-E2-AA-	
2800D002-AA-	AMOT Safety and Storage device type 2800
20100D130-0-ACB	
82434X001	EA/EB100 ACTUATOR LID - 'O' RING (BAGGED) 1 Stück 43564L001 O-Ring Nitrile
82434X003	1k POTENTIOMETER WIRED 'EA' (BAGGED)
82434X009	Capacitor. 6uF (Bagged)
83448X080	Service Kit for GGE Valve - 08GGH Service kit for GGE valves 08GGH consisting of: 1 piece 43603L002 O-ring Viton 1 piece 43602L002 O-ring Viton 1 piece 43607L002 O-ring Viton 2 pieces 43611L002 O-ring Viton 1 piece 43600L002 O-ring Viton 1 piece 43564L001 O-ring Nitrile 1 piece 43423L045 Spirol Pin 1 piece OMMGG00293 Service Kit Manual
EA10017S220A-BMF-	For AMOT Temperature control valve Model GEF Electric actuator Model: EA Size/Nominal torque: 100/100Nm Shaft connection: 17mm square Operating voltage: 220V Extras: 4-20mA electronic positioner with position feedback
8060A12-AA-	For AMOT Temperature control valve type G 3-wire PT 100 temperature sensor Cable entry: M20 Screw-in thread: 1/2"

TEMPERATURE SENSOR-8060A12-AA	BSP TR
8200B11H2-AA	SER. NO: R2832 SETTING: 5320HZ (R) RANGE: FSD 6000 HZ
1672E1F1-AA-	PRESSURE SENSING VALVE
1672E3F1-AA	AT THE POINT OF ORDER WE WILL NEED THE SET POINT IN RISING OR FALLING ALTERNATIVELY THE SWITCHES WILL BE PROVIDED UNSET 1672E Pressure sensing valve - NPT Threads, Range 50 - 300 PSI (F) - Seal material Buna
1672E3F1-AA-	AT THE POINT OF ORDER WE WILL NEED THE SET POINT IN RISING OR FALLING ALTERNATIVELY THE SWITCHES WILL BE PROVIDED UNSET 1672E Pressure sensing valve - NPT Threads, Range 50 - 300 PSI (F) - Seal material Buna
1672E3F1-AA--	AT THE POINT OF ORDER WE WILL NEED THE SET POINT IN RISING OR FALLING ALTERNATIVELY THE SWITCHES WILL BE PROVIDED UNSET 1672E Pressure sensing valve - NPT Threads, Range 50 - 300 PSI (F) - Seal material Buna
1 1/2EFCF18001-0-AA	1.5EFCF 3WAY THERM VALVE - 180F
1 1/2ELCT14001-0-AA	1.5ELCT 3WAY THERM VALVE - 140F Thermostatic valve Type E - Valve size: 1 1/2" - Model type: EL - Threaded connections - Material: Cast iron - Threaded NPT ANSI B2.1 - Control Temperature SW1 140 - Standard Element - Leak hole: None
2230C120G240FN-AA	2-WAY TEMP. SENSING VALVE TEMPERATURE VALVE NPT Installation & Port Threads Seal material Viton 1-3/8", 34.9mm install depth Calibrated to 240 Deg F
2230C120E185FN-AA	2-WAY TEMP. SENSING VALVE TEMPERATURE VALVE NPT Installation & Port Threads Seal material Viton 1-3/8", 34.9mm install depth Calibrated at 185 F
2185L102	ORIFICE,ALUM,NPT,0.8 MM - 2185L102
4155A220E-AA	SENSOR - TEMP Temperature valve - Installation BSP (T),Port BSP (T),std finish - Seal material: Viton - Element extension: 1.03" / 26mm
4143A001-AA	DIFFERENTIAL PRESSURE VALVE, STANDARD, ATEX APPROVED
1096X110-SPR	SPARE ELEMENT ASSEMBLY 110F (43C)
1096X095-SPR-	SPARE ELEMENT ASSEMBLY 95F (35C) CONTROL TEMP.
3BRBC10007-00-AA	
3BRCB10717-00-AA	3BRCB10717-00-AA - THERMOSTATIC VALVE
shaft	
CERT-UK-1000-2.1	CERT-UK-1000-2.1

2433X170-SPR	SPARE ELEMENT ASSEMBLY 170F (77C) CONTROL TEMP.
5BRC B170 07 00-AA	For 6 elements
3BRCB/C	For 2 elements
46011X290	CONV. KIT,33, 5, 6 AND 8BO TO BR, CODE 07
46342X304	SEAL KIT - 3BR, NITRILE
46011X190	CONV. KIT,2-4BO TO BR, CODE 07
Thermostat element	Operating temperature range: 72-80 °C Amot is the thermostat element used within the valve control mechanism.
3142-5D-258	SET: 35C thermostatic valve core
2433X120-SPR	SPARE ELEMENT ASSEMBLY 120F (49C) CONTROL TEMP.
46342X404-	SEAL KIT - 4BRB, 4BRC, 4BRD, NITRILE
2433X115-SPR-	SPARE ELEMENT ASSEMBLY 115F (46C) CONTROL TEMP.
2433X130-SPR	SPARE ELEMENT ASSEMBLY 130F (54C) CONTROL TEMP
SVX394-	X-VALVE SOLENOID 24V 3" MICROSWITCH MANUAL RESET / CLOSE
HAX-507	HOSE ADAPTOR 4 1/4" FOR 5" X VALVE
SVX-591	X-VALVE SOLENOID 24V 5" NO MICROSWITCH POWER TO SHUT
47981I026	
4140ck1v11aa0-Ee	AMOT Single step pressure switch type 4140C set point: 2.0 bar (F) Microswitch type K Standard finish Conduit thread: PG 9 Pressure connection: 1/8" BSPT Pressure Range 1: 0,28-3,45 bar falling 0,48-3,72 bar rising
4140dk1e00ce2-Ee	
2433x095	
46342x301	
1672e1f1-Aa	
1125X120	ASSY - ELEMENT - 120F
4634x401	
4500d	
Mpd2rt5p1	
2bfcbl1001-00-Aa	
4140er1e00ce2-Ee	

4140dk1e00cg4-Ee	single step Temp. switch Type 4140D
4140dr1v00cg3-Ee	AMOT Single Step Temperature switch Type 4140D Set: 80 ° C rising Microswitch type R standard design Cable gland: PG 9 Sensor protection sleeve 80 mm with thread 3/4 "BSPPI Temperature range 3: 66 - 87 ° C
479811028	
3/4cmat17006-0-Aa	
4057d029k1aa	
4420eh4f02	
2brcb 17007 ? Oo-Aa	
479811031	
4123c2110ba-Aa	AMOT Air start valve Manuel and Electrical Solenoid Valve line connection : Flanges to ND 40 DIN 2503 Pilot thread : 1/4" BSP Tr Vent thread : 3/8" Manuel operator position : Standart Coil voltage : 24 V DC Standart housing to IP43
2bcsj11001-00-Aa	
2 1/2bobf07511-00-Aa	
4140cr1e31aa0-Ee	
41773x006 6ged/Gpd	
1096x130-Spr	
4140ck1e11a0-Ee - Set: 2 Bar (F)	
58x4 1183	
3brcc09507-Oo-Aa	
80244x043b	
3/4cmau13001-0-Aa	
8012d050r0009r301	
4140dk1e00ce4-Ee	
1.5-Bocu-10001-00	
1125x130	
4110b3320f-Aa	
1096x175-Spr	
5brdf13007-00-Ahr	
3-Way Control Valve	

4140e-K1e00ce2-Ee	
5736 9h C27 29,5 Degree ,Three Way,Check Valve	
4140e120400aik-Ba	
Part No: 46457I025, Model: 6gpdcbf A216; M-Aa Sn: E50760-001, Ref: 6	
1096x140-Spr	For AMOT Thermostatic valve model B Thermostatic element 1096X140 regulating temperature: 60°C (57-66°C)
4140ck1e31aa0-Ee	
4140dk1e00cb2-Ee	
49260I002 Rev4	
11079I001	
4057d083k2-Aa	
308/255	
Model : 2-1/2boc-105-01 - , - 2 1/2bocc10501-00-Aa	
8060a12-Aa	
11080I001	
9113x001	
805947	
4420e4h4g2	
4429	
6410790	
47981I033	
1096x110	
8064c00-Aa	
P/N: 2 1/2bocc10501-00-Aa	
46342x201	
162/114	
4bocf14002-D4-Aa	
2433x075	
4140dk1e00ce1-Ee	

Pn: 43406l040, Model: 6gpdcbf Å216; M-Aa Sn: E50760-001, Ref: 20
47581l001
4140ck1e12aa0-Ee - Set: 4 Bar (F)
2 1/2bocb11001-F2-Aa
26101ain-Aa
9128x001
P/N 1096x130-E
1096x185-Spr
2230c120e096cnaa
4140 Dk1h00ce3ee
1/2elcu11001-A-Aa
1096x150
49259x Rev
4057d022h1-Aa
2brrc075-07-00-Aa
4140ck1e12aa0-Ee - Set: 5 Bar (F)
49592x
1205
4140er1e00ce2-Aeq
1096x-140/60
Pn: 46457l220, Model: 6gpdcbf Å216; M-Aa Sn: E50760-001, Ref: 8
49261x A14805-008
80243x043
4140fkieiiaao-Ee