Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Anderson Negele

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Anderson Negele Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Anderson Negele Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
TFP-161/030/6MM/6MM/MPU / MB0-150	74161.0311 Temp. Sensor 1xPt100, class A Length 30 mm, diameter 6 mm Sensor tip 6 mm With transmitter Process connection: G1 / 2 '' hygienic Electrical connection: M12 plug connection With the following configuration: Transmitter mpu-m range: 0-150 ° C WNR: 90251900 Origin: Germany Net weight 0.128 KG
Anzeige	
TSMF /M01/X/0/0037/03/X/0/0/H/15C/4	Temperature sensor for food Housing design: Mini version With the following configuration: Process connection TS M01: G3 / 8 "3mm sprung Neck tube variant X: no neck tube (<100 ° C) RTD Type 0: 1xPt100 Class A, 2-wire Sensor length TS 37 mm TS 03 protective tube diameter: 3 mm Reduction tip (from 50mm) X: without reduction Material TM sensor element 0 - 1.4404 without 3.1 Surface Ra TS 0: Ra <0.8µm (standard) Transmitter TSM H: TTM.H (hybrid) Measuring range TTM 15C: 0 ... 150 ° C Electrical connection TSM 4: M12 plug 1xPt 4pol
EL /061/01/109/1/1/1/1/A/0/0/0/0	Pressure gauge for food applications EL With the following configuration: Measuring range 061 - 0...10 BAR Fixed value for Logo 01 - Fixed value Process connection EL 109 - SMS 38mm, female Connection direction 1 - below Cushioning 1 - glycerine filled case Calibration option 1 - zero point Transfer liquid 1 - paraffin oil/ med. white oil

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Material A - standard Temperature 0 - default Lens / glass 0 - standard Surface 0 - default Fixed value 0: Fixed value Unfortunately we cannot offer you the EL061851091111A0000 with the configuration ..85.. This EL is a special version of the EL/061/01/109/1/1/1/1/A/0/0/0/0 offered here, which is sold for selected partners is reserved. The offered EL/ 061/01/109/1/1/1/1/A/0/0/0/0 offers the same range of functions.
NSL-F /00/0650/10/S01/O/2/I42/M/X/ M/X/X	Potentiometric level sensor, Output: 4...20 mA, analogue active Auxiliary voltage: 18...36 V DC With the following configuration: Version NSL-F 00: Straight version Bar length EL 650 mm Bar diameter NSL 10: 10 mm Process connection S01: CLEANadapt G1" Material certificate 3.1 O: Without material certificate Installation position 2: from above, head vertical Output signal I42: IO-Link, 1x4...20mA Electrical connection M: 1x M12 - 4p plug, analog Interface/Display X: no display Lid M: stainless steel without viewing window PEEK insulator at rod tip XX: Rod end without insulation Special configuration X: Standard configuration The device you requested is no longer available with the A4x signal module, which is replaced by the compatible successor I4x with an additional IO-Link interface.
TSMF /C01/X/0/0030/04/X/0/0/H/15C/ 4	Temperature sensor for food Housing design: Mini version With the following configuration: Process connection TS C01: CLEANadapt M12 Neck tube variant X: no neck tube (<100 °C) RTD Type 0: 1xPt100 Class A, 2-wire Sensor length TS 30 mm Protection tube diameter TS 04: 4 mm Tip reduction (from 50mm) X: without reduction Material TM sensor element 0 - 1.4404 without 3.1 Surface Ra TS 0: Ra<0.8µm (standard) Transmitter TSM H: TTM.H (hybrid) Measuring range TTM 15C: 0...150 °C Electrical connection TSM 4: M12 connector 1xPt 4-pin.
EL /061/01/004/1/0/1/1/A/0/0/0/0	Pressure gauge for food applications EL With the following configuration: Measuring range 061 - 0...10 BAR

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Fixed value for Logo 01 - Fixed value Process connection EL 004 - Tri-Clamp 1.5" connection direction 1 - bottom Damping 0 - Standard / without damping Calibration option 1 - zero point Transfer fluid 1 - paraffin oil/ medical white oil Material A - Standard Temperature 0 - Standard Lens / Glass 0 - Standard Surface 0 - Standard Fixed value 0: Fixed value
TFP-161/050/6MM/6MM/MPU PT100	
TFP-164/00/MPU PT100	
TFP-41/050/6MM/3MM/MPU PT100	
MAN-63/TC3/4/0...7 bar/GZ/U	
EK 055 01 1 002 1 1	With the following configuration: Measuring range 055: -1.0...+2.0 BAR Value for Logo 01 - Fixed value Connection direction 1 - bottom Process connection EK 002 - Tri-Clamp 3/4" Transfer fluid 1 - paraffin oil/ medical white oil Damping 1 - without
EK /475/01/1/002/1/3	With the following configuration: Measuring range 475: -1.0...+6.0 BAR Value for Logo 01 - Fixed value Connection direction 1 - bottom Process connection EK 002 - Tri-Clamp 3/4" Transfer fluid 1 - paraffin oil/ medical white oil Damping 3 - ventilated housing, CPM-An
TSBF /N01/X/0/0050/06/X/0/0/H/15C/0/1/S	7400 Food temperature sensor DIN B enclosure With the following configuration: Process connection TS N01: without thread Neck tube variant X: no neck tube (<100 °C) RTD Type 0: 1xPt100 Class A, 2-wire Sensor length TS 50 mm Diameter of protective tube TS 06: 6 mm Tip reduction (from 50mm) X: without reduction Material TM sensor element 0 - 1.4404 without 3.1 Surface Ra TS 0: Ra<0.8µm (standard) Transmitter TSB H: TTB.H (Hybrid) Measuring range TTM 15C: 0...150 °C Display orientation TSB 0: no display, head vertical

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Electrical connection TSB 1: 1x cable gland Lid for TSB S: Stainless steel lid Successor to the TFP-49/100/6MM/6MM/MPU
Nwm-141-Gwl	
Dry Run Protection Pump/1	
Sl5088100001296	LEVEL TRANSMITTER CALIBRATED WEIGHT TO 129.6
Empty Signal Tf/G 9.8	
Tpp01200411	PRESSURE TRANSMITTER
Vgw-Dc	
Sbc52p	COUNTER
Emz-132	
Ha6071g00201205	PRESSURE TRANSMITTER, CONDUIT HOUSING, 0-100 PSIG RANGE, 3/4IN TRI-CLAMP CONN., STANDARD SENSOR, 316LSS DIAPHRAGM, EP, 25 FT. CABLE
Ncs-Gwl-11	
Vnv-Wdh	
Gb1-070g097121	PRESSURE INDICATOR DIFFERENTIAL 120VAC 20MA
7442.0184, Tfp-42p/017/4mm/4mm/ Mpu /Tb0-200	
Sl5088110500396	TRANSMITTER 0-30IN MIN TO 0-140IN MAX CAL 39.6IN
Pulse100	LIQUID LEVEL MONITOR
Sl-5-093-1-0-10-01386	TRANSMITTER 0-140MAX
Sr077g00501100	TRANSMITTER
71100010002400w	CHART RECORDER 115/230VAC
Sr077g004g1100	TRANSDUCER
Rsp10a000	CONTROL
Sl6089100102040	LIQUID LEVEL TRANSMITTER (SS)
Sp100b1	PRESSURE TRANS

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Sl6093100102000	LEVEL CONTROL
Sy070g0051124	PRESSURE TRANSDUCER
Sr077g01701100	SANITARY PRESSURE TRANSMITTER CAL RANGE 0-300PSIG
Tfp014005110000	PRESSURE TRANSMITTER 0-300PSIG
Sr074g00501100	PRESSURE TRANSMITTER 0/160 PSIG 2IN TRI-CLAMP SS

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.