



Aplisens

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Aplisens Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Aplisens Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
4-20mA Passive Differential Pressure	Sensor to monitor the differential pressure of the chiller water line at 0-6bar pressure Half finger cuff must be connected
APR2200-ALW	
06163019	
2VM-EP-SS6-20M-RM	
ĐÑ-2000 aletnative is APR-2000GALW	
APC-2000	
APC-2000ALW/Q24/	
APC-2000PZ	
APR-2000ALW (Art.Nr: APR-2000ALW/Exia/-0,5...7kPa/C)	
APRE-2000	
APRE-2000 (1/4" NPT)	
APRE-2000G	
APRE-2000G/N/	
APT-2000ALW	
APC-2000AL	
ATLR.PT100.NI100	
CTR/ Pt100/ A/ 3/ d=6mm/ AISI316/ L=50mm/ S=50mm/ DIN 25/ PZ/ KZ/ Q/ RU	
CTR/ Pt100/ A/ 3/ d=6mm/ AISI316/ L=70mm/ S=0mm/ FP (G3/4")/ PZ/ KZ/ Q/ RU	
CT-	
R/NA/Pt100/B/3/d=7mm/L=100mm/S=50mm/MP(M20x1,5)/AISI/AT/0...100C/23mA/RU	
CTR-ALW/WW	
CTR-Pt-100/Q/A/4/C/3/L=20/G1/8/Lp(силикон)=10m/RU	
CTR-Pt-100/Q/A/4/C/3/L=20/G1/8/Lp(силикон)=20m/RU	
ERH-01-06-1-1	

[LI-24ALW](#)[MS-100](#)[MS-100K](#)[MS-100K/Gly zerin](#)[PC -28 0-2.5 MPa PD M](#)[PC-28/ Q24/ 0...10bar/ M12/ G1/4/ RU](#)[PC-28/ Q24/ 0...10bar/ PK/ G1/4/ RU](#)[PC-28/0...0,6MPa/PD/G1/2/RU](#)[PC-28/0...1.6MPa/PD/ P/ RU](#)[PC-28/0...60kPa/ PD/ P/ RU](#)[PC-28/0...](#)[PC-28/Q05/0...0,6MPa/PD/M/RU](#)[PC-28/Q05/0...1,6MPa/PD/M/RU](#)[PC-28/Q05/0...1MPa/PD/M/RU](#)[PCE-28.SMART/0...25bar/PD/G1/4"](#)[PCE-28.SMART/0...25bar/PM12\(IP67\)/G1/4"](#)[PCE-28.SMART/0...70bar/PD/G1/4"](#)[PCE-28/ Exia / 0...1MPa / PK / CM20x1.5](#)[PCE-28/Exia/0...1,6MPaabs/PD/M](#)[PCE-28/Exia/0...600kPaabs/PD/M](#)[PR-28/0...6,3 kPa/PD/C/VM-3/](#)[SG-16/0...50mH2O/Letfe=51m/RU](#)[SG-25S.Smart](#)[SGE-25](#)[SGE-25 S](#)[WW-11N](#)[WW-45 \(PMS-11K\)](#)[APC-2000 ALW/IP67/0...0,7MPa/GP/RU](#)[PC-28](#)[CT-R/ NA/ Pt100/ B/ 3/](#)[APRE-2000G](#)

Differential pressure transmitter with HART protocol, €340.00 €340.00 - Stainless steel housing with angle plug DIN 43650, -ATEX compliant: no - Output signal: 4...20 mA + HART, - Sensor measuring range (?P): - 7...7mbar, -Set measuring range: must in case of order be specified -Process connection: PCV Art.No: APRE-2000G/-7...7mbar/PCV Stat. Item number: 9026 20 20 Country of origin: Poland

KR08150595	
PCE-28/0...25bar/PD/CG1/2"	Pressure transmitter with angle plug according to DIN/EN 175301, - Measurement accuracy: 0.2% - Measuring range: 0...25 bar -Output signal: 4...20mA, -Process connection: CG1/2 Art.Nr: PCE-28/0...25bar/PD/CG1/2" TAG No.: PT-401; PT-501; PT-557 Stat. Item no.: 90 26 2020 Country of origin: Poland
PT100 CT136/100/1/2NPT/Pt100/A2	
CT-GN1-Pt100-A-3/OG2.9/L=	Thermometer with NA connection head with transmitter, - Sensor type: Pt-100, Kl. A- 2- wire, -Measuring range: -10...60°C, - Protection tube: ø 9 mm; 100mm long, -Process connection: 1/2"NPT Stat. Item number: 90251900 Country of origin: Poland
WW-11ALW	Backlit display -Current input 4...20 mA -Aluminum casing -Protection class IP 66 -ATEX Compliant: Exia Art.No: WW-11ALW/Exia
APR2200-ALW	IP67
PRE-50G	Differential pressure transmitter €342.00 €342.00 with angle plug DIN 43650 -Measurement accuracy: 0.6% - Measuring range (?P): 0...7 kPa - Output signal: 4...20mA, -Process connection: Type C with 1/4" NPT F Art.No.: PRE-50G/0...7kPa/PD/C
Druckmessumformer mit	PCE-28 Pressure transmitter with Angled plug according to DIN/EN 175301, -Measurement accuracy: 0.2% -Measuring range: 0...25 bar -Output signal: 4...20mA, -Process connection: G1/4" male Art.No: PCE-28/0...25bar/PD/G1/4
Druckmessumformer mit	PCE-28 Angled plug according to DIN/EN 175301, -Measurement accuracy: 0.2% -Measuring range: 0...400 bar -Output signal: 4...20mA, - Process connection: G1/4" male Art.No: PCE-28/0...400bar/PD/G1/4
SGE-25	Hydrostatic level probe - standard version, -Measuring range: 0...1.5 mH2O -Measuring accuracy: 0.3% - Output signal: 4...20 mA, -Connection cable PU with capillary line: L= 12m. Art.No.: SGE-25/0...1.5mH2O/PU/L=12m
PCE-28	Pressure transmitter with field housing -Measurement accuracy: 0.2% - Measurement range: 0...25 bar - Output signal: 4...20mA, -Process connection: CM30x2 Article no.: PCE-28/0...25bar/PZ/CM30x2
	Differential pressure transmitter with HART protocol, -Aluminum housing

APR-2000/ALW/IP67/0...1bar/	with digital display, -ATEX compliant: no, -Measurement accuracy: 0.075% - Output signal: 4...20 mA + HART, - Sensor measuring range (?P): 0...1 bar -Set measuring range: 0...600 mbar - Process connection: Type C with 1/4" NPTF and gold-plated membrane and PTFE seal Art.No: APR-2000/ALW/IP67/0...1bar/ 0...600mbar/C/316L/Au/PTFE/ST
APC-2000/ALW/IP67/0...7 bar/0...6bar/	Pressure transmitter with HART protocol, -Aluminum housing with digital display, -ATEX compliant: no, - Measurement accuracy: 0.075% - Output signal: 4...20 mA + HART, - Sensor measuring range: 0...7 bar -Set measuring range: 0...6 bar -Process connection: with pressure seal SP DN80 PN40 Art.No: APC-2000/ALW/IP67/0...7 bar/0...6bar/ SP-DN80-PN40//ST
APC-2000/ALW/IP67/0...1bar/11...650mbar/	Pressure transmitter with HART protocol, -Aluminum housing with digital display, -ATEX compliant: no, - Measurement accuracy: 0.075% - Output signal: 4...20 mA + HART, - Sensor measuring range: 0...1 bar -Set measuring range: 11...650 mbar - Process connection: with pressure seal SP DN80 PN40 Art.No: APC-2000/ALW/IP67/0...1bar/11...650mbar/ SP-DN80-PN40//ST
APC-2000/ALW/IP67/0...2 bar/	Pressure transmitter with HART protocol, -Aluminum housing with digital display, -ATEX compliant: no, - Measurement accuracy: 0.075% - Output signal: 4...20 mA + HART, - Sensor measuring range: 0...2 bar -Set measuring range: 0...1600 mbar - Process connection: with pressure seal SP DN80 PN40 Art.No: APC-2000/ALW/IP67/0...2 bar/ 0...1600mbar/SP-DN80-PN40//ST
APC-2000AL W	Pressure transmitter with HART protocol, -Aluminum housing with digital display, ATEX compliant: no - Measurement accuracy: 0.075% - Output signal: 4...20 mA + HART, - Sensor measuring range: 0...25 bar - Set measuring range: 0...25 bar - Process connection: G1/2" external Item no: APC-2000ALW/0...25bar/G1/2
Apc-2000alw	
Sge-25 (Sge-25/0 Mh2o/L=10m)	
Pms-970t/230/4/Wy	
Pre-28	
Apt-200alw	
05132383 0exiallct6 X 0...1	

Pg-28	
05132383 0exiallct6 C 0...2,5	
Apc-2000 Alw/0-1 Bar/S-Tk-P/K=1 M	TRANSMİTTER
Pr-50g	
Ctgn1-100-G1/2quot;-Pt100-B-2	
Sge-25.Smar	
Pce-28p	
316l/316ss	
Atlr.Pt100.Ni100	
Apre-2000g/-250...250pa/0-100pa/Pcv.	
Erh-04-07-2-K	
Pce-28	
Apr2200 Alw Spk Dn 80	
Apr-2200alw	
Pce-28 4-20 Ma	
Apce-2000pd	
Erh-01-04k-3	
Apc-2000/Alw/0...700 Kpa)	
Vm-5	
Pem-1000	
Bak-Q80 I Q60	
Ctgn1-50-G1/2quot;-Pt100-B-2	
Apr2200 Alw Spk Dn 80	
05132383 0exiallct6 X 0...2,5	
APR-2000AL W	Differential pressure transmitter with HART protocol, -Aluminum housing with digital display, ATEX compliant: no -Measurement accuracy: 0.075% - Output signal: 4...20 mA + HART, - Sensor measuring range (ΔP): 0...0.25 bar -Set measuring range: 0...51"H2O -Process connection: Type C with 1/4" NPTF -incl. stainless steel mounting bracket C-2" -TAG-No.: Please specify Art.No: APR-2000ALW/IP67/0...0.25bar/0...51"H2O/C/C-2"(SS)/MT/ST
Nema-4x (Ip-66)	
Pre-50g - Obsolete , Replaced By Apre-2000pd/-250?250pa/0?100pa/Pcv	
Connection For Transmitter Apr.2000galw	
Apt-28	
Pce-28/0...10bar/Pd/1/2nptm	

[Filter For Transmitter Apr.2000galw](#)

[Apr.2000galw](#)

[Pms-970p](#)

[Apis-250-D00-Rst-Ian-T00-P0-M1-W0-A0](#)

[Erh-01-04k-4.0](#)

[Pc-28](#)