Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Aquametro

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Aquametro Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Aquametro Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Vzo 4 -Re 0,00125	Art nr. 89763 -- CONTOIL® oil meter with reed pulse generator -- Pulse value 5 ml Measuring principle: ring piston Nominal pressure: PN 25 -- Nominal size: DN 4 mm with internal thread for copper pipe screw connection: 1 / 8´´ Installation position: horizontal / vertical Max. Flow: 80 l / h -- Continuous flow: 50 l / h Min. Flow: 1 l / h Max. Permissible temperature: 60 ° C Total quantity on roller counter: 100,000l Pulse value: 0.00125 l -- Min. Readable amount: 0.001 l Measurement deviation: 1 - 2 l / h ± 2.5% of the measured value 2 - 80 l / h ± 1% of the measured value Repeatability: </ = than: 0.2% Built-in safety filter: 0.125 mm
PMK-basic 20 4.0_190_3/4"	92504 aquabasic® cold water meter Measuring principle: multi-jet impeller Cold water meter in dry running design Thread connection: G 1 " Nominal pressure: PN 16 Installation length: 190 mm Nominal size: DN 20 Installation position: horizontal Max. Flow rate: 5 m^3 / h Continuous flow: 4 m^3 / h Min. Flow rate: 0.025 m^3 / h Temperature max. 40 ° C Kvs value: 5.2 m^3 / h Pressure loss at: 600 mbar Measuring range: R 160 Inlet section: 0 x DN 20 Outlet section: 0 x DN 20

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Protection class: IP 66 Approval MI-001 Registration capacity: 100,000 m3 Min. Readable amount: 0.1 l
98276	Aquastream® M / Puls 97508 mounted / param. System module aquastream® M-Bus / Pulses including assembly and parameterization
VZF II 50 FL 130/25	Characteristics: Display of total amount, Quantity resettable (up to 8 counters, 4 from resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Configurable outputs. Nominal diameter: DN 50mm Connection flanges: DN 50 Nominal pressure: PN 25bar Overall length: 350mm Installation position: horizontal / vertical Temperature max .: 130 ° C Measuring range: 750 ... 30000l / h Max. Continuous flow: 20000l / h Max. Measurement deviation: ± 1% of the measured value Repeatability: ± 0.2% Registration ability: 100Mio Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analog: 4 ... 20mA Digital: pulses, frequency, logic Nominal voltage: 24V DC Supply via 4 ... 20mA: 6 ... 30V DC Protection class: IP66 / IP68 / IP69 Ambient temperature: -25 ... + 70 ° C
95593	VZF II electronics for VZF for S / N 4938017
VZO 4 -RE 0,00125	89763 CONTOIL® oil meter VZO 4-RE 0.00125 Rotary piston meter for mineral oil, with roller counter Nominal diameter: DN 4 mm Connection below: G1 / 8 “internal thread Nominal pressure: PN 25 bar Dimensions: 65 x 65 x 79 mm Installation position: horizontal / vertical

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Temperature max .: 60 ° C Measuring range (at Visc. 1 ... 20 mPa.s): 1 ... 80 l / h Continuous flow rate Qn max: 50 l / h Max. Error: 2.0 ... 80 l / h ± 1% 1 ... 2 l / h + 1 / -2% Repeatability: ± 0.2% Registration capacity: 100,000 l With built-in reed pulse generator RE Contact load max .: 48 V AC / DC, 50 mA, 2 VA Pulse value: 0.00125 l
VZF II 50 FL 130/25	CONTOIL® flow meter for mineral oil. Electronic counter with display. Properties: Display of total amount, Quantity resettable (up to 8 counters, 4 from resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Configurable outputs. Nominal diameter: DN 50mm Connection flanges: DN 50 Nominal pressure: PN 25bar Overall length: 350mm Installation position: horizontal / vertical Temperature max .: 130 ° C Measuring range: 750 ... 30000l / h Max. Continuous flow: 20000l / h Max. Measurement deviation: ± 1% of the measured value Repeatability: ± 0.2% Registration ability: 100Mio Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analog: 4 ... 20mA Digital: pulses, frequency, logic Nominal voltage: 24V DC Supply via 4 ... 20mA: 6 ... 30V DC Protection class: IP66 / IP68 / IP69 Ambient temperature: -25 ... + 70 ° C
vz020	
VZO 15 RC 130/16	Item No.: 92041 CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 16 Overall length: 165 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Nominal width: DN 15 mm with thread 3/4" for screw connections: 1/2" Installation position: horizontal/vertical Max flow: 600 l/h Continuous flow: 400 l/h Minimum flow: 20 l/h Max. allowed temperature: 130°C Amount total on roller counter: 1'000'000 l Minimum readable volume: 0.01 l Deviation: 20 - 600 l/h ± 1% of the measured value Repeatability:
VZO 15 RC 130/16	Artikelnr.: 92041 CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 16 Overall length: 165 mm Nominal width: DN 15 mm with thread 3/4" for screw connections: 1/2" Installation position: horizontal/vertical Max flow: 600 l/h Continuous flow: 400 l/h Minimum flow: 20 l/h Max. allowed temperature: 130°C Amount total on roller counter: 1'000'000 l Minimum readable volume: 0.01 l Deviation: 20 - 600 l/h ± 1% of the measured value Repeatability:
VZO 4 -RE 0,00125	Item No.: 89763 CONTOIL® oil meter with reed pulse generator Pulse value 1.25 ml Measuring principle: ring piston Nominal pressure: PN 25 Nominal width: DN 4 mm with internal thread for copper pipe fitting: 1/8" Installation position: horizontal/vertical Max flow: 80L/h Continuous flow: 50 l/h Minimum flow: 1 l/h Max. allowed temperature: 60°C Amount total on roller counter: 100'000l

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Pulse value: 0.00125 l Minimum readable volume: 0.001 l Deviation: 1 - 2 l/h ± 2.5% of the measured value 2 - 80 l/h ± 1% of the measured value Repeatability: Built-in safety filter: 0.125 mm
VZF II 25 RC 130/16	Item No.: 95535 CONTOIL® flow meter for mineral oil. Electronic counter with display. Characteristics: display of amount total, Quantity resettable (up to 8 counters, 4 of resettable), flow rate, temperature, mass and normalized volume in m3, liters, US gallons or tons, kilograms and pounds. Configurable outputs. Nominal diameter: DN 25mm Thread connection device: 1 1/4" Screw connection pipe 1" Nominal pressure: PN 16bar Length: 190mm Installation position: horizontal / vertical Maximum temperature: 130°C Measuring range: 75...3000l/h Max. continuous flow: 2000l/h Max. error of measurement: ±1% of the measured value Repeatability: ±0.2% Registration capacity: 100 million Display LCD: 8 digits 8mm high Outputs: 1 analogue and 2 digital Analogue: 4...20mA Digital: pulses, frequency, logic Rated voltage: 24V DC Supply via 4...20mA: 6...30V DC Protection class: IP66/IP68/IP69 Ambient temperature: -25...+70°C
AM Viscomaster Dynamic	HFVM11L729HNC3FJREZZZ 95431 Heavy Fuel Viscosity Meter Viscomaster 1 Sensor Range And Performance: Viscosity accuracy ±0.2cP (0-10cP range) then ± 1% FS of calibrated range, Viscosity limit 20,000cP 1 Immersion depth: 0mm: no stem extension and with standard spigot L Wetted parts: 316L Stainless, Diamond Like Carbon coated tines 729 Process connection: 1 1/2-inch Cone Seat

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Compression fitting 316/316L H Calibration: 2 1/2-inch schedule 40 boundary (Viscosity limits 200cSt=T piece) N Transmitter Housing Option: AquaMetro REDUCED FUNCTIONALITY version (red + Aquametro label) C Output signal: Integral transmitter, channel A = mA + HART, Channel B = mA output, Channel C = RS485 Modbus 3 Indicator: No F Ex approval ATEX flameproof J Application Configuration: Line Viscosity; [4mA=0cSt, 20mA=50cSt] R Calibration range: 5 to 50cP viscosity calibration only, no density calibration) E Language: English inst. Manual config and English. manual Z Future Option 1: Reserved for future options Z Cable entries: 1/2 ´´NPT Z Factory option: Standard product 200966
VC322 Viscosity Controller Step	Art. Nr.: 200973 3-point-step-controll digital universal controller Dimension:96x96 mm Supply: 100..250V AC Input: -viscosity (4-20mA) 0-50cSt -temperature (4-20mA) 0-200 °C Input switchable Output: -2 analog (1 Visco & 1 Temp) -2 relay outputs
VZO 4 -RE 0,00125	89763 CONTOIL® oil meter with reed pulse generator Pulse value 1.25 ml Measuring principle: ring piston Nominal pressure: PN 25 Nominal width: DN 4 mm with internal thread for copper pipe fitting: 1/8" Installation position: horizontal/vertical Max flow: 80L/h Continuous flow: 50 l/h Minimum flow: 1 l/h Max. allowed temperature: 60°C Amount total on roller counter: 100'000l Pulse value: 0.00125 l

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Minimum readable volume: 0.001 l Deviation: 1 - 2 l/h ± 2.5% of the measured value 2 - 80 l/h ± 1% of the measured value Repeatability: Built-in safety filter: 0.125 mm
VZO 15 RC 130/16	92041 CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 16 Overall length: 165 mm Nominal width: DN 15 mm with thread 3/4" for screw connections: 1/2" Installation position: horizontal/vertical Max. flow: 600 l/h Continuous flow: 400 l/h Min. flow: 20 l/h Max. permissible temperature: 130°C Quantity total on roller counter: 1,000,000 litres Min. readable quantity: 0.01 l Measuring deviation: 20 - 600 l/h ± 1% of the measured value
VZO 4 -RE 0,00125	Item number: 89763 CONTOIL® oil meter with reed pulse generator Pulse value 1.25 ml Measuring principle: ring piston Nominal pressure: PN 25 Nominal width: DN 4 mm with internal thread for copper pipe fitting: 1/8" Installation position: horizontal/vertical Max. flow: 80 l/h Continuous flow: 50 l/h Min. flow: 1 l/h Max. permissible temperature: 60°C Quantity total on roller counter: 100,000l Pulse value: 0.00125 l Min. readable quantity: 0.001 l Measuring deviation: 1 - 2 l/h ± 2.5% of the measured value 2 - 80 l/h ± 1% of the measured value Repeatability: Built-in safety filter: 0.125 mm
VZF II 40 FL 130/25	Item no.: 95544 CONTOIL® flow meter for mineral oil.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Electronic counter with display. Characteristics: Display of total quantity, Quantity resettable (up to 8 counters, 4 of resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Parameterizable outputs. Nominal diameter: DN 40mm Connection flanges: DN 40 Nominal pressure: PN 25bar Length: 300mm Installation position: horizontal / vertical Temperature max.: 130°C Measuring range: 225...9000l/h Max. continuous flow: 6000l/h Max. measurement deviation: ±1% of the measured value Repeatability: ±0.2% Registration capacity: 100 million Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analogue: 4...20mA Digital: pulses, frequency, logic Rated voltage: 24V DC Supply via 4...20mA: 6...30V DC Protection class: IP66/IP68/IP69 Ambient temperature: -25...+70°C
VZF II 20 FL 130/25	Item no.: 95512 CONTOIL® flow meter for mineral oil. Electronic counter with display. Characteristics: Display of total quantity, Quantity resettable (up to 8 counters, 4 of resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Parameterizable outputs. Nominal diameter: DN 20mm Connection flanges: DN 20 Nominal pressure: PN 25bar Length: 165mm Installation position: horizontal / vertical Temperature max.: 130°C Measuring range: 40...1500l/h Max. continuous flow: 1000l/h Max. measurement deviation: ±1% of the measured value Repeatability: ±0.2%

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Registration capacity: 100 million Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analogue: 4...20mA Digital: pulses, frequency, logic Rated voltage: 24V DC Supply via 4...20mA: 6...30V DC Protection class: IP66/IP68/IP69 Ambient temperature: -25...+70°C
VZO 15 RC 130/16 -	Article number: 92041 CONTOIL® oil meter Measuring principle: Annular piston Nominal pressure: PN 16 Overall length: 165 mm Nominal diameter: DN 15 mm with 3/4" thread for screw connections: 1/2" Installation position: horizontal/vertical Max. flow rate: 600 l/h Continuous flow: 400 l/h Min. flow rate: 20 l/h Max. permissible temperature: 130°C Total quantity on roller counter: 1,000,000 l Min. readable quantity: 0.01 l measurement deviation: 20 - 600 l/h ± 1 % of measured value Repeatability:
Flanged - DN 20 - PN25,	Working Ambient Temperature 130 Degrees with RV1 Pulse Output - Diesel Meter
VC322 Viscosity Controller Step	Item No.: 200973 3-point step control digital universal controller Dimensions: 96x96 mm Power supply: 100-250V AC Input: -viscosity (4-20mA) 0-50cSt -temperature (4-20mA) 0-200°C Input switchable Output: -2 analog (1 Visco & 1 Temp) -2 relay outputs
VZF II 40 FL 130/25-	Article number: 95544 CONTOIL® Flow Meter for mineral oil. Electronic counter with display. Characteristics:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Display of total quantity, Quantity resettable (up to 8 counters, 4 (resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Configurable outputs. Nominal diameter: DN 40mm Connection flanges: DN 40 Nominal pressure: PN 25 bar Installation length: 300mm Installation position: horizontal / vertical Maximum temperature: 130°C Measuring range: 225...9000 l/h Maximum continuous flow rate: 6000 l/h Maximum measurement deviation: ±1% of the measured value Repeatability: ±0.2% Registration capacity: 100 million LCD display: 8 digits, 8mm high Outputs: 1 analog and 2 digital Analog: 4...20mA Digital: Pulse, Frequency, Logic Nominal voltage: 24V DC Power supply via 4...20mA: 6...30V DC Protection class: IP66/IP68/IP69 Ambient temperature: -25...+70°C
80113 / 2017	Nachfolgermodell Aquastream® M/Puls 97508
83552 Rw/Rd 25	
94252 Pmgf 32-Rh1 5.0_150_1 1/4quot;	
In0,1/Rw/Rd 25 83561	
89216,Topas Pmw -	
Pmg 32-Ih (6.0_260_1 1/4quot;)	
Ard15/3315-H3/0	
Ard 20/1221-H2 -In0,1/Rw/Rd 20	
Pmw 32 02b	
Vzo 8 (92630)	
94793	
Art.No. 83527 Rv1/Rd 20	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
94588	
Vzo 15 Rc 130/16-Rv0,1	
Vzo 40 Fl 180/25	
Art.No. 92048 Vzo 20 Rc 130/16-Rv1	
94525 50 50_200	
92049 Vzo 20 Fl 130/25	
Vzo-15	
Type:7829 Ennajrhba, Ser No=296865 By Hfvm11l729hnc3fjrezzz (95431)	
81153.	
Vz020	
80113	
12886	
4	
80695	
89629 Topas Pmg -	
1	
Ard 20/1221-H2	
93533	
P/N 92280, Vzf 50 Fl 180/25	
Vzf25fl130/25	
Od03	
94606	
83565 In0,1h/Rw/Rd 25	
Vzo 4 - Re 0,1	
16028	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
89654 Topas Pmgf -	
92630 Vzo 8	CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 25 Overall length with PS set: 130 mm Nominal diameter: DN 8 mm with internal thread for copper pipe fitting 1 / 4" Installation position: horizontal / vertical Max. Flow: 200 l / h Continuous flow: 135 l / h Min. Flow: 4 l / h Max. Permissible temperature: 60 ° C Lot totally on roller counter: 1'000'000 l Min. Readable quantity: 0.01 l Bias: 4 - 5 l / h ± 2% of the measured value 5 - 200 l / h ± 1% of the measured value Repeatability: </ = as: 0.2% Built-in safety filter: 0.150 mm
93763	
Vzo 25 Rc 130/16-Rv1	
083509	
Art.No. 92041, Vzo 15 Rc 130/16	
13199	
96167	
96158	
Dip 406 A1/R/Tor/2	
Ard 251222-G6+ip1rwrd25	
81169	
Tmc19321	
(83526) Rw/Rd 20	
94525	
13018	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
P/N 94101	
Vzo 40 Fl 130/25	
89224 Topas Pmwf -	
Art.No. 92042 Vzo 15 Rc 130/16-Rv0,1	
94609	
Rw/Rd 20	
80522.	
12795 Kolben Graphit Rd 25	
Vzo 25 Rc 130/16	
94249	
Vzfa25 Rc130/16	
Vzo 20 Fl 130/25-In0,01 91903	
89642 Topas Pmgs -	
92503 Pmk-Basic 15 2.5_165_1/2quot;	
13021	
Vzo 4-Re	
09190200	
P/N: 89763 Vzo 4 -Re 0,00125	
89771 Vzo 8 -Re0,0125	
94604	
P/N: 92041 Type: Vzo 15 Rc 130/16	
(83037) Ard 20/1221-A2	
80113 Aquapuls 1 L	
Ard25/1112-P6-Ina/Rw/Rd25	
12985	
Art.No. 80113 Aquapuls 1l	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
P/N: 92680 Type: Vzo 4	
94600	
83099 Ard 25/3315-G6	
P/N: 80695 Type: M-Bus Mini-Master	
Hfvm11l729hnc3fjrezzz (95431)	
94608	
89252 Topas Pmwf -	
Vzo 20 Rc 130/16	
94606 Pmwf-Basic 32 10._150_1 1/4quot;	
13020	
92050 (Vzo 20 Fl 130/25-Rv1)	
92047 Vzo 20 Rc 130/16	
81152	
96166.	
3	
40251	
89270;Topas Pmws -	
Vzo50fl-130/25	
2	
Vcs04	
Ard25/1112-P7-Dn25-Pn16	
94255	
96112	
Wpd80+od01	
94607	
8356900	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
83509	
Ard25/1112-P6-Dn25-Pn16	
P/N: 89763 Type: Vzo 4 -Re 0,00125	
89206 Topas Pmw 32-Rh1 Obsolete, Replaced By 94249 And 96158	
89763	
92059	
94530	
Sj35n	
30-10000 Lt/H-3/4quot;	
Vz025	
Aquametro-96166-Ce-Pr3;Fung-Wasserzõ;Hler-R49-Dn15-32-Istanbul-Turkiye	
Pmd 20 -Gtas - 84025	
96044	
Contoil Vzo 20 Rv By 92050 (Vzo 20 Fl 130/25-Rv1)	
89206 Topas Pmw -	
83031	
92059 Vzo 25 Fl 130/25	
89244 Topas Pmwf -	
81151	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.