



Arca Regler

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Arca Regler Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Arca Regler T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Typ 824.E110-003	electro-pneumatic positioner Input 4-20mA Plastic hood IP54 simple acting Cable bushing M20x1.5 Air connection G1/4 with position transmitter 3-wire for stroke >= 20mm
Arca Regler	
Arca Regler	
827A.E2-000-M10-G	Intelligent positioner Input 4-20 mA, 2-wire connection Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 Type 827A.E2-000-M10-G Intelligent positioner Input 4-20 mA, 2-wiring Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4
827A.E2-A00-M10-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP 66 single acting with analog module, feedback signal 4 to 20 mA Cable gland M20x1.5 Air connection G 1/4 Type 827A.E2-A00-M10-G Smart Positioner Input 4-20mA, 2-wiring Metal housing IP 66 single acting Cable gland M20x1.5 Air connection G 1/4 with analog module
	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 Single-acting Cable gland M20x1.5 Air

827A.E2-0B0-M10-G	connection G1/4 with binary module Type 827A.E2-0B0-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 Cable gland M20x1.5 Air connection G1/4 with binary module
827A.E2-0S0-M10-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting with SIA module 2 inductive slot initiators Cable gland M20x1.5 Air connection G1/4 Type 827A.E2-0S0-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with slot initiator
827A.E2-AB0-M10-G	Intelligent positioner Input 4-20 mA, 2-wire connection Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 with analog module, with feedback sensor 4-20 mA with binary module, with electronic limit switch Type 827A.E2-AB0-M10-G Intelligent positioner Input 4-20 mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5
827A.E2-AS0-M10-G	Intelligent positioner Input 4-20mA, without Ex 2-wire connection Metal housing IP66 single acting with analog module, feedback 4 to 20 mA with slot initiators 2 inductive proximity switches Cable gland M20x1.5 Air connection G1/4 Type 827A.E2-AS0-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting with analog module, feedback 4-20mA with SIA module, slot initiator Cable gland M20x1.5 Air connection G1/4
827A.E2-00H-M10-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with HART module Type 827A.E2-00H-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with HART module
827A.E2-A0H-M10-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module, feedback signal 4-20mA with HART module Type 827A.E2-A0H-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with HART module
827A.E2-0BH-M10-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with binary module with HART module Type 827A.E2-0BH-M10-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with binary module with HART module
827A.E2-0SH-M10-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with slot initiators with HART module Type 827A.E2-0SH-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with slot initiator with HART module
	Intelligent positioner Input 4-20mA, 2-wire connection Metal

827A.E2-ABH-M10-G	housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with binary module with HART module Type 827A.E2-ABH-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with binary module with HART module
827A.E2-ASH-M10-G	Type 827A.E2-ASH-M10-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module, feedback sensor 4-20 mA with SIA module, 2 slot initiators, with HART module Type 827A.E2-ASH-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with slot initiator with HART module
827A.E2-00P-M10-G	Intelligent positioner Input digital, 2-wire connection Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 with Profibus Type 827A.E2-00P-M10-G Intelligent positioner Input digital, 2-wiring Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 with Profibus
827A.E2-000-M12-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer Type 827A.E2-000-M12-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer
827A.E2-00H-M12-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer with HART module Type 827A.E2-00H-M12-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer with HART module
827A.X2-000-M10-G	Type 827A.X2-AS0-M10-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 Protection class II 2G Ex ia IIC T4 Gb simple-looking Cable entry M20x1.5 Air connection G1/4 with analog module, feedback 4-20mA with slotted initiators, 2 inductive proximity switches The information on explosion protection in the data sheet and the Operating instructions must be observed.
Typ 827A.X2-A00-M10-G	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 Protection class II 2G Ex ia IIC T4 Gb simple-looking Cable entry M20x1.5 Air connection G1/4 with analog module, feedback 4-20 mA The information on explosion protection in the data sheet and the Operating instructions must be observed.
827A.X2-AS0-M10-G	Type 827A.X2-AS0-M10-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 Protection class II 2G Ex ia IIC T4 Gb simple-looking Cable entry M20x1.5 Air connection G1/4 with analog module, feedback 4-20mA with slotted initiators, 2 inductive proximity switches The information on explosion protection in the data sheet and the

	Operating instructions must be observed.
827A.E2-000-M10-G	Positioner Type 827A.E2-000-M10-G Intelligent Positioner Input 4-20 mA, 2-wiring Metal Housing IP 66 single acting Cable-Gland M 20x1,5 Air-Connection G 1/4
002200	Export documents Export document charges
002300	Certificate 2.1
Actuator seal number 3 of Arca brand 8C1-P1 series control valve	
2101860 Diaphragm, Membrane, Mfi	
827a.X2-Ab0-M10-G	
2174647	
1059110	
2257141	