Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Ardetem

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Ardetem Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Ardetem Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Dip400-A1r	DIGITAL PANEL METER UNIVERSAL POWER SUPPLY Display: +/- 10000 points (4 digits) IP65 front face protection Format: 48 x 96 mm Bidirectional input: mA / mV / V 1 analog output 4-20 mA active + 2 relays Scale factor programmable Special linearisation on 20 pts Accuracy class: 0.1 % of the full scale at + 25°C Supply for 2 or 3-wire sensor Programmable on front face or with optional software Universal power supply: 20 to 270 vac and 20 to 300 vdc
AI4 3	4-CHANNEL SUPPLY FOR 2-WIRE TRANSMITTER POWER SUPPLY: 24VDC Supply with 4 outputs for 2-wire transmitter Nominal values of the outputs: 24 VDC / 22 mA Galvanic isolation between outputs/outputs and supply/outputs Protection from short-circuits Mains presence witness light For DIN rail mounting
TRMv5-4A3RN	DIGITAL MEASURE TRANSMITTER, UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ... programmable) Input: In = 1 and 5A ; Un = 60V L-N / 100V L-L or 100V L-N, 190V L-L or 250V L-N, 440V L-L or 350V L-N, 600V L-L Cycle time: 40 ms Galvanic partition: IN / OUT / SUPPLY: 2kV

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	32 measurable parameters 4 analog outputs (mA) + 3 relays + RS485 MODBUS Universal power supply: 20 to 270 vac and 20 to 300 vdc Mini format: 48x96mm Depth: 112mm ; For DIN rail mounting
EVAN3000-2A2RF	ELECTRICAL NETWORK ANALYSER,UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ... programmable) Input: In = 1 and 5A ; Un = 60V L-N / 100V L-L or 100V L-N, 190V L-L or 250V L-N, 440V L-L or 350V L-N, 600V L-L Cycle time: 20 ms Galvanic partition: IN / OUT / SUPPLY: 2kV 32 measurable parameters Universal power supply: 20 to 250 Vac and 21.5 to 250 Vdc For DIN rail mounting Porgrammable by optional software WITH CONNECTION TO THE LOCAL COMMUNICATION BUS VIA DIN RAIL FOOTINGS + 2 analog outputs + 2 relays + Ethernet
TPIs-4R	OPTIONAL MODULE OF 4 RELAY OUTPUTS
DRB-5	DIN RAIL FOOTING FOR TWO 7.2 mm WIDE HOUSINGS
µCONSOLE-TAC TILE	TACTILE LCD µCONSOLE FOR PROGRAMMING THE CONVERTERS
C1-µUSB	USB - MICRO USB CABLE FOR PROGRAMMING + SOFTWARE SLIMSET
PECA11D-2RF	ELECTRICAL NETWORK ANALYZER, ANALYSIS AND DISPLAY OF THE DISTURBANCES, UNIVERSAL POWER SUPPLY Current input: 1A and 5 A AC Voltage input: 175 V and 600 V AC For all network types Graphical rear-lit LCD 25 measurable parameters: 3U, 3V, 3I, cos, f, F, P, Q, S, E... Analysis of the disturbances according to the

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	standard EN50160 Recording and display of the errors of U, I, F, Flicker, Harmonics and THD over 1 week Function oscilloscope 3 logic inputs 2 relay outputs (setpoint or pulses) Output: RS 485 Modbus/Jbus communications Ethernet Modbus TCP/IP output + embarked web server Unviersal power supply: 20 to 270 vac and 20 to 300 vdc Format: 96x96mm
TRMv5-2A	True RMS DIGITAL TRANSMITTER FOR ELECTRICAL MEASURES UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ...) Programmable via software or touchscreen µconsole (not included) Inputs: In = 1 and 5A Un = 100/190/440/600 V Cycle time: 40 ms Galvanic isolation: Input / Output / Power Supply: 3kV - 50 Hz 32 measurable parameters 2 Unidirectional mA analogue outputs Universal power supply: 20 to 250 VAC and 21.5 to 250 VDC Dimensions: 45.2*119*122 mm DIN rail mounting Observation: VERSION INSIDE NEW HOUSING REPLACING THE TRM4-2A
µCONSOLE-TAC	Tools for programming the TRMv5: TACTILE LCD µCONSOLE FOR PROGRAMMING THE CONVERTERS
TMvP-HI-SP12/05	Tools for programming the TRMv5: TACTILE LCD µCONSOLE FOR PROGRAMMING THE CONVERTERS
TMR3 4An-2	
TRMv5-4AN	DIGITAL MEASURE TRANSMITTER, UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ... programmable) Input: In = 1 and 5A ; Un = 60V L-N / 100V L-L or 100V L-N, 190V L-L or 250V L-N, 440V L-L or 350V L-N, 600V L-L

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Cycle time: 40 ms Galvanic partition: IN / OUT / SUPPLY: 2kV 32 measurable parameters 4 analog outputs (mA) + Modbus RS485 Universal power supply: 20 to 270 vac and 20 to 300 vdc Mini format: 48x96mm Depth: 112mm ; For DIN rail mounting ***4 analog outputs (mA) + Modbus RS485
TMv10	CONVERTER PARAMETRABLE BY SWITCHES UNIVERSAL POWER SUPPLY Universal input: mA, mV, V, Pt100, TC,resistance,... Selection of the input type and caliber by switches Isolated analog output 0-4-20 mA or 0-10 V Supply for 2-wire sensor Universal power supply: 20 to 250 vac and 20 to 250 vdc
PECA21-1RF	ELECTRICAL MEASURE CENTRAL, UNIVERSAL POWER SUPPLY Measurement in true RMS value (TRMS) Current input: 1A or 5 A AC Voltage input: 100, 190, 440 or 600 V AC Cycle time: 20 ms (50Hz) For all network types Graphical rear-lit LCD 35 measurable parameters: 3U, 3V, 3I, cos, f, F, P, Q, S, E... Display of the energies on 9 digits Output: RS 485 Modbus/Jbus Ethernet Modbus TCP output + embarked web server + 1 relay Universal power supply: 20 to 250 Vac and 20 to 250 Vdc Format: 96x96mm
PECA21-1RF	ELECTRICAL MEASURE CENTRAL, UNIVERSAL POWER SUPPLY Measurement in true RMS value (TRMS) Current input: 1A or 5 A AC Voltage input: 100, 190, 440 or 600 V AC Cycle time: 20 ms (50Hz) For all network types Graphical rear-lit LCD 35 measurable parameters: 3U, 3V, 3I, cos, f, F, P, Q, S, E... Display of the energies on 9 digits Output: RS 485 Modbus/Jbus Ethernet Modbus TCP output + embarked web server + 1 relay

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Universal power supply: 20 to 250 Vac and 20 to 250 Vdc Format: 96x96mm
TRMV5-4AN	DIGITAL MEASURE TRANSMITTER,UNIVERSAL POWER SUPPLYFor alltypes of AC electrical networksFullyprogrammable (CT, VT, ...programmable)Input:In = 1 and 5A ;Un =60V L-N / 100V L-Lor 100V L-N, 190V L-Lor 250V L-N, 440V L-Lor 350V L-N,600V L-LCycle time: 40 msGalvanicpartition: IN / OUT / SUPPLY: 2kV32 measurable parameters4 analogoutputs (mA) + Modbus RS485Universal power supply: 20 to 270 vac and20 to 300 vdcFor DIN rail mounting
TRMv5-2A	TRMS DIGITAL MEASURE TRANSMITTER, UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ... programmable Programmable via software or tactile LCD micro-console (not included) Input: In = 1 and 5A ; Un = 60V L-N / 100V L-L or 100V L-N, 190V L-L or 250V L-N, 440V L-L or 350V L-N, 600V L-L Cycle time: 40 ms Galvanic partition: IN / OUT / SUPPLY: 2kV 32 measurable parameters 2 analog outputs (mA) Universal power supply: 20 to 270 vac and 20 to 300 vdc Mini format: 48x96mm Depth: 112mm For DIN rail mounting **VERSION INSIDE NEW HOUSING REPLACING THE TRM4-2A
TRM42A	Measurement unit with 2 analog outputs
TRMv5-2A	True RMS DIGITAL TRANSMITTER FOR ELECTRICAL MEASURES UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ...) Programmable via software or touchscreen µconsole (not included) Inputs: In = 1 and 5A Un = 100/190/440/600 V Cycle time: 40 ms Galvanic isolation: Input / Output / Power Supply: 3kV - 50 Hz

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	32 measurable parameters 2 Unidirecional mA analogue outputs Universal power supply: 20 to 250 VAC and 21.5 to 250 VDC Dimensions: 45.2*119*122 mm DIN rail mounting
TRMv5-2A	True RMS DIGITAL TRANSMITTER FOR ELECTRICAL MEASURES UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ...) Programmable via software or touchscreen µconsole (not included) Inputs: In = 1 and 5A Un = 100/190/440/600 V Cycle time: 40 ms Galvanic isolation: Input / Output / Power Supply: 3kV - 50 Hz 32 measurable parameters 2 Unidirectional mA analogue outputs Universal power supply: 20 to 250 VAC and 21.5 to 250 VDC Dimensions: 45.2*119*122 mm DIN rail mounting Observation: VERSION INSIDE NEW HOUSING REPLACING THE TRM4-2A
C1-µUSB	USB - MICRO USB CABLE FOR PROGRAMMING + SOFTWARE SLIMSET
TPIv10-ARN	TRANSMETTEUR PROGRAMMABLE ENTREE UNIVERSELLE S:ANA + 2 RELAIS + RS485 ALIM: UNIVERSELLE Entrée universelle : mA,mV,V,TC,PT100,résistance,... Classe de précision : 0,1% Temps de réponse typique de 300 ms Facteur d'échelle programmable Alimentation capteur 2 fils Sortie analogique isolée tension ou courant 2 Sorties relais inverseurs Sortie RS485 Modbus Alimentation universelle 20 à 250 vac et 20 à 250 vdc

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Montage Rail Din Programmable par logiciel ou µconsole tactile (non incluse)
µCONSOLE-TPIv	µCONSOLE FOR PROGRAMMING THE CONVERTERS TPIv
PECA21-1RF	ELECTRICAL MEASUREMENT CENTRAL, UNIVERSAL POWER SUPPLY Measurement in true RMS value (TRMS) Current input: 1A or 5A AC Voltage input: 100, 190, 440 or 600V AC Cycle time: 20 ms (50 Hz) For all network types Graphical rear-lit LCD 35 measurable parameters: 3U, 3V, 3I, cos, f, F, P, Q, S, E... Display of the energies on 9 digits Output: RS 485 Modbus/Jbus Ethernet Modbus TCP output + embedded web server + 1 relay Universal power supply: 20 to 250 Vac and 20 to 250 Vdc Size: 96x96mm
TRMv5-2A-SPB	ELECTRICAL MEASURE TRANSMITTER S: 2 ANALOG INPUTS - UNIVERSAL POWER SUPPLY SPECIAL VERSION FOR CONCRETE MIXER Unbalanced three-phase network 3-wire 3 CTs Fully programmable (CT, VT, ...) Input: In = 5A; Un = 250V LN / 440V LL Cycle time: 40 ms 2 analog outputs 0-10 V (motor power) Programmable via touch-screen µconsole (not included) or software Universal power supply: 20 to 250 VAC and 21.5 to 250 VDC DIN rail mounting
D75 N / Digital Panel Meter	
Trm4 2a Spb	
Trm4-2a-Spb	DIGITAL MEASURE TRANSMITTER, UNIVERSAL POWER SUPPLY SPECIAL ALGORYTHM FOR CONCRETE MIXING MACHINE 3-wire unbalanced network measurement of the engine power Fully programmable (CT, VT, ... programmable) Input: In = 1 and 5A ; Un = 175 / 600Vac Cycle time: 40 ms 20 measurable parameters 2 analog outputs 0/10V Universal power supply: 20 to 270 vac and 20 to 300

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	vdc Mini format: 48x96mm Depth: 112mm ; For DIN rail mounting
Dip-400 A1r	
Peca3001	
Strect 20	
20064 Peca11d2rf	
Peca 30 Es	
Sp 125 Ard	
Trm1a2	
Art.Nr. 20017	
Art.Nr. 20009	
Tpi 302 Serial:0302-388- Obsolete, Replaced By Tpi400	
Tpa-Trm-3-2a-3 - Obsolete, Replacement 20182 Trm4 2a	
Usb-Ser For Trm4-2a-Spb	USB-RS485 ISOLATED PROGRAMMING INTERFACE + SOFTWARE SUPERVISION
Tmp-Hi-2	
Tai 60	
Sp-Vision	SOFTWARE ARDETEM SUPERVISION + SUBD9 CABLE FOR EVA
Tpi400 A	
Trmv5-2a	DIGITAL MEASURE TRANSMITTER, UNIVERSAL POWER SUPPLY version in new housing replacing the TRM4-2A For all types of AC electrical networks Fully programmable (CT, VT, ... programmable) Input: In = 1 and 5A ; Un = 175 / 600Vac Cycle time: 40 ms Galvanic partition: IN / OUT / SUPPLY: 2kV 32 measurable parameters 2 analog outputs (mA)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Universal power supply: 20 to 270 vac and 20 to 300 vdc Mini format: 48x96mm Depth: 112mm ; For DIN rail mounting
Tmp-Hi	
Art.Nr. 20012	
Tpm-Hi Sp12/05	
C1-µusb	USB - MICRO USB CABLE FOR PROGRAMMING + SOFTWARE SLIMSET
Eva Synchro 2000	ELECTRICAL NETWORK ANALYZER Input: CT: .../1A or .../ 5A PLEASE CONFIRM Voltage caliber: 70V and 120Vac Power supply: 125Vdc For singe or 3-phase balanced/unbalanced 3/4 wire networks, Parameters: U,V,I,f,cos,P,Q,S, E act., E react., ... Class: 0.2 (for U and I) Class: 0.5 (for ENERGY) Digital communications RS485 / 422, MODBUS / JBUS Level of the logic inputs: 24-48Vdc (in standard) Format: 75x149mm, For DIN rail mounting
(Trm4-2a) Measurement Unit With 2 Analog Outputs	
20223 Dip40 0a1 R	
Usb-Rs485	ISOLATED PROGRAMMING INTERFACE + SOFTWARE SUPERVISION
Dip400	DIGITAL PANEL METER UNIVERSAL POWER SUPPLY Display: +/- 10000 points (4 digits) IP65 front face protection Format: 48 x 96 mm Bidirectional input: mA / mV / V Scale factor programmable Special linearisation on 20 pts Accuracy class: 0.1 % of the full scale at + 25°C Supply for 2 or 3-wire sensor Programmable on front face or with optional software

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Universal power supply: 20 to 270 vac and 20 to 300 vdc EKSTRA OZELLIKLERI FIYATI ASAGIDAKI GIBIDIR POSSIBLE OPTIONS FOR DIP400: Analog output = 100 EUROS 2 relays = 94 EUROS 4 relays = 199 EUROS Digital communications RS485 = 202 EUROS 2 logic inputs = 199 EUROS Bargraph display = 95 EUROS
Eva2501r 5a2	ELECTRICAL NETWORK ANALYZER Input: CT: .../1A or .../ 5A PLEASE CONFIRM Power supply = ? PLEASE CONFIRM For single or 3-phase balanced/unbalanced 3/4 wire networks CT and VT ratios programmable Measurable parameters: U,V,I,f,cos,P,Q,S, E act., E react., ... Digital communications RS485 / 422, MODBUS / JBUS + 5 analog outputs (mA) Response time: 180 to 325ms Format: 75x149mm, for DIN rail mounting
Peca11	
Peca11d-2rf	ELECTRICAL NETWORK ANALYZER, ANALYSIS AND DISPLAY OF THE DISTURBANCES, UNIVERSAL POWER SUPPLY Current input: 1A and 5 A AC Voltage input: 175 V and 600 V AC For all network types Graphical rear-lit LCD 25 measurable parameters: 3U, 3V, 3I, cos, f, F, P, Q, S, E... Analysis of the disturbances according to the standard EN50160 Recording and display of the errors of U, I, F, Flicker, Harmonics and THD over 1 week Function oscilloscope 3 logic inputs 2 relay outputs (setpoint or pulses) Output: RS 485 Modbus/Jbus communications Ethernet Modbus TCP/IP output + embarked web server Unviersal power supply: 20 to 270 vac and

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	20 to 300 vdc Format: 96x96mm
Trm 2	
20085	
Trm4-2a	DIGITAL MEASURE TRANSMITTER, UNIVERSAL POWER SUPPLY For all types of AC electrical networks Fully programmable (CT, VT, ... programmable) Input: In = 1 and 5A ; Un = 175 / 600Vac Cycle time: 40 ms Galvanic partition: IN / OUT / SUPPLY: 2kV 32 measurable parameters 2 analog outputs (mA) Universal power supply: 20 to 270 vac and 20 to 300 vdc Mini format: 48x96mm Depth: 112mm ; For DIN rail mounting
Trm3-2a-2	
20164 Peca11d2rf	
Á;Console Lcd	
Trm4-2a-2 90-270vca	
Peca11 Dc130 1	
Usb-Ser	USB-RS485 ISOLATED PROGRAMMING INTERFACE + SOFTWARE SUPERVISION FOR TRM4
20224 Dip402 R	
Tmp-Hi-3-Sp12/05	
Dip-Bar2-A1	
Tma-Hi	
20182 Trm4 2a	
Dip 400	
Peca11 Dc 15-50	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.