**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



# Ari Armaturen

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

**Ari Armaturen** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

*Firmamız Ari Armaturen Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.*

| Ürün | Açıklama |
|---|---|
| Figur 45.601 DN 15 | ARI-CONA B<br>Bimetal condensate drain with external screen DN 15<br>Nominal pressure: PN 40<br>Material: 1.0460<br>Connection type: threaded socket<br>Connection type input: threaded socket Rp 1/2<br>Type of connection output: threaded socket Rp 1/2<br>Overall length (mm): 95<br>Controller: R32<br>PS 1 (bar): 32 bar<br>TS 1 (° C): 250 ° C<br>TS 2 (° C): 450 ° C<br>PS 2 (bar): 14.5 bar<br>Differential pressure (bar): 32 bar |
| THRUST ACTUATOR type ARI-PREMIO-PLUS | (YOKE VERSION) 2,2-5 kN<br>4.3.3.PART LIST:<br>Board Support<br>50.138 |
| THRUST ACTUATOR type ARI-PREMIO-PLUS | (YOKE VERSION) 2,2-5 kN<br>4.3.3.PART LIST:<br>Trip Slide<br>50.141 |
| ES11 230VAC Positioner | |
| TYP:23.470+SINGLE | |
| ARI-PREIO Type 5 KN , 230 V 60 Hz | |
| 0254000013 | Positioner ES11 230VAC |

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| DN15 PN16 | |
| ARI PREMIO 2,2 KN ELEKTRIC THRUST ACTUATOR | 4-20 MA OUTPUT,POWER 220 VAC-60HZ |
| ARI STEVİ 440 CONTROL VALVE - GLOB TYPE DN25 PN16 | BODY ENGJL250,CLAP 1.4021(STAINLESS),PTFE SEALING |
| 911410030G191 | Electric thrust Ari-Premio-Plus 2G<br>Electric thrust Ari-Premio-Plus 2G 25kn<br>Data sheet: 000033-1.pdf<br>Operating instructions: 0040501007-1.PDF<br>Discount group: I11<br>Tension: 100-240V AC 50-60Hz<br>Actual speed: 0.38mm/sec<br>Performance: 132Sec<br>Spindle overhang: 83mm<br>Cup: thread M16<br>Valvor hub: hub 50mm<br>Control: 4-20mA DC<br>Switch outputs: with a relay card<br>Position detector: Analog output map (y out)<br>Heating resistance: 230V 50/60Hz, 15 watts<br>LED status display: Yes |
| SEAL FOR EQUALIZING VALVE FLAP | 4-00584-B2-BF-TCS-ME-SAS-0049,Resim Poz No: ITEM 2 |
| EQUALIZING VALVE FLAP & LEVER | 4-00584-B2-BF-TCS-ME-SAS-0049 |
| EQUALIZING VALVE SEAT | 4-00584-B2-BF-TCS-ME-SAS-0050 |
| SET OF SEALS FOR DRIVE UNIT | 4-00584-B2-BF-TCS-ME-SAS-0047,Resim Poz No: ITEM 3 |
| SECONDARY EQUALIZING VALVE | 4-00584-B2-BF-TCS-PO-PID-0002 |
| SECONDARY EQUALIZING VALVE | 4-00584-B2-BF-TCS-PO-PID-0002 |
| SOLENOID VALVE FOR SECONDARY EQUALIZING | 4-00584-B2-BF-TCS-PO-PID-0006 |
| FLOW CONTROL VALVE | 4-00584-B2-BF-TCS-PO-PID-0002 |
| 259020080 ARI-SAFE | Full lift safety valve D/G with flanges<br><br>Fig. ...902 Open lifting device, open bonnet<br><br>DN 80/125<br><br>Set pressure, bar: 16,1 |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Nominal pressure: PN 40/16<br>Flanges: DIN PN40 / PN 16<br>Input: DIN PN40<br>Output: DIN PN16<br>Material: EN-JS1049 |
| ARI-PREMIO-Plus 2G TYPE:5,0kN | DN 50 |
| ARI-FABA-Plus 35040 | DN150 globe valve metal bellow // UIF code: 505BDGB_150 |
| FABA-Plus 52046 | 500AHHB_150 |
| RI21 230VAC | 0277000032 position indicator |
| ES11 230VAC | 0254000013 position indicator |
| 0389020086 | Rollmembran DP34<br>NBR<br>800cm² |
| PREMIO 2.2 KN PROPORTIONAL VALVE | |
| Set of chevron cuffs 0490010156 | |
| V-ring PTFE 0490010159 | |
| Repair kit set | |
| 0490000302 | Shift carriage unit PREMIO<br>2.2- 5.0kN |
| SN 001263156-761 | 910000001G191<br>EL actuator PREMIO<br>2.2-25kN<br>Datasheet: 000038-1.pdf<br>Operating instructions: 0040501009-1.pdf<br>Valve stroke: 30mm<br>Drive type: PREMIO 2.2kN<br>Motor type: BLDC motor<br>Voltage: *3~400V 50/60Hz<br>Actuating speed: 0.38mm/sec<br>Setting time: 79s<br>Spindle projection: 83mm<br>Coupling: Thread M12<br>Shift slide: yes<br>Additional limit switches: 2 pieces 10A 250V (standard) |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Position indicator RI32: * 4-20mA direct<br>Connection board: NA (acc. t000043859)<br>Turning point: External turning point |
| 0490000071 | Board carrier PREMIO complete<br>2.2-5.0kN<br>BLDC / ESP |
| Filter dn 150 pn 16 jl1040 | |
| Figur 25.902 DN 25 | ARI-SAFE<br>Full-lift safety valve with flanges - open hood - open lift - according to VdTÜV leaflet 100, AD2000-A2 and EN ISO 4126-1<br>Open hood/open lift<br>TÜV.SV.22-663.D/G<br>EN-JS1049 DN 25/ 40<br>Data sheet: 900005-1.pdf<br>Operating instructions: 0040401000-1.pdf<br>Discount group: I91<br>Setting pressure (bar g): 10.4<br>Pressure range (bar): > 9.0 - 16.0<br>Nominal pressure: PN 40<br>Flange bore: DIN PN40/PN16<br>Inlet according to DIN PN40<br>Outlet according to DIN PN16<br>Acceptance final test: TÜV setting certificate |
| Figur 12.405 DN 150 | ARI-STEVI 405<br>Shut-off valve in straight-through form with flanges<br>EN-JL1040 DN150<br>Data sheet: 405001-1.pdf<br>Operating instructions: 0040304000-1.pdf<br>Discount group: I51<br>Nominal pressure: PN 16<br>Flange bore: according to DIN PN16<br>Spindle seal: V-rings/PTFE graphite<br>Drive: DP34<br>Effective force (with pneumatic drive): spring opens when air fails<br>Spring range (bar)/stroke (mm): 0.20-0.80 stroke 38mm<br>req. Control pressure (bar): 3.5 bar<br>Max. permissible control pressure (bar): 5.5<br>Max. closing pressure (bar): 9.2<br>Spacer column length: L1=228mm<br>Spacer column spacing: 100mm<br>Coupling: Thread M16x1.5 |
| DP34-22G192 | Pneumatic actuator DP<br>Pneumatic actuator DP 34<br>Column diameter 22mm<br>Data sheet: 000003-1.pdf |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Operating instructions: 0040504000-1.pdf<br>Discount group: I11<br>Drive: DP34<br>Effective force (for pneumatic actuator): Spring opens when air fails<br>Valve function: Through-flow operation<br>Spring range (bar)/stroke (mm): 0.20-0.80 stroke 38mm<br>Max. permissible actuating pressure (bar): 6<br>Distance column length: L1=228mm<br>Distance column spacing: 100mm<br>Coupling: Thread M16x1.5 |
| 5,0 KN (90-264VAC) | |
| Figur 55.470 DN 100 | ARI-STEVI 470/422<br>Straight-through control valve with flanges and shaft-guided cone<br>1.4581 DN100<br>Data sheet: 470001-1.pdf<br>Operating instructions: 0040305000-1.pdf<br>discount group: I11<br>Nominal pressure: PN 16<br>Flange bore: according to DIN PN16<br>Cone design: Parabolic cone<br>Kvs value: 160<br>Characteristic curve: equal percentage<br>spindle seal: EPDM<br>Exterior treatment: unpainted<br>Actuator: AUMA<br>Drive type: SAR 07.2<br>Type: Aumatic AC<br>Design: Non Intrusive with MWG<br>Voltage: 400V/50Hz<br>Current type: 3PH three-phase current<br>torque to be set: DÖL 30Nm / DSR 30Nm<br>max.dp shut-off (bar): 16<br>max.dp control operation (bar): 9<br>Output speed: 5.6 1/min<br>Valve lift: 30mm stroke<br>Coupling: Thread M16x1.5<br>Actuating time: 80.4sec<br>Connection flange: F10 DIN ISO 5210<br>Connection type: Connection type A<br>Connection thread: TR20x4<br>Signal generator: 5 NO contacts max. 250V 1A<br>potential-free, with common<br>reference potential,<br>End position OPEN/CLOSE, selector switch REMOTE,<br>torque error CLOSE/OPEN,<br>1 changeover contact max. 250V 5A,<br>collective fault message<br>Positioner: 3-point adaptive<br>Input signal: 4 - 20mA 2-wire |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Position indicator: analog feedback (standard)<br>4-wire/2-wire active<br>Output signal: 4 - 20mA |
| Figur 55.470 DN 80 | ARI-STEVI 470/422<br>Straight-through control valve with flanges and shaft-guided cone<br>1.4581 DN 80<br>Data sheet: 470001-1.pdf<br>Operating instructions: 0040305000-1.pdf<br>discount group: I11<br>Nominal pressure: PN 16<br>Flange bore: according to DIN PN16<br>Cone design: Parabolic cone<br>Kvs value: 100<br>Characteristic curve: equal percentage<br>spindle seal: EPDM<br>Exterior treatment: unpainted<br>Actuator: AUMA<br>Drive type: SAR 07.2<br>Type: Aumatic AC<br>Design: Non Intrusive with MWG<br>Voltage: 400V/50Hz<br>Current type: 3PH three-phase current<br>torque to be set: DÖL 30Nm / DSR 30Nm<br>max.dp shut-off (bar): 16<br>max.dp control operation (bar): 14.3<br>Output speed: 5.6 1/min<br>Valve lift: 30mm stroke<br>Coupling: Thread M16x1.5<br>Actuating time: 80.4sec<br>Connection flange: F10 DIN ISO 5210<br>Connection type: Connection type A<br>Connection thread: TR20x4<br>Signal generator: 5 NO contacts max. 250V 1A<br>potential-free, with common<br>reference potential,<br>End position OPEN/CLOSE, selector switch REMOTE,<br>torque error CLOSE/OPEN,<br>1 changeover contact max. 250V 5A,<br>collective fault message<br>Positioner: 3-point adaptive<br>Input signal: 4 - 20mA 2-wire<br>Position indicator: analog feedback (standard)<br>4-wire/2-wire active<br>Output signal: 4 - 20mA |
| 22967100MKA53-113F: DN 80<br>AUTOMATIC MOTORIZED GATE VALVE | VALVE SIZE: DN80<br><br>PRESSURE RATING : PN16<br><br>MATERIAL : SS |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | REFER DETAIL-1 |
| 704235 | Thrust actuator ARI-PREMIO Type: 2.2 kN 230 V, 50-60 Hz, In 78/91 mA, P 18/21 VA, V 0,38/0,45 mm/s |
| SAFE-TC 940 DN25 | |
| SN 100182638-106 | Figure 23.405 DN 50<br>ARI-STEVI 405<br>Straight-through shut-off valve with flanges<br>EN-JS1049 DN 50<br>Data sheet: 405001-1.pdf<br>Operating Instructions: 0040304000-1.pdf<br>Nominal pressure: PN 25<br>Flange bore: according to DIN PN25<br>Spindle seal: V-rings/PTFE-graphite<br>Drive: DP32<br>Active (b.pneum.Antr): Spring closes in case of air failure<br>Spring range (bar)/stroke (mm): 1.99-2.90 stroke 13mm<br>Required control pressure (bar): 3.2 bar<br>Max. permissible control pressure (bar): 6<br>Max. closing pressure (bar): 15.3<br>Distance column length: L1=188mm<br>Distance between columns: 100mm<br>Coupling: thread M10<br>Signal generator: 2 pcs mechanical open/close<br>Discount group: I51 |
| SN 0703988299 | Figure 23.440 DN 40<br>ARI-STEVI 440<br>Straight-through control valve with flanges<br>EN-JS1049 DN40<br>Data sheet: 440001-1.pdf<br>Operating Instructions: 0040301000-1.pdf<br>Nominal pressure: PN 16<br>Flange bore: according to DIN PN16<br>Kvs value: 25<br>Characteristic curve: equal percentage<br>Spindle seal: V-rings/PTFE-graphite<br>Acceptance material testing: APZ EN10204 3.1<br>Drive: DP32<br>Wirkw.(b.pneum.Antr) : Spring closes in case of air failure<br>Spring range (bar)/stroke (mm): 1.50-2.90 stroke 20mm<br>Required control pressure (bar): 3.2 bar<br>Max. permissible control pressure (bar): 6<br>max. closing pressure (bar): 16<br>Distance column length: L1=188mm<br>Distance column spacing: 100mm<br>Coupling: thread M10<br>Positioner: EPS 14 (EEx ia IIC) |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Input signal: 4 - 20mA 2-wire<br>Set : 4 mA valve closed<br>Input with supply air (bar): 6 bar |
| SN 100830477-036 | Figure 23.451 DN 50<br>ARI-STEVI 451/463<br>Three-way control valve with flanges and bellows seal<br>EN-JS1049 DN50<br>Data sheet: 450001-1.pdf<br>Operating Instructions: 0040306000-1.pdf<br>Nominal pressure: PN 16<br>Flange bore: according to DIN PN16<br>Function of the valve: mixing function<br>Kvs value: 40<br>Characteristic curve: linear<br>Spindle seal: stainless steel bellows<br>Safety stuffing box: pure graphite<br>Drive: PREMIO-Plus 2G 2.2kN<br>Voltage: 24V AC/DC<br>Actuating speed: 0.38mm/sec<br>Actuating time: 53sec<br>max. closing pressure (bar): 6.5<br>Spindle projection: 83mm<br>Coupling: thread M12<br>Valve lift: 20mm stroke<br>Control: 4-20mA DC<br>Position indicator: Analog output card (Y out)<br>Discount group: I11 |
| SN 100830163-045 | Figure 12.440 DN 40<br>ARI-STEVI 440<br>Straight-through control valve with flanges<br>EN-JL1040 DN 40<br>Data sheet: 440001-1.pdf<br>Operating Instructions: 0040301000-1.pdf<br>Nominal pressure: PN 16<br>Flange bore: according to DIN PN16<br>Kvs value: 16<br>Characteristic curve: equal percentage<br>Spindle seal: V-rings/PTFE-graphite<br>Drive: PREMIO<br>Valve lift: 20mm stroke<br>Drive type: PREMIO 2.2kN<br>max. closing pressure (bar): 12.8<br>Motor type: BLDC motor<br>Voltage: 100-240V AC 50-60Hz<br>Actuating speed: 0.38mm/sec<br>Actuating time: 53s<br>Spindle projection: 83mm<br>Coupling: thread M10<br>Shift slide: yes |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Additional limit switches: 2 pieces 10A 250V (standard)<br>Discount group: I11 |
| ARI-PREMIO-Plus 2G | Type: 2.2kN |
| SPAREPART1706G1 | spare parts<br>Control valve<br>Description: 1x 0490000091 Option board PREMIO-Plus complete<br>1x 0273020122 Option board PREMIO-Plus esp<br>1x 0273020107 Sled PREMIO-plus<br>Figure: 22423 ARI-STEVI 450/423 Three-way control valve with flanges<br>Nominal diameter: DN200<br>Material: EN-JS1049<br>Note: The spare parts kit includes the requested items.<br>1 (50.154), 3 (50.141) and 4.<br>The ES11 type positioner is<br>not an accessory component for the thrust drive<br>ARI-PREMIO-Plus according to the control valve of the<br>Serial number 100390121-030! |
| 0254000013 | Position controller ES11 230VAC<br><br>PLEASE NOTE!!! XXX<br>The ES11 type positioner is not an accessory component for the thrust drive<br>ARI-PREMIO-Plus according to the control valve of the<br>Serial number 100390121-030! This drive variant is<br>the Control via a control signal already integrated.<br>The ES11 positioner is used as Accessory component for the ARI-PREMIO thrust drive |
| TRIP SLIDE-50.141 | |
| ANALOG OUTPUT CARD | |
| STEVİ440/PN40 | Service kit of Armaturen pneumatic valve |
| SN 100589817-001 | 910000001G191<br>EL actuator PREMIO<br>2.2-25kN<br>Datasheet: 000038-1.pdf<br>Operating instructions: 0040501009-1.pdf<br>Valve stroke: 30mm<br>Drive type: PREMIO 5kN<br>Motor type: BLDC motor<br>Voltage: *3~400V 50/60Hz<br>Actuating speed: 0.38mm/sec<br>Setting time: 79s<br>Spindle projection: 83mm |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Coupling: Thread M12<br>Shift slide: yes<br>Additional limit switches: 2 pieces 10A 250V (standard)<br>Position indicator RI32: * 4-20 mA direct<br>Connection board: NA (acc. t000043859)<br>Turning point: External turning point |
| 0490000092 | PREMIO-Plus option board complete |
| ARI-PREMIO®-Plus 2G | Aksesuar |
| ARI-STEVI BBD 415 | according to SN 100656674-408<br>Figure 35.415 DN 32ARI-STEVI BBD 415<br>Blowdown valve in straight-through design with flanges and pneumatic<br>drive<br>1.0619+N DN 32<br>Nominal pressure: PN 40<br>Flange bore: according to DIN PN40<br>Kvs value: 6.4<br>Spindle seal: Roof collars/PTFE graphite<br>Drive: P-drive 80 $cm^2$<br>Spring rate (bar)/stroke (mm): 1.55-2.40 Stroke 7mm<br>Max. closing pressure (bar): 40 bar<br>Required operating pressure (bar): 4.0 bar<br>Max. permissible actuating pressure (bar): 6 bar<br>Signal transmitter: 1 pc. mechanical.<br>Solenoid valve: DN2.5 230V/50-60Hz with high-pressure valve<br>Discount group: I55 |
| 910000001G191 | according to SN 100656675-122<br>910000001G191<br>EL actuator PREMIO<br>2.2-25kN<br>Datasheet: 000038-1.pdf<br>Operating instructions: 0040501009-1.pdf<br>Valve stroke: 7mm<br>Drive type: PREMIO 2.2kN<br>Motor type: BLDC motor<br>Voltage: 100-240V AC 50-60Hz<br>Actuating speed: 0.38mm/sec<br>Setting time: 19s<br>Spindle projection: 83mm<br>Coupling: Thread M10<br>Shift slide: yes<br>Additional limit switches: 2 pieces 10A 250V (standard) |
| SN :805947312 | ARI-PREMIO BLDC TYPE:5kN / S4,S5 / 100-240V / 50/60HZ / HUB TRAVEL:50MM / SN:805947312<br><br>STEVI-440 / PN25 / Kvs 25 / GLP / V-Ring / SN:100564800-324 |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | A complete valve assembly is required. |
| SN :100501871-186 | ARI-PREMIO THRUST ACTUATOR TYPE:2.2kN / S4,S5 / 230V / 50/60HZ / HUB TRAVEL:20 MM / SN:100501871-186<br><br>STEVI-470 / PN25 / Kvs 10 / LIN / V-Ring / SN:100501871-187<br><br>A complete valve assembly is required. |
| SN :100510559-186 | ARI-PREMIO THRUST ACTUATOR TYPE:25kN / RI21/32 / 100-240V / 50/60HZ / HUB TRAVEL:50MM / SN: 100510559-186<br><br>ONLY THE ACTUATOR PART IS REQUIRED. |
| SN :100501875-224 | ARI-PREMIO THRUST ACTUATOR TYPE:2.2kN / RI21 / 230V / 50/60HZ / HUB TRAVEL:20MM / SN:100501875-224<br><br>ONLY THE ACTUATOR PART IS REQUIRED. |
| SN :100510657-204 | ARI-PREMIO THRUST ACTUATOR TYPE:15kN / RI21/32 / 100-240V / 50/60HZ / HUB TRAVEL:30MM / SN: 100510657-204<br><br>STEVI 470 / PN25 / Kvs100/ GLP / LOK / V-Ring / SN: 1000510657-204<br><br>A complete valve assembly is required. |
| SN :100498207-092 | ARI-PREMIO THRUST ACTUATOR TYPE:12kN / RI21/32 / 100-240V / 50/60HZ / HUB TRAVEL:17MM / SN: 100498207-092<br><br>STEVI-405 / PN25 / O/C / V-Ring / SN:100498207-092<br><br>A complete valve assembly is required. |
| 0389020080 | Rolling diaphragm DP32<br>NBR<br>250cm² |
| 35.046 DN 80 PN 40 | METAL BELLOWS / SHUT-OFF VALVE |
| 12.046 DN 40 PN16 | METAL BELLOWS / SHUT-OFF VALVE |
| 35.046 DN 25 PN16 | METAL BELLOWS / SHUT-OFF VALVE |
| 23.046 DN 40 PN25 | METAL BELLOWS / SHUT-OFF VALVE |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| 12.046 DN 32 PN16 | METAL BELLOWS / SHUT-OFF VALVE |
| 23.046 DN 40 PN40 | METAL KORUKLU / KESME VANASI |
| 35.046 DN 15 PN 40 | METAL BELLOWS / SHUT-OFF VALVE |
| 0254000013 | |
| 901 | |
| 55.006 | |
| 911100028g191 Ari-Premio 2,2kn | |
| Ari -Safe | |
| Le22015ep080 | |
| Figur 12.924 Dn 40 | |
| Ari Zesa - En-Js1030 - Dn200 Pn16 | |
| 22046 Dn25 | |
| Fig23.046 Dn32 Pn25 | |
| 23.046 Dn20 Pn25 | |
| 0466000403 | |
| Self Tapping Screw For Ari-Premio 5.0 Kn S/N 444990 | |
| Ari -Safe Electronic Controller | |
| 2.2kn 115vac | |
| Figur 22.046 Dn 32 | |
| 1.4408 Dn 20 | |
| 23.046 Dn15 Pn25 | |
| Figur 35.440 Dn 32 | |
| Fig23.046 Dn50 Pn25 | |
| 0254000013 , Type Es11 | |
| Figur 25.901 , Dn 100 | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| Ari-Stevi 470/422 (Figur 35.470 Dn 20) Sn1231064336 | |
| Figur 67.961 | |
| Ari-Stevi 470/422 (Figur 23.470 Dn 25) Sn1231064335 | |
| Fig23.046 Dn40 Pn25 | |
| 52.006 | |
| 0466000325 | |
| Fig. 23.470 Dn125 | |
| 22046 Dn 50 | |
| Vh00000411 | |
| Ari-Zesa Fig.012 | |
| Figur 72.487 | |
| Fig.Vsmwa+ap4 Dn80 | |
| 55006 | |
| Figur 23.006 Dn 150 | |
| Sq10 (9600100000g191) | |
| Figur 22.046 Dn 25 | |
| Fig23.046 Dn100 Pn25 | |
| Elektrischer Schubantrieb Ari-Premio-Plus 2g 2,2kn (911130030g191) | |
| Pn25 Dn20 | |
| 50.40 | |
| Figure 901/902,Werkstoffe | |
| Fig. 12.441 Dn150 Premio 12kn | |
| Ari-Premio 12 Kn | |
| 911100000g191 (Sn1231064335) | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| 92052 | |
| Figur 23.003 / Dn 50 / Ari-Checko-V | |
| Figur 35.046 | |
| Ari-Stevi 440 (Figur 35.440) Sn1231164966 | |
| El-Stellantrieb Premio 5kn (911150000g191) | |
| Pn25 Dn200 | |
| Sealing Ring-Item 27 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1 | |
| Cona S | |
| 22047 | |
| 0466000221 | |
| 22050 Dn 125 | |
| Fig34.046 Dn300 Pn25 | |
| Figur 23.470 / Dn 50 / Ari-Stevi 470/422 | |
| 23.046 Dn25 Pn25 | |
| Fig34.046 Dn200 Pn25 | |
| 45600 | |
| Es11 230vac | |
| 0466000451 | |
| Zetrix Pn40 Dn100 | |
| Figur 12.440 Dn 80 | |
| 95001 | |
| 12-15 Kn | |
| Figur 22.046 Dn 20 | |
| Ari-Stevi 445 | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| Ari-Premio 5.0 Kn, Art N: 911150000g191 | |
| Svw 10 44 Bar G 1/2 A, -Not Available, Alternative Model Figur 67.961 | |
| Schubantrieb Ari-Premio (Premio 5kn) Artikel-Nr 910000001g191 | |
| Pn25 Dn40 | |
| Ari-Premio-Plus 2g (911160030g191) | |
| Figur 35.405 Dn 25 Type Ari-Stevi 405 | |
| 911100000g191 (Sn1231064336) | |
| Ri21 | |
| Figur 35.470 Dn 20 | |
| Ari-Safe 12.911 | |
| Ari-Stevi 405 (Figur 35.405) Sn1230563960 | |
| Ari-Stevi 12440 | |
| Figur 35.405 Dn 40 | |
| Fig.921 Pn16 Dn25 | |
| Ta7 | |
| 9512440 | |
| Ari -Safe Dn40/65 | |
| 9555445 | |
| EPS11.1 Positioner | 0254000015<br>4-20 mA<br>4763-01200121000004<br>Type: 4763<br>Design: electro-pneumatic<br>Control: 2-wire<br>Input signal: 4-20 mA<br>Electrical connection: M20x1.5<br>Degree of protection: IP54<br>Connection: G 1/4<br>Stroke [mm]: 7.5-90<br>Temperature max .: +70 |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| | Temperature min.:-20<br>Housing material: aluminum |
| 426755 By Ari-Premio (Premio 5kn) Artikel-Nr. 910000001g191 | |
| Fig23.046 Dn20 Pn25 | |
| Premio 5kn (910000001g191) | |
| Elektrischer Hlk-Schubantrieb Ari-Paco 0,85kn | |
| 911150000g191 (Sn1230563960) | |
| Ari-Stevi 440 | |
| Figur 12.440 Dn 25 | |
| Spring- Item 37 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1 | |
| 224700 + Dp34+ Eps15 | |
| Ari-Premio-Plus 2g (911130030g191) | |
| Figur 23.470 Dn 25 | |
| Figur 12.901 , Dn 65 | |
| Fig23.046 Dn150 Pn25 | |
| Figur 25.901 , Dn 32 | |
| Figur 22.046 Dn 50 | |
| 0490000303 | |
| Ari -Safe Dn 65/100 | |
| Ari-Stevi 470/422 (Figur 23.470 Dn 25) | |
| Old Reference Number -- Deufra Oa8 - New Reference Number Sq10 | |
| 550017-550045 | |
| 911100000g191 (El-Stellantrieb Premio 2,2kn) | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| 22046 Dn 125 | |
| 12-470 | |
| 0254000075 | |
| Conas639. | |
| 9110400126 | |
| Ari-Safe - Trd721 | |
| Ari Zesa - En-Js1030 - Dn100 Pn16 | |
| 1301073555 | |
| 2.2kn 230vac | |
| Spindle-Item 14 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1 | |
| 23.470 Dn 25 (Ari-Stevi 470/422) | |
| Figur 35.921 , Dn 50 | |
| Dn250/Pn16 Ari Fig.22.046 | |
| 50.40.3 | |
| 911250100g191 | |
| Ari-Stevi 405 (Figur 35.405 Dn 40) | |
| 2.2kn | |
| Figur 22.046 Dn 15 | |
| Gasket-Item 7 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1 | |
| Ari-Paco 0,85y | |
| Fig34.046 Dn250 Pn25 | |
| Premio 2.2kn, Art N: 910000001g191 | |
| Fig.Vsmwa+ap4 | |
| Zg1 | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*

**Yursat Dış Tic. Mühendislik**
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

| Ürün | Açıklama |
|---|---|
| Fig.Vsmwa+ap3.5 | |
| Packingrings-Item 31 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1 | |
| 0277000032 | |
| 220120300193 | |
| Fig23.046 Dn65 Pn25 | |
| 911150000g191 (Sn1231164966) | |
| Figur 22.046 Dn 40 | |
| Pn 40 | |
| Repair Kit For Dn 50 | |
| Figur 22.450 Dn 150 | |


*YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.*