

Bachofen

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Bachofen Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Bachofen Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
SC-N2-ATEX bar SWITCHcontrol	60100792 2-way position feedback with 2 NAMUR round initiators Fabr. Pepperl & Fuchs Type: NCN4-12GM35-NO ATEX identification: for gases: Ex II 2G Ex ia IIB T6-T1 Gb (Zone 1 + 2) for dust: Ex II 2D Ex ia IIIB T135 ° C Db (zone 21 + 22) Ambient temperature -20 ° C to + 70 ° C in closed aluminum housing with optical position indicator Degree of protection: IP67 including operating instructions German / English HS code: 90328900 total net weight 5.00 kg Country of origin Germany
Hydraulic Unit HY-9001-xxxx	- Aluminum tank 10 L - Basic block including return filter and accumulator charging valve - Electric motor 1.1 kW - Gear pump 5 l/min - Max. working pressure: 85 bar - Pressure switch set to 50 bar - Accumulator 1.4 liters
60100792	SC-N2-ATEX bar SWITCHcontrol 2-fold position feedback with 2 NAMUR round initiators Make Pepperl & Fuchs Type: NCN4-12GM35-NO ATEX identifier: for gases: Ex II 2G Ex ia IIB T6-T1 Gb (Zone 1+2) for dust: Ex II 2D Ex ia IIIB T135°C DB (Zone 21+22) Ambient temperature -20°C to +70°C

Ürün	Açıklama
	in a closed aluminum housing with optical position indicator Degree of protection: IP67 including operating instructions German / English
1-86-XV-1015	
8021/100VG0004M----A-Z--S----110	Ident number 4073172 Nominal diameter(100): DN 100 (Kvs 95; Cv 110), Function(G): Sliding gate valve 8021, Design(0): GS1-intermediate flange design PN10-PN40 (for flanges according to DIN EN 1092-1, form B), Housing material(0): C-steel 1.0619, Safety position(0): Spring closes, Actuator(4): Diaphragm actuator 250 cm ² , Springs(-): Standard spring fitting, Sliding disk, movable(-): Carbon material, Sliding disk, fixed(-): Standard coating, Stainless steel 1.4571, Kvs/Cv values(A): red. to 63%, characteristic curve (-): linear, additional special versions (110): i/p positioner, type PS2 6DR5110-ONG00 (or 6DR5110-ONN00), HART, IP66
LPD 136 C	
Ewe 1 Ch 8610	
B1t-M12ss - Pressure Switch	
A057471	
Mp66s K53 No:182312/07 - Dc Servo Motor	
Er20.X0b.G00	
A004421 Wf 18	
Uds-3 44-031551101 - Pressure Switch	
P/N: 137-53-203 Type: Mmz 3600	
Bag/Uds7-881482-118-4-0-10	
Bfs-10-O-G1/4-MS-We-St	
A004421 Wf 18	
A057473	

Ürün	Açıklama
Er20 X0b G00	
Ps4102v-Z	
170122985	
Bachofen-Ewe-1-Adc-24- Obsoletereplaced-By-Lmz3600- Adc24-100-Walter-M3;Ller-Ag-Istanbul- Türkiye	