Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Badotherm

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Badotherm Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Badotherm Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
0,5 Präzisionsthermometer	können sie uns es anbieten?
Pressure Indicator	Scale: 0-40 bar, Accuracy: 0.5% (Full Scale), Resolution: 100 mbar (3.5 digits), ATEX, 1/4” NPT EN 837 CLASS 800 1/2''
Temperature Indicator	Scale : -30 , + 60 C , Accuracy : 1% of reading ± 0.25°C, Resolution : 0.1 °C, (3.5 digits) DIN 16202 CLASS 800 1/2''
Bourdon tube pressure gauge EN 837-1, 0-25 Bar	Bourdon tube pressure gauge EN 837-1 Crimp ring housing 60 mm D, stainless steel with front ring made of stainless steel prepared for filling Connection G1/4 B, eccentric at the back stainless steel Measuring range 0-25 bar Accuracy class 1.6
Bourdon tube pressure gauge EN 837-1, 0-16 Bar	Bourdon tube pressure gauge EN 837-1 Crimp ring housing 60 mm D, stainless steel with front ring made of stainless steel prepared for filling Connection G1/4 B, centrally at the back stainless steel Measuring range 0-16 bar Accuracy class 1.6

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Bourdon tube pressure gauge EN 837-1, 0-10 Bar	Bourdon tube pressure gauge EN 837-1 Crimp ring housing 60 mm D, stainless steel with front ring made of stainless steel prepared for filling stainless steel Measuring range 0-10 bar Accuracy class 1.6
Bourdon tube pressure gauge EN 837-1, 0-10 Bar	Bourdon tube pressure gauge EN 837-1 Case 60 mm D, stainless steel with glycerine filling Connection G1/4 B, centrally at the back stainless steel Measuring range 0-10 bar Accuracy class 1.6 Note: only in NG60
Bourdon tube pressure gauge EN 837-1, 0-40 Bar	Bourdon tube pressure gauge EN 837-1 Crimp ring housing 60 mm D, stainless steel with glycerine filling Connection G 1/4 B below, stainless steel Measuring range 0-40 bar Accuracy class 1.6
MANOMETER: DIAMETER: 63mm 0-16 BAR, G1/4"	BOTTOM CONNECTION, LIQUID FILL NONE, COMPLETE STAINLESS, KL 1.6
PM-100N.2.1.1.0.99(0-60kg/m²)	Bourdon tube pressure gauge Version: stainless steel measuring mechanism Cushioning: none Process connection: G 1/2“-AG below Fastening edge: without Measuring range: 0...60 kg/m² Option: without
100 mm diameter, ½” , bottom feeding.	
100 mm diameter, ½”, tail length 150 mm.	
160mm. 0/70 msw-fsw, rear output, enclosure	type 1/2" size CL.0.25 Manometer
160mm. 0/100 msw-fsw, rear output, enclosure type	1/2" size CL.0.25 Manometer
BDT18 63A3S4F2B6516	PRESSURE GAUGE
Bourdon tube pressure gauge	Nominal size: 100 mm Version: stainless steel measuring mechanism

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Process connection: 1/2“- NPT below Fastening edge: without Cushioning: glycerin Measuring range: 0...16 bar Class: 1.0 Degree of protection: IP65
1/2 6mm adjustable sleeve	
CONTACT MANOMETER -0/16 BAR - PRESSURE TRANSMITTER	G 3/4"-MEMBRAN/THREAD:1.4571 -SS BODY(BADOTHERM)
PM-100N.1.1.1.0.J	Bourdon tube pressure gauge Version: brass Cushioning: without Process connection: G 1/2“ male thread below Fastening edge: without Measuring range: 0...40 bar
EN 13190 Bimetal	
6 kg/cm2	
PM-100N.2.2.2.3.P	Design: Chemical design made entirely of stainless steel Damping: with glycerine filling Process connection: G 1/2" A eccentric rear Mounting edge: 3-edge front ring Measuring range: 0...60 bar (no double scale, only bar)
PM-100N.2.2.1.0.L.99	Design: Chemical design completely in stainless steel Damping: with glycerine filling Process connection: G 1/2" A bottom Mounting edge: without Measuring range: 0...100 bar Option: with drag pointer
12LBA10CT501 HRSG HP LIVE STEAM TEMPERATURE INDICATOR (BDTE18-fi6-160mm-SW2(316) L=200mm/85-S=75-1/2"NPT M/0-160C/-MT)	
Gas pressure thermometer EN 13190	Stainless steel case, 160 mm ø with neck tube Temperature sensor vertical, Form 9 8 mm ø,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	60 mm long, Stainless steel 1.4541 Union nut with double nipple 1/2 NPT Measuring range -20-0-+120°C Accuracy class 1.0
Bourdon tube pressure gauge EN 837-1	Case 160 mm Stainless steel with glycerine filling 1/2 NPT bottom connection, stainless steel Measuring range 0-6 bar Accuracy class 1.0
Manometer -1 - +1,5bar 1/2''	100mm
Manometer 0-10bar 1/2''	100mm
Dial size 100mm	
Dial size 160mm	
Bourdon Pressure Gauge	Bourdon Pressure Gauge / Dial Size: ø160mm / Range: 0+160 Bar / Accuracy: Cl. 1.0% / Window: Safety Glass / Case filling: Glycerine / Mounting: bottom connection Thread Size: 1/2” NPT / ATEX Cert. / Calibration Certified
US-F	
BDT18SB 160R/S Type A	Pressure range 0....+6 Bar/Psi
Bdt19/S-C -160	Manometer Model : BDT19/S-C -160 US-F
Manometre	
12131090115301250000 Bdt18 A 160mm - 1/2quot;Npt	
25810e1a713551000000	
1213101011301250000	
12241010111309250000 Bdt20 A 100mm - 1/2quot;Bsp 0+10 Bar	
Bdt13-Cs C 53000000000000000379	
Dwg. 1.3006.021	
Model: Bdt/18e	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
12121090106601250000	
12121090124301250000	
0..200a	
6x100mm	
20510410773053000000 Bdtg18 A 160mm 0+160 ;C	
13101014420209330000 Bdt9-18 A 100mm - 1/2quot;Bsp 0+250 Mbar	
Bdt18-Type A	
Bdt18 A 100mm Bottom	
Bdt19/S-A -160	Manometer Model : BDT19/S-A -160 US-F
Bdt18/A-Bpf01	
19998300000000000484 Bdt20p A 100mm - 1/2quot;Bsp 0+40 Bar	
29998300000000000072	
Model: Bdt19 Type:A	
12121010111301250000	
04131430	
Bdtg18 A 100mm	
12131090120601250000	
Bdt 18/A 0-25 Bar	
Model: Bdt18/E63q	
Bdt-19/S-A 100 Completely Inox	
25610410815551000000 Bdtb18 A 100mm 0+200 ;C	
2001001a3922c3000000 / Bdtg18 Skin A 100mm	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Bdtb1-18	
Bdt 18/A 0-6 Bar	
Bdt18 A 100mm - 1/2quot;Npt	
Model: Bdtg-Distance-E	
20510410473053000000 Bdtg18 A 160mm 0+120 ;C	
11369018	
0...300a	
12491010113309330000 Bdt12 A 160mm - 1/2quot;Bsp 0+25 Bar	
Bdt20/D	
12191090127601250000	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.