Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Baelz

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Baelz Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Baelz Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
367-2-K-SS-A3-DN 50/2"-Kvs 36/Cv 42	Order no. 367-3435 Three-way control valve ANSI 300, cooling pipe + bellows SA216 WCB, max. 650 ° F / 343 ° C, stroke 22 mm; o. drive Housing: SA 216 WCB Flange connection: ANSI B 16.5 max. 650 ° F / 362 psi - 100 ° F / 362 psi max. 343 ° C / 25 bar - 38 ° C / 25 bar Stroke: 0.87 inch / 22 mm; Spindle Ø 10 mm DN 50/2 ", Kvs 36 / Cv 42 Installation length ANSI / ISA 75.08.01: 10.51 inch / 267 mm Passage (A-AB) and corner (B-AB) Kvso: 0.004% Flow rate: ____ Pressure drop: ____ max.permissible differential pressure, mixing valves (2 inputs / 1 output) ____ bar max.permissible differential pressure, diverter valves (1 input / 2 outputs) ____ bar Net weight: 21.5 kg
3-way control valve ANSI 300, cooling	tube+bellows SA216WCB, max. 650°F/343°C, stroke 22 mm 367-2-K-SS-A3-DN 50/2"-Kvs 36/Cv 42 without actuator body: SA 216 WCB flanged connection: ANSI B 16.5 max. 650°F/362 psi - 100°F/362 psi max. 343°C/25 bar - 38°C/25 bar stroke: 0,87 inch / 22 mm; spindle-Ø 10 mm DN 50 / 2", Kvs 36 / Cv 42 face-to-face length ANSI/ISA 75.08.01: 10,51 inch / 267 mm straight way (A-AB) and angle way (B-AB) Kvso: 0,004%
Linear motorized actuator 3-point 2000	N; 18 mm/min 373-E07-20-18-S21-230 stroke max. 22 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	incl. yoke and coupling (S21) IP 42; 230 V, 50/60 Hz
373-E07-20-18-S21-230	Order no. 373-E07-20-18-30 3-point motorized lift drive 2000 N; 18 mm / min Stroke max. 22 mm Including stand and coupling (S21) IP 42; 230 V, 50/60 Hz Net weight: 2.4 kg
356-1-VA-DN 15-PN 16/25/40-Kvs 3,8	Order no. 356-353 Stainless steel straight-way control valve 1.4571, max. 240 ° C, stroke 16 mm; without drive Housing and seat: 1.4571 internal parts in contact with the medium: 1.4571 / 1.4021 max. 240 ° C / 40 bar - 100 ° C / 40 bar Spindle Ø 10 mm DN 15, PN 16/25/40, Kvs 3.8 Flow rate: ____ Pressure drop: ____ max.permissible delta p: 25 bar Net weight: 5.5 kg + Order no. 373-E07-20-06-001 3-point motorized lift drive 2000 N; 6 mm / min. 373-E07-20-06-S21-230 1 piece Stroke max. 22 mm Including stand and coupling (S21) IP 42; 230 V, 50/60 Hz Net weight: 2.4 kg
356-1-VA-DN 15-PN 16/25/40-Kvs 3,8 (alternative)	Order no. 356-353 Stainless steel straight-way control valve 1.4571, max. 240 ° C, stroke 16 mm; without drive Housing and seat: 1.4571 internal parts in contact with the medium: 1.4571 / 1.4021 max. 240 ° C / 40 bar - 100 ° C / 40 bar Spindle Ø 10 mm DN 15, PN 16/25/40, Kvs 3.8 Flow rate: ____ Pressure drop: ____ max.permissible delta p: 25 bar Net weight: 5.5 kg +

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Linear diaphragm actuator Order no. 373-P21-007 3 springs on top 373-P21-3-Fo-S21-22mm 1 piece 306.34 Ambient conditions: 0... 80 ° C, 0... 90% r.h. required Control air pressure: 3 bar, max. 6 bar up to max. 22 mm stroke including drive stand and coupling (S21), including push-in fitting for hose Ø 8 mm for fittings with spindle Ø 10 mm Net weight: 5.3 kg
Best.-Nr. 375-E03-002	Rotary motor drive * 40 Nm; 3 min .; 2 additional Limit switch 375-E03-40Nm-3min.-2EZ-230 Angle of rotation 90 °; free shaft end IP42; 230 V, 50/60 HZ Net weight: 1.9 kg
6590-1202	PID temperature three-point step controller 0 ... + 300 ° C * Y bar graph; 1 PT100, 1 alarm, RS485; 48x96x140 mm 6590 / BY3-2.4-230 Control panel front installation, IP 65 1 AI, 1 alarm relay Y-bar graph display and position indicator RS485 Modbus RTU 230 V, 50/60 Hz Net weight: 0.5kg
127037	
185 DN15 PN40	
24180	
340-068 + 373-E45-40-15-521-2	
340-BK-E40-40-20-S21-2EZ-FG200	
342-BK-SS-373-P21-6-Fu-86	
342-BK-SS-DN 50-PN 16-Kvs 36	
346-AI-BB-EMF DN 250 PN 16	
354-373-E40	
356-373-EO7	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
360 EMC-373-E11	
373 E02	
373-E02-10-18-220-50-2EZ	
373-E07 DN100	
373-E07-20-06-5005	
373-E07-20-18- S21	
373-E07-20-18-463	
373-E07-20-18-S21-24 (Best.-Nr. 373-E07-20-18-305)	
373-E44-40-18-001	
373-E45-40-15	
373-E45-40-15-171-1 + MP373-E45-1051	
373-E45-40-15-521-1	
373-E45-40-15-S21-230	
375-E41	
375-EO3	
38-X2	
590-1-DN 80-PN	
5B91030-001	
6443 R-375, IV 96 6443R-375/1	
6490/... µCelsitron	
6490/1-2.4-230	
6490/2,0-300[C-USC.4-20mA	
6490/2-2.4-230-S12B	
6490-0201	
6490-0202	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
6490-1302	
6590	
6590 / 0	
6590/2-2.4-024	
6590/B4-2.4-230 (6590-1302)	
6590A	
6590A/4-2.4-230	
6597-0101	
6597-1-S9-2.33-230 (6597-0101)	
87-001	
99.0S373-923	
B375E03-031	
BAELZ 6490/1-2.2-230	
Baelz 87	
BAELZ6490	
DN 15,PN16 KVS 3,8	
DN40 PN16/25	
D-VENTIL	
HDT (HA3P) 4B	
KT 21923	
KT 7691	
KT 7757	
KT 7980	
KT 8213	
KT 8391	
KVS9 - 3425 DN25 - PN16/25	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
OHLP 10	
P21-3FU-S21-22mm	
RSM 51/8 (DRSM 50/6 NG"ES)	
RSM 63/8 FG	
WBS 340 B-AD-40-16-25	
WBS 340-B-AD-65-16-63	
375-E03-602	motor rotary drive* 100 Nm; 20s.; 2 additional limit switches 375-E03-100Nm-20s-2EZ-230 angle of rotation 90°; ISO5211 with SW14 IP67; 100-230V 50/60 Hz
342-2452	D-VALVE Valve with actuator mounted closed without power Three-way control valve with cooling tube and DW bellows 5.3103, max. 350°C, stroke 22 mm; without drive 342-2-BK-SS-DN 80-PN 25-Kvs 105 KS 22553 Housing: GJS-400-18-LT - 5.3103 max. 350°C/17.5 bar - 50°C/25 bar with cooling tube and double-walled bellows Spindle diameter 10 mm DN 80, PN 25, Kvs 105 Passageway: (A-AB) Kvso: 0.004% Corner path: (B-AB) Kvso: 2% max. permissible differential pressure, mixing valves (2 inlets/1 outlet) 3.3 bar max. permissible differential pressure changeover valves (1 inlet/2 outlets) 0.6 bar Net weight: 28.6 kg 373-P21-019 Linear diaphragm actuator* 6 springs below 373-P21-6-Fu-S21-22mm Ambient conditions: 0...80°C, 0...70% rH Required control air pressure: 3 bar, max. 6 bar Stroke: max. 22 mm including drive stand and coupling (S21), including plug-in screw connection for hose Ø 8 mm for fittings with spindle diameter 10 mm Net weight: 5.22 kg

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
342-3455	D-VALVE Valve with actuator mounted closed without power Three-way control valve with cooling tube and bellows 1.0619, max. 350°C, stroke 22 mm; without drive 342-2-BK-SS-DN 100-PN 25/40-Kvs 130 Case: GP240GH - 1.0619 max. 350°C/25 bar - 50°C/25 bar Spindle diameter 10 mm DN 100, PN 40, Kvs 130 Passageway: (A-AB) Kvso: 0.004% Corner path: (B-AB) Kvso: 2% max. permissible differential pressure, mixing valves (2 inlets/1 outlet) 3.6 bar max. permissible differential pressure changeover valves (1 inlet/2 outlets) 0.6 bar Net weight: 45, Order No. 373-P21-023 Linear diaphragm actuator* 12 springs below 373-P21-12-Fu-S21-22mm Ambient conditions: 0...80°C, 0...70% rH required / max. control air pressure: 6 bar Stroke: max. 22 mm including drive stand and coupling (S21), including plug-in screw connection for hose Ø 8 mm for fittings with spindle diameter 10 mm Net weight: 6 kg
Alternative position	D-VALVE Valve with actuator mounted closed without power Alternative to Position 1 Order No. 342-2452 Three-way control valve with cooling tube and DW bellows 5.3103, max. 350°C, stroke 22 mm; without drive 342-2-BK-SS-DN 80-PN 25-Kvs 105 KS 22553 Housing: GJS-400-18-LT - 5.3103 max. 350°C/17.5 bar - 50°C/25 bar with cooling tube and double-walled bellows Spindle diameter 10 mm DN 80, PN 25, Kvs 105 Passageway: (A-AB) Kvso: 0.004% Corner path: (B-AB) Kvso: 2% max. permissible differential pressure, mixing valves (2 inlets/1 outlet) 3.3 bar max. permissible differential pressure changeover valves (1 inlet/2 outlets) 0.6 bar Net weight: 28.6 kg

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Order No. 373-P21-019 Linear diaphragm actuator* 6 springs below 373-P21-6-Fu-S21-22mm Ambient conditions: 0...80°C, 0...70% rH Required control air pressure: 3 bar, max. 6 bar Stroke: max. 22 mm including drive stand and coupling (S21), including plug-in screw connection for hose Ø 8 mm for fittings with spindle diameter 10 mm Net weight: 5.22 kg Order No. 87-011 Digital I/P positioner LCD, input 4...20mA, including mounting on 373-P... 87-M automatic initialization with LCD and lever return for baelz diaphragm actuators, single-acting Input signal: 4...20 mA (2-wire) Protection class: IP 66 Cable gland: polyamide PA, black, M20x1.5 Connection: G1/4, internal thread Stroke: 12...66 mm WxHxD 144x87x76 mm Net weight: 0.8 kg Order No. ZB87-321-M Pressure gauge mounting block mounted incl. 2 pressure gauges, 0-10 bar (not for 87-RM-Ex) Case diameter 40 mm Price includes assembly; without positioner Net weight: 0.5 kg Order No. 268-101-M Three-way solenoid valve, socket connection, female thread brass, 0-6 bar; max. 100°C; including assembly 268/2-230V-M Housing: Brass Seal: FKM Medium temp.: max. -10...+100°C Pressure range: 0...6 bar in conjunction with baelz 373-P... Pmax. 6 bar G 1/4, seat diameter 2 mm, Kvs 0.11 Appliance socket EN175 301-803/A with LED and varistor IP 65; closed without power (OSG) 230 V, 50/60 Hz including installation on baelz diaphragm actuator Net weight: 0.8 kg Order No. 54298-001-M-87 Diaphragm pressure regulator mounted on P21/22/P31/32/P41 only in conjunction with 87, 88, 88-8792 54298/1-M-87 with sintered filter

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Housing: upper part zinc die-cast Internal parts: brass/stainless steel Input max. 16 bar Output 0.5...10 bar Connection G 1/4; pressure gauge Ø 50 mm (Price without positioner 87, 88, 88-8792, without pneumatic drive) Net weight: 1 kg
Alternative position 2	D-VALVE Valve with actuator mounted closed without power Alternative to position 2 Order No. 342-3455 Three-way control valve with cooling tube and bellows 1.0619, max. 350°C, stroke 22 mm; without drive 342-2-BK-SS-DN 100-PN 25/40-Kvs 130 Case: GP240GH - 1.0619 max. 350°C/25 bar - 50°C/25 bar Spindle diameter 10 mm DN 100, PN 40, Kvs 130 Passageway: (A-AB) Kvso: 0.004% Corner path: (B-AB) Kvso: 2% max. permissible differential pressure, mixing valves (2 inlets/1 outlet) 3.6 bar max. permissible differential pressure changeover valves (1 inlet/2 outlets) 0.6 bar Net weight: 45.3 kg Order No. 373-P21-023 Linear diaphragm actuator* 12 springs below 373-P21-12-Fu-S21-22mm Ambient conditions: 0...80°C, 0...70% rH required / max. control air pressure: 6 bar Stroke: max. 22 mm including drive stand and coupling (S21), including plug-in screw connection for hose Ø 8 mm for fittings with spindle diameter 10 mm Net weight: 6 kg Order No. 87-011 Digital I/P positioner LCD, input 4...20mA, including mounting on 373-P... 87-M automatic initialization with LCD and lever return for baelz diaphragm actuators, single-acting Input signal: 4...20 mA (2-wire) Protection class: IP 66 Cable gland: polyamide PA, black, M20x1.5 Connection: G1/4, internal thread Stroke: 12...66 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	WxHxD 144x87x76 mm Net weight: 0.8 kg Order No. ZB87-321-M Pressure gauge mounting block mounted incl. 2 pressure gauges, 0-10 bar (not for 87-RM-Ex) Case diameter 40 mm Price includes assembly; without positioner Net weight: 0.5 kg Order No. 268-101-M Three-way solenoid valve, socket connection, female thread brass, 0-6 bar; max. 100°C; including assembly 268/2-230V-M Housing: Brass Seal: FKM Medium temp.: max. -10...+100°C Pressure range: 0...6 bar in conjunction with baelz 373-P... Pmax. 6 bar G 1/4, seat diameter 2 mm, Kvs 0.11 Appliance socket EN175 301-803/A with LED and varistor IP 65; closed without power (OSG) 230 V, 50/60 Hz including installation on baelz diaphragm actuator Net weight: 0.8 kg Order No. 54298-001-M-87 Diaphragm pressure regulator mounted on P21/22/P31/32/P41 only in conjunction with 87, 88, 88-8792 54298/1-M-87 with sintered filter Housing: upper part zinc die-cast Internal parts: brass/stainless steel Input max. 16 bar Output 0.5...10 bar Connection G 1/4; pressure gauge Ø 50 mm (Price without positioner 87, 88, 88-8792, without pneumatic drive) Net weight: 1 kg
373-E07-20-18-469	3-point motor drive 2000 N; 18 mm/min; 230 VAC 373-E07-20-18-S21-2EZ-V2-22mm-230 Drive type: electric Travel: 22 mm Construction: S21 f. fitting spindle-Ø 10 Power supply: 230 VAC Actuating force: 2000 N Actuating speed: 18 mm/min Control: 3-point Input signal: 3P Additional limit switches: yes IP protection rating: IP 42

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
6590/1	
342-061 + 373-P21-023	
Wbs-340-B-Ad-E4	
185-373-E07	
375-E41-151	
6590/2	
D-Textbaustein	
2290-A-D-2.3-230-Sa	
E40-40-20(E4-Ty20)	
Baelz-Motorhubantrieb-F3;R-Regelbetrieb-Balz-373-E45-40-15-Istanbul-Turkiye	
2290 A D 2 3 230 Sa	
373-E07/21-Ty18 (24v)	
585998 / 3445	
K.-Nr. M12 , By 373-E45-40-15-171-5	
373-E07	
373-E02-10-18-220-50-2ez Obsolete!! Replaced By 373-E07-20-18-S21	
356 Ms Dn 15 Pn 16 25 40 Kvs 3 8	
2290-A-D-2.4-230-Sa	
342--Ss-373-E07(Nd-50)	
373-E02 Obsolete!! Replaced By 373-E07-20-18-S21...	
373-07-20-18-305	
340-018	
Typ Rsm 63/8 Sg (115 V, 50/60 Hz)	
Typ Rsm 63/8 Sg (24 V, 50/60 Hz)	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
373-E45-40-15-171-5	
342?Bkss?Rg	
373-E02-10-18-S21-230	
373 P21 18 Fu	
6590/B4-2.4-230	
36590 / 2-2.4-024	
36590/2-2.4-24	
D-Ventil	
356-116	
373-E02 Obsolete!! Replaced By 373-E07-20-18-S21	
342-Bk-Ss	
373-E07 Serien-Nr:29965	
342-Bkss-Rg	
86	
373-E45-40-15-001	
373-E07 Elektroantrieb	
373-E02 Obsolete, Replacement 373-07-20-18-305	
373-E07/21-Ty18	
P10wk.-Nr.M12f.Nr	ACTUATOR 115V
Baelz-Typ-Rsm-638sg-Ersatz-F3;R-Sm-644-3r-24-V-5060-Hz-Istanbul-Turkiye	
86/Ip8000	
373 E07 20 18 301	
373-E02-10-18-001 (373-E02-10-18-S21)	
340 B Ad E02 21 Ty18 2ez	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
6490/2-2.4-230	
6590/1-2.4-024	
70802-40-R-10	
340 -B- Dn100-Pn16 Kvs 130 Regelventil	
373-E02-21-Ty18-S21-No Longer Available, Replacement Is373-E07-20-18-S21	
Cover For 6590b	
373-E07 Dreh-Antrieb	
356-122	
Drsm 50/6 Ng Es	
342ekss4	
Baelz 36590 / 2-2.4-024	
342-Bk-Ss-E02-21-Ty18	
6490-0222	
Zb86-T	
373-E02	220v
373-E 07	
373-E02-10-18-220-50-2ez !! By 373-E07-20-18-S21	
399608-65a	
340-091	
356-Ms-373-P21-6-Fo	
2290 A D 2 4 230 Sa	
Typ Rsm 63/8 Sg (230 V, 50/60 Hz (220? 240 V)	
3340-Bk-Ss-Dn 65-Pn 16-Kvs 63 (With 373-E07-20-18-S21-24)	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Diaphragm Seal For 192-4-S Dn 65 Pn 16 Kvs 30 Mnr 22363	
Driver For M12/11964, By 373-E45-40-15?	
Baelz-Motorhubantrieb-F3;R-Regelbetrieb-Balz-373-E07-20-18-S21-Istanbul-Turkiye	
373-E02-10-18-S21..	
340-093	
373-E07-20-18-S21	
356-Ms-Dn 15-Pn 16/25/40-Kvs 3,8 + 373-P21-3-Fo-S21-16mm + 86/Ip8000-M	
Baelz-Typ-Rsm-638sg-Ersatz-F3;R-Sm-6443r-230-V-5060-Hz-Istanbul-Turkiye	
373-E02-10-18-S21 (373-E02-10-18-005)	
373 E02 10 18 S21	
373 P21	
342-??-Ss-373-E07(Nd-50)	
373 E44 40 18 001	
373-E45-40-15-S21-2ez-Fg1-230	
6490	
373-E02/21-Ty18	
342-063 + 373-P21-027	
342-018	
373-E02-21-Ty18-S21-Replacement Is373-E07-20-18-S21	
43 E02	
373-E88-Als75-S41	
373-E07-20-06-S21-230	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Baelz--Typ-Rsm-638sg-Ersatz-F3;R-Sm-6443r-115-V-5060-Hz-Istanbul-Turkiye	
340-Bk-Ss-373-P21-6-Fu-86	
340-B-Ad-E02-21-Ty18-2ez	
373-E40	
Cover For 6590a/4-2.4-230 Obsolete!! Replaced By 6590/B4-2.4-230	
36590 2 2 4 24	
342-Bk-Ss-373-P21	
340-B-Ad	
6590 24 V, 50/60 Hz Alternative	
6590-0222	
340 B Ad	
342 Bk Ss E02 21 Ty18	
373 E02 21 Ty18	
360 -Em - C-2- Dn50-Pn40 16 Kvs 18 Regelventil	
356-Ms-Dn 15-Pn 16/25/40-Kvs 3,8	
343-E02	
373-E02-10-18-S21-230 Obsolete, Replacement 373-E07-20-18-S21-230!!!	
375-E03-031	
340-B.K	
373-E45-40-15-171-A	
373-E07-20-18-301	
373 E07 21 Ty18	
342-058 + 373-P21-019	
340-Bk	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.