

## Bcs

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Bcs** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Bcs T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">CNX 100</a>	
<a href="#">LC 1</a>	
<a href="#">Model CNX-100</a>	
<a href="#">MTH8</a>	
<a href="#">P-20/75/215</a>	
<a href="#">P-40/120/185</a>	
<a href="#">type CNX-50</a>	BCS compression load cells - rated load: 50 tons; - accuracy class: $\pm 0.1\%$ of rated load; - shielded high-temperature cable, 10 m long; - unit weight: 3 Kg.
<a href="#">Microprocessor-based digital indicators type M748</a>	spare for 11M282 - range: programmable through keyboard; - 7-segments LED display, 14 mms high, red; - stabilized power supply unit, 5 V DC, for the load cells; - zeroing and calibration through keyboard; - failure alarm, with SPDT relay, 2 A; - analog output, 0÷20 or 4÷20 mA, programmable; power supply: 230 V – 50/60 Hz; - aluminium box, IP65 protection, dimensions 253x217x95 mm.

<a href="#">M748 Load Cell</a>	
<a href="#">Load Cell</a>	2 Adet BCS Marka Cnx-30 10 Metre Kablolulu Tipte 30 Ton , 2 Adet BCS Marka Cnx-30 12 Metre Kablolulu 30 Ton
<a href="#">code:16194</a>	ord. produzione:9255/08E0 1/2008 Capacity:42cc/rev max wheel dish :127 mm
<a href="#">TS500A-0001</a>	SWITCH POSITION 002
<a href="#">P-20/80/170</a>	BCS shear pin load cell, type P-20/80/170; - rated load: 20 tons; - accuracy class: $\pm 1\%$ of rated load; - MIL-STD connector and shielded high temperature cable, 15 m long; - dimensions: dia. 80 mm, L 170 mm.
<a href="#">P-15/60/150-</a>	BCS shear pin load cells, type P-15/60/150; - rated load: 15 tons; - accuracy class: $\pm 1\%$ of rated load; - MIL-STD connector and shielded high temperature cable, 15 m long; - dimensions: dia. 60 mm, L 150 mm.
<a href="#">P-40/120/270</a>	BCS shear pin load cell, type P-40/120/270; - rated load: 40 tons; - accuracy class: $\pm 1\%$ of rated load; - MIL-STD connector and shielded high temperature cable, 15 m long; - dimensions: dia. 120 mm, L 270 mm.
<a href="#">FL-25/200/292</a>	BCS flange load cell, type FL-25/200/292; - rated load: 25 tons; - accuracy class: $\pm 0.2\%$ of rated load; - shielded high temperature cable, 15 m long; - dimensions: int/ext dia. 200/292 mm, thickness 58 mm.
<a href="#">FL25</a>	
<a href="#">A-4577.Dwg , A-5628i.Dwg</a>	
<a href="#">FI 30/14014/9</a>	
<a href="#">Cop08</a>	
<a href="#">Cn-150</a>	
<a href="#">M748dp</a>	
<a href="#">P-80/110/381</a>	
<a href="#">27483</a>	
<a href="#">17m150</a>	
<a href="#">M748-Ta</a>	
<a href="#">Cnx100</a>	
<a href="#">P-15/70/185</a>	
<a href="#">35a-Aaa-Ddba-1ba</a>	
<a href="#">Type Cop08dp</a>	
<a href="#">Lc1(Exc+,Exc-,Sig+,Sig-,Shield)</a>	

<a href="#">Lc 1</a>
<a href="#">Fl-8/60/152</a>
<a href="#">Cnx100_Serial_136355</a>
<a href="#">Cnx-100-43402</a>
<a href="#">Bbz0306081646</a>
<a href="#">Type Cnx-100</a>
<a href="#">Zsnc -30 Ton</a>
<a href="#">Type- Cxx3/B</a>
<a href="#">Bbz02056513</a>
<a href="#">Type Cnx-30</a>
<a href="#">Type Cnx-50</a>
<a href="#">M871</a>
<a href="#">Op-97</a>
<a href="#">M748 051-510</a>
<a href="#">P-15-70-185</a>
<a href="#">Cnx 15</a>
<a href="#">13m092</a>
<a href="#">2sh-5</a>
<a href="#">Cnx50</a>
<a href="#">Cnx100, ??:125585 - Not Available</a>
<a href="#">Loadcell Junction Box</a>
<a href="#">Type Cn-150</a>
<a href="#">P/N: Cnx-100 100 Ton</a>
<a href="#">P-8/41/152</a>
<a href="#">Type M748</a>
<a href="#">Cnx 100 - Not Available</a>