

Belimo



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Belimo** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Belimo Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|---|--|
| Gm24a-Sr | BELIMO damper actuator with mechanical position indicator and Manual adjustment (temporary, permanent) Nominal voltage: AC / DC 24 V Control: DC 0 ... 10 V continuously Working range: DC 2 ... 10 V Feedback: DC 2 ... 10 V Torque: 40 Nm Running time: 150 s Rotation angle: max. 95 ° Direction of rotation: selectable (left / right) Connection: cable 1 m Protection class: IP 54 |
| CM24-F-L | |
| BLF24-T-TUR AC/DC 24V | |
| LF24 S | |
| Rotary electric drive LF230-S | |
| electric drive NM24A-SR | |
| LM230ASR | Rotary drive, 5 Nm, AC 100...240V, 150 s, IP54 |
| R2040-16-S3 | BELIMO 2-way control ball valve thread PN25, DN40, kvs 16.0, made of brass as Straight valve with internal thread Rp 1 1/2" permissible operating pressure ps 1600 kPa |
| R2040-25-S3 | BELIMO 2-way control ball valve thread PN25, DN40, kvs 25.0, made of brass as Straight valve with internal thread Rp 1 1/2" permissible operating pressure ps 1600 kPa |
| R2050-40-S4 | BELIMO 2-way control ball valve thread PN25, DN50, kvs 40.0, made of brass as Straight valve with internal thread Rp 2" permissible operating pressure ps 1600 kPa |
| R2032-16-S3 | BELIMO 2-way control ball valve thread PN25, DN32, kvs 16.0, made of brass as Straight valve with internal thread Rp 1 1/4" permissible operating pressure ps 1600 kPa |

| | |
|------------------------------------|---|
| NRQ24A | BELIMO valve drive, AC/DC 24 V Open-close torque 8 Nm, running time 9 s with connection cable 1 m |
| SRQ24A | BELIMO valve drive, AC/DC 24 V Open-close, torque 16 Nm Running time 9 s, with 1 m connection cable |
| LRQ24A | BELIMO valve drive, AC/DC 24 V Open-close torque 4 Nm, running time 9 s with connection cable 1 m |
| LMC24A | BELIMO damper drive, AC/DC 24 V 3-point or open-close, torque 5 Nm Running time 35 s, with 1 m connection cable |
| LMC230A-F | BELIMO damper drive, AC 230 V 3-point or open-close, torque 5 Nm Running time 35 s, with 1 m connection cable Axle form fit 8 x 8mm |
| NV24A-MP-RE | BELIMO linear actuator for 2 and 3-way valves Retrofit adapter for mounting on valves various types and manufacturers Stroke direction and closing point selectable overload-proof and maintenance-free mechanical position indicator and Manual override (temporary, permanent) Rated voltage: AC/DC 24V, 50/60Hz Control: 3-point, continuous, MP-Bus Sensor connection: 1 sensor or switch Sensor type: active or passive Working range: DC 2...10 V* Feedback: DC 2...10 V* Actuating force: 1000 N Nominal stroke: 20 mm Actuating time: 150 s / 20 mm* Connection: terminals Degree of protection: IP 54 *Can be parameterised with: PC-Tool and ZTH... Notice !! Notice !! Notice !! Replacement for old drive NV24-MFT installed on third-party valve |
| H765N/EV24A-MP-TPC | Alternatively BELIMO 3-way control valve flange PN16 DN 65, kvs 63 as mixing valve Fitting and seat: cast iron GG25 Closing body: stainless steel Plunger/bypass seat: stainless steel Tappet seal: EPDM O-ring Medium temperature: 5... 120 °C Characteristic A-AB/B-AB: equal percentage/linear Leak rate A-AB/B-AB: max. 0.05 / 1% of kvs BELIMO linear actuator for 2 and 3-way valves Stroke direction and closing point selectable overload-proof and maintenance-free mechanical position indicator and Manual override (temporary, permanent) Rated voltage: AC/DC 24V, 50/60Hz Control: 3-point, continuous, MP-Bus Sensor connection: 1 sensor or switch Sensor type: active or passive Working range: DC 2...10 V* Feedback: DC 2...10 V* Actuating force: 2500 N Nominal stroke: 40 mm Actuating time: 150 s / 40 mm* Connection: terminals, cable 1 m Degree of protection: IP 54 *Can be parameterised with: PC-Tool and ZTH... !! Notice !! Notice !! Notice !! Complete valve and actuator replacement!! Attention: valve probably not identical, If necessary, the piping at the bypass connection to be adapted on site!! |
| GM230A | BELIMO damper drive, AC 230 V Open-close, torque 40 Nm Running time 150 s, with 1 m connection cable |
| S2A | Auxiliary switches for drives LM..A, NM..A, SM..A, GM..A, LR..A, NR..A, SR..A, GR..A, DR..A Auxiliary switch: 2 x EPU adjustable |
| | Damper drive, AC 230 V 3-point or open-close, torque 10 Nm |

| | |
|-----------------------------------|--|
| NM230A-S | Running time 150 s, with 1 m connection cable with auxiliary switch |
| NM230ASR | Damper drive, AC 230 V constant DC 2...10 V, torque 10 Nm Running time 150 s, with 1 m connection cable |
| GM24A-SR | BELIMO damper actuator with mechanical position indicator and Manual override (temporary, permanent) Rated Voltage: AC/DC 24V Control: DC 0...10 V continuous Working range: DC 2...10 V Feedback: DC 2...10 V Torque: 40 Nm Running time: 150s Angle of rotation: max. 95° Direction of rotation: selectable (left/right) Connection: cable 1 m Degree of protection: IP 54 |
| GM24A-MP | BELIMO damper actuator with mechanical position indicator and Manual override (temporary, permanent) integrated MP-Bus interface to the digital Connection to a DDC controller with MP-Bus Interface or via BELIMO gateway to a higher-level bus protocol Rated Voltage: AC/DC 24V Control: MP bus Sensor connection: 1 sensor or switch Sensor type: active or passive Torque: 40 Nm* Running time: 150 s* Angle of rotation: max. 95°* Direction of rotation: selectable (left/right)* Connection: cable 1 m Degree of protection: IP 54 *Can be parameterized with: PC tool |
| LMC24A-F | |
| LM24A-SR | Damper actuator LM24A-SR with mechanical position indicator and Manual adjustment (temporary, permanent) Rated voltage: AC/DC 24 V Control: DC 0...10 V continuous Operating range: DC 2...10 V Feedback: DC 2...10 V Torque: 5 Nm Running time: 150 s Rotation angle: max. 95° Direction of rotation: selectable (left/right) Connection: 1 m cable Protection class: IP 54 |
| SR24A-MF | Belimo actuator for ball valve AC/DC 24V SR24A-MF 20Nm, 90s adjustable. IP54, MFT Type: SR24A-MF |
| GR24A-MP-5 | Belimo drive for choke class AC/DC 24V GR24A-MP-5 40Nm, Continuous or variable, 90s, IP54 |
| SRA-3K0_0TP_AC8 | SRA-3K0_0TP_AC8 Drive 20 Nm / 180 in-lb AC/DC 24 V, continuous CCV, M4 Terminal cover IP54 MF/MP;In0.5-10V;Out0.5-10V;35s |
| NR24-CT | |
| 6121-0044 | |
| Uflk1738 | |
| G6125c+2xaf24-Mft | 5FLG 2W 263CV S/R PROP |
| G314+nvd24-Mft | |
| B331af24 | |
| Zone215s-35+z24nc | |
| B223+lf24-Mft Us | |

| | |
|------------------------------------|-----------------------------|
| G213+lf24-Sr | |
| B215tfx24 | |
| Cmb24-Sr-R | |
| B350vs+2xaf24 | 24V ON/OFF 2 3WAY BAL VALVE |
| Uglk1410 | |
| Uflk6914 | |
| Ubtfx0000 | |
| G780d+af24-Mft | 3FLG 3WDIV 85CV 24V PROP SR |
| Zone215n-35 | |
| B223+lf120 Us | |
| Efb24 N4 | |
| B220+lf24-Mft | |
| Fsaf120-S Us | |
| G250nvg24mft | |
| B339+afrx24-Mft | |
| B263+afrx24-Mft | |
| B210b+lf24-3 | |
| B239+afrx24-Mft95 | |
| B229 | |
| Fgvl+avkb24-3 | |
| Lf24-Mft-20 Us | |
| Nfb24-Sr | |
| B330af24sr | |
| B332vs+amx24-Mftx1 | |
| Zs-Ccv-110 | |
| B309b+tfrb24-Sr | |
| B216+lrb24-Sr | |
| B264+arx24-Mft | |
| Gkx24-3-T N4 | |
| F780hdu+gmx24mftx1 | |

| |
|---------------------------------|
| K4-2 |
| B322+lrb24-Sr |
| Uflk1136 |
| Tfrx120 |
| B349+af24-Mft95 |
| Tool-06 |
| B309+tr24-3 |
| B318+tr24-3 |
| Lfc24-3-S Us |
| B318 |
| B313+tfrx24-3-S |
| B211+tr24-Sr |
| B225+lrb24-Sr |
| Nmx24-Sr |
| 2xaf-24 -S |
| B249af24sr |
| Lrcb24-3-S |
| Uglk1476 |
| B219 |
| Fsaf24-Sr-S |
| Fsaf24 Us |
| Zs-150 |
| G350psr-X1 |
| Sy2-230-3-T |
| Sa1-Us |
| Lf24-Sr Us |
| Zs-Ccv-90 |
| B225+lf120 |
| B225+lrb120-3 |
| Lm24a-S-Tp |
| Lhb24-3-T-100 |

| | |
|------------------------------------|-------------------------------|
| B313+lr24-Mft | |
| Sy324pr | |
| B331+af24-Mft-S | |
| B331+af24-Mft | |
| F7200hsu+sy3-24sr | 8, 3W , BUTTERFLY W/ ACTUATOR |
| B231+arb24-Sr | |
| B665+ar24-Mft | |
| G250sumft-X1 | |
| G665cs+nvf24-Mft-E | 2.5 FLG 2-WAY SR 24VAC/DC |
| B217+lrb24-Sr | |
| Fgvl+evb24-Mft | |
| Zs-Spgv-10 | |
| Hnd01f65020 | |
| G680+2xgmx24-Mftx1 | 3 FLG VLV 90CV W/2 GM24-MFT |
| Lm24-Sr-T-2.0-U | |
| B350+ar24-Mft | |
| Lmx24-Mft-X1 | |
| B224+lf24-Mft-S | |
| Uglk1212 | |
| B249vs2xaf120 | 22WAY 120V S/R 108CV 133LB |
| Zone225s-80+z120no | |
| Nf24-S | |
| Uglk0032 | |
| F680hdu | |
| Gkx24-Sr-T N4 | |
| B212tf24sr | |
| Lmcb24-Sr-T | |
| Zone24nc | |
| B215ht290 | |
| B223+lf24-Mft-S Us | |

| | |
|------------------------------------|--------------------------|
| B680vs+sy2-24mft | |
| Lf24-Mft-S-20 Us | |
| Lf120-Us | |
| Fsaf24-Bal | |
| Uflk1230 | |
| Fm24-Sr95-Us | |
| B215ht046+lrb24-Sr | |
| B220tfrx120 | |
| B248+arb24-3 | |
| G224s+nfx24-Mft-X1 | |
| B214vs+lmb24-3x1 | |
| Efb120-S N4 | |
| B311+tf24-3 | |
| G332d | |
| Tf24-Mft | |
| Uglk1272 | |
| Lm24-T/Us | |
| Sy2-24 | |
| G7100d | 4 FLG DIV VLV 190CV C.I. |
| Lux24-Mft | |
| B211+lf24 | |
| P140a-Gr | |
| S2 | |
| Lub24-3 | |
| Cq24a-T | |
| B248+afrx24-Mft-S | |
| Lhb24-Sr-100 | |
| Tfrx24-Sr | |
| Zone325s-80+z24nc | |
| Efb24-Sr N4 | |
| Zdb-Lu | |

| | |
|---|-------------------------------|
| B310+tfrx24-3-S | |
| B222+lf24-Sr-S Us | |
| Ugvl+svkx24-Mft | |
| B309b+lrb24-Sr | |
| Af24-Sr | |
| Sm24-Us | |
| Afb24-Sr-Sn4 | |
| B350+afrx24-Mft-S | |
| Ch24-Sr-L60.2 | |
| K-Am25 | |
| F665hdu+afrb24-Mft | |
| Uglk1800 | |
| Fsaf120 Us | |
| G240psr-X1 | |
| B231+afrb24 | |
| Zone215s-10+z120no | |
| Nfb24-S | |
| B232+afrbup | |
| Lmc24a-Sr-F Gew - , - Lmc24a-Sr-F | |
| G665+2xaf24-Mft | 2.5 FLG VLV 65CV W/2 AF24-MFT |
| Unv-Bkt-002 | |
| Uglk1074 | |
| G680cpx1 | |
| Lf24-Econ-R03 Us | |
| F6250hdu+sy3-24mft | |
| Zs-Bfv-30 | |
| Gmb24-3-T N4h | |
| G240+amb24-Sr-X1 | |
| B329+afrx24-Mft-S | |
| Sbg24 | |

| |
|-----------------------------------|
| Lmqb24-Mft |
| Uflk3936 |
| Zg-Efb |
| Uflk1352 |
| B265+afrx24-Mft-S |
| Tmcb24-3-T |
| B312+tr24-3-T |
| B313b+tfrb24-Sr |
| B249vss+2xaf120-S |
| Afb24-Mft-N4 |
| F7250hd+sy4-110 |
| Fsaf24-Bal-S |
| Bae165 |
| Tfrb24-Sr-S |
| Phose4 |
| B262 |
| B214+tf24-Mft |
| B231af24sr |
| B351+afrx24-Mft |
| Fsnf120-Fc |
| Uglk1204 |
| Afx24-Mft95 |
| B222+lf24-Sr Us |
| Lrb24-3 |
| Uflk1842 |
| B313b+lf120 |
| Ubtfx0002 |
| G320+lf24-Mft |
| Zk2-Gen |
| B220b+tfrb120 |

| | |
|--|-------------------------|
| Nfb24-Sr-N4 | |
| Afxup | |
| G215+nvfd24-Mft-E | |
| Af24-- By Sf24a | |
| Uflk1844 | |
| Afbup | |
| Nvf24-Mft2 - By Nvk24a-Mp-Tpc Or | |
| Nvk24a-Mp-Re | |
| G6100c+2xaf24-Mft | 4 170CV PROPFLGDVLV 24V |
| Fsnf120-S Us | |
| Lf24-Mftus | |
| Gm24a-Sr Damper S¼r¼c¼ | |
| Nfbup-S | |
| Uflk1840 | |
| B215b | |
| Bv.10.24 | |
| B210b+lr24-1-Us | |
| B214+lf24-Mft Us | |
| B252+afrb24 | |
| G680-Af24-Mft-Us | |
| Af24-Sr95 | |
| B231+arx24-Mft-Tn4 | |
| G315+lf24-Sr | |
| B278+afrx24-Mft-S | |
| Zone215n-35+z24nc | |
| B213 | |
| B348+afrx24-Mft-S | |
| Ahb24-Sr-100 | |
| P6065w800e-Mp | |
| F6400hd+gw05 | |
| B208b+tr24-3/300 | |

| | |
|---|-----------------------------|
| Eslf120 Rus | |
| G765d | 2 1/2 3-WAY DIVERTING VALVE |
| Lm24a-Mp | |
| Lrb24-3-T | |
| B217b-Lf24-Sr | |
| Afrb24-Sr | |
| G665snvg24mft | 2.5FLNG 65CV 24V 2/10VDC |
| Kh-Afb | |
| B238+afrb24-S | |
| G340 | |
| Efb24-Sr-S | |
| Tf120-Uss | |
| G332+nv24-Mft-Uss | CONTROL VALVE ASEMBLY |
| Uflk1144 | |
| Unv035 | |
| Af-P | |
| Gm24-Uss | |
| Lrqb24-Mft | |
| Amcx24-Mft | |
| Sm24a-S | |
| Fsaf120a | |
| Sy3-120sr | |
| G212s-Nvd24-3-Uss-250psi-Cv-0.4 | |
| Lmc24 | |
| Gkb24-3 | |
| Gkx24-Mft-T N4 | |
| G232 | |
| B211+lf24-3 | |
| G224s+svb24-Sr | |
| B2200vss108+2af120 | |
| G314-Nvd24-Mft-Uss | |

| | |
|--|------------------------------|
| G225+nfx24-Mft95 | |
| B209+tfrb24-Sr | |
| B212+tfx120 | |
| Tr24-Sr-Uş | |
| Uflk1102 | |
| Fsaf120-S | |
| Uglk1250 | |
| Fslf24 Us | |
| B209b | |
| G250+afb24-Sr-X1 | |
| Uglk1350 | |
| B323+lf24-Mft | |
| Gkrx24-Mft | |
| Ugvl+lvx120-3 | |
| B349+afrx24-Mft-S | |
| Sm24a+zşma | |
| Nfx24-Mft-X1 - Available Only In Usa | |
| B232vs+af24-S | |
| G232+nv24-3 | |
| B220vs | |
| Uglk1550 | |
| F7150hs+sy3-120sr | 6 3WAY BUTTERFLY W/ 0-10VDC |
| B220+lf24-Mft-S Us | |
| B223+lf24-3 | |
| B350vs+2xaf120 | 120V ON/OFF 2 3WAY BAL VALVE |
| G780+gmx24-Mft-X1 | 3FLG MIX 91CV 24V NSR PROP |
| Nfb24 | |
| G7100d+af24-Mft | 4FLG 3W DIV 154CV 24VPROP SR |
| Tfb24-S | |
| B239+afrx24-Mft-S | |

| | |
|--|-------------------------------|
| B251+arx24-Mft | |
| G240s | |
| B220+lf24-Mft Us | |
| Uflk3924 | |
| Amx24-Pc | |
| B278+afrx24-Mft | |
| B311b-Lr24-Mft-Us | |
| Sy4-24 | |
| Gkx24-Sr | |
| P2050b | |
| B239+afrx24-Mft | |
| Nru-24-Sr- Aletnative Nr24a-Sr | |
| F7150hsu+sy2-24p | 3W 6BTTRFLYVLV 24V 3POINT ACT |
| 13131-00001 | |
| Sm24a-S-Tp | |
| Ccv-Ext-Kit | |
| Lmqb24-1 | |
| Nv24-Mtf , Nv24a-Mp-Tpc | |
| Zg-Nm3 | |
| D680nl | |
| B320+lf24-Mft | |
| Tfrb24-Sr | |
| B325vsaf24mft | |
| Zg-Lf112 | |
| Uflk1138 | |
| G250snvf24mfte | 2 2-WAY SR 24V W/NVF ACT |
| Uflk1350 | |
| Khaf | |
| Uglk1068 | |
| B349+afrx24-Mft | |
| B320b+tr24-3 | |

| | |
|------------------------------------|---|
| Sy9-230mft | |
| B264+afrx24-Mft-S | |
| 21409-00001 | |
| B251af24 | |
| B254+afrbup | |
| B215+lf24-Mft-S Us | |
| G250+afbup-X1 | |
| Tfrx24 | |
| B212+tr24-3 | |
| Sm230a+s2a | |
| G7100+gmx24-Mft-X1 | 4FLG MIX 91CV 24V NSR PROP |
| Af24-Sr-Us | |
| Lmc24a-Sr | |
| Nrx24-3-T-N4 | |
| Ahb24-3-200 | |
| Fsnf120-S | |
| B209b+tr24-3 | |
| B240+arx24-Sr-T | |
| B320+lf24-S | |
| Fslf24-Fc-Us | |
| Zg-Dc1-K | |
| Zggm2 | |
| B254af24s | |
| Fsaf24a | |
| Sr24a-Sr | BELIMO valve actuator with mechanical position indicator and Manual adjustment (temporary, permanent) Rated voltage: AC / DC 24V Control: DC 0 ... 10 V continuous Working range: DC 2 ... 10 V Feedback: DC 2 ... 10 V Torque: 20 Nm Running time: 90 s Turning angle: max. 95 ° Connection: cable 1 m Protection class: IP 54 |
| Uflk1750 | |
| G232-Lm24-Sr-Us | |
| | |

| | |
|--------------------------------------|-------------------------------|
| B207+lf24 | |
| B325+lrb24-3-S | |
| B218+lf24-Mft Us | |
| Smq24a | |
| Af24-S | |
| B254af120 | |
| B217+lrb120-3 | |
| Uflk1200 | |
| G7100d+af24 | 4 3WAY DIVERTING N/C 24V 2POS |
| Lm24-Mu | |
| Kg10a | |
| Tf24s | |
| B252+afrx24-Mft | |
| G225s+nfbup-X1 | |
| Zone315s-35 | |
| B308+tr24-3 | |
| Zg-102 | |
| Zg-Gv12 | |
| B280+afrx24-Mft | |
| Lmb24-3-P10-T | |
| B222+lf24 Us | |
| B261+afrx24-Mft-S | |
| Tr24-3 | |
| B15.24.30se/58400822 | |
| G240+svkb24-Sr | |
| B219+lf24-S | |
| Cfu-D222 | |
| Ubtfx0001 | |
| Zone220s50z24no | |
| Fsnf230 | |
| G214s+lf24-3 | |

| | |
|------------------------------------|-------------------------------|
| Zone220n-50 | |
| B6150vs+sy5-24 | 6 2W 3300CV 24V NON-S/R 2-POS |
| Uglk1412 | |
| Ar100-Rc1 | |
| Afb24-Mft95 | |
| Uglk1804 | |
| Bf230-2 | |
| Zg-R01 | |
| Amb24-3 | |
| F6200hdu+sy3-24mft | |
| Gmb24-3-T-N4 | |
| Uflk1232 | |
| B217b+tr24-3-T | |
| Uflk3352 | |
| B240vsumftx1 | |
| Uglk-Col-Hy02 | |
| Uflk1834 | |
| B207+lf24-Mft Us | |
| Amcx24-Mft95-37 | |
| B325vs+af24-S | |
| G780d+af24 | 33WAYFLGDIV 24V SR 85CVON/OFF |
| B208+tfrb24-Sr | |
| Lmb24-3 | |
| B329+arx24-Mft | |
| Fsnf120-S-Fc | |
| F6150hdu | |
| Uglk1012 | |
| Gmb24-Sr | |
| B280+afrx24-Mft-S | |
| Gkb24-3-T N4h | |

| | |
|------------------------------------|------------------------------|
| F6200hs+sy4-120-Sr | 8 2-WAY BUTTERFLY NSR 110V |
| G6100c+gmx24-Mftx1 | 4 2W GLF 24V NSR ASSEMBLY |
| Lf230-S | |
| Uflk1146 | |
| Zg-Nmsa-1 | |
| Uflk1348 | |
| Gm24a-Mf | |
| Uglk1416 | |
| Zip-Rs232-Us | |
| Uglk1402 | |
| B217b+tr24-Sr-T | |
| B210+lf24-Mft-S Us | |
| Zip-Usb-Mpus | |
| Fsnf120 Us | |
| B219+lf24-3 | |
| B207b+tr24-Sr | |
| G240+afbup-S-X1 | |
| Zg-101 | |
| Sn2 | |
| G6125c+2xaf24 | 5FLG 2W 263CV W/2 AF24 S/R |
| G7100+2xgmx24-Mftx | 4FLG 3W 190CV 24V NSR PROP |
| B340af24 | |
| Fsnf24-Fc-Us | |
| G780+af24-Mft | 3FLG 3W MIX 91CV PROP SR 24V |
| B210+lf24-Mft | |
| Sy11-230mft | |
| Lhb24-3-200 | |
| Ev600s-713 | |
| B315b+tr24-Sr-T | |
| F7250hdu+sy4120mft | 10BTRFLY,3W,120V |
| Sy10-110 | |

| | |
|------------------------------------|------------------------------|
| B340+afrx24-Mft-S | |
| Uflk1302 | |
| Uglk1474 | |
| G350+nvf24-Mft | |
| G780+2xaf24-Mft | 3FLG 3-WAY 91CV W/2 AF24 MFT |
| Lf230 | |
| P6250s-127-Arx24pi | |
| Ahb24-Sr-200 | |
| B219+lrb120-3 | |
| Lmb24-Sr-T | |
| Gkb24-Mft-T N4h | |
| Tfrb120 | |
| B313btfx24 | |
| Gkrx24-3 N4 | |
| Nm230a-Tp | |
| Af120sus | |
| Sy2-24mft | |
| B208+lrb24-3 | |
| B220b+tr24-Sr-T | |
| B250+arb24-3 | |
| Uglk1210 | |
| B218+lrb24-3 | |
| B348af24 | |
| B315+tfrb24-Sr | |
| Af24-S.9-Us | |
| B280af120 | |
| Lf24-Mft-S | |
| Lf230 Us | |
| B232 | |
| B224vs+amx24-3x1 | |

| | |
|-----------------------------------|-------------------------------|
| Sy10-230mft | |
| B211+lrb24-3 | |
| Uflk2902 | |
| F6300hd+sy4-110 | 12 2WBFV 120VNSR SSDISC8250CV |
| Gmb24-Mft-X1 | |
| F6150hsu+sy2-24p | 6BTTRFLYVLV 24V 3 POINT ACT |
| Tfrx120-S | |
| B232vs+afb24-X1 | |
| B208+lf24-Mft Us | |
| Uflk1748 | |
| B219+lf24-Mft Us | |
| Afx24-Sr | |
| B251+afrx24-Mft | |
| Uflk3432 | |
| Gkx24-Mft | |
| B252+afrx24-Mft-S | |
| Fgvl+evb120-3 | |
| B213+lf24-Mft Us | |
| Tfrx24-Mft | |
| Uflk1142 | |
| G240s+amx24-Mftx1 | 1.5 2W STEAM 24VNSR PROP 28CV |
| Lmb2410p | |
| B329+arb24-3 | |
| Afrx24-Mft | |
| B350vs | |
| Zg-R05 | |
| B309b+tr24-Sr/300 | |
| Sy1-110p | |
| Cmb24-3 | |
| Sgvl+lvx120-3 | |
| B240+afrx24-Mft-S | |

| |
|------------------------------------|
| Nm24 |
| B219vs+nfbup-S-X1 |
| B347+afrx24-Mft |
| Tfrb24-3-S |
| B325+lf24-Mft |
| B265+afrx24-Mft |
| Sgf24 |
| B277+afrx24-Mft |
| B207b+tr24-3 |
| Tfrx24-3 |
| Zone225s-80+z120nc |
| Wbv-BI63 |
| B309b |
| B208b |
| Uglk1274 |
| B10.24sl/58400822 |
| B332l+afrbup |
| Amx120-Sr |
| D665nl |
| Lmb24-3-P5-T.1 |
| B210+tf24-Sr |
| B277+arb24-3 |
| B308+tr24-3-T |
| Lf24-3 Us |
| G340+afx24-Mft-X1 |
| B315+tfx24 |
| Nm24a |
| B320+lrb24-Sr |
| G225+nfbup-X1 |
| Uflk1108 |

| | |
|---|------------------------------|
| B211+lf24-Mft-S Us | |
| G224+nmb24-Sr-X1 | |
| Lm72a Hfg 5nm 48-110vdc M.P | |
| Sgvl+svkx24-Mft | |
| B330+afrx24-Mft-S | |
| P500a-Gr | |
| B212b-Tf24-3us-Nc/Fo | |
| B217+lf24-Sr | |
| Ind-Af2 | |
| Uflk1454 | |
| Tfrx24-Mft-S | |
| Uglk1400 | |
| Tfrx24-3-S | |
| Uflk1224 | |
| Am24sr | |
| B222+lrb24-Sr | |
| Lf120 | |
| B340+afrx24-Mft | |
| B225vs+amb24-3x1 | |
| B252+arx24-Mft | |
| B231+arb24-3 | |
| Tf24-3-S | |
| B312 | |
| Nfx24 | |
| Srfa-S2-5 | |
| B312+tf24-Sr | |
| G325+nv24-Mft | |
| G250s+nv24-Mft | 2 40CV 24V PROP/MFT ACTUATOR |
| G6100c+2xaf24-S | |
| Ahb24-3-100 | |
| B264+arb24-Mft | |

| | |
|--|---------------------------|
| Fsafb24-Sr | |
| B254+afrx24-Mft | |
| B665af24 | 2.5FLGD 2WAY SS BALL S.R. |
| Bae72-S | |
| Zone320s-35+z24nc | |
| Af24mftsp30001 | |
| G665+af120 | 2 1/2 FLNGD 120V 65CV NSR |
| NVF24-MFT-E | |
| Nm230a | |
| B210+lf24-Mft Us | |
| Uglk1010 | |
| B211 | |
| Zone225n-80+z24no | |
| G332+nvf24-Mft-E | |
| Uflk1236 | |
| Uflk1442 | |
| Tr24-3-T | |
| B312+lrb24-3 | |
| Lf24-Sr-S Us | |
| B230+lrb24-Sr | |
| Nr230a | |
| Af24-S-Us | |
| B220ht290 | |
| F680hdu+2xaf120-S | |
| B214b | |
| Am 230-2mb , By Sm230a | |
| Se4f24 | |
| Zs-100 | |
| B2050vss-15+lf120s | |
| B215+lrb24-3 | |

| | |
|------------------------------------|-----------------------------|
| B225lrb24srt | |
| F7200-150shp | |
| B309 | |
| Lmx24-Mft95 | |
| Gm24sr | |
| G215+nvd24-3 | |
| Gmb24-3 | |
| G325 | |
| Sy8-120mft | |
| B253+afrx24-Mft | |
| Uglk1806 | |
| B223+lf24 Us | |
| G240s+nvf24-Mft | 1 1/2 28CV 24V S/R 88# |
| B222+lf24-Mft-S Us | |
| B239vss+af120 | 1.52W S.S.84CV BLVLV W/120V |
| Zg-Gv11 | |
| Nv243 | |
| G340umft-X1 | |
| Nvf24-Mft2-E | |
| Ugvl+lvkx24-Mft | |
| B310+lrb24-3 | |
| G250+nv24-3 | |
| B224+nrx24-Mft-Tn4 | |
| Uflk1734 | |
| Efx24-Mft | |
| B351+arb24-Sr | |
| F680hd+gmb24-3-X1 | |
| Lf24-Sr-E Us | |
| B210b | |
| Uglk1552 | |
| | |

| | |
|--|-------------------------------|
| B262+afrx24-Mft | |
| B209tf24mft | |
| B249+afrx24 | |
| G6100cs+2xaf24-Mft | 4FLG 24VAC S/R PROP 170CV |
| B215ht073+tr24-3 | |
| Fsaf120a-S | |
| G250s+nvf24-Mft | 22W 40CV 24V S/R-OPEN 250# SS |
| Uflk2142 | |
| Arb24-Mft | |
| Zs-T | |
| B315b+tr24-3 | |
| Af24-Pwm-Us | |
| Z220s-230 | |
| Lm24 | |
| Lm24-S-T-, By Lm24a-S-Tp | |
| G7150+2gmb24-3-X1 | |
| B213+lf24-Mft-S Us | |
| B219vs+af24-S | |
| Uflk1438 | |
| Lf24-Mft-S Us | |
| G350d+nvf24-Mft-E | 23WAY DIV 24V 40CV SPRING DWN |
| Gmu24-Sr-40nm | |
| Nrx24-Mft-T-N4h | |
| B209+lf24-Mft Us | |
| Lmc24a-Sr-F | |
| Nv24a-Mp-Tpc | |
| G765d+af24-Mft | 2 1/2FLNG 3WY DIV 68CV 24V |
| Smu24-S | |
| Lr24-Sr-Us | |
| Sm24a-Sr | |
| Uglk1202 | |

| | |
|------------------------------------|---|
| Vfp-600 | |
| B261+afrx24-Mft | |
| Nvg24mft | |
| F6350hd+gw04 | |
| Gkrx24-3 | |
| B329+af24-Sr | |
| G240nv24mft | |
| G314?Mft | |
| Uglk1420 | |
| Afb24-Sr-S | |
| B317+tfrx24-3-S | |
| Uflk1446 | |
| Tr24-Sr/300 | |
| Fslf120-S Us | |
| Zg-Gv19 | |
| S1a | |
| Efb24-S | |
| Ps-100 | |
| D6150-NI | |
| Afb24-Mft | |
| Uflk1736 | |
| Zone325s-80+z120nc | |
| G240s+nv24-Mft | |
| Zone315n-35+z120nc | |
| B209+tfrx24-Mft | |
| P1000a | |
| Gmx24-Mft | |
| Lr24a-Sr | <p>BELIMO valve actuator with mechanical position indicator and Manual adjustment (temporary, permanent) Rated voltage: AC / DC 24V Control: DC 0 ... 10 V continuous Working range: DC 2 ... 10 V Feedback: DC 2 ... 10 V Torque: 5 Nm Running time: 90 s Turning angle: max. 95 ° Connection: cable 1 m Protection class: IP 54</p> |

| |
|------------------------------------|
| B238+arx120-3 |
| B312+lf24-Sr |
| B215+lr120-3 |
| B309+lrb24-3 |
| Afrxupn4 |
| B280 |
| Fgvl+avkb24-Mft |
| B309b+tr24-3 |
| B6600s400+gkrx24-3 |
| Uflk1744 |
| Zone220s-35+z120nc |
| Sf24a |
| Gkb24-Sr |
| B348+arb24-Sr |
| B212+lrb24-3 |
| Ev250s127arb24 |
| B320 |
| Lmb24-3-P5-T |
| Nv24a-Mp-Re |
| Lrx24-3-S |
| Ev24a-Mp-Tpc |
| K-Lm12 |
| B220vsnf24 |
| Uglk1004 |
| Uflk1440 |
| B251+afrb24 |
| Amb24-3-S |
| H780n+av24-Mft |
| Uglk1006 |
| B211+tr24-3 |

| | |
|------------------------------------|-------------------------------|
| B212+lf24-Mft-S Us | |
| G780d | |
| B10.24.Iv | |
| F7250hdu+sy4-110 | |
| Lmx120-3-F | |
| F680hdu-Sy1-24 | BUTTERFLY VALVE 3INCH 2WAY |
| B222+lf120-S | |
| B278+arb24-Sr-Tn4 | |
| B212+tr24-3-T | |
| B207+lf24-Mft-S | |
| Unv-006 | |
| B310+lrb24-Sr | |
| B310+lf24-Sr | |
| Nm24-1 | |
| B238+afrx24-Mft | |
| Zone220n-50+z120no | |
| B240+arx24-Mft+w31 | |
| Zone315s-10+z24nc | |
| Kh-Tf | |
| S2a | |
| F6100-300shp+2af24 | 4 2-WAY BUTTERFLAY W/AF24 ACT |
| B338+afrx24-Mft-S | |
| Sy2-110 | |
| B262+afrx24-Mft-S | |
| G765af24mft | 2 1/2 3WY 68CV MIX GLBE VLV |
| B217+lf24 | |
| F6100hdu+grb24-3-7 | |
| B222+lf24-3 Us | |
| B209b+lrb24-3 | |
| G6125c | 52-WAY FLANGED VALVE 263CV |

| | |
|------------------------------------|--|
| G7100s | |
| B254+afrx24-Mft-S | |
| B215b+tr24-Sr-T | |
| G213nvd243 | |
| G232s+svkb24-Sr | |
| B212b+lf24 | |
| Nmv-D3-Mft | |
| Lmq24a-Mf | |
| G350d+nvf24-Mft | 23WAY DIV 24V 40CV SPRING UP |
| Uglk0030 | |
| G780+afx24-Mft-X1 | |
| Smq24a-Sr | |
| Uglk1404 | |
| B209+tfrb24-3 | |
| B320+lf24 | |
| B210+tr24-3-T | |
| Tfb120 | |
| B215+lf24-Mft Us | |
| Uglk1008 | |
| B208+lf24-Mft-S Us | |
| Arx24-Sr | |
| Lrb24-Sr | |
| B219+lf24-Mft-S Us | |
| Lrx24-3 | |
| Gmb24-3-X1 | |
| NVK24A-MP-RE | BELIMO actuator with emergency setting function for 2- and 3-way valves. Retrofit adapter for mounting on valves of various designs and manufacturers stroke direction and closing point selectable overload-proof and maintenance-free, mechanical Position indicator and manual adjustment (temporary, permanent) Rated voltage: AC/DC 24 V, 50/60 Hz Control: 3-point, continuous, MP-Bus Sensor connection: 1 sensor or switch Sensor type: active or passive Operating range: DC 2...10 V* Feedback: DC 2...10 V* Actuating force: 1000 N Nominal stroke: 20 mm Motor operating time: 150 s / 20 mm* Emergency setting function: 35 s / 20 mm |

| Emergency position: adjustable Connection: Terminals Protection class: IP 54 *Can be parameterized with: PC-Tool and ZTH... | |
|---|-------------------------------|
| B277 Arb24-3 | |
| Trc24a-Sr | |
| Uflk1234 | |
| Efb24-Mft-S N4 | |
| B223+Irx24-Mft | |
| B278 | |
| Efb24 | |
| B316 | |
| Lf120 Us | |
| B220btfx24300 | |
| Lrb24-Mft | |
| B325+lf24-Sr | |
| Lf24 Us | |
| Gkx24-Mft-X1 | |
| B318+lf24-S | |
| Gmu24-Sr | |
| Uflk1400 | |
| B348+afrx24-Mft | |
| Fsafb24-Sr-S | |
| Uglk1478 | |
| Zone215n-25+z24no | |
| Lf24-Mft Us | |
| B224+lf120 | |
| B254af24 | |
| Sf24a Sr | |
| Nsv-Bat | |
| B351+afrx24-Mft-S | |
| F6150hs | |
| F765hs+2xaf24-X12 | 2.5 BTRFLY VLV 196CV W/2 AF24 |

| | |
|------------------------------------|--|
| NVK24A-MP-TPC | BELIMO actuator with emergency setting function for 2- and 3-way valves. Stroke direction and closing point selectable, overload-proof and maintenance-free mechanical position indicator and manual adjustment (temporary, permanent) Rated voltage: AC/DC 24 V, 50/60 Hz Control: 3-point, continuous, MP-Bus Sensor connection: 1 sensor or switch Sensor type: active or passive Operating range: DC 2...10 V* Feedback: DC 2...10 V* Actuating force: 1000 N Nominal stroke: 20 mm Motor operating time: 150 s / 20 mm* Emergency setting function: 35 s / 20 mm Emergency position: adjustable Connection: terminals, cable 1 m Protection class: IP 54 *Can be parameterized with: PC-Tool and ZTH... |
| F6250hd+sy4-120mft | |
| B211+lrx24-Mft | |
| B215+lrb24-Sr | |
| B677 | |
| Uflk2200 | |
| B218+lf24-Mft-S Us | |
| B6250s-110+afrx24 | |
| Lm24-Sr-T | |
| Uglk1150 | |
| Uflk8184 | |
| F650hd+afbup-S-X1 | |
| B277+arx24-Mft | |
| Ads-100 | |
| B2100vb-024 | |
| B350+arb24-3 | |
| B280af24 | |
| Sy1-110 | |
| P1000 | |
| B224vspx1 | |
| Lrx24-Mft | |
| G225+nf24-Sr | |
| F6150hd+hnd02 | |
| F6100-150shp | |

| | |
|--|-----------------------------|
| Uflk1240 | |
| B277+afrx24-Mft-S | |
| Tfrx24-S | |
| Sm110 | |
| Zone225s-80+z24nc | |
| G6125c+gmb24-3x1 | 5FLG 263CV 2W NSR W/GMB24-3 |
| Sgvl+svx24-3 | |
| Uflk1836 | |
| B232vs+afbup-S-X1 | |
| B329+afrx24-Mft | |
| Plastic Coupling For Nv24-Mft - Obsolete | |
| Sr230a-R | |
| Zone24nc-S | |
| B313b | |
| B313 | |
| Arx24-Sr-T-N4 | |
| Uglk1406 | |
| Uflk1450 | |
| G219s+lvkx24-Mft | |
| B212+tfrb24-Sr | |
| B210+lrb24-3 | |
| Uflk1132 | |
| G240spx1 | |
| Afbup-S | |
| G240ps-X1 | |
| B308 | |
| Uglk-Stm-1800 | |
| G780d+af120 | 3FLG 3-WAY DIV 120V |
| G780ds+af24 | 3 FLG 3-WAY 24V S/R 133LB |
| B350+afrb24 | |

| | |
|--|---|
| B222+lf120 Us | |
| Uglk1418 | |
| B2050vs-01+lf24 | |
| Uflk1340 | |
| Uflk1436 | |
| Am24-Sr | |
| Bf-230-2-FI - Alternative Is Bf230-2 | |
| Nfbup | |
| B232+afrx24-Mft | |
| F6200hdu+sy3-110 | 82WAY BTRFLY 110V ON/OFF AUX |
| B224+lrb24-3-T | |
| Lrb24-3-S | |
| P2050b010+lrx24-Mft | |
| B210b+lrb24-Sr | |
| G232+svkb24-Sr | |
| G7100ds+af24-Mft-S | 3FLNG3WY DIV 24V SR 2SW SS |
| Nm24a-V | |
| Econ-Zip-10k | |
| B212+lf24-Mft Us | |
| Ubtfx0024 | |
| F6200hd+sy4-110 | BUTTERFLY VALVE 8INCH 2WAY W/ACTUATOR 3560IN-LB |
| B224vsspx1 | |
| Act00400 | |
| Sm24-S-Us | |
| Uglk-Stm-1802 | |
| G240+afx24-Mft-X1 | |
| B318b+tfrb24-3 | |
| Zone315s-10+z120nc | |
| B239af24sr | |
| B264 | |
| G680+gmb24-3x1 | 32WYFLNG90CV 24V NSR 360# FLT |

| | |
|---|--------------------------|
| Zone120no-S | |
| B212b+lf120 | |
| Nfb24-S-N4h | |
| Ufsp0008 | |
| Blf24-T | |
| B309+tr24-3-T | |
| B250+afrx24-Mft-S | |
| G665c+nvf24-Mft | 2.5 65CV PROPFLGDVLV 24V |
| Uflk1228 | |
| Cr24-B1 | |
| Tr24-Sr | |
| B340vs+2xaf24 | |
| B209b+lf24-3 | |
| B211b+tfrb24 | |
| B309+lrb24-3-T | |
| Fsnf24-S Us | |
| Lmc24-Sr-F-- By Lmc24a-Sr-F | |
| B311+lrb24-Sr | |
| B215+lf24 | |
| Lhb24-Sr-200 | |
| B317+lrb24-3 | |
| Gmb24-3-T N4 | |
| Nv24-Mft-50 | |
| B347+afrx24-Mft-S | |
| B238 | |
| B232vsaf24mfts | |
| Efb120-S | |
| B313+tr24-Sr-T | |
| Lrb120-3 | |
| Uglk1472 | |

| |
|------------------------------------|
| Sf24a-S2 |
| Uglk1870 |
| G315+lmb24-Srx1 |
| Uflk1828 |
| B211tf24sr |
| Tf24 |
| Tfcb120-S |
| B213+lf24 |
| B350af24sr |
| Uglk1214 |
| Afr120us |
| F6500hd+sy8-120mft |
| B662 |
| Fsnf230 Us |
| G212 |
| Uglk1070 |
| C215q-J/230-T |
| Hnd01 |
| B214+lf24-Mft-S Us |
| Uflk1402 |
| Zscv60 |
| Fslf120-S |
| Lf24-Econ-R10 Us |
| B338+afrx24-Mft |
| Uflk7410 |
| Zone315n-10+z24nc |
| Waf-4 |
| B312+lrb24-Sr |
| Uflk1130 |
| P2050b050+lf24-Mft |

| |
|-----------------------------------|
| B349afrb24sr |
| Nr24a |
| P2050b050+lr24mft |
| Gm24a-Sr-Tp |
| Blf230 |
| Fslf24-S Us |
| B250+afrx24-Mft |
| Ugvl+svkb24-Mft |
| Uglk1014 |
| Lf24-3-S Us |
| P2050b030+lr24mft |
| G225s+svkx24-Mft |
| G340dnvf24mft |
| Sy3u230-Mf-T |
| Uglk2202 |
| Uglk1802 |
| Pta-250 |
| B312+tr24-Sr-T |
| Uflk1448 |
| B315+tf24-Sr |
| Sy-Hoa-24 |
| Grc24a-5 |
| B223+lf24-S |
| Uglk1002 |
| G350-Nv24-Mft-Us |
| Afrx24-Mft95 |
| B322+lf24-S |
| Efb24-Mft-S |
| Lmb24-Mft |
| Arb24-Sr |

| | |
|------------------------------------|---------------------------|
| Uglk1206 | |
| Uflk1742 | |
| B315l | |
| Vfp400 | |
| B214vs+lf120 | |
| B230+lrb24-Mft | |
| B215ht073 | |
| B253af24s | |
| B209+lrx24-3 | |
| B6400s-186 | |
| B214+lrb24-3 | |
| Fgvl+evb24-Sr | |
| G780dnvg24mft | 3 3WAY DIV 24V 360# PROP |
| G680+gmx24-Mftx1 | 3FLNGVLV 90CV 24V 2-10VDC |
| Uglk1422 | |
| B250s | |
| R3050-BI4 | |
| FsIf120 Us | |
| Afrb24-Mft | |
| G250nvf24mfte | |
| Smc24 | |
| Efb24-Mft | |
| B215ht029+lrb24-Sr | |
| Lf24-Mft | |
| Ep050r Mp | |
| B252+afrb24-S | |
| Nmv-D2-Mft | |
| Afbup-Sn4h | |
| B249 | |
| G250ps-X1 | |
| Af230 | |

| | |
|------------------------------------|------------------------------|
| B240+afrx24-Mft | |
| B238+arb24-Sr | |
| Fsnf24 Us | |
| Zone120nc | |
| Af24-Sr-S-Us | |
| Sf24-S | |
| Lmb24-3-S | |
| B231af24 | |
| Lf24-Sr-E-Us | |
| F780hdu+2af24-Mft | |
| B212+lrb24-Sr | |
| Nvf24-Mft-E-50 | |
| Gmx120-3 | |
| Sf24a-Sr | |
| B210+tfrb24-3-S | |
| B222+lrb24-3 | |
| B322+lf24-Mft-S | |
| B330+afrx24-Mft | |
| 12748-00001 | |
| B219b+lf24-3 | |
| Lmb24-3-T | |
| B239vss+gmb24-3-X1 | 1.5 2W 84CV 24V 360IN-LB FLT |
| B210+lrb24-Sr | |
| Zg-Tf2 | |
| Amb24-3-X1 | |
| Nmu24-S | |
| B350af24 | |
| Zone225s-80+z24ncs | |
| G780 | 3FLG 3-WAY MIX. 91CV |
| Uflk1242 | |

| |
|-----------------------------------|
| Sm24a-Sr-Tp |
| B320vs+af24-Mft |
| Lub24-Sr |
| Uglk1480 |
| F665hdu+amx24-Mft |
| Afb24 |
| B211b+tr24-3 |
| Uglk1276 |
| Uglk1208 |
| B313b+tr24-Sr |
| Lf24-Sr-Us |
| Arx24-3-T |
| Efb24-Sr-N4 |
| B214b+lf120 |
| F680hd+gmx24-Mft |
| B251 |
| Fsaf24-S Us |
| Lrb24-Sr-T |
| Lf24-Sr |
| Uflk1458 |
| Lmb24-Sr |
| B339+af24-Mft |
| G225+nfb24-Sr-X1 |
| B340 |
| Tfrb24 |
| Ugsp0004 |
| Gkrx24-Mft N4 |
| B210b+tr24-Sr-T |
| Lmx24-Fr-F |
| Tfx24-S |
| G680c+afbup-X1 |

| | |
|-----------------------------------|--|
| B265af120 | |
| F6150hdu+sy2-24 | CONTROL VALVE 6INCH 2WAY BFV 24VAC 2POSITION |
| G680c+nvf24-Mft-E | |
| B264+afrx24-Mft | |
| Arx24-Mft | |
| B254+arb120-3 | |
| B222+lf120-S Us | |
| Efb120 | |
| B220+lf120 | |
| Afrx24-Mft-N4 | |
| Uflk1300 | |
| G6150c | |
| G6100c+gmb24-3x1 | 42WYFLNG170CV 24V 360# FLTG |
| B249+afrx24-Mft | |
| B213+lrb24-3 | |
| Uflk1746 | |
| G680+af24 | 3FLG ON/OFF 24V S/R 90CV |
| Uflk2954 | |
| Lrx24-3-T | |
| G220+lf24-Sr | |
| Uglk1000 | |
| B320vs+afb24-X1 | |
| Ugvl+lvkb24-Sr | |
| Gmx24-Mft-X1 | |
| Uflk3900 | |
| Ugvl+lvx24-Mft | |
| Uflk1100 | |
| G213s+lf24-Sr | |
| B239vs | |
| B222+lf24-Mft Us | |

| | |
|-----------------------------------|---|
| Lf24-S Us | |
| Fsaf230 | |
| B338+af120-S | |
| B225vs+af24-S | |
| Nf24 | |
| B209b+tr24-Sr | |
| Afrx24-S | |
| Uflk1238 | |
| R6080w100-S8 | |
| B263+afrx24-Mft-S | |
| Efb24-S N4 | |
| LV24A-MP-TPC | Belimo lifting drive AC/DC 24V LV24A-MP-TPC 150s, 500N, IP54, continuous, MP-Bus type: LV24A-MP-TPC |
| Efb24-Sr | |
| Lm24-Sr-Us | |
| Gkrb24-3-5 | |
| Nrx24-3-T-N4h | |
| Nfb24-Mft | |
| Afb24-Mft-S | |
| Dn150 | |
| Ext-Sw-V2 | |
| B220+lf24-3-S | |
| Gkrb24-Mft-5-14 | |
| Lf230-S Us | |
| Sr24a-Sr-5 | |
| B231af120 | |
| B210+tfrx24 | |
| Sy10-120mft | |
| Fgvl+evb24-3 | |
| Uflk1740 | |
| B249+afrx24-Mft-S | |

| | |
|-----------------------------------|-------------------------------|
| Uglk1200 | |
| G215+lmb24-3-X1 | |
| Lm24-Sr-T Us | |
| Uflk1342 | |
| B253+arb24-3 | |
| G665gmx24mftx1 | 2 1/2 FLANGED 65CV 24V/DC MFT |
| Unv-007 | |
| G665 | |
| Uflk1140 | |
| Nkqb24-Sr | |
| B315+lf120-Us | |
| Zg-118 | |
| K6 | |
| G219+lmb24-Srx1 | |
| G250 | |
| Nf24-S-Us | |
| B239vss | |
| Uglk1554 | |
| Srf24a | |
| B248+arx24-Mft | |
| B341+afrx24-Mft-S | |
| Afrbup-S | |
| B313+lrb24-Sr | |
| Nfb24-Sr-S | |
| Sm230a-Tp | |
| Tfb24 | |
| Sm 24 Sr | |
| B310b+lrb24-Sr | |
| G214s+lf24-Sr | |
| B350+arb24-Sr | |
| B232af120 | |

| | |
|--|--|
| B209+Irx24-Sr | |
| GM24.13 | Belimo GM24.13 rotary actuator, 40 Nm, AD/DC 24V On/Off, 3-point |
| B312b | |
| B312b+lf24-Mft | |
| K41 | |
| Zg-105 | |
| B207 | |
| Zg-112 | |
| B211+lf24-Mft Us | |
| Piccv-15-Pt | |
| Uflk1452 | |
| B341+afrx24-Mft | |
| B212+lf24-3 | |
| B211b+tr24-3/300 | |
| R680r+sr24a | |
| Trf230 | |
| B217+lf24-Mft-S | |
| B218 | |
| B218b+Irb24-Sr | |
| R679 Ac Chr Eo , By R6080w100-S8 | |
| Fslf24-S | |
| B317+lf24 | |
| Uglk1066 | |
| Nf24a | |
| Lmx120-Sr | |
| P2200s-563+afrx24-Ep | |
| Arx24-3-S | |
| Uglk1072 | |
| F665hdu+af24 | |
| B220+Irb24-3 | |

| | |
|-------------------------------------|------------------------------|
| Tfrb24-S | |
| B311+tf24-Sr | |
| B311+lf24 | |
| Uglk1076 | |
| Z-Escm | |
| G6100c | 4 125# 2-WAY GLOBE VLV |
| Ev250s127arx24ev | |
| B6250s-110+afrx-Up | |
| B250+afrbup | |
| Zone320s-35+z120nc | |
| B215ht290+tr24-Sr | |
| G340+nvf24-Mft-E | |
| Vrp24v-50hz | |
| B312b+tr24-Sr/300-U | |
| B225vs+af24-Mft95 | |
| Amb24-Mft | |
| Nm24a-Sr(Exnm24-Sr) | |
| B309b+lrb24-3 | |
| G780s+af24-Mft | 3FLNG3WY 24V SR PROP SS TRIM |
| Uglk1872 | |
| Uflk1832 | |
| Uglk1016 | |
| B208+tfrx24 | |
| B214+lf24-Sr | |
| B210b+lf120 | |
| Dr230a-7 | |
| B211+lrx24-3 | |
| Tfrx24-Sr-S | |
| G7125 | |
| B350af120 | |

| | |
|------------------------------------|---|
| Zone215n10120nc | |
| G250px1 | |
| Af24-Sr95-Uş | |
| B350+afrx24-Mft | |
| Nr24a-Sr | BELIMO valve actuator with mechanical position indicator and Manual adjustment (temporary, permanent) Rated voltage: AC / DC 24V Control: DC 0 ... 10 V continuous Working range: DC 2 ... 10 V Feedback: DC 2 ... 10 V Torque: 10 Nm Running time: 90 s Turning angle: max. 95 ° Connection: cable 1 m Protection class: IP 54 |
| B225ht2800+lf120 | |
| Fslf120-S-Fc | |
| B349+arb24-3 | |
| H650n | |
| G225+nmb24-Sr-X1 | |
| Gmb 24-Sr | |
| Uflk1838 | |
| Af24-Mftus | |
| F7150hd+sy3-24 | |
| G665+2xgmx24-Mftx1 | 2.5 FLG VLV 65CV W/2 GM24-MFT |
| B213btf24sr | |
| Lmx24-3-S | |
| G314+lmb24-3-X1 | |
| G680c+af24-Mft | 3FLNG 2WY 24V S/R DCA |
| B223+lf120-S Us | |
| G680cs+afx24-Mftx1 | |
| B223+lf24-Mft | |
| Uflk5138 | |
| Lf120-S Us | |
| B331+afrb24-S | |
| Lmc230a | |
| Uflk1358 | |
| Fsnf230-S Us | |

| | |
|---|----------------------------|
| Uflk1354 | |
| G350 | |
| P2200s-601+arx24-Ep. | |
| Fsaf24a-S | |
| B210b+lf24-Sr | |
| Lmx120-3 | |
| B222+lf24-S Us | |
| B232+afrx24-Mft-S | |
| B207+lrb24-3 | |
| B217+lf24-Mft Us | |
| Uflk1134 | |
| F6100hd | |
| Lhb24-3-100 | |
| Uflk1408 | |
| B312+tfrb24-Sr | |
| B219+tr24-Sr | |
| Kh-Af-1 | |
| B312+lf24-Mft | |
| Uglk1414 | |
| Af24sr | |
| Uflk2608 | |
| Lma-De0_301_T0g/Lmq24ax-F | |
| Nmx24-3 | |
| B219+lrb24-3 | |
| Uflk1338 | |
| G350+nvf24-Mft-E | |
| Uflk1308 | |
| Tfrb120-S | |
| F7150hsu+sy2-24sr | 6BFLY 3WAY 24V 2-10VDC NSR |
| Zg-Gv10 | |
| | |

| | |
|--|-------------------------|
| Lmb24-10p-Hm | |
| B232vspx1 | |
| Sy3-24mft | |
| Lf-24-S | |
| Zdb | |
| Efx24-Mft-Sn4 | |
| Uflk1830 | |
| Bae 72b-S - Not Available, Alternative | |
| Bae72-S | |
| B209+lf24-Mft-S Us | |
| Cmb24-3-T | |
| Sm24-Sr94-Us | |
| B251+afrx24-Mft-S | |
| G224+nv24-Mft | |
| B21.24.P/58400840 | |
| Uglk2272 | |
| Ah-Gma | |
| Sm24v-24vcc | |
| Km-24 | |
| Fsaf24-S | |
| G250+nv24-Mft-Us | CONTROL VALVE ASSEMBLY |
| G215s | |
| P5000a-Gr | |
| B213b+lrb24-Sr | |
| F6500hd+sy8-110 | |
| G765+evb24-Sr | |
| B232vssaf24 | |
| B680+af120 | 3FLG 265CV 2POS SR 120V |
| G213s-Nvfd24-Mft-E-Us | |
| B225ht464+lf120 | |
| Zone215s-35+z120nc | |
| | |

| | |
|---|---|
| G780+af24 Uflk1444 | 3FLG 3WAY 2POS S/R 24V 85CV |
| B217+lf120 | |
| Sgvl+svx24-Mft | |
| B332vs+afb24-X1 | |
| B320btfx24 | |
| Gmb 24-3 Valve | |
| B230+lf24-Sr | |
| Zg-Gv36 | |
| B213+lf24-3-S | |
| Uflk1752 | |
| B238+afrx24-Mft-S | |
| Lm24a - Mf | BELIMO damper actuator with mechanical position indicator and Manual adjustment (temporary, permanent) Rated voltage: AC / DC 24V Control: DC 0 ... 10 V continuous * Working range: DC 2 ... 10 V * Feedback: DC 2 ... 10 V * Torque: 5 Nm * Turning angle: max. 95 ° * Direction of rotation: selectable (left / right) * Connection: cable 1 m Protection class: IP 54 * Parameterizable with: PC-Tool |
| Gmb24-Mft | |
| B217+lf24-Mft-S Us | |
| Afb24-Sr | |
| Nmu230 | |
| B341+arx24-3-T | |
| B680+af24 | 3FLGD 2WAY SS BALL S.R. |
| G6100cgmx24mft | 4FLG 2-WAY 125# W/GMX24 ACT |
| Gkb24-3-X1 | |
| Ugsp0012 | |
| B278+arb24-3 | |
| Uflk1226 | |
| G220s+lf120 | |
| B213+lrb24-Sr | |
| Nmcb24-Sr | |
| F6100hdu+gmb24-3-X1 | |

| | |
|------------------------------------|-----------------------------|
| Nv24mft | |
| G665s+af24-Mft | 2.5VLV W/ACTUATOR |
| Uflk1346 | |
| Zone315s35+z120ncs | |
| Zg-R06 | |
| Tfrb24-3 | |
| Sy3-24 | |
| G250s+afx24-Mft-X1 | |
| Uflk1456 | |
| G780s+af24-Mft-S | 3FLNG3WY 24V SR PROP 2SW SS |
| Afb24-Pc | |
| B253+afrx24-Mft-S | |
| B261+arx24-Mft | |
| G6150c+2xaf120 | 6FLG 2W 344CV 120V SR 2POS |
| P2075b100 | |
| Gkx24-3 | |
| B225ht464 | |
| Uflk1356 | |
| B225vs+afx24-Mftx1 | |
| B331afrx24mft | |
| Uflk1344 | |
| Uglk1064 | |
| Srvu230-5 | |
| B330+af24-Mft | |
| B352+afrbup | |
| Gkb24-Sr-T N4h | |
| Zone215s10z24no | |
| B220tfx24 | |
| Lf24-Sr.9us | |
| Ext-Sw-Ne152c2 | |
| | |

| | |
|---------------------------------|---------------------------|
| Zone220n50z24no | |
| 43442-00001 | |
| B320+tf24-Sr | |
| Lfc24-3-R Us | |
| B248+afrx24-Mft | |
| Lh24a-Mf100-Tp | |
| Tf120s | |
| Afb24-S | |
| B217-Lrb24-Sr-T | |
| G250+nvf24-Mft | |
| F780hsu+2xaf24 | 3 3WAY BFLY 120V S/R 2POS |