

Beluk

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Beluk Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Beluk T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
3TA092H2-IA18X-00	Thyristor controller 50 kvar / 400 V 3TA092H2-IA18X-00 For switching capacitors 2 phases are switched Mains voltage: 400 V, 50/60 Hz Nominal current: 72 A. Control signal: 8 - 30 V DC Temperature range: -10 - 60 ° C, > 45 ° C power reduction Cooling: natural air cooling ON Installation altitude: <1000 m Installation: vertical Dimensions: 200 x 160 x 215 mm H x
1231524	
1231525	
1231809	
3TA162H2-IA18C-00	
BLR-CX 14	
H2 50kvar/400V	
	thyristor controller 100kvar / 400V 3TA162H2-IA18C-00 3TA162H2-IA18C-00 For switching capacitors 2 phases are switched Mains voltage: 400 V, 50/60 Hz Rated Current:

3TA162H2-IA18C-00	145A Voltage fan: 230 V, 50/60 Hz Control signal: 8 - 30 V DC Temperature range: -10 - 60 °C, > 45 °C derating Cooling: Forced AF Installation altitude: < 1000 m Installation: Vertical Dimensions: 260 x 160 x 215 mm H x W x D Fusing: Maximum 160 mA (slow) Stage power: 100 kvar at 400 V (controller in the outer conductor)
3TA092H2-IA18X-00	Thyristorsteller 50 kvar / 400 V Standard 50kvar/400V 3TA092H2-IA18X-00 For switching capacitors 2 phases are switched Mains voltage: 400 V, 50/60 Hz Rated Current: 72A Control signal: 8 - 30 V DC Temperature range: -10 - 60 °C, > 45 °C derating Cooling: natural air cooling ON Installation altitude: < 1000 m Installation: Vertical Dimensions: 200 x 160 x 215 mm H x W x D Fusing: Maximum 160 mA (slow) Stage power: 50 kvar at 400 V (controller in the outer conductor)
3ACM12R-BEL-O	1231209 RESPIRATOR BLR-CM12R Ub: 115/230V, 50/60Hz, 10VA Voltage: 50-530V, 50/60Hz, 1VA I: 15mA - 5A, 1VA, +20% overload Switching outputs: 12 normally open contacts Signaling contact: 1 changeover contact, potential-free, programmable 1 normally closed contact, potential-free, programmable (fan, THD) Digital input: 1x 50-250VAC Front shield: BELUK MB German
1231810	3TB115H2-EC36X-00 Thyristor controller 50 kvar / 690 V For switching capacitors Two phases are switched. Mains voltage: 690V, 50/60Hz Rated current: 42 A Supply voltage: 230V, 50/60Hz Control signal: 8 - 30 V DC Temperature range: -10 - 60 °C, > 45 °C power reduction Cooling: natural air cooling ON Installation altitude: < 1000 m Installation: Vertical Dimensions: 200 x 156 x 243 mm H x W x D Fuse: Maximum 160 mA (slow-blow) Step power: 50 kvar at 690 V (adjuster in the outer conductor)
H2 50kvar/400v Thyristorsteller	
Blr-Cx12r	
3ta092h2-ia18x-00 Thyristorsteller H2 50kvar/400 V	
Blr-Ca12	
Blr-Cx 6 Cx 06r Mikroprozessor-Regler	
Bel-Ts 100 H2	
Bel-Ts 50 H2	
Blr-Cx 14 Mikroprozessor-Regler	
1231532	
Bel-Ts100h2 Modul Thyristor-145a/400v	
1231806	
Bel-Ts100h2	

[Bel-Ts50h2 Modul Thyristor-72a/400v](#)

[Blr-Cx-12r](#)