

Benzlers

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Benzlers** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.



Firmamız Benzlers Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
BG-244-M2AA-8064	
IEC80B5	M0622/36./B/G/C/F/6/-/-/-/- NET WEIGHT : 28.53 KG EXACT RATIO : 39.857:1 INPUT DESIGN : PREPARED FOR IEC MOTOR OUTPUT SHAFT : STANDARD PREPARED FOR MOTOR SIZE : IEC80B5 MOUNTING POSITION : BASE MOUNTED POS. 6 LUBRICATION : MINERAL OIL 320 ADDITIONAL GEARBOX FEATURES : STANDARD
C51554-M1 (Optional)	FOOT M0620 REPLACES BG244 KIT
K0732/12./B/M/C/C/1/A/7.5/A/-/-	Benzler Serie K EXECUTION : same as Serial Number 86273 (WO-BG5815) 2021 OUTPUT SPEED :109.17RPM MOTOR POWER : 7.50 KW NET WEIGHT EACH : 127.0 KG FREQUENCY : 50 HZ PROTECTION : IP55 MOTOR TYPE : STANDARD BUSCK MOTOR (991047) TERMINAL BOX POSITION : 0°(A) MOTOR VOLTAGE SUPPLY : 3-PHASE 400 VD UNIT VERSION : STANDARD UNIT WITH FEET TYPE OF UNIT : MOTORISED WITH IEC MOTOR OUTPUT SHAFT : STANDARD SINGLE EXTENSION ON LEFT Ø50x95mm MOUNTING POSITION : 1 LUBRICATION : MINERAL MOBILGEAR 600 XP 320 ADDITIONAL FEATURES : NO
208813NA	
36334-A	
7207768-1	
7207768-2	
9820278.001	

99170681	
A44003-1	
B42863-1	
B43163-1	
B94624-M2	
BD40 L U 2 220 B SM	
BD66 H N 1 1100 B LS MCH90 / B14	
BS40/K/1/8HU-B/-/-/P/3/IEC71B14/-/-/-/-/-	
BS40/K/8HU-B/P/3/IEC71/-/-/B14	
BS50/FX/00/P/2/-/-/-/-	
IEC71B14 84,00:1 (K)	
J110	
J110/-/20/-/-/110/-/1/BV/-/-/-/-	
J12B	
J190-20-190-2	
J21A-05—045-2	
J32A	
J52A-15- - 060 - 2 BH	
J72B	
K0732125BGKJ5	
M03223.6BMCD1B1.5A--	
MULTIFLEX 13 20/50	
RXP3 812 special	
J52A/-/15/-/-/060/-/2/--/-/-/-/-	NET WEIGHT : 60.0 KG RATIO : 15.39:1 TORQUE ARM : TORQUE ARM STANDARD HOLLOW SHAFT : STANDARD HOLLOW SHAFT DIAMETER HOLLOW SHAFT : 60MM (Same as BT52) DIAMETER INPUT SHAFT : 38MM (Same as BT52) BACKSTOP : -- GEAR ACCESSORIES : -- SEALS ADDITION : STANDARD SEAL MOUNTING POSITION : POSITION H2 PAINTING : BENZLERS BLUE ADDITIONAL FEATURES : -
M0522/45./B/M/C/G/3/A/.75/A/-/-	OUTPUT SPEED : 33.33RPM POWER : 0.75 KW TOTAL WEIGHT : 35.1 KG EXACT RATIO : 43.2:1 FREQUENCY : 50 HZ PROTECTION : IP55 INPUT DESIGN : MOTORISED WITH IEC MOTOR *OUTPUT SHAFT : STANDARD 35x70MM (BG244 = 32x55MM) MOTOR TYPE : BENZLERS MOTOR TERMINAL BOX POSITION : 0° MOTOR VOLTAGE SUPPLY : 3-PHASE 400 VY MOUNTING POSITION : BASE MOUNTED POS. 3 LUBRICATION : MINERAL OIL 320 ADDITIONAL GEARBOX FEATURES : NO ADDITIONAL MOTOR FEATURES : NO
BT 52	RATIO: 15,39 (F) T0=79643 Reducer Demand quantity: 4pcs Coupling Demand for the Gearbox : 6pcs Coupling Rubber Demand for the Gearbox: 12pcs
M0522/45/B/M/C/G/3/A/75/A	RATIO: 43.2 RPM:32.4 Engine Power: 0.75 KW Reducer Demand quantity: 4pcs Coupling Demand for the Gearbox : 6pcs Coupling Rubber Demand for the Gearbox: 12pcs

C51554-M1	Adapterplatte BG244 to M05 Alternative offer position for the *star marked position !: Since the foot dimensions and also the height between the BG244 and the M05 differ slightly, we offer you an adapter plate with the following item to compensate for these dimensions. If the customer does not need this adapter plate, he must adapt the application accordingly!
J100-05--100-2	
BS40 ENV	
RE 5024 HS RE210	Gear set
RE 5024 HS RE510	Gear set
J110/-/20/-/-/110/-/2/--/-/-/-/-	NET / GROSS WEIGHT : 331.0KG / approx. 378KG RATIO : 19.99:1 TORQUE ARM : TORQUE ARM STANDARD HOLLOW SHAFT : STANDARD HOLLOW SHAFT DIAMETER : 110MM INPUT SHAFT DESIGN : STANDARD 55MM BACKSTOP : - GEAR ACCESSORIES : -- SEALS ADDITION : STANDARD SEAL MOUNTING POSITION : POSITION H2 COOLING ADDITION : NO COOLING PAINTING : BENZLER'S BLUE ADDITIONAL FEATURES :-
47226142-02	9914585,001,2011
BS40	
RE 6014 HS 410L AV4 RS + EP + FL + PH SP	Ratio: 410:1 Overall length: 1056,5mm (21mm longer as the old Gearbox, please check before order)
Cone Ring Number: 32213-9-106	
Multiflex 13	
Gearbox BS40 15:00:1	
BS50/M2AA/80A6	80.00 1/(1) 0011.50rpm 0.37kW IECB14 400VY 50Hz POS Lubrication OIL SHC634 9807247.001
?36334-1 Gummielement	
Bg365 1ec 32b5 B3	
Bs40 Osb 80 B/6 Exch ,Htnr. 008f033799 Menge:1 Lagerplatz:Ct49e48amp;49	
Bd66-H-N-1-50-Abl	
B 37393 Ds7 Obsolete Motor Coupling Half	
Bdk66-L-N-1-900-Sm	
Bs 71-F-Tt 28:1 Lh Food	
2245 5195	
Type :Bs40 6,67:1	Exact translation: 6,67: 1 Output shaft: O: 20mm hollow shaft Lubrication: splash lubrication, oil not included Prepared for mounting an IEC standard motor Size: IEC B14 71 flange Weight: about 3 kg
A46314-1	
Kupplung M13 Komplettbohrung 24mm/14mminklusive Kupplungsgummi	
Bs40 Al-Tt	
Gb13003 - Oboslete , Is Gba 16004 Hq Avf810 Nc	
Multiflex 13	

M0122/9.0/B/G/C/D/5/-/---/-/-/-
Bs 71-F-Tt 28:1 Lh
M0432200bmck 1 A.55a
Bs40f-0o-Vm-3-Iec 63-B14a
Bd40/Bbm/Ba90sa4/300
(No.2)no 22455195-2
A44003-1 Worm Wheel Bd66 4i 7:1
J100 Rl
Dz 3.1 I=1:1
J52a/-/15/-/-/060/-/2/--/-/-/-/- Benzler Serie J TRANSLATION: 15.39: 1 TORQUE CAP: STANDARD TYPE "R" INCLUDED HOLEWAVE: STD. 60 mm feather key DIN6885 / 1 DRIVE SHAFT: STD. 38 mm feather key DIN6885 / 1 RETURN LOCK: Yes, but this would be delivered loose as we have the , : Do not know the direction of rotation (ARTICLE: J52BACKSTOP). ACCESSORIES: NO SEALS: STD SEALS LUBRICATION: GEARBOX IS DELIVERED WITHOUT OIL! MOUNTING POSITION: H2 (HORIZONTAL SHAFT POSITION) PAINTING: BENZLER STANDARD RAL5009 COUNTRY OF ORIGIN: SWEDEN CUSTOMS TARIFF NUMBER: 84834021
J32a Aufsteckgetriebe
Bd66-H-N-1-50-Abl-Lrk-Sm
Bs40-6,67-M2aa71a4
Tv 512 Byj190-20-190-2
Bs 40 Al-Tt 3,5:1 Rh
90056-0164
Rd40/2r/D/H2/Bh/4/Iec100/180/B14
1/2\ Z=12 D=20+klein
Bs50 A90I2/B14-U-45;
90603-2423
J52a Aufsteckgetriebe
J72b Aufsteckgetriebe
A45633
Bs40/Iec71b14
J71-J72 Ro
J100 Rr
Be-3-8016-05 Wheel Shaft
Replacement For 10+ Bs 40, 40:1
Ta400
Bs 71-F-Tt 28:1 Rh
Screw Jack

J12b/-/15/-/-/045/-/2/--/-/-/-/-/	Benzler Serie J NET WEIGHT : APPROX. 20 kgs RATIO : 15.09:1 TORQUE ARM : STANDARD R HOLLOW SHAFT : STD. Ø45 mm INPUT SHAFT DESIGN : STD. Ø19 mm BACKSTOP : -- GEAR ACCESSORIES : -- SEALS ADDITION : STD SEALS LUBRICATION : DELIVERED WITHOUT OIL MOUNTING POSITION : H2 PAINTING : BENZLER STANDARD COLOUR
Type :Bs40 15:1	Exact translation: 15: 1 Output shaft: O: 20mm hollow shaft Lubrication: splash lubrication, oil not included Prepared for mounting an IEC standard motor Size: IEC B14 71 flange Weight: about 3 kg
A613731	
Bs71a	
J71/72 Rr	
J52a	
Be-3-8016-05	
B42863-1 Pinion Shaft J72 Step 1	
208813na Ritzelwelle Letzte Stufe	
Bs40/K/8hu-B/P/3/Iec71/-/-/B14 Getriebe	
A46314-2	
J100-20-100-20	
Bs40 Osb 80 B/6 Exch ,Htnr. 008f033799 Menge:1 Lagerplatz:Ct49e48&49	
Bd58-5	
B 37393 Ds7	
J100 Ro	
B43163-1 Gear Wheel J72 Step 1	
J71/72 RI	
Bd4002	
J21a	
M0632200bmck5a.55a	
C41984-M30	
J190-20-190-2	
A439931	
Ta30	
Bs40	
991319/3	
A46334-1	
Bd66-L-N-1-500-Sm	
B02734-4	
Gearbox Btm72-3-K-H2-0-Bv (Connecting Motor 18.5kw, 1450rpm)	

Benzlers

YURSAT yedek para tedarigi yapan bir Őirkettir. Sitemizde bulunan markaların yetkili distrib¼t¼r¼ yada temsilcisi deęildir.

Bs40:1
Bg365 1ec 32b5 B3 9481: 1 : G : 221 01g, Lubrication Bpgp 4843449-002, Coupled Coming With Motor 75
Bs 50 42:1 43097 7 Reducer
Bs71
6-4722 7524 02
Replacement For 10+ Bs 40, 60:1
A53783 Ds6
Tv122c20, 9820278.001,19.44:1 By J100-20- 100-20
Bd58-14
Item 208813nadescription Final Pinion G20/21/22
Ta25
Bd58-H-N-2-50-Mch Without Motor
Bdl58-L-U-280-Bb
991319/3 Reducer
Bd58 H U 1 250/400 Shm Sm/Ls Mcv100b14
Bs112/63
1/2" Z=12 D=20+ Klein
Bs40-Env-Iec71b14
Bs71k-0-0-2
As 4.5-Flexiwarp X1-5r-10
Gba 16004 Hq Avf810 Nc
Csk25pp
K1231/50./B/G/K/L/4/-/-/-/-/-
A53783 Ds6 Obsolete Gb Coupling Half
Bs40 Al-Tt 3,5:1 Rh Food

Benzlers

YURSAT yedek para tedarigi yapan bir Őirkettir. Sitemizde bulunan markaların yetkili distrib¼t¼r¼ yada temsilcisi deęildir.