

Berluto

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Berluto** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Berluto T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	Aıklama
DRV 225 - 1"	Internal thread according to ISO 228 Max. Pre-pressure: 40 bar Setting range: 1.5 - 20 bar Housing: gunmetal CC499K internal parts in contact with media: brass CW614N Piston seal: NBR Seals: NBR included; Pressure gauge 0-25 bar, 63mm, R1 / 4 "
DRV 508 - DN 80	Flanges according to DIN EN 1092 PN25 Overall length: 310 mm. Max. Pre-pressure: 25 bar Setting range: 1.5 - 10 bar Housing: gunmetal CC499K inner parts in contact with media: Brass CW614N & stainless steel 1.4404 Membrane: NBR Seals: NBR
DRV 608 - DN 80	Flanges according to DIN EN 1092 PN25 Overall length: 310 mm. Max. Pre-pressure: 25 bar Setting range: 3 - 10 bar Housing: gunmetal CC499K inner parts in contact with media: Brass CW614N & stainless steel 1.4404 Membrane: NBR Seals: NBR
022603	DRV 226 - 3/4" Internal thread according to ISO 228 Max. pre-pressure: 60 bar Setting range: 20 - 45 bar Body: gunmetal CC499K internal wetted parts: brass CW614N Piston seal: NBR Seals: NBR
002003	DRV 200 - 3/4 " Internal thread according to ISO 228 Max. pre-pressure: 25 bar Setting range: 1.5 - 8 bar Body: gunmetal CC499K internal wetted parts: brass CW614N Diaphragm: CR Seals: NBR
DRV 425 - 1 1/4"	042505 External thread according to ISO 7 Max. Pre-pressure: 40 bar Setting range: 2 - 20 bar Housing: gunmetal CC499K internal parts in contact with media: Brass CW614N & Hostaform C Piston seal: NBR Seals: NBR with Manometer 0-25 bar,63mm,R1/4" 1 peice
	External thread according to ISO 7 Max. Pre-pressure: 40 bar Setting

DRV 402-1/2"-SA	range: 1.5 - 6 bar Housing: gunmetal CC499K internal parts in contact with media: Brass CW614N & Hostaform C Membrane: FPM Seals: FPM *** Customs fee number. 84811005 *** The above-mentioned pressure reducers conform to the Pressure Equipment Directive 2014/68 / EU. (PED 2014/68 / EU category I) + Manometer 0-10 bar
DRV 602 - DN 125 - PN 25	060211-55000 Flanges according to DIN EN 1092 PN25 Overall length: 400 mm. Max. pre-pressure: 25 bar Setting range: 1.5 - 6 bar Body: gunmetal CC499K internal parts in contact with media: Brass CW614N & stainless steel 1.4404 Diaphragm: NBR Seals: NBR *** Customs fee number. 84811099 ***
009013-00010	Manometer 0-25 bar
009009-00010	Manometer 0-10 bar
KSV 80 1 1/2"	External thread connection according to ISO 228 Max. supply pressure: 12 bar Housing: stainless steel 1.4408 Internal parts in contact with media: stainless steel 1.4404 Seat seal: FPM
V4A - ball - 1 1/2" 240x240mm	
Repair kit DRV 608 DN 150	096112
DRV 408 - 2"	External thread according to ISO 7 Max. pre-pressure: 25 bar Setting range: 1.5 - 10 bar Housing: gunmetal CC499K Internal parts in contact with media: Brass CW614N & stainless steel 1.4404 Membrane: NBR Seals: NBR
047806	DRV 478 - 1 1/2" External thread according to ISO 7 Max. pre-pressure: 25 bar Setting range: 0.5 - 9 bar Housing: gunmetal CC499K Internal parts in contact with media: Brass CW614N & stainless steel 1.4404 Membrane: NBR Seals: NBR
009002-00010	Manometer (0-10 bar)
DRV 225 - 1 1/2"	Internal thread according to ISO 228 Max. pre-pressure: 40 bar Adjustment range: 1.5 - 20 bar Case: Gunmetal CC499K media-wetted internal parts: Brass CW614N & Gunmetal CC499K Piston seal: NBR Seals: NBR
DRV 608 - DN 125 PN 16	Technical Specifications: Flanges according to DIN EN 1092 PN16 Face-to-face length: 400 mm Max. inlet pressure: 16 bar Adjustment range: 3 - 10 bar Body material: Red bronze CC499K Wetted internal parts: Brass CW614N Stainless steel 1.4404 Diaphragm: NBR Seals: NBR Customs tariff number: 84811099 The above valves comply with the Pressure Equipment Directive 2014/68/EU, Category I.
096111	Repair kit DRV 608 DN 125
DRV373-1"-SA	0,5-4 bar pressure reducing valve
067209	
Fsv 27	
Drv 672/413 - Dn 80	
Drv 225 - 1"	Internal thread according to ISO 228 Max. Form: 40 bar Adjustment range: 1.5 - 20 bar Housing: gunmetal CC499K Internal wetted parts: Brass CW614N Piston seal: NBR Seals: NBR above-mentioned Pressure reducers are compliant with the Pressure Equipment Directive 2014/68 / EU. (PED 2014/68 / EU category I)
Drv 672 /413- Dn 80	