

Bernier



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Bernier Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Bernier T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | Aıklama |
|--------------------------------|--|
| Cma 5w22 | Push-Pull plug with 22 contacts polarization W without backshell |
| Cma 5y22ra7-60 | |
| Cma 5w14 | Push-Pull plug with 14 contacts polarization W without backshell |
| Cma Ra19-95 | Specific backshell with double knurling diameter 9.5mm |
| CMA 5N14 | Push-Pull plug with 14 contacts polarization N without backshell |
| Cma Ra8 | 105° Elbow backshell for CMA connector and with a thread for a backshell addition |
| Cma Ra7-80 | Straight backshell diameter 8mm |
| CMA5Y22 | Connector, 22-pin, pin, solder, 22xAWG26, stainless steel, without backshell, Coding "Y" |
| CMA 3Y22 | Receptacle with 22 solder cts polarization Y with panel sealing and thread for backshell |
| CMA RA7-70 | Straight backshell diameter 7mm |
| CMA 5W14 | Push-Pull plug with 14 contacts polarization W without backshell |
| CMA RA19-95 | Specific backshell with double knurling diameter 9.5mm |
| CMA 7T14 | Receptacle with 14 solder contacts for all keyways for test panel |
| CMA7N14 | Socket single hole, 14-pin, socket, solder, 14xAWG22, stainless steel, without end housing, coding "N" |
| CMA 7W14 | Receptacle with 14 solder contacts polarization W |
| CMA BA06MC | Receptacle with 14 solder contacts polarization W |

| | |
|---|--|
| BOU000MESE02 | Tool to crimp the metallic clamp width 6.10mm |
| CMA-RA7-70 | Straight backshell diameter 7mm |
| CMA7Y22 | Single-hole socket, 22-pin, socket, solder, |
| CMARA7-70 | Backshell straight, CMA series, Cable entry: 7mm, with shield connection |
| CMA5N14RA7-70 | |
| Cma 5 Y 22 | |
| B593 | Metalic collar width 6.10 mm |
| Cma Ra18-127 | Specific backshell with knurling diameter 12.7mm |
| Cma 7 Y 22 Pm | |
| Pam07sbases | |
| Cmaba86-35mc | |
| Cma Ba06 | |
| Cma 7 Y 22 | |
| Cma 5n14ra8-70 | |
| Cma3y10ra18-79 Consists Of Cma 3y10 And Cma Ra18-79 | |
| Cma 5y10 | |
| Cma5y22ra7-80 | |
| Cma 6 Y 22 Pm | |
| Cma5y10ra18-79 Consists Of Cma 5y10 And Cma Ra18-79 | |
| CMA RA7-70 | Straight backshell diameter 7mm |
| Cma R7 Y 22 Pm | |
| Cma 5y22 | Push-Pull plug with 22 contacts polarization Y without backshell |
| Cma Ra18-79 | Specific backshell with knurling diameter 7.9mm |
| Pam07smodur2crb | |
| Cma 3y10 | |