

Bernoulli System Ab

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Bernoulli System Ab Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Bernoulli System Ab Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Cylinder set C7 100-900	Part no:50800100
BSG 350 GRP 0,2 MM 1100 M ³ /H	2-10 BAR PISTON AISI 316
SİLİNDİR PNOMATİK MAT:316/AL DIMENSION: C4 100-900	FOR BERNOULLI BSG 350 BR YD 50800100, Cylinder set C7 100-900 (Sparepart s for BSG 350 Serial no 2781-2783)
61130230	IB-9 CONTROL CARD
BF-B-02	AUTOMATIC BACKWASH BERNOULLI FILTER 3 x 250 m ³ /h 100 micron (2 + 1)
BF-B-01	AUTOMATIC BACKWASH BERNOULLI FILTER 3 x 250 m ³ /h 100 micron (2 + 1)
BF-B-03	AUTOMATIC BACKWASH BERNOULLI FILTER 3 x 250 m ³ /h 100 micron (2 + 1)
BSG 150/200 C7 50-530	700 9900 00104 Cylinder for BSG 150/200 C7 50-530
BSG 200 0.3W LCP	700 0000 00123 Bernoulli BSG 200 0.3W LCP V1 Self-cleaning basket filter 504 20,850.00 -15.00% 17,722.50 Self-cleaning basket filter with control of cleaning intervals in Dependence on contamination and operating time. Materials: Housing GRP (blue) Filter basket SS 316L Operating pressure: 0.8 - 10 bar Maximum operating temperature: 60°C Filter fineness: 0.3 mm Seals: Nitrile

Ürün	Açıklama
	Connections: Product Inlet/Outlet DN 200 PN 10 Flushing port DN 65 PN 10 Maximum flow rate: 100 - 520 m³/h Flushing volume: 61 m³/h Rinse time: approx. 28 seconds. Voltage: 230 V 50 Hz Protection class: IP 65 Compressed air min. 6 bar
BSS 200 0.3W LCP	Bernoulli BSS 200 0.3W LCP V1 Self-cleaning basket filter 504 26,750.00 -15.00% 22,737.50 Self-cleaning basket filter with control of cleaning intervals in Dependence on contamination and operating time. Materials: Housing SS 316L Filter basket SS 316L Maximum operating pressure: 10 bar min.: 0.8 bar Maximum operating temperature: 80°C Filter fineness: 0.3 mm Seals: EPDM Connections: Product Inlet/Outlet DN 200 PN 10 Flushing nozzle DN 100 PN 10" Maximum flow rate: 100 - 522 m³/h Flushing volume: 51 m³/h Rinsing time: approx. 25 seconds. Voltage: 230 V 50 Hz Protection class: IP 65 Compressed air min. 6 bar
ILC-S-IF	700 9800 00100 ILC-S-IF control unit Option / Additional cost PLC control with touchscreen for: - advanced settings - Operating indicator - Alert list - Modbus / Profinet ... Adaptable to customer requirements Optional with -Leakage monitoring -Compressed air monitoring -Remote access -Monitoring and alerting of other filters such as bypass filters
266/25SW	Prematic MK compressor Container: 25 l

Ürün	Açıklama
	Maximum pressure: 10 bar Voltage: 230V 50Hz Power consumption: 1.5 kW Sound level: 75 dBA including wall brackets, pressure regulator and Automatic condensate drain with container If compressed air is available on site, a compressor is not required.
Kompressor Prematic MK 266/25SW	Container: 25 l Maximum pressure: 10 bar Voltage: 230V 50Hz Power consumption: 1.5 kW Sound level: 75 dBA including wall brackets, pressure regulator and Automatic condensate drain with container If compressed air is available on site, a compressor is not required.
C1/C11/C7 50 (16/26)	700 9900 00122 Gasket set Cover/piston rod to cylinders C1/C11/C7 50 (16/26)
50500160	
Ls103	
C1 32-300	
78801145	
68850100	
42810180	
41500130	
Bss200	
Bss100	
23100303	
35810160	
155.lb 10	
40100600	
lb-9	