Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Besa

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Besa Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Besa Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
249-CR-H2	Safety valves spring actuated Valve Type : 249-CR-H2 DN in x out : ¾" x 1" Threaded connections in/out : GAS-F/F Orif. Diam / Orif. Area : 10 mm / 0.78 cm2 Set Pressure : 300 BAR(G) Overpressure : 10% Blowdown : 20% -new value Suitable to discharge 45600 kg/hr of Water @ 38°C (density : 992.9kg/mc) Material construction Body Inlet / seat : 1.4418 Body Outlet / bonnet : ASTM A216WCB Cap : ASTM A216WCB Disc : 1.4028 Spindle : 1.4401 Guide : 1.4401 Spring : Alloy steel Note:Fully interchageable with s/n 15-9-2 Single weight 2 kg Custom tariff 84814010
249-CR-H2	Safety valves spring actuated Valve Type : 249-CR-H2 DN in x out : ¾" x 1" Threaded connections in/out : GAS-F/F Orif. Diam / Orif. Area : 10 mm / 0.78 cm2 Set Pressure : 300 BAR(G) Overpressure : 10% Blowdown : 20% -new value Suitable to discharge 45600 kg/hr of Water @ 38°C (density : 992.9kg/mc)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Material construction Body Inlet / seat : 1.4418 Body Outlet / bonnet : ASTM A216WCB Cap : ASTM A216WCB Disc : 1.4028 Spindle : 1.4401 Guide : 1.4401 Spring : Alloy steel Note:Fully interchageable with s/n 15-9-2
249-CR-H2	Description Safety valves spring actuated Valve Type : 249-CR-H2 DN in x out : 1” X 1-½” Threaded connections in/out : GAS-M/F Orif. Diam / Orif. Area : 10 mm / 0.78 cm2 Set Pressure : 280 BAR(G) - Is the set pressure that we have supplied this s/n -If you need 300 bar as per your description pls confirm in order- Overpressure : 10% Blowdown : 20% Suitable to discharge 43096 kg/hr of Water @ 35°C Material construction Body Inlet / seat : 1.4418 Body Outlet / bonnet : ASTM A216WCB Cap : ASTM A216WCB Disc : 1.4028 Spindle : 1.4401 Guide : 1.4401 Spring : Alloy steel Note:Fully Interchangeable with s/n 15-9-6 with set pressure 280 bar
Safety valve	249-CR-H2-Liquids-DN 1" x 1"1/2-GAS M/F-do=10 mm Set press.: 300bar(g) Water @ 35°C (liquid) a. r. o. Fully interchangeable with s/n 15-9-6 ***The valve with the metioned serial no. was supplied with set pressure 280 barg. In case of order, please confirm correct set pressure, price won't change***
139-CR-H4-DN	Safety valve 139-CR-H4-DN 3/4" x 1/2"-GAS M/F-do=8 mm Set pressure: 48 psig (3,1 barg) Heat Transfer Oil @ 300°C

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Fully interchangeable with s/n 81120 (1998) With the goods, we will provide in paper format: - N° 1 original of the internal test certificate 3.1 with the results of the hydraulic and tightness tests - N° 1 copy of the declaration of conformity CE-PED (2014/68/UE) - N° 1 original of the use and maintenance manual - N° 1 sectional and overall dimensions drawing per valve type Additional documentation in number of copies, format and / or different languages, if available and feasible, will be considered at cost and in any case to be defined before the issuance of your possible order.
249-CR-H2 Safety valve	249-CR-H2-Liquids-DN 1" x 1"1/2-GAS M/F-do=10 mm Set press.: 300 barg Water @ 35°C (liquid) Fully interchangeable with s/n 15-9-6 ***The valve with the metioned serial no. was supplied with set pressure 280 barg. In case of order,
242-G-H3 DN 25	
249-CR-H2-DN 3/4" x 1"-GAS F/F-do=10 mm	Safety valve Set press.: 300 bar(g) Weeks Suitable to discharge Water@35°C a. r. o. Over pressure 10% Blowdown 20% Body inlet 1.4418;Outlet body-Bonnet-Cap in ASTM A216WCB Disc in 1.4418, Spindle in St.St 316L, Spring in Alloy Steel Unit weight 2 kg Custom Tariff 84814010
Safety valve	249-CR-H2-Liquids-DN 1" x 1"1/2-GAS M/F-do=10 mm Set press.: 280 bar(g) Suitable to discharge WATER@35°C Overpressure 10% / Blowdown 20% Body-Inlet/Seat : St.St 420 Body Outlet/Bonnet/cap ASTM A216WCB Spindle in st.st 316L, Disc St.St 420,Metal Tightness, Spring in Alloy Steel Closed Bonnet ,Closed cap Without lever Design Conditions Temp. -10/+150°c Press. In/out 389.5/63 Single weight 3 ***fully interchangeable with s/n 15-9-6

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Safety valve	252-C-H3-Semi nozzle-DN25x40-PN160x40-do=18 mm Set press.: 75 barg Fully interchangeable with s/n 15-577-2 Body, bonnet and cap: ASTM A216 WCB Seat: 1.4401+stellite Disc: 1.4028 Spring: Alloy steel Other internals: 1.4401 Suitable to discharge 8012 kg/h of superheated steam @ 350°C Min/max allowable temperatures: -10°C / +365°C Max inlet/outlet allowable pressures: 126,1 bar / 31,5 bar
Safety valve 249-CR-H2	Liquids-DN 3/4"x1"-GAS FxF-do=10 mm Set press.: 300 barg Fully interchangeable with s/n 15-9-6 Water @ 38°C Single weight 3 kg
249-CR-H2	Safety valve 249-CR-H2-Liquids-DN 3/4"x1"-GAS FxF-do=10 mm Set press.: 300 barg Fully interchangeable with s/n 15-9-2
262-C	
241-C	
131-C	
139-Cr	
249-Cr-H3 160	
Dn1 1/2	
261-L	
241f-C	
291-C	
132-C	
241b-I	
251-L	
242f-C	
242-G	
242bf-C	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
241f-I	
249-Cr	
132b-C	
242-C	
241t-C	
252-C	
131b-C	
281-C	
281-L	
131-I	
131-G	
241t-I	
139-I	
Sn 15-9-1/5	
261-C	
241tb-C	
249-Cr-H3	
292-C	
292-L	
241bf-I	
241bt-I	
131b-I	
241-G-H3	
291-I	
242f-G	
262-L	

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
241bf-C	
132-G	
241f-G	
Type 249-Cr-H2	Safety valve type 249-CR-H2 DN ¾"x1" THREADED CONNECTION GAS-F/F Set @ 300 Bar(G) Other details as per attached data sheet. Interchangeable with s/n 15-9-2 Net weight : 2 kg each valve Custom tariff 84814010
282-L	
282-C	
241tb-I	
241-G	
252-L	
249-I	
241	
Bs-Ha32	
241b-C	
281-I	
241-I	
251-C	
241bt-C	
291-L	
242b-C	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.