

Blickle



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Blickle Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Blickle Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Lk-Poev 125k-3	Sheet steel swivel castor, heavy version, with screw-on plate Heavy duty wheel with elastic solid rubber tires 'Blickle EasyRoll', with Polyamide wheel center Housing: Made of strong sheet steel, with double ball bearings in the slewing ring, with slewing ring seal. The special one Dynamic Blickle riveting of the slewing ring results in a minimal slewing ring clearance with smooth running and a high one Lifetime due to the strain hardening of the ball raceways. Bolted wheel axle. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: black Tread / tires: Made of high-quality elastic solid rubber in smooth running quality 'Blickle EasyRoll'. Wheel center / rim: Made of high-quality, break-proof polyamide 6. Vulcanised tire. Base hardness: 65 ° Shore A Wheel Ø: 125 mm Tire width: 40 mm Load capacity: 250 kg Bearing type: ball bearing Overall height: 155 mm Plate size: 140 x 110 mm Screw hole distance: 105 x 75-80 mm Screw hole Ø: 11 mm Throat castor: 48 mm Temperature resistance: -25 ° C to 80 ° C
Lk-Poth 125k-3	Sheet steel swivel castor, heavy version, with screw-on plate Wheel with thermoplastic polyurethane tread, with heavy Polyamide wheel center Housing: Made of strong sheet steel, with double ball bearings in the slewing ring, with slewing ring seal. The special one Dynamic Blickle riveting of the slewing ring results in a minimal slewing ring clearance with smooth running and a high one Lifetime due to the strain hardening of the ball raceways. Bolted

Ürün	Açıklama
	wheel axle. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: dark gray Tread / Tire: Made of high quality, thermoplastic polyurethane. Wheel center / rim: Made of high-quality, break-proof polyamide 6. Base hardness: 94 ° Shore A Wheel Ø: 125 mm Wheel width: 40 mm Load capacity: 350 kg Bearing type: ball bearing Overall height: 155 mm Plate size: 140 x 110 mm Screw hole distance: 105 x 75-80 mm Screw hole Ø: 11 mm Throat castor: 48 mm Temperature resistance: -25 ° C to 70 ° C
GSTA 200/4	Heavy-duty flange wheel with Blickle polyurethane tread Softhane®, with cast wheel center Technical specifications: • Wheel Ø: 200 mm, wheel width: 50 mm, load capacity at 4 km / h: 700 kg, Number of screw holes: 4, screw hole Ø: 16.5 mm, center hole Ø: 60 mm, hole circle Ø: 100 mm Tread: • high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A. • Very high driving comfort thanks to particularly thick, elastic tread • very gentle on the floor, low-noise operation • low rolling resistance • very abrasion resistant • high cut and tear resistance • Color green, non-marking, non-staining • very good chemical bond with the wheel center
101323	
102554	
102556	
106636	
123584	
125/ 15Ê	
137904	

Ürün	Açıklama
137905	
150131	
150749	
263541	
267302	
577361	
605063	
620989	
850265	
850415	
913866	
ALTH 125/15 K	
ALTH 200	
ALTH 200x50/20-40K	
B-ALST 125K	
B-G 80G	
BH-ALBS 200K	
BH-ALST 100K-3	
BH-ALST 160K - 579557	
BH-ALTH-101K-1 (284307)	
BH-POEV 160K	
BH-SETH 200K	
BO-GTH 150K	
B-PATH 200R	
BPA-TPA 50G	
B-PHN 200G	

Ürün	Açıklama
B-POEV 160K	
B-RD 162R-VLI	
BS-GB 160K	
B-V 162R	
B-V 202R	
B-VE 200R	
B-VEHI 125R	
B-VPP 160R	
FSTH 50X18/17-10K	
FTH 52x15/12-12K	
F-ZP 125R-F	
GB 150/20-50K	
GB 152/25K	
GB 250/25K	
GBN 202/35H7	
GSPO 80/20K	
GSTN 150/25H7 (754394)	
GTH 200/25K	
GTHN 200/30H7	
GTHN 251/40H7	
GTHN 252/40H7	
HPO 82X70/20-70K	
HRP-POA 63G	
HRSP-POA 72G	
JPPR 1001 5100	
L -RD 202R	

Ürün	Açıklama
L-ALEV 125K-FI	
L-ALEV 200K-SG	
L-ALST 125K-FI	
L-ALST 160K-FI	
L-ALST 200K-FI	
L-ALST 80K-FI	
L-ALTH 100 K FI	
L-ALTH 150K	
L-ALTH 150K-FI	
L-ALTH 150K-FL	
L-alth 80K-as	
LE-PATH 200R-FI	
LE-POEV 160K-FI	
LER-VE 100R	
LE-VE 200R-FI	
LEX-PO 125KD-FI	
LEZ-PO 75G-FI	
LH-ALBS 160K	
LH-ALST 200K	
LH-GB 200K	
LH-GB 200K-FI	
LH-SE 202K-ST-SG	
LH-SETH 200K-FI	
LH-SPO 175G-FI	
LI PHN 102 G	
LI-PHN 200G	

Ürün	Açıklama
LK-ALBS 100K-1-FI	
LK-ALBS 200K-FI	
LK-ALST 100K-1-FI	
LK-ALST 160K	
LK-ALST-160K-FI 627034	
LK-ALTH 80K-FI	
LK-G125G-1	
LK-POEV 160K	
LKR-ALTH 100K-FI-AS	
LKR-ALTH 125K	
LO-ALTH 250K	
LO-GTH 150K	
LPA-PATH 50 G-FI	
L-PATH 80G-FI	
LPA-TPA 100G-FI-ELS	
L-POEV 100 K FI	
L-POEV 100K	
L-POEV 1250K-FI	
L-POEV 80K-FI	
L-PTH 200R	
LRA-TPA 75K-FK-GS10	
LRA-TPA75K-FI-FK	
LRA-TPA75K-FK	
LRA-VPA 50 G FI	
LRA-VPA 50 G-ES	
LRA-VPA 75K-FA	

Ürün	Açıklama
L-RD 162-Fi-VLI	
L-RD125R-FI	
LSD-GB 302K-RAH-RI4H	
LSD-GTH 302K-RI4H	
LSD-GTH-100K	
LSD-SE-300K	
LS-GB 160K-ST	
LS-GB 160K-ST-RI4	
LS-GSPO 152K-35	
LS-GTH 300K-ST	
LS-SETH 125K	
L-V 125R	
L-V 162R	
L-V 200K	
L-V 200K-FI	
L-V 202R	
L-VPP 160R-Fi	
P 340/25-90K	
POEV 100/8K-SG	
POEV 125/15R	
POEV 160/20	
PS 310/25-75K	
PS 315/25-75K	
PS 430/25MM -90K	
PS 430/30MM-90K	
RTH 200x85/50-4+2	

Ürün	Açıklama
SPKVS 150K	
SPO 125/15G	
SPO 125/20K	
SP-ZP 100C-FI-F	
SP-ZP 80C-FI-F	
S-ZP 125R-F	
TPA 101/12G-ELS	
TPA 80/12G-ELS	
V 350/25-75K	
WH 160	
BH-ALST-150XK	
BH-ALST-150XK FI	
LK-SPO 80G	754876 Pressed steel swivel castor, heavy duty, with top plate fitting, Heavy-duty wheel made of polyamide Technical specifications: • Wheel Ø: 80 mm, wheel width: 37 mm, load capacity at 4 km/h: 350 kg, Bearing type: plain bearing, total height: 110 mm, plate size: 100 x 85 mm, Screw hole distance: 80 x 60 mm, screw hole Ø: 9 mm, overhang Castor: 40mm Housing: LK series • Strong sheet steel, electrogalvanised, blue passivated, Cr6-free • Double ball bearing in the slewing ring • Stable central bolt (from wheel Ø 125x50 mm) • Slewing ring seal • Minimum slewing ring play, smooth running, long service life the special dynamic Blickle riveting Wheel: SPO series • high-quality polyamide 6, unbreakable, hardness 70 Shore D, very robust, heavy version, color natural white Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -25 °C to +80 °C, reduced load capacity above +35 °C

Ürün	Açıklama
GSTA 250/4	754387 Heavy-duty flanged wheel with Blickle polyurethane tread Softhane®, with cast wheel body Technical specifications: • Wheel Ø: 250 mm, wheel width: 60 mm, load capacity at 4 km/h: 800 kg, Number of screw holes: 4, screw hole Ø: 16.5 mm, center hole Ø: 60 mm, bolt circle Ø: 100 mm Tread: • High-quality Blickle Softhane® polyurethane elastomer, hardness 75 Shore A • Very high level of driving comfort thanks to the particularly thick, elastic tread • very floor-friendly, low-noise operation • low rolling resistance • very abrasion resistant • high cut and tear resistance • Color green, non-marking, non-staining • very good chemical connection with the wheel center wheel body: • robust cast iron • Center bar with center hole and screw holes • Screw holes with spherical collar countersinks • lacquered, color silver Other characteristics: • Assembly using spherical collar screws and spherical collar nuts according to DIN 74361 • high chemical resistance to many aggressive media • Temperature resistance: -30 °C to +70 °C, briefly up to +90 °C, Reduced load capacity above +40 °C
L-ALST 150K	755956 Stahlblech-Lenkrolle, mittelschwere Ausführung, mit Anschraubplatte, Schwerlast-Rad mit Polyurethan-Laufbelag Blickle Softhane®, mit Aluminium-Radkörper Technische Daten: • Rad-Ø: 150 mm, Radbreite: 50 mm, Tragfähigkeit bei 4 km/h: 400 kg, Lagerart: Kugellager, Gesamthöhe: 190 mm, Plattengröße: 140 x 110 mm, Schraublochentfernung: 105 x 75-80 mm, Schraubloch-Ø: 11 mm, Ausladung Lenkrolle: 60 mm Gehäuse: Serie L • Stahlblech, galvanisch verzinkt, blau passiviert, Cr6-frei

Ürün	Açıklama
	• zweifache Kugellagerung im Drehkranz • stabiler Mittelbolzen (ab Rad-Ø 150 mm) • Drehkranzabdichtung • minimales Drehkranzspiel, leichtgängiger Lauf, hohe Lebensdauer durch die spezielle dynamische Blickle-Vernietung - Rad: Serie ALST • Laufbelag: hochwertiges Polyurethan-Elastomer Blickle Softhane®, Härte 75 Shore A, Farbe grün, spurlos, kontaktverfärbungsfrei • Radkörper: Aluminium-Druckguss, Farbe silbergrau - Sonstige Eigenschaften: • hohe chemische Beständigkeit gegen viele aggressive Medien • Temperaturbeständigkeit: -20 °C bis +70 °C, kurzzeitig bis +90 °C, verringerte Tragfähigkeit bei über +40 °C
LS-GSPO 150K-35-ST-RI4	Technical data: • Wheel Ø: 150 mm, wheel width: 55 mm, load capacity at 4 km/h: 2,500 kg, - Bearing type: ball bearing, overall height: 205 mm, plate size: 175 x 140 mm, screw hole distance: 140 x 105 mm, screw hole Ø: 14 mm, Swivel castor projection: 65 mm - Housing: LS series • Particularly robust welded steel construction, galvanized, yellow passivated, Cr6-free • Axial deep groove ball bearings ISO 104 and tapered roller bearings ISO 355 im slewing ring • Welded, very stable central bolt, screwed and secured • Protected against dust and splash water • Grease nipples - Wheel: GSPO series • high quality cast polyamide, reaction cast, unbreakable, hardness 80 Shore D, color natural beige
BH-ALST 100K-3	752602 Sheet steel fixed castor, heavy-duty version, with screw-on plate, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 100 mm, wheel width: 40 mm, load capacity at 4 km/h: 320 kg, - Bearing type: ball bearing, total height: 140 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm - Housing: BH series

Ürün	Açıklama
	• Sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
LH-ALST 100K-3	684464 Sheet steel swivel castor, heavy-duty version, with screw-on plate, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 100 mm, wheel width: 40 mm, load capacity at 4 km/h: 320 kg, Bearing type: ball bearing, total height: 140 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm, Projection swivel castor: 45 mm Housing: LH series • strong sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate • double ball bearings in the slewing ring • very stable center bolt, screwed and secured • Particularly insensitive to shocks and impacts thanks to four special shaped, hardened bearing shells Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
BH-ALST 125K-3	625418 Sheet steel fixed castor, heavy-duty version, with screw-on plate, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 125 mm, wheel width: 40 mm, load capacity at 4 km/h: 370 kg, Bearing type: ball bearing, total height: 165 mm, plate size: 140 x

Ürün	Açıklama
	110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm Housing: BH series • Sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
LH-ALST 125K-3-FI	625517 Sheet steel swivel castor, heavy-duty version, with screw-on plate, with 'stop-fix' lock, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 125 mm, wheel width: 40 mm, load capacity at 4 km/h: 370 kg, Bearing type: ball bearing, total height: 165 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm, Projection swivel castor: 45 mm Housing: LH series • strong sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate • double ball bearings in the slewing ring • very stable center bolt, screwed and secured • Particularly insensitive to shocks and impacts thanks to four special shaped, hardened bearing shells Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A, color green, non-marking, non-staining from contact • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
913865	LH-ALST 150XK-FI Sheet steel swivel castor, heavy-duty version, with screw plate, with 'stop-fix' brake, heavy-duty wheel with Blickle Softhane® polyurethane tread, with aluminium wheel center

Ürün	Açıklama
913866	BH-ALST 150XK Sheet steel fixed castor, heavy-duty version, with screw plate, Heavy-duty wheel with Blickle Softhane® polyurethane tread, with aluminium wheel center
265751	LK-ALTH 80K Sheet steel swivel castor, heavy duty, with screw plate, Heavy-duty wheel with polyurethane tread Blickle Extrathane®, with aluminum wheel center Technical data: • Wheel diameter: 80 mm, wheel width: 30 mm, load capacity at 4 km/h: 200 kg, Bearing type: ball bearing, total height: 110 mm, plate size: 100 x 85 mm, Screw hole spacing: 80 x 60 mm, screw hole diameter: 9 mm, projection swivel castor: 40 mm Housing: LK series • strong sheet steel, galvanized, blue passivated, Cr6-free • double ball bearing in the slewing ring • stable center bolt (from wheel diameter 125x50 mm) • Slewing ring seal • minimal slewing ring play, smooth running, long service life due to the special dynamic Blickle riveting Wheel: ALTH series • Tread: high-quality polyurethane elastomer Blickle Extrathane®, Hardness 92 Shore A, color light brown, non-marking, non-staining • Wheel body: die-cast aluminum, color silver gray Other features: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load-bearing capacity above +40 °C
448746	HTH 82x65/20-65K Forklift roller with polyurethane tread Blickle Extrathane®, with metal wheel body Technical data: • Wheel diameter: 82 mm, wheel width: 65 mm, load capacity at 4 km/h: 590 kg, Ball bearing: 6204 ZZ, axle hole diameter: 20 mm, clamping length: 65 mm Tread: • high-quality polyurethane elastomer Blickle Extrathane®, hardness 92 Shore A • low rolling resistance • very abrasion-resistant • high cut and tear resistance

Ürün	Açıklama
	• Color light brown, traceless, contact discoloration free • very good chemical bond with the wheel body wheel body: • Metal Other features: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load-bearing capacity above +40 °C
754450	HTH 82x65/20-71K Forklift roller with polyurethane tread Blicke Extrathane®, with metal wheel body Technical data: • Wheel diameter: 82 mm, wheel width: 65 mm, load capacity at 4 km/h: 590 kg, - Ball bearing: 6204 ZZV, axle hole diameter: 20 mm, clamping length: 71 mm Tread: • high-quality polyurethane elastomer Blicke Extrathane®, hardness 92 Shore A • low rolling resistance • very abrasion-resistant • high cut and tear resistance • Color light brown, traceless, contact discoloration free • very good chemical bond with the wheel body wheel body: • Metal Other features: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load-bearing capacity above +40 °C
LPX-PGV 120XR-PG2-EL-FA	Stainless steel swivel castor with screw plate, Wheel with elastic solid rubber tire, with aluminum wheel center, with Thread guard made of steel, electrically conductive Technical data: • Wheel diameter: 120 mm, wheel width: 30 mm, load capacity at 4 km/h: 150 kg, - Bearing type: roller bearing, total height: 164 mm, plate size: 120 x 80 mm, - Screw hole distance: 100 x 60 mm, screw hole Ø: 11 mm, - Castor projection: 45 mm Housing: LPX series • high-quality chrome-nickel steel (1.4301 / AISI304), rust-proof, vibratory ground • all individual parts including axle material are rust-resistant • Four-point ball bearing for optimal absorption of vertical and horizontal forces • hardened precision fork head made of corrosion-resistant steel

Ürün	Açıklama
	(1.4034 / AISI420) • excellent steering characteristics, particularly resistant to bumps and blows • Grease nipple Bike: PGV series • Tread: high-quality elastic solid rubber in smooth running quality, hardness 80 Shore A, color black • Wheel body: die-cast aluminum, color silver gray Other features: • high chemical resistance to many aggressive media, but not against oils • Temperature resistance: -25 °C to +134 °C, reduced load-bearing capacity above +35 °C • suitable for autoclaving • electrical conductivity (ohmic resistance) $\leq 104\Omega$
L-ALTH 200K-FI-AS-CO	Sheet steel swivel castor, medium-duty version, with Screw-on plate, with locking device 'stop-fix', Heavy-duty wheel with polyurethane tread Blicke Extrathane®, with Aluminium wheel body, with strongly convex tread, antistatic Technical data: • Wheel diameter: 200 mm, wheel width: 50 mm, load capacity at 4 km/h: 400 kg, Bearing type: ball bearing, total height: 235 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm, Castor projection: 63 mm Housing: L Series • Sheet steel, galvanized, blue passivated, Cr6-free • double ball bearing in the slewing ring • stable center bolt (from wheel diameter 150 mm) • Slewing ring seal • minimal slewing ring play, smooth running, long service life due to the special dynamic Blicke riveting Wheel: ALTH series • Tread: high-quality polyurethane elastomer Blicke Extrathane®, Hardness 92 Shore A, color gray, non-marking, non-staining • Wheel body: die-cast aluminum, color silver gray Other features: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load-bearing capacity above +40 °C • electrical conductivity (ohmic resistance) $\leq 107\Omega$
L-ALTH 125K-12-FI	Sheet steel swivel castor, medium-duty version, with Screw-on plate, with locking device 'stop-fix', Heavy-duty wheel with polyurethane tread Blicke Extrathane®,

Ürün	Açıklama
	with aluminum wheel center Technical data: • Wheel diameter: 125 mm, wheel width: 40 mm, load capacity at 4 km/h: 250 kg, - Bearing type: ball bearing, total height: 155 mm, plate size: 92 x 63.5 mm, - Screw hole distance: 44.5 x 71 - 78 mm, screw hole Ø: 7.9 mm, - Castor projection: 40 mm - Housing: L Series • Sheet steel, galvanized, blue passivated, Cr6-free • double ball bearing in the slewing ring • minimal slewing ring play, smooth running, long service life due to the special dynamic Blickle riveting - Wheel: ALTH series • Tread: high-quality polyurethane elastomer Blickle Extrathane®, Hardness 92 Shore A, color light brown, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray - Other features: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load-bearing capacity above +40 °C
LS-GTH 202K	Welded steel heavy-duty swivel castor, heavy swivel head design, Heavy duty wheel with polyurethane tread Blickle Extrathane®, with Cast wheel center Technical data: • Wheel diameter: 200 mm, wheel width: 80 mm, load capacity at 4 km/h: 1,600 kg, - Bearing type: ball bearing, total height: 255 mm, plate size: 175 x 140 mm, screw hole distance: 140 x 105 mm, screw hole Ø: 14 mm, - Castor projection: 65 mm - Housing: LS series • particularly robust welded steel construction, galvanized, yellow passivated, Cr6-free • Axial deep groove ball bearings ISO 104 and tapered roller bearings ISO 355 in slewing ring • Welded, very stable center bolt, screwed and secured • dust and splash-proof • Grease nipple - Wheel: GTH series • Tread: high-quality polyurethane elastomer Blickle Extrathane® Hardness 92 Shore A, color yellow, non-marking, non-staining • Wheel body: robust grey cast iron • with grease nipple, painted, color silver - Other features:

Ürün	Açıklama
	• high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load-bearing capacity above +40 °C
HRP-POA 50G	757019 Lifting castor with integrated locking foot and screw plate, Wheel made of polyamide Technical data: • Wheel diameter: 50 mm, wheel width: 24 mm, load capacity: 250 kg, bearing type: Plain bearing, total height: 84 mm, total height max.: 88 mm, adjustment range: 4 mm, plate size: 73 x 73 mm, screw hole spacing: 58 x 58 mm, Screw hole diameter: 7 mm, projection of swivel castor: 38 mm Housing: HRP series • Die-cast aluminum, powder-coated, ivory color • sealed ball bearing in the slewing ring • Steel mounting plate • Locking foot made of hard rubber • Height adjustment using an open-end wrench or integrated adjustment wheel • Steel parts galvanized, blue passivated, Cr6-free Wheel: POA series • high-quality polyamide 6, break-resistant, hardness 70 Shore D, color black Other features: • Load capacity determined under the following test conditions: • -Speed: max. 1km/h-Temperature: +15°C to +30°C-Hardness
BPA-PATH 50G	Castor wheel with mounting plate Wheel with thermoplastic polyurethane tread, with polyamide- Wheel body Technical data: • Wheel diameter: 50 mm, wheel width: 19 mm, load capacity at 3 km/h: 75 kg, Bearing type: Plain bearing, Overall height: 71 mm, Plate size: 60 x 60 mm, Screw hole distance: 38 x 38 / 48 x 48 mm, screw hole Ø: 6.2 mm Housing: BPA series • Steel sheet, electrogalvanized, blue passivated, Cr6-free Bike: PATH series • Tread: high-quality thermoplastic polyurethane (TPU), hardness 94 Shore A, dark grey color, non-marking, non-contact discoloration • Wheel body: high-quality polyamide 6, break-resistant, silver-grey color Other characteristics: • Very high chemical resistance to many aggressive media • Temperature resistance: -25 °C to +70 °C, briefly up to +90 °C, Reduced load-bearing capacity above +35 °C

Ürün	Açıklama
B-Alst 160k Rolle	
Lh-Gsp080k-Fi	
Lk-Alst 100k-1-Fi Rad	
Alth 125/15 K Extrathane Schwerlastrad	
Li-Phn 200ik	
L-V 200k Rolle	
L 150/160 -L-160.60.03	
Le-Path 200r-Fi Rolle	
Bh-Spo 100k-1	
Lk-Alth 80k-Fi Lenkrolle Mit Bremse	
L-Vpp 160r-Fi Drehen. Rolle Mit Bremse (Schwarzer Gummi)	
Rad Mit Polyurethankabel D-200mm,Blickle Gth 200/25k	
Fuehrungsrolle Fpo 25x10/6-6k	
622106	
Gspo 152/35k	
B-V 162r Stahlblech-Bockrolle	
Bs-Gth 252k	
Bo-Alth-200k	
Lra-Tpa75k-Fi-Fk Umlenkrolle	
F-Zp 125r - F Roller	
Le-Poev 100r-Fistahlblech-Lenkrollen	
Fsth 70x25/20-15k	
L-Poev 1250k-Fi Rolle	
Bh-Seth 200k Rolle Fest	
150*45	

Ürün	Açıklama
Lenkrolle 150 Mmlh-Seth 150k	
Bh- Alst 100k-3	
L -rd 202r Lenkrollen	
Lh-Gth 200k	
Gth202/30k	
Bh-Gspo 125k	
Bpa-Poa 50g	
Lsd-Gth-100k Rolle Drehbar	
Lk-Albs 100k-1-Fi	
Lsd-Se 250k-Ra	
Bh-Gsp080k	
Bh-Albs 200k Fixierte Rolle	
150749 Le-Poev 201k-Sg	
Lsoa-Albs 200k-Ra-761312	
Lh-Gth 160k	
Gb 200/20k	
Lh-Gth 125k-1	
B-Poev 160k Rollen Schwenkkrane	
Rad Mit Polyurethankabel D-250mmblickle Gth 252/30k	
102556 Super-Elastik-Vollgummi- Reifenbsev 4.00-4-Rp	
B-Rd 162r-Vli Nicht Drehbar Rolle (Grauer Gummi)	
Lk-Po 200k-St-Fs	
Lk-Poev 160k Drehbarer	
Bh-Poev 160k Nicht Drehbar	

Ürün	Açıklama
125/ 15?	
L-Alth 150k-Fi Rolle Drehbar	
Alev 125/15k	
101323 Rad Fest Blickle B-Ve 100rident-Nummer: 101323	
B-Alev-161k	
L-Alst 160k-Fi	
Lk -Alst 100k-1-Fi	
LS-Se 160 K	
Bs-Gth 604k	
B-Vpp 160r Nicht Drehbar Rolle (Schwarzer Gummi)	
Bh-Gspo 100k-3	
562876	
Lra-Tpa75k-Fk Rolle	
Lh-Gth 202k	
Bk-G 125g-1	
Lez-Po 75g-Fi	
Lh-Gb 200k-Fi Lenkrollen	
L-Alst 160k-Fi Rolle	
Lk-Spo 160g-Fi	
850415 B-Poev 201k-Sg	
Lh-Gsp080k-St	
Lh-Gth 175k	
Sp-Zp 80c-Fi-F Lenkrolle Mit Bremse	
Bsd-Se 200 K	
457283	

Ürün	Açıklama
45336	
Fsth 100x25_15k	
Gev 520/40k	
B-Pth 200r	
Gth 504/60k	
752607	
137904 Lenkrolle Ls-Gb 202 K	
Se 252/25 K	
Ls-Vle 310k	
B-Ve 200r Rolle Fest	
106636 Rad Drehbar Mit Bremseblickle Le-Ve 100r-FI Ident-Nummer: 106636	
Gspo 80/20k Heavy Duty Polyamide Block Wheel	
562884	
Rad Alev 125/15k	
Bs-Se 160 K	
L-V80r-St	
Spkvs250k	
L-Alst 250k-3-St	
Bpa-Vpa 50k	
Gthn_252_40h7	
Lex-Po 125kd-Fi Roller	
Ps 315/25-75k Rad	
L-Path 80g-Fi Lenkrolle Mit Bremse	
Lh-Gb 200k Lenkrollen	
Bh-Alst 200k	

Ürün	Açıklama
Das Rad Fest, Stahlblech, Dbh-Poev 100k-1	
Ls-G 250k	
Lkra-Tpa 101g-Gs12	
Bh-Svs 127k	
Lh-Gth 125k-3	
Lh-Alst 100k-3	
Hrsp-Poa_72g_757023 Radkopf	
Gth 202/35k	
Gth150/20k	
Rth 200x85/50-4+2 Rad	
102554 Super-Elastik-Vollgummi-Reifenbsev 3.00-4-Rp	
Ls-Alb 200k-Ra-760676	
L-Alev 125k-Fi	
Lk-Alst 100k-1-Fi P. Roller With Brake	
Poev 125/15r Rad	
L-Alst 125k-Fi Rolle	
150131 B-Poev 201k-Sg	
46714	
115643	
L-Po 125r-Fi-Fp	
Geva 300/5	
45369	
L-Alst 200k-Fi	
Ls-Gb 250k-St-Ri2	
Brd162r	

Ürün	Açıklama
Se 252/25k	
Lh-Gth 100k-3	
Lsd-Gth 302k-Ri4h	
B-Alth 100k	
00227278	
L-Poev 100 K Fi Stahlblech Lenkrollerad- Und Drehkranzbremse "stop-Fix"	
Lh-Albs 160 K Rad Rotor Ohne Bremse	
L-V 162r Stahlblech-Lenkrolle	
Gth 177 / 25k	Wheel with polyurethane tread Blickle Extrathane®, with cast iron wheel center Wheel: Tread / Tires: Made of high-quality polyurethane elastomer Blickle Extrathane®. Tread color: light brown Wheel center / rim: Made of cast iron, with grease nipple, painted. Surface hardness: 92 ° Shore A Wheel Ø: 175 mm Wheel width: 80 mm Load capacity: 1300 kg Bearing Type: Ball Bearing Axle hole Ø: 25 mm Hub length: 80 mm Temperature resistance: -25 ° C to 70 ° C
250/20k	
L-Alth 100 K Fi Stahlblech Lenkrolle Mit Feststeller	
250/20k-Sg	
Lrd162rst	
Lh-Gth 127k-Is	
Albs 100/15k	
451697	
Lsd-Se 200 K	
115646	

Ürün	Açıklama
S-Zp 125r - F Roller	
Gthn 252/40h7 Radident-Nummer: 104572	
Lk-Albs 200k-Fi Drehbare Rolle	
Lh-Gth 150k	
Lo-Alth-200k-St	
125 15?	
Sp-Zp 100c-Fi-F Lagerung Rad Drehbar Mit Bremsed=100 Mm Sp-Zp 100c-Fi-F	
Bh-Albs 200 K Das Rad Nicht Drehbar Ohne Bremse	
Bs-Gspo 302k	
Bh-Gspo 65k	
Gthn 251/40h7 Ruota Di Frizione	
Lra-Vpa 50 G Fi Stahlblech Apparate - Lenkrollerad- Und Drehkranzbremse	
318451	
B-Alev 125k	
Ls-Vle 310k-Ra	
Lkra-Tpa 101g-Fi-Gs12	
Das Rad Drehbar Mit Bremse, Blechlh-Poev 100k-1-Fi	
Gspo125/25k	
Hth80x40/20-40kk	
L-Alth 80k-As Rad Mov.	
Hth 60x35/15-35kpolyurethan- Laufrollenlaufbelag Gegossen	
606541	
Bh-Spo 150k	

Ürün	Açıklama
L-Alst 80k-Fi Pov. Rolle Mit Bremse	
470088	
Zwillings-Lenkrolle Lsd-Gth-252k-Rah-Ri2h	
Ls-Ps 310k	
B-Alst 200k	
Antriebsraeder Rth 200x85/50-4+2	
Rk-Hth 060x035/32x09-35- Zgabelhubwagen-Rolle Mit Polyurethan- Laident-Nummer: 148149	
Gth 200/25k Rad	
Rolle Nicht Drehbar D:100 Chape: 100x85b-Poev 100k	
Lh-Gth 127k	
9990014272	
Se-252/25k	
(754880) Lk-Vsth-65k	Sheet steel compact swivel castor with mounting plate Wheel with Blickle Extrathane® polyurethane tread, with steel wheel center Housing: Made of strong pressed steel, with double ball bearing in the turntable, with slewing ring seal. Wheel axle bolted. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: light brown Tread / Tire: Made of high-quality polyurethane elastomer Blickle Extrathane®. Wheel center / rim: Made of steel. Tread poured. Surface hardness: 92 ° Shore A Wheel Ø: 65 mm Wheel width: 40 mm Load capacity: 250 kg Bearing Type: Ball Bearing Total height: 92 mm Plate size: 100 x 85 mm Screw hole distance: 80 x 60 mm Screw hole Ø: 9 mm Discharge swivel castor: 40 mm Temperature resistance: -25 ° C to 70 ° C
463935 (Fsth 40x20/10-8k)	

Ürün	Açıklama
B-Alth 100k Rad Fix.	
L-Rd 162-Fi-Vli Dreden. Rolle Mit Bremse. (Grauer Gummi)	
Gth 200_25k	
L-Alth 150k Rolle Drehbar	
B-G 80g Rad	
B-Alst 200k Rolle	
L-Rd125r-Fi Rollen	
B-Alst 125k Rolle	
595678	
45377	
B-Vehi 125r	
L-Alev 200k-Sg Rad	
Bh-Alst 160k	
Ls-Gth 604k	
Geva 250/4	
B-Phn 200ik	
761312	
Lra-Vpa 50 G-Es Stahlblech Apparate - Lenkrolleeinsteckstift 11mm	
B-Alst 160k	
137905 Lenkrolle Mit Feststeller Ls-Gb 202k-St	
850265 Le-Poev 201k-Sg	
Ls-Gth 252k	
Alt -160/20 K	
L-Poev 100k Rolle	

Ürün	Açıklama
Lh-Seth 200k-Fi Rolle Lenkrolle Mit Bremse Stop-Fix	
Ls-Seth 125k Swivel Castors	
L-Poev 80k-Fi Rolle	
P 340/25-90k Rad	
Spo 125/20k Rad	
Alev 250/25 K	
B-Path 200r Rolle	
Li Phn 102 G	
Bh-Alst 250k	
Rht 225x70/120 - 12 - P	
Le-Poev 160k-Fi Rollen Schwenkkrane	
Lpa-Vpa 50k	
Le-Ve 200r-Fi Rolle Drehbar	
L-V 200k-Fi Lenkrolle Mit Bremse	
Bh-Po 200k-Fs	
Ps 310/25-75k Rad	
L-Alev-161k	
L-Alst 200k-Fi Rolle	
127 P02	
Lh-Gth 100k-1	
760676	
Lpa-Path 50 G-Fi Rolle	
51615	
Bsd-Spo 160k-35	
L-V 125r Stahlblech-Lenkrolle	

Ürün	Açıklama
B-V80r	
Fsth 80x25/25-15k	
Rad, Stahlblech, Bh-Alth 180k	
Gthn 200/30h7 Rad	
Ff125	