



Böhmer

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Böhmer Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Böhmer Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
PT1315	DN20, PN315 Ø22 KHG V315.720/1
PT1316	DN16, PN400 Ø18 KHG V400.716/1
PT1314	DN20, PN315 Ø22 KHG V315.720/1
PT6022	DN16, PN400 Ø18 KHG V400.716/1
PT1321	45549 Ø22 DN25, PN63
PT1322	DN20, PN315 KHG V315.720/1
KHGV400.312-1	
004.4908	BALL VALVE BBS/MKG 050 100 VERSION C THREADED, SCREWED FULL PASSAGE NOMINAL SIZE DN50 NOMINAL PRESSURE PN100 NPT FEMALE THREAD NPT2 ANSI/ASME B1.20.1 LENGTH DIN3202 M3 EC TYPE EXAMINATION

Ürün	Açıklama
	MARK: CE 0045 TUEV TYPE EXAMINATION COMPONENT CODE TUEV.A.143-16 HOUSING STEEL BALL STAINLESS STEEL 1.4301 GASKETS PTFE, METALLIC MOUNTED O-RINGS FPM SHIFT SPINDLE STAINLESS STEEL 1.4006V SPINDLE SCREW BRASS COLOUR: ANTHRACITE ACTUATION: GEAR HANDLE
Block ball valve 0081614 DN20 PN315 steel	NBR, IG DIN2353, BBS/BHG Case: steel Bolting: steel Ball: Hard chrome-plated steel Gasket: Polyamide O-rings: NBR Spindle: stainless steel Length: 110mm
BKH 30S	
017.1766	BALL VALVE BBF/FSL 050 016 VERSION G FLANGE, FULLY WELDED FULL PASSAGE NOMINAL SIZE DN50 NOMINAL PRESSURE PN16 FLANGES DIN EN 1092-1 FORM B1 LENGTH 230 MM GEM. DIN EN 558 AGV-1 GAS VERSION GEM. EN 13774 G-DIN-DVGW-REG-NO. DG-4313CR0350 MARK: CE 0045 PERMITTED AMBIENT TEMPERATURE: -20 DEGREES C TO +60 DEGREES C HOUSING STEEL BALL STAINLESS STEEL 1.4301 GASKETS PTFE, SPRING ASSISTED, O-RINGS FPM SHIFT SPINDLE STAINLESS STEEL 1.4006V SPINDLE SCREW BRASS COLOUR: ANTHRACITE ACTUATION: GEAR HANDLE
014.1097	FLL V 040.050-2 050 040

Ürün	Açıklama
	FLANGE TAP /BAUL.DIN3202 F1 FLANGE SEALING STRIP DIN 2526 FORM C, RZ 63 HOUSING STEEL TSTE355
KHG V 400.312	
019.1455	DHG L 250.312-1 012 250 THREE-WAY VALVE / THREADED CONNECTION SWITCHING TRAVEL 90 DEGREES
PAB 414-H	Plate Type Heat Exchanger Type: PAB414-H Technical data: Rated power: 100 kW Nominal pressure: 10 bar Water temperatures: Inlet: 35 °C Outlet: 40 °C Oil temperatures: Inlet: 50 °C Outlet: 40 °C Medium: Hydraulic oil HLP46 Number of plates: 121 pieces Oil flow: 350 dm ³ /min Pressure loss: Oil side: max. 1 bar Water side: max. 0.5 bar Material: 1.4401 Connection piece: Water: DN50 Oil: DN50 Supplier: BÖHMER Type: PAB414 Level switch (flange connection) Distance: XXX = 1100 Supplier: KSR-KÜBLER Type: BNA-25/16/C-MXXX-V60-MRA-4/M5/R22-5 olfest-ZVSS250