



## Boll & Kirch

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Boll & Kirch** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Boll & Kirch T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

### ¼r¼n

### Aıklama

[aquaBoll 6.18.3 Gr 521 DN 300](#)

Filter type : aquaBoll 6.18.3 Size : 521 Connection size : DN 300 Connection flanges according to : Hole pattern of the connection flanges according to : EN 1092-1 PN16 Dimension sheet : Z154933 --- OPERATING CONDITIONS --- Fluid to be filtered : cooling water Fluid group according to PED : 2 Fluid Type according to PED : Liquid Max. flow rate : 520.00 m<sup>3</sup>/h Operating pressure : 6.00 bar Maximum allowable pressure : 16.00 bar Operating temperature : not specified Permitted Operating temperature min : 0.00 °C Permitted Operating temperature max : 60.00 °C Pressure loss with clean screens: <0.2 bar at 520.00 m<sup>3</sup>/h Required pre-filtration : 10.00 mm --- BACKWASH --- Backwash medium : Own medium Minimum operating pressure after filter: 2.00 bar Flow rate: 12.40 l/s at 6.00 bar Flushing time : 20 s Control medium : air 4-6 bar ISO8573-1:2010(7/4/4) Motor power : 0.090 kW Operating voltage : 3 ph 400 volts Frequency : 50Hz Control voltage : 230 volts Control : Type 2300 : Z46600 Operating language control: German --- CONSTRUCTION/ACCEPTANCE --- Construction and design : PED2014/68/EU AD-2000 : Article 4, paragraph 3 Total volume : 250.00 liters Pressure test according to: Boll & Kirch with certificate --- Construction/Form Certificates --- FB-7-80 pressure test 3.1 : yes --- MATERIALS --- Filter housing made of : EN-GJS-400-18-LT Inner parts made of: CrNi steel Gasket made of : EPDM --- FILTER ELEMENTS --- Type of element : CrNi steel gap candle no. of filter elements : 16 candle head piece and end pieces Made of : CrNi steel, TIG welded Gap width: 100 µm Screening area in operation: 12880 cm<sup>2</sup> Total screen area: 14720 cm<sup>2</sup> --- ACCESORIES --- Attached differential pressure indicator: 4.46.2 (optical + electrical) Sealant differential pressure gauge : EPDM Backwash differential pressure setting: 0.60 bar / alarm 0.80 bar Sludge drain valve : pneum. powered flap Sludge drain valve nominal size: DN 80 --- Accessories/connections --- Entry/exit with adapter : yes Vent : Option 5.7.0 standard, Z149256 blind flange with screw plug : G1/4" Drainage : blind flange without drilling Measuring point N5 : Option 5.6.0 standard, Z149256 plug connection Measuring point N6 : blind flange without bore Measuring point N7 : Option 5.6.0 standard, Z149256 plug connection --- Accessories/Nozzle alignment ---

	Assembly code : S3D2 --- Accessories/fastening material --- Cover Bolts/Nuts and Washers : A4-70 --- Accessories/differential pressure measurement --- DDA connector : hose connection --- Accessories/Electrical --- Control : loosely enclosed --- Accessories/Miscellaneous --- Lifting eyes : yes Nominal diameter flushing orifice : 35 Earth connection : yes --- CORROSION PROTECTION --- Primer coat outside: 2K-Ep RAL 5005 100-200 µm Corrosion protection inside : epoxy --- LABELLING --- Operating/Factory Plate : English CE marking according to : - Machinery Directive 2006/42/EC : CE --- DOCUMENTATION --- Language of the operating instructions in : English Operating instructions: 1 Acceptance certificates/certificates: 1 Declaration of Conformity : included
<a href="#">3270003+3270013+3270013</a>	Sealing ring For filter 3761703/2
<a href="#">3035046 + 3031849</a>	O-Ring for filter 3761703/2
<a href="#">1147180</a>	
<a href="#">Filtering element,</a>	Filtering element, Dimensions 94x244 mm, type: HF1-G MG-F I=>A. Filtration rating - 3 mµ, full flow: 2626.4 nm3/min. Filter type - BFD-C DBB M 140 600 04 DN40 Manufacturer: BOLL & KIRCH Filterbau GmbH
<a href="#">Filtering element</a>	Filtering element - CRY 1980079, Dimensions 129x394. Filtering element type: HF1-TC MG-H. Material of filter element - stainless steel. Filtration rating - 10 µm, full flow: 430l/min. Filter type - BFD 110 550 40 04 DN50.
<a href="#">Filtering element</a>	Filtering element - CRY 1980076, Dimensions: 80x394 mm. Filtering element type: stainless steel. Filtration rating - 10 mµ. Full flow: 1621 kg/h. Filter type: BFD 110 550 40 04 DN50
<a href="#">Filtering element -</a>	Filtering element - CRY 1940118. Dimensions: 62x208 mm. Filter element type: GC1-HR-A. Filtering material: VA/Stainless Steel. Filtration rating - 3 mµ. Full flow: 1621 kg/h. Filter type
<a href="#">Filtering element</a>	CRY 1980078, dimensions 129*394 HF1-TC MG-L
<a href="#">Filtering element</a>	Filtering element - CRY 1980076 . Dimensions 80x394 mm. Filtering element type: HF1-TC MG-H. Filtering element material - stainless steel. Filtration rating: 10 mµ. Full flow: 185 l/min. Filter type: double filter BFD 110 550 40 04 DN50
<a href="#">1944319</a>	
<a href="#">1940085</a>	
<a href="#">4.46.2</a>	
<a href="#">1341165</a>	
<a href="#">3040268</a>	O-RING - 123.4 x 3.53 - 2-249 713.015.001.0040(OEM), Buyer Part : 7130150010040,
	STRIPPER - A-92 102 10/7-N (PERBUNAN)

<a href="#">3544103</a>	713.015.001.0043(OEM), Buyer Part : 7130150010043
<a href="#">3040163</a>	O-RING - 135.8 x 5.33 - 2-356 (PERBUNAN) 713.015.001.0034(OEM), Buyer Part : 7130150010034
<a href="#">Part No.: 1980119</a>	
<a href="#">Part No.: 1946344</a>	
<a href="#">Part No.: 1980226</a>	
<a href="#">1942562</a>	
<a href="#">1980080</a>	Filter element
<a href="#">2656655</a>	magnetic valve
<a href="#">4206553</a>	Spule
<a href="#">2600264</a>	silencer
<a href="#">7608089</a>	
<a href="#">3635419</a>	Seal kit
<a href="#">2656655</a>	magnetic valve
<a href="#">4206553</a>	COIL
<a href="#">4105912</a>	RECEPTACLE
<a href="#">2600264</a>	SOUND ABSORBER
<a href="#">2656655</a>	5/2 WEGE-VENTIL VALVE
<a href="#">4206553</a>	COIL
<a href="#">4105912</a>	RECEPTACLE
<a href="#">2600264</a>	SOUND ABSORBER
<a href="#">2.293.2 200.250.05 DN50</a>	
<a href="#">2.78.2.160.750.08 DN80</a>	
<a href="#">BFD.180.900 DN80</a>	
<a href="#">BFD 140.660 DN50</a>	
<a href="#">Fabr. Nr: 3720366/1 R</a>	Type: 2.293.2 200.250.05 DN50
<a href="#">Fabr. Nr.: 3908305/2B</a>	Filter type: BFD 140.660 DN50
<a href="#">Fbr. Nr:3706337/1 L</a>	2.78.2.160.750.08 DN80
<a href="#">Fabr. Nr:39003332 / 390S332</a>	Type: BFD.180.900 DN80
<a href="#">Spare Parts</a>	
<a href="#">1141289</a>	

<a href="#">7605706</a>	
<a href="#">3040128</a>	O-Ring
<a href="#">1941078</a>	
<a href="#">3040023</a>	O-RING
<a href="#">3140003</a>	Round cord ring
<a href="#">1980085</a>	filter element
<a href="#">1942562-</a>	Sternsieb
<a href="#">1109801</a>	Korbsieb
<a href="#">Type 6.61 Dn200</a>	Fabr.No: 3884059/4A S.N.:22074600001
<a href="#">2.04.5.110.260 DN 50</a>	
<a href="#">2705519</a>	gear m=1.5 / z=50 / b=12
<a href="#">5005528</a>	valve seat 05/10/15
<a href="#">5061823</a>	flushing socket 6.46 / 6.48
<a href="#">5005528</a>	Valve seat
<a href="#">165001-66080</a>	HOUSING, TURBINE
<a href="#">165001-66090</a>	REDUCER
<a href="#">165001-66100</a>	TURBINE
<a href="#">151695-35830</a>	MOUNTING BUSHING
<a href="#">151695-35840</a>	FLUSHING BUSH
<a href="#">165001-66140</a>	SPRING
<a href="#">165001-66310</a>	BOLT
<a href="#">165001-66360</a>	DISC
<a href="#">21-6499</a>	
<a href="#">20405-Dn32-90145</a>	
<a href="#">Duplex Filter For Heavy Fuel Oil With Dn32</a>	SIEHE ANHANG
<a href="#">3038313</a>	
<a href="#">0222384</a>	
<a href="#">14322</a>	
<a href="#">20459014532</a>	

<a href="#">3030062</a>	
<a href="#">2.68.2.355.750.15-Dn150</a>	
<a href="#">0628661</a>	
<a href="#">0222418</a>	
<a href="#">2604886</a>	
<a href="#">171287</a>	
<a href="#">9270-60</a>	
<a href="#">0500002 (Projektnumme:R 4043765/1)</a>	Net weight: 0.952 kg / piece Differential pressure contact gauge
<a href="#">20405-Dn80-170500</a>	
<a href="#">2611123</a>	
<a href="#">Aisi313-100micron</a>	
<a href="#">0628659</a>	
<a href="#">2045909525-Id0229249</a>	
<a href="#">Z39296bl.1-Part64</a>	
<a href="#">2.04.5909525</a>	
<a href="#">1830996</a>	
<a href="#">2610023</a>	
<a href="#">3634510</a>	
<a href="#">661/Gr20</a>	
<a href="#">2.04.5.90.95 Dn 25 (Ex.D50170)</a>	
<a href="#">184/100-L5</a>	
<a href="#">Dn100pn10</a>	
<a href="#">5906594</a>	
<a href="#">2.04.5.110.210-Dn40</a>	
<a href="#">1002824(Exf25my)</a>	
<a href="#">3630049</a>	
<a href="#">3132369</a>	
<a href="#">2529-150</a>	
<a href="#">510d10</a>	
<a href="#">Z39296bl.1-Part10</a>	

[3542193](#)