Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Bühler

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Bühler Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Bühler Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Bühler	24VDC BÜHLER 1.61.050.46801 MAHLO MOTOR
Sample Gas Cooler Rc1.1	Voltage: 230V 50 / 60Hz Heat exchanger: double PVDF Hose connections / thread: metric Peristaltic pump: without Filter: without Humidity sensor: without Status signal: alarm output HC code: 84195080 Weight 15,000 kg
Fl Rd/Be 70w 1761,8	
Fl Sp/Be 70w 1761,8	
2888999	Contact MKS 1 / K (NC or NO contact) 90269000
NV 77-XP-HY-5-MS-2M12/820-2S-KN-KT	Level switch for tank installation Version MS, with float SK604 Ventilation filter Hydac BF 7 with filling protection Connector: 2xM12 4-pin Display and control unit 2 x PNP outputs freely programmable 2 x analog output (4-20mA, 0-10V or 2-10V) Measuring range: 25 to 785mm L = 820mm HC code: 90261089
20-9182	
P/N: 113043	
250 MM, REF : VERDUTEX 40-8020	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
200705090018 4565999	4 INLET-OUTLET EXCHANGER GLASS TUBE
137002500	Pressotronik 700 pressure transmitter Pressure range 0 ... 250 bar Output 4-20 mA, plug connection M12 Operating voltage: 8-33 VDC Max. Ambient temperature +85 ° C Media temperature: -15 .. + 125 ° C Material: 1.4305,1.4571, Al2O3, FPM Burst pressure: 625 bar Connection: G 1 / 4A
4680999	Gas scrubber type 161 PVDF spec. Material: PVDF
Q11008100 44921120102	Peristaltic condensate pump CPsingle-SA-AC Permit: - Voltage: 115V / 230V 50 / 60Hz Housing: Housing version for separate assembly Flow rate / material: Q = 0.3 l / h with Tygon hose (Norprene) A-60-G Connection: angled hose connector -PVDF
Q11009751 1008000	Level switch for tank installation NT M-MS-G3 / 4-M3 / 500-2K Container connection: G 3/4 2 x contact K8 (NC / NO) L = 500mm 2 x K8 at the lowest point NO
NT 63-K-MS-M3/1270	Q11012362 1063000 Level switch tank installation Version MS, with float SK604 PU Resolution: 5mm L = 1270mm / 0 to 100°C = 4-20mA L1 = 25mm (20mA) / L2 = 1235mm (4mA)
EGK 4S 4 CHANNEL GAS COOLER	
SAMPLE GAS COOLER RC1.1 DOUBLE CHANNEL	
SAMPLE GAS COOLER RC1.1 SINGLE CHANNEL	
102509P 254x1,5x32 mm	
SP 04 G/03	63-003-07 230V/50Hz 7,2U/min Norprene hose 3.2x1, 6x126 A-60-G Engine SM 131

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Q11017165 1038000	temperature switch TSM-2-MS-G1/2-M3/280-TM50NO/TM70NC Version brass L = 280mm 1 x thermal contact TMS-50 °C normally open 1 x thermal contact TMÖ-70 °C opener
PT-771-600-1S-K	Q11019084 1377000 display and control unit with attached transmitter 0-600bar Plug connection: M12x1, 4-pin. 1 x PNP - freely programmable output and analogue output (4-20mA, 0-10V or 2-10V) Connection: G1/4, bursting pressure: 900bar Media temperature: -15...+125°C, Ambient temperature: +85°C
137002500	Pressure transmitter Pressotronik 700 Pressure range 0...250 bar Output 4-20 mA, connector M12 Working voltage: 8-33 VDC Max. ambient temperature +85 °C Media temperature: -15..+125°C Material: 1.4305,1.4571,Al2O3,FPM Bursting pressure: 625 bar Connection: G 1/4A
Sortex B	(wie bild)
Q11021962 4596211022600000000000	Sample gas cooler RC1.1 Voltage: 230V 50/60Hz Heat exchanger: double stainless steel Hose Connections/Threads: Metric Peristaltic pump: none Filters: without Humidity sensor: without Signal outputs: status output
Q11022112 44921120101	Peristaltic condensate pump CPsingle-SA-AC Permit: - Voltage: 115V/230V 50/60Hz Housing: Housing version for separate assembly Flow rate/material: Q=0.3 l/h with Tygon tubing (Norprene) A-60-G Connection: Straight hose tail -PVDF
9124030034	Hose for peristaltic pump Q=0.3 l/h Material: Norprene / PVDF
NIVOVENT 21-0-SML 96484-1 LEVEL LIQUIDATOR	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
2150S232 :LIGHT ASSEMBLY DELTA ABRASIMET	
sample gas pump 4228114101100	(Sample Gas Pump P1.1E—Voltaj: 230V—Pompa Kafası: PVDF)
1.13.042.402	
9100110124	Display board ABT400
Q11024699 1064000	Level switch tank installation NT 64-MS-2M12/250-1K-TK70NC Switch tube MS and float SK601 PU 1 x contact (K101) NC/NO 1 x temperature contact TKÖ-70 (70°C opener) L = 250mm L1 at lowest point NO
Q11024879 1008000	Level switch tank installation NT M-MS-G3/4-M3/250-1K-TM70NC Tank connection: G 3/4 1 x contact K8 (opener / closer) Temperature contact TMÖ-70 (70°C opener) L=250mm 1 x K8 at the lowest point NO
MVRS-50031-010	PILOT CONTROL DIAPHRAM EPT 1140
MVRS-83000-810	SHAPE DIAPHRAM EPT 1140
UNN-48004-013	COMPRESSOR SPRING
113042402	1.13.042.402
Q11027102 4228123111200	Sample gas pump P1.1E Voltage: 230V/50Hz Pump head: PVDF with adjustable bypass valve; Head turned 180° Valves up to 70°C Including screw-in fittings DN 4/6 Incl. mounting bracket and anti-vibration set Housing version with 3m connecting cable and on/off switch
Q11029175 44921120101	Peristaltic condensate pump CPsingle-SA-AC Permit: - Voltage: 115V/230V 50/60Hz Housing: Housing version for separate assembly Flow rate/material: Q=0.3 l/h with Tygon tubing (Norprene) A-60-G Connection: Straight hose tail -PVDF v
Q11033791 1083000	Level switch tank structure

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	NS OM-VA-MKS/550 with float SK903 L1 = 550mm including surge protection pipe
2888999	Contact MKS 1/K (opener or closer)
2889999	Contact MKS 1/W (changer) (Reed switch approvals) UL NRNT2 E70063 CSA 3105897
Q11034484 1077000	Level switch for tank installation NV 77-XP-HY-5-MS-2M12/280-2S-KN-KT-VS Version MS, with float SK604 Ventilation filter Hydac BF 7 with filling protection and contamination indicator Connector: 2xM12 4-pin Display and control unit 2 x PNP output freely programmable 2 x analog output (4-20mA, 0-10V or 2-10V) Measuring range: 25 to 245mm L=280mm
Q11034484 1077000	Level switch for tank installation NV 77-XP-HY-5-MS-2M12/370-2S-KN-KT-VS Version MS, with float SK604 Ventilation filter Hydac BF 7 with filling protection and contamination indicator Connector: 2xM12 4-pin Display and control unit 2 x PNP output freely programmable 2 x analog output (4-20mA, 0-10V or 2-10V) Measuring range: 25 to 335mm L=370mm
4501040	Heat exchanger DTV Material PVDF Gas inlets/outlets DN 4/6 Condensate outlets DN 5/8
MKS 1/W (Wechsler) Contact	2889999 (Reed switch approvals) UL NRNT2 E70063 CSA 3105897
Q11036781 1008000	Level switch tank installation NT M-MS-G3/4-M3/250-1K-TM70NC Container connection: G 3/4

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	1 x contact K8 (opener / closer) Temperature contact TMÖ-70 (70°C normally closed) L=250mm 1 x K8 at the lowest point NE
Q11037668 44921120101	Peristaltic condensate pump CPsingle-SA-AC Approval: - Voltage: 115V/230V 50/60Hz Housing: Housing version for separate installation Flow/material: Q=0.3 l/h with Tygon hose (Norprene) A-60-G Connection: Straight hose connector -PVDF
4501040	Heat exchanger DTV Material PVDF Gas inlets/outlets DN 4/6 Condensate outlets DN 5/8
Q11037834 44921120101	Peristaltic condensate pump CPsingle-SA-AC Approval: - Voltage: 115V/230V 50/60Hz Housing: Housing version for separate installation Flow/material: Q=0.3 l/h with Tygon hose (Norprene) A-60-G Connection: Straight hose connector -PVDF
Q11037937 4256113149000	Measuring gas pump P2.3 Voltage: 230V 50/60Hz Pump body: PTFE with adjustable bypass valve Valves: up to 100°C Incl. screw-in fittings PVDF 1/4-1/6 Incl. mounting bracket and rubber-metal buffer
1475299520	Display and control unit NT M-MS-2M12-2K-TT71-2S/520 mounted on level switch Supply voltage: 24V DC Input: Pt100 Output: 2 switching outputs PNP 2 level contacts K8 L=520mm
NS 10/0-AM-LA5-SK166 / 600	Level switch for external installation with float SK166 with pipe socket D = 20mm L1 = 600 mm Output signal 4-20mA / resolution 5mm _____ Note: Change in the type code LA replaces the K in the old designation, this version is 100% identical
Oil Cooler Sensor	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
NT64-MS-M3/370-2K	L=370MM \ MAX.1BAR/80C/24VDC \ L1=270 NO/L2=310 NO
PRESSOTRONIC 700	
NT64-MS-S6/370-3K-KT	L=370MM/0-100C=4-20MA \ L1=170NO/L2=210NO/ L3=250NO
P 1.1E- 220 V	
Wollin SK34B	
D-40880 PT-771-600-1S-K/0-600BAR	
P1.1E	
28 1/min BP8-ATEX	
PKE 4	gas cooler PKE 4; 230V; 50/60 HZ
P1.1 GAS SAMPLİNK BY-PASS	
P1.1 4228114101000	
55319990	Reactor Cartridge type MC for Bünox2+ Item No:55319990)
55319990	MC type converter cartridge for Bünox2+ 1.4571/Granules/Glass fiber/Viton
UXE-26702-031	
V77-XP-HY-5-MS-2M12 /280-2S-KN-KT-VS	DI 16, DC24V
Nt61-Ms-S6 / 320-2w	
Ovt4c-4-0-0-0-14-3-1-00-00-00-14	
4200015-2	
25 2114 20 02 00	
Dts-6	DTS-6 4501023
4202002-5	
25 2070 20 02 00	
Fgf 4w 20017000	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
Lief.-Nr. : 1.61.050.468	Geared motor 24VDC 0.75A; 5000mNm; 7,2rpm max 7000mNm; 7.6 ohms; 6Stufen Translation 377
4220011-1	
4200075-1	
1.13.021.602	DC motor; 24VDC; Ø31mm; round; 0.65A; 11W; 32,0mNm; nN 320rpm; n0 4300 RPM;
BCI24-DM337-101S-4	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.