Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

BULUNAMADI

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

BULUNAMADI Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız BULUNAMADI Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Xcste7311	EN IEC 60947-5-1 AC 15 240 V 1,5 A
M/6025	2-10 BAR.. Cylinder diameter (mm): 25
RHM0550MD701S1 G6100	X Axis Encoder
SWU17-60	Compression springs / flat wire / lacquered, unlacquered / 40% spring deflection / 200° heat resistant
AT051U-D-A F03+F05-N-11DS	
LV2521-08	
3V210-08	
01VS03NC03	
01VS050003	
67-012-01	SOCKET, TESTER TIP #12 - YELLOW
67-016-01	SOCKET, TESTER TIP - #16 - BLUE
67-020-01	SOCKET, TESTER TIP - #20 - RED
67-022-01	SOCKET, TESTER TIP - #22 - BROWN
68-012-01	PIN, TESTER TIP (#12)
68-016-01	PIN, TESTER TIP (#16)
68-020-01	PIN, TESTER TIP (#20)
68-022-01	PIN, TESTER TIP (#22)
67-023-01	SOCKET, TESTER TIP - #23 - BLACK
67-024-01	RETENTION TIP - SOCKET - #24 -

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	FABCO-GO
479-002-057-01	BAL SCREW], FOR ROLLSHOP Z AXIS
F5 filter	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
F/F 1½" diameter valve	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
M/F 1½" 90° elbow	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
Teflon tape roli	instruction manual
metal pre-filtration cage	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
sheets of white micro textile to be folded	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
EN 14420-7 - 80 - AF_EN 10088-1 1.4301(eqv. AISI TP304)_G3 Thread	
Push in Fitting - DN20 acc. to DS (or Equivalent)_Brass w/ Nickel Coating or SS_G3/4 Thread + FF Coupling G3/4xG1	
BGP-10A	olid fuel injection tank 10 l.
A000001	NivoCont RKR 505-1 Vibrating rod level switch for powders and granular solids with stainless steel rod Standard version (+110°C) Process Connection: 1 1/2" BSP Housing: Painted aluminum Sample Length: 50 cm Supply voltage: 20...255V AC/DC Output: SPDT relay
760187187	360 Evolve 1U 24 Port Modular Panel
760092429	GigaSPEED X10D® MGS600 Series Information Outlet, white
CO199K2-08F005	MiNo6A Cat 6A U/UTP Reduced Diameter RJ45 Patch Cord, LS-CM Dual Rated 5ft
CO199K2-08F007	MiNo6A Cat 6A U/UTP Reduced Diameter RJ45 Patch Cord, LS-CM Dual Rated 7ft
CO199K2-08F030	MiNo6A Cat 6A U/UTP Reduced Diameter RJ45 Patch Cord, LS-CM Dual Rated 30ft
K1135.11610100	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
K1135.11608100	
DLS-27N-40-C-PO-G1-E4000	Capacitive level limit switch with non-insulated cable probe for level detection of powder, sand, gravel, cement and liquids. Installation: vertical Maximum electrode length: 6 m Electrical connection: M12-C Parameter setting: 2x potentiometers Supply voltage: 7–36 VDC Output: PNP-PO Process connection: G1" Cable length: E 4000 mm with tension weight Cable diameter: 6 mm Cable insulation: none Housing / sample material: 1.4301 (AISI 304) / 1.4404 (AISI 316L) Housing protection class: IP67 Medium temperature: −40 ... +200 °C Ambient temperature: −20 ... +80 °C Thread temperature: −25 ... +85 °C Suitable for Non-Ex applications
DLS-27N-40-C-PO-G1-E2000	Capacitive level limit switch with non-insulated cable probe for level detection of powder, sand, gravel, cement and liquids. Installation: vertical Maximum electrode length: 6 m Electrical connection: M12-C Parameter setting: 2x potentiometers Supply voltage: 7–36 VDC Output: PNP-PO Process connection: G1" Cable length: E 2000 mm with tension weight Cable diameter: 6 mm Cable insulation: none Housing / sample material: 1.4301 (AISI 304) / 1.4404 (AISI 316L) Housing protection class: IP67 Medium temperature: −40 ... +200 °C Ambient temperature: −20 ... +80 °C Thread temperature: −25 ... +85 °C Suitable for Non-Ex applications
MOTOR PROPELLER HOUSING COVER	
WGE-GG-NBR-150/PD	toff valve, GG25/NBR, DN150, PN10 GG25/stainless steel/NBR, double-acting Nominal diameter: DN150 (flange dimensions according to PN10) Operating pressure: max. 10 bar Control pressure: 6 bar Casing: GG25 Slider blade: stainless steel 1.4307 Housing seat: NBR 3-ply pack:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Actuation: pneumatic actuator, double-acting
WGS-LP-150	2 side protection plates WG, DN150 stainless steel sheet
WGE-GG-NBR-300/PD	Fabric slide valve, GG25/NBR, DN300, PN6 GG25/stainless steel/NBR, double-acting Nominal diameter: DN300 (flange dimensions according to PN10) Operating pressure: max. 6 bar Control pressure: 6 bar Casing: GG25 Slider blade: stainless steel 1.4307 Housing seat: NBR 3-ply pack: 1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Actuation: pneumatic actuator, double-acting
WGS-LP-300	2 side protection plates WG, DN300 stainless steel sheet
WGE-GG-NBR-200/MW	Cloth slider, GG25/NBR, DN200, PN8 Housing: GG25, Slide blade: Stainless steel As an intermediate flange fitting with a non-rising spindle. Nominal diameter: DN200 (flange dimensions PN10) Operating pressure: max. 8 bar Casing: GG25 Slider blade: stainless steel 1.4307 Spindle: Stainless steel 1.4305 Housing seat: NBR 3-ply pack: 1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Operation: Handwheel
WGE-GG-NBR-125/MW	Cloth slider, GG25/NBR, DN125, PN10 Housing: GG25, Slide blade: Stainless steel As an intermediate flange fitting with a non-rising spindle. Nominal diameter: DN125 (flange dimensions) (according to PN10) Operating pressure: max. 10 bar Casing: GG25

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Slider blade: stainless steel 1.4307 Spindle: Stainless steel 1.4305 Housing seat: NBR 3-ply pack: 1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Operation: Handra
Ball Valve - AISI 316 - 1" BSP	
Ball Valve - AISI 316 - 3/4" BSP	
ROJ CHRONO X3 WEFT FEEDER	
ROJ CHRONO X3 PANEL	56C00616 V/400, A/0.95, HZ 50-60
CCH152CD1 0417 Oil Filter	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.