

## BULUNAMADI

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**BULUNAMADI** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız BULUNAMADI T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Xcste7311</a>	EN IEC 60947-5-1 AC 15 240 V 1,5 A
<a href="#">M/6025</a>	2-10 BAR.. Cylinder diameter (mm): 25
<a href="#">RHM0550MD701S1 G6100</a>	X Axis Encoder
<a href="#">SWU17-60</a>	Compression springs / flat wire / lacquered, unlacquered / 40% spring deflection / 200° heat resistant
<a href="#">AT051U-D-A F03+F05-N-11DS</a>	
<a href="#">LV2521-08</a>	
<a href="#">3V210-08</a>	
<a href="#">01VS03NC03</a>	
<a href="#">01VS050003</a>	
<a href="#">67-012-01</a>	SOCKET, TESTER TIP #12 - YELLOW
<a href="#">67-016-01</a>	SOCKET, TESTER TIP - #16 - BLUE

## BULUNAMADI

YURSAT yedek par¼a tedariki yapan bir Őirkettir. Sitemizde bulunan markaların yetkili distrib¼t¼r¼ yada temsilcisi deĐildir.

<a href="#">67-020-01</a>	SOCKET, TESTER TIP - #20 - RED
<a href="#">67-022-01</a>	SOCKET, TESTER TIP - #22 - BROWN
<a href="#">68-012-01</a>	PIN, TESTER TIP (#12)
<a href="#">68-016-01</a>	PIN, TESTER TIP (#16)
<a href="#">68-020-01</a>	PIN, TESTER TIP (#20)
<a href="#">68-022-01</a>	PIN, TESTER TIP (#22)
<a href="#">67-023-01</a>	SOCKET, TESTER TIP - #23 - BLACK
<a href="#">67-024-01</a>	RETENTION TIP - SOCKET - #24 - FABCO-GO
<a href="#">479-002-057-01</a>	BAL SCREW ], FOR ROLLSHOP Z AXIS
<a href="#">F5 filter</a>	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
<a href="#">F/F 1½" diameter valve</a>	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
<a href="#">M/F 1½" 90° elbow</a>	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
<a href="#">Teflon tape roli</a>	instruction manual
<a href="#">metal pre-filtration cage</a>	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
<a href="#">sheets of white micro textile to be folded</a>	Kit PETRO-PIT® 410 Complete hydrocarbon filtration system
<a href="#">EN 14420-7 - 80 - AF EN 10088-1 1.4301(eqv. AISI TP304) G3 Thread</a>	
<a href="#">Push in Fitting - DN20 acc. to DS (or Equivalent) Brass w/ Nickel Coating or SS G3/4 Thread + FF Coupling G3/4xG1</a>	
<a href="#">BGP-10A</a>	olid fuel injection tank 10 l.
<a href="#">A000001</a>	NivoCont RKR 505-1 Vibrating rod level switch for powders and granular solids with stainless steel rod Standard version (+110°C) Process Connection: 1 1/2" BSP Housing: Painted aluminum Sample Length: 50 cm Supply voltage: 20...255V AC/DC Output: SPDT relay
<a href="#">760187187</a>	360 Evolve 1U 24 Port Modular Panel
<a href="#">760092429</a>	GigaSPEED X10D® MGS600 Series Information Outlet, white
<a href="#">CO199K2-08F005</a>	MiNo6A Cat 6A U/UTP Reduced Diameter RJ45 Patch Cord, LS-CM Dual Rated 5ft
<a href="#">CO199K2-08F007</a>	MiNo6A Cat 6A U/UTP Reduced Diameter RJ45 Patch Cord, LS-CM Dual Rated 7ft
<a href="#">CO199K2-08F030</a>	MiNo6A Cat 6A U/UTP Reduced Diameter RJ45 Patch Cord, LS-CM Dual Rated 30ft
<a href="#">K1135.11610100</a>	

<a href="#">K1135.11608100</a>	
<a href="#">DLS-27N-40-C-PO-G1-E4000</a>	Capacitive level limit switch with non-insulated cable probe for level detection of powder, sand, gravel, cement and liquids. Installation: vertical Maximum electrode length: 6 m Electrical connection: M12-C Parameter setting: 2x potentiometers Supply voltage: 7-36 VDC Output: PNP-PO Process connection: G1" Cable length: E 4000 mm with tension weight Cable diameter: 6 mm Cable insulation: none Housing / sample material: 1.4301 (AISI 304) / 1.4404 (AISI 316L) Housing protection class: IP67 Medium temperature: -40 ... +200 °C Ambient temperature: -20 ... +80 °C Thread temperature: -25 ... +85 °C Suitable for Non-Ex applications
<a href="#">DLS-27N-40-C-PO-G1-E2000</a>	Capacitive level limit switch with non-insulated cable probe for level detection of powder, sand, gravel, cement and liquids. Installation: vertical Maximum electrode length: 6 m Electrical connection: M12-C Parameter setting: 2x potentiometers Supply voltage: 7-36 VDC Output: PNP-PO Process connection: G1" Cable length: E 2000 mm with tension weight Cable diameter: 6 mm Cable insulation: none Housing / sample material: 1.4301 (AISI 304) / 1.4404 (AISI 316L) Housing protection class: IP67 Medium temperature: -40 ... +200 °C Ambient temperature: -20 ... +80 °C Thread temperature: -25 ... +85 °C Suitable for Non-Ex applications
<a href="#">MOTOR PROPELLER HOUSING COVER</a>	
<a href="#">WGE-GG-NBR-150/PD</a>	toff valve, GG25/NBR, DN150, PN10 GG25/stainless steel/NBR, double-acting Nominal diameter: DN150 (flange dimensions according to PN10) Operating pressure: max. 10 bar Control pressure: 6 bar Casing: GG25 Slider blade: stainless steel 1.4307 Housing seat: NBR 3-ply pack: 1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Actuation: pneumatic actuator, double-acting
<a href="#">WGS-LP-150</a>	2 side protection plates WG, DN150 stainless steel sheet
<a href="#">WGE-GG-NBR-300/PD</a>	Fabric slide valve, GG25/NBR, DN300, PN6 GG25/stainless steel/NBR, double-acting Nominal diameter: DN300 (flange dimensions according to PN10) Operating pressure: max. 6 bar Control pressure: 6 bar Casing: GG25 Slider blade: stainless steel 1.4307 Housing seat: NBR 3-ply pack: 1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Actuation: pneumatic actuator, double-acting
<a href="#">WGS-LP-300</a>	2 side protection plates WG, DN300 stainless steel sheet
<a href="#">WGE-GG-NBR-200/MW</a>	Cloth slider, GG25/NBR, DN200, PN8 Housing: GG25, Slide blade: Stainless steel As an intermediate flange fitting with a non-rising spindle. Nominal diameter: DN200 (flange dimensions PN10) Operating pressure: max. 8 bar Casing: GG25 Slider blade: stainless steel 1.4307 Spindle: Stainless steel 1.4305 Housing seat: NBR 3-ply pack: 1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Operation: Handwheel

[WGE-GG-NBR-125/MW](#)

Cloth slider, GG25/NBR, DN125, PN10 Housing: GG25, Slide blade: Stainless steel As an intermediate flange fitting with a non-rising spindle. Nominal diameter: DN125 (flange dimensions) (according to PN10) Operating pressure: max. 10 bar Casing: GG25 Slider blade: stainless steel 1.4307 Spindle: Stainless steel 1.4305 Housing seat: NBR 3-ply pack: 1x GFO® - Fiber ² TWARON® edge-reinforced 1x NBR O-ring 1x synthetic fiber, PTFE-impregnated Operation: Handra

[Ball Valve - AISI 316 - 1" BSP](#)

[Ball Valve - AISI 316 - 3/4" BSP](#)

[ROJ CHRONO X3 WEFT FEEDER](#)

[ROJ CHRONO X3 PANEL](#)

56C00616 V/400, A/0.95, HZ 50-60

[CCH152CD1 0417 Oil Filter](#)