

Busch

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Busch** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Busch T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
R 5 RA 0063 F 503 GMXG	1.5kW ; 3x230 / 400V +/- 10% ; 50Hz ; 1500 rpm ; IE3 Bg.90L ; B14-160 ; IP55 ; Iso.Kl.F 6 terminals D / Y, delivery condition is Y connection Gas ballast ##### Please note that rotary vane vacuum pumps of the R5 For transport reasons, generally delivered without oil filling will. Upon request, we will be happy to provide the vacuum pump oil for the delivery for the first oil filling of the pump (s) against calculation. #####
0992525287	Maintenance kit R 5 0165/0205/0255/0305 D.
0945000409	Sieve insert R 5 HO Type 0250
0916529297	Complete exhaust valve Execution 0.1hPa Customs tariff number: 84149000 Country of origin: CH Net weight: 0.09 kg
0722516729	Slider 220 x 52 x 5.9 Aerodur Selenium / EGS core
0520513440	Cooler without turbulence conversions d310 / d'220 x 75 aluminum Net weight 2,397 kg Customs tariff number 84149000
0397556447	Fan cover EN AW -1050A H24
0532140160	Air duct element with sound absorber insert d72 x 500 Net weight: 0.507 kg Customs tariff number: 84213925
0532140157	Air duct element individually packed d72 x 250 with sound absorber insert

0722516729	slider 220x52x5.9 Aerodur Selenium/EGS core
level switch	Article No. 0652563748 HLS-T / O-ring seal KSR horizontal float switch HLS-T Float 35mm Material: stainless steel 1.4435 Electrical connection: M12 / 4-pin connector Process connection: G 3/4 " Zn. 204368 Switch contact level: opener, max. 230VAC 0.5A / max. 100VDC 0.5A Switch contacts temperature: normally closed, max. 250VAC 2.5A / max. 250VDC 1.5A Temp. -10°C ... +140°C S.G. 840kg/m ³ Pressure: 1.0 bar Switching functions: 1st level 2. Temperature switch 110°C 3.Temp PIN assignment Pin 1 : common power supply common line of all switching functions Pin 2 : Temperature switch 110 °C Pin 3 : temperature switch 130 °C Pin 4 : Level switch
R5-RB/RC 0006 C	VACUUM PUMP
0531000002	oil filter 3/4 - 16 UNF, d76 x 79
SV 1025	
R5 RA 0063 F 4R3 GMZZ	1111151238 1.5kW; 3x230/400V +/-10%; 50Hz; 1500rpm; IE3 Bg.90L; B14-160; IP55; Iso.Kl.F 6 terminals D/Y, delivery condition is Y connection oil return valve suction side: Suction flange G1 1/4 vertical Air filter 0063 paper, upright reducing nipple Hose nipple LW32 Exhaust side: Exhaust cover silencer Sight glass G3/4 curved gas ballast Oil Busch VM 100 Paint RAL 7016 "Standard"
R5 RA 0305 D 5A3 DMZT	1111204020 + Nominal suction capacity: 300.0 m ³ /h + Final pressure: 0.500 hPa (mbar) + Net weight: 250.0 kg Engine: + Standardization (certification): IEC + Coupling for engine: B5-300/d38x80/3~ + phase: 3~ + Voltage at 50 Hz: 400/690 V + Rated motor power at 50 Hz: 8,300 kW + Rated motor speed at 50 Hz: 1,500 rpm + Motor flange: B5 / 300 + Motor efficiency: IE3 + IP protection class: IP55 + Insulation class: F (155°C) Options: + Theme option: Aqua + Sealing material: fluorine rubber (FKM) + Large gas ballast valve that can be shut off + Suction connection: G 2 vertical + Inlet filter type: filter 0250 polyester G 2½ + Filter orientation: horizontal 0°; inlet 0° + Inlet accessories: hose nipple LW60 and ball valve + Exhaust air connection: exhaust air cover G 2 + Installation: anti-vibration buffer + Cooling system: air cooling + Type of oil (rating plate): VSC 100 synthetic oil + Delivery condition: with oil filling + with temperature switch + Slider material: selenium + with post-separator + Paintwork: anthracite gray (RAL 7016) / standard + Designation (rating plate): RA 0305 D 5A3
Mink MM 1252 AV	
0532121864	Filter cartridge 0250 Polyester, food grade
0532121864	Filter cartridge 0250 Polyester, food grade
R5 Ra 0302 D	
r5 ra 0040 f	
1342162241	MINK MM 1322 A V08 VJXX 6.0kW; 3x190-200/380-400V; 50Hz; 3000rpm; IE3 8.0kW; 3x208/230/460V; 60Hz; 3600rpm; IE3 8.0kW; 3x208/230/460V +/-10%; 60Hz; 3600rpm 8.0kW; 3x220/440V; 60Hz; 3600rpm; IE3 8.0kW; 3x200/400V; 60Hz; 3600rpm; IE2 Bg.132S; B5-300; IP55; Iso.Kl.F 9 terminals YY/Y, delivery condition is Y-circuit 3x PTC thermistor temperature sensor Motor cURus certified Suction side: Suction connection G2 inside Check valve Vacuum limiting valve (150mbar) - under 200mbar not suitable for continuous operation - Pressure side: Integrated silencer Gas outlet R1 1/4 outside
0512000016	Coupling sleeve I 80 Mounted with retaining rings Old material no.: 512.016.00
2000104426	VACTEST TRP 900 + calibration Mobile measuring device TRP 900 Measuring principle: Piezoresistive Measuring range: 1600 to 1mbar USB interface DN16 KF with G1/4 internal thread + Factory calibration of vacuum measuring device 4 reference points per pressure decade, 1000

	to 1e-4mbar
R5 RA0063 F	
NEW LIP SEAL	
GAUGE WATCHDOG OILER/ SIGHT GLASS	
V532140159	air filter element with silencer* air filter element with silencer* d72 x 375 Like 0532140159 However, individually packed in a box
0531000001 / Oelfilter	oil filter 3/4-16UNF / d93 x 142 Oil filter including packaging with Busch logo Old material number: 531.001.00
V532140160	air filter element with silencer* air filter element with silencer* d72 x 500 Like 0532140160 However, individually packed in a box
0531000005 / Oelfilter	oil filter 1-12UNF / d93 x 210 Type W 962 Oil filter including packaging with Busch logo M+H
0532000006	filter cartridge 0630 paper 0532 000 006
0532121865	filter cartridge 0630 Polyester, food grade PES Separation efficiency 99% at 10µ particle size Dimensions: HT=195+1/-2mm; OD=254mm; ID=195mm Washable With marking of the article number and Busch logo O2 up to 40°C/2 bar, BAM II-3654/2002-II
0532 121 863	filter cartridge 0100 Polyester food safe Separation efficiency 99% at 10µm particle size Washable
V531000002	Oil filter d76 x 79 packed oil filter 3/4 - 16 UNF, d76 x 79 color black
V532140159	Air extraction element with silencer* d72 x 375 Like 0532140159
0992573694 / Maintenance kit RD 0200-0360 A	Maintenance kit RD 0200-0360 A filter system Consisting of: 0010 0486000513 O-ring 36 x 2.5 1 PC 0020 0486000505 O-ring 22 x 2 1 PC 0030 V531000002 Oil filter 1 PC 0040 0532571826 Exhaust filter with Coanda endcap d130 x 459 1 PC 0050 0486000501 O-ring 15 x 2 2 PC 0060 0850201143 Folded carton service kit for R5 RD 576 x 150 x 150 within 1 PC
R5 RA 0063 F 403 GMXG	1111162450 Rotary vane vacuum pump Busch R5 RA 0063 F 403 GMXG • Nominal suction capacity: 63.0 m ³ /h • Final pressure: 1,500 hPa (mbar) Motor: • Standardization (certification): IEC • Coupling for motor: B14-160/d24x50/3~ • Phase: 3~ • Voltage at 50 Hz: 230/400 V • Rated motor power at 50 Hz: 1,500 kW • Rated motor speed at 50 Hz: 1,500 rpm • Motor flange: B14 / 160 • Motor efficiency: IE3 • IP protection class: IP55 • Insulation class: F (155°C) Options: • Sealing material: Fluororubber (FKM) • Gas ballast valve • Suction connection: G 1¼ vertical • Exhaust air connection: Exhaust air cover G 1¼ • Installation: Vibration metal buffer • Cooling system: Air cooling • Oil type (type plate): VM 100 mineral oil • Delivery condition: without oil filling • Paint finish: Anthracite grey (RAL 7016) standard • Designation (type plate): RA 0063 F 403 Old material no.: 1111162450
1111140741 / R5 RA 0063 F 403 TCXZ	Rotary vane vacuum pump Busch R5 RA 0063 F 403 TCXZ • Nominal suction capacity: 76.0 m ³ /h • Final pressure: 1,500 hPa (mbar) Motor: • Standardization (certification): IEC (cURus) • Coupling for motor: B14-160/d28x60/3~/d25 • Phase: 3~ • Voltage at 50 Hz: 190-200 V 380-400V • Rated motor power at 50 Hz: 2,000 kW • Rated motor speed at 50 Hz: 1,500 rpm • Voltage at 60 Hz: 208-230 V 440-460 V • Rated motor power at 60 Hz: 2,400 kW • Rated motor speed at 60 Hz: 1,800 rpm • Motor flange: B14 / 160 • Motor efficiency: IE3 (IE2) • IP protection class: IP55 • Insulation class: F (155°C) • Motor protection: 3xPTC thermistor temperature sensors Options: • Sealing material: Fluororubber (FKM) • Gas ballast valve • Suction connection: G 1¼ vertical • Exhaust air connection: G 1¼ and blind cover • Installation: Vibration metal buffer • Cooling system: Air cooling • Oil type (type plate): VM 100 mineral oil • Delivery condition: without oil filling • Service cover: Standard service cover with oil drain tap • Paint finish:

	Anthracite grey (RAL 7016) standard • Designation (type plate): RA 0063 F 403 Old material no.: 1111140741 Net weight: 85,000 KG
SAMOS SI 0320 E1	2.2KW
V531000002	V531000002 / Oil filter d76 x 79 packaged oil filter 3/4 - 16 UNF, d76 x 79 color black
R5RA 0063 F	63m ³ vacuum pump
Mm 1322 Av	
Rc0100.E506.1001	PUMP TYPE RC 0100
Ra 0250/0302 D Standard	
Felt For Type: Ra 0063 F 503	
092200001	
0831000100	
0532000034	
Rc0063-E-503	VACUUM PUMP 3HP 3PHASE 230/460V RC SERIES
Ra0040	PUMP
993516590	
0532-000-508	
Ra 0250d	
0532.140.156	
0362524302	
Ve 101	
Mm 1252 A V	
0486000590	
Ra 0016 C + Inlet Filter	
0537524514	
1111922106ra004f	PUMP
0831000099	
0540 000 004	
0532140159 (431919g11)	
8212286.805002400	
0530000003	
0486.000.549	
532.006.00	
0473106433	
Sb0530 D Oho Uj Xx	
Oil Filter For Ra 0302 D 563 Dlxz	

0532.140.159	
Kb-0016-E300	VACUUM PUMP 3600RPM 3/4HP 1.5TORR
0724000587	
0532.121.864	
0532-000-512	
0532.140.160	
7001	
Overhaul Kit Mm11-Av, P/N 0993128311	
0534000041	Sieb kegelig mw 0,50 d 0,24 d74,4 x h50 A4
0532140157	
Se 0905 D	
0531000002	
0722.516.729	
Ra0063 F	
Part107-8493635	
Re 0016 B	
993106213	
Ra0100f	
0722106274	
0990115018	
Gu 8fx185101-611	
0532.140.157	
532.002.00	
0990542292	
0990516591 Ra 0250/0302 D Standard	
Ra0100f503	
0532121863	
Sv1100.C003	PUMP 230/460V
Rb-0021-S015-1002	VACUUM PUMP 3PH 230/460V
R5-0025f	
411 0012	
V0722000455	
423077/Dyzz/Mk	
0531.000.002	
Ra0025f	
Ra 165 D 5	

Sv 1025 B 000 1kxxx	
Sb 0310 D Oho Uh 1321131665	
0532140159 Ersetzt Die Alte Art.Nr. 0532 000 508	
R5-Ra 0302 D	
0520513156	
Oil Filter For Ra 0100 F 503	
0532141267	
Sv1025 C000 1kxx No Co136000486	
D8f2-8-096	
Rc0063-E506-1101	VACUUM PUMP 3HP 230/460V 60Z 3PHASE
Sv1025.C000.1kxx	VACUUM PUMP 3PHASE
Sv1025.B000.1kzz	VACUUM PUMP 3.3AMP 200-480V 50/60HZ 1740RPM
Sb 0530 D 0h0 Uj Xx	
0992516595	
0534 000 018	
Rb 0021 C	
Ra 0040 F	
R5 100	
0916.529.297	
Rc0063-E506-1001	VACUUM PUMP 3HP 3PHASE 230/460V RC SERIES
Mm1252 Av	
0532140159 (460082e12)	
0525513155	
0532140156 (Ex 0532000512)	
0990000250	
0460 513 160	
Typ 0250 G2 1/2 / G2 1/2	air filter
8497792.9655	
532140156	
532140160	
0532000031	
0722000360	
0525 513 155	
0486000505	
0583000001	

1.827.231.016	
1111922210	PUMP
Ra0063f50611x2	VACUUM PUMP-1111.922.210
8205700.0201	
1111922104	PUMP
Ra 0063 F+ Inlet Filter	
722533535	
0722-516-729	
993000195	
R5 160-305	
Cb 0250 B	
0532000004	
Ra0025.E5z6.1001	VACUUM PUMP 3PH 1.5HP 1740RPM 230/460V 60HZ
Mink Mm 1252 Av	
0532000002	
1111922004	PUMP
Mm 1252 A Vv3	
0520 513 156	
0916 143 238 Unknown Part Number	
Sv1025.C000.Ikvx	VACUUM PUMP 3PHASE
Output Filter For Wv 1000 C 0h1	
437.080.00	
Ra0063e	
8209200.9178	
0524121854-Pos321	
0831122572 Iso Vg100	
0990.516.591	
Sb-0530-D-0a0-Uj-11	MOTOR DRIVEN PUMP 23A 5.5KW 200/240VAC 50/60HZ
R5 0160-0305	
0531.000.001	
R5 0160-305	
Ra-0025-E5z6-1006	VACUUM PUMP .5TORR DISPLACEMENT 20CFM
0532-000-509	
1111922209	PUMP
0223524313	

Sb0530d-0h0-Ui-Xx	MOTOR DRIVEN PUMP 2915/MIN 16.4A 220-240V 9.50A
M1322aa8000mk	
0532000507	
Sv 1063 B	
0473000009	
0831128556	
Ra0302d	
487000012	
0487000032	
Mm1144bv	
Nc2000mvdyyxf	
Sv 1040 C Flow 40m Å179; / H 120mbar 1.25 Kw 346-420/200-242 V 50 Hz	
Air Filter For Busca R5 Ra02 02 D	
Kc 0010 D, P 20 Hpa (Mbar)	
R5 160-0250	
0524 108 653	
993106212	
Mink Mm 1144 Av	
0524509237	
Ra0063.F503.Gmzz	
0916 126 769	
Part108-8493635	
Mi1502 Bv	
Ra 0100 F (Ex Ra0100f5r3)	
R5 160-302	
0530000005	
1111145352	
Output Filter For Ra 0100 F 503	
Output Filter For Ra 0302 D 563 Dlxz	
Rc0100e	
Ra0040f(Ex, R-Rc0040)	
Vmh 100 Iso Vg	
Rc0040-E506-1001	VACUUM PUMP 3PH 230/400V 50HZ 1.1KW
Ra-0630.B4z6.1001	VACUUM PUMP 25HP SINGLE STATE
993506181	
Ra0063.F506.11xx	

0990106211	
080038660	
Vh1025c	
Rb0021 C	
Ra 160/202d	
Ra 0063 F 503 G(Obsoete By Ra0063.F506.11xg)	
0512135941	
Vm032	
0472-000-008	
0473507139	
V532140157	V532140157 / Air reservoir element with silencer Air cylinder element with sound dampener* d72 x 250 Like 0532140157 However, individually packaged in a carton
Typ Sv 1025 C 000 Ikxx	
N002500000	
Rc 0063 E 5z1	
Oil Filter For Wv 1000 C 0h1	
Sv1016c000 Ihxx	
0532119814	
Ra 0302 D	
1111922109	PUMP
Mm1202-Av-Aqua	VACUUM PUMP 50/60HZ
0945000	
Ra0165.D506.1001	VACUUM PUMP
Oil Filter For Busca R5 Ra02 02 D	
Mm1202	PART
0993516590	
Ra 0040 F 503	
Sv1016c000 Iixx	
0722000016	
Ra-0100-F-503	VACUUM PUMP 100M3H 50HZ
0831000059	
R-5 1600 M3/H	
Mm-1104-Av	VACUUM PUMP MINK 62-75M3/HR .06BAR 60HPA
0025-0055 C/E/F	
Ra0063.F506.11xg	

Ra0255d	
Direct European Model: 1113147644	
Sb 530 D Oho Uj Xx	
0540 000 001	
Ra 0040 F Flow 63mã179;/H 0,1mbar (0,07mbar) 1,1kw 3x230-400v 50hz	
Ra0040f5z611xx	PUMP
0722000455	
Mm 1322 A V Aqua	
0480.000.134	
0821108187	
Ra 0100 F	
Iso Vg 100	
Rc 00 63 E502	
Claw (Outlet) Mm 1252 Av	
Ra 0630 B 4z1 Zzzz	
R5 0160 D	
Kb0016e300	
Typ 0250	Air filter G2 1/2 / G2 1/2 Type 0250, suitable for food Polyester insert Net weight: 4.6 kg Customs tariff number: 84213920
Se0170c	
Ra-0025-E506-1001	VACUUM PUMP 1.5HP 20CFM 230/460V
532140157	
0722000489	
0992000009	SERVICE KIT R 5 0400/0630 B/C
1351108411of	
Ra 0025 F Z03	
0480.000.128	
Mm 1320 A V08	
0543138026	
Rc0040-E	VACUUM PUMP SINGLE STAGE ROTARY VANE
0532140154	
Oil Separator For Busca R5 Ra02 02 D	
N002000000	
993506360	
Ra0255	

Sb0200dohouexx	
Si 0320 E 1ho Zz	
0532000003	
0437.534.364	
Ra 0160 D	
Mm 1102 B V	
54503401	GAUGE
0722.000.454	
1111922237	VACUUM PUMP
0531.000.005	
0992106214	
414554a11	
Sv 1040 C 000 Inxx	
0532140156	
Ra 0250 D501	
8240600.024c 2/2 Dn40 (1\1/2)	
532.003.00	
99304501	KIT
Nc 0400 B	
0532140159	
0722522486	
0532141269	
0532.903.299	
Ra0202d	
Ra 0255 D	
Mm 1252 A P	
Cb 220 C	
P/Sv10-40 C	
993000225	