

Calpeda

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Calpeda** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Calpeda T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
16001612000	For NM50 / 160B, # 2018007173 Mechanical seal 32 mm, Tungsten carbide / tungsten carbide / FPM, type R2 with reduced sliding surfaces and Anti-rotation groove, item 36.00
14002680000 (Optional)	O-ring for sealing cover, FPM, item 42.04
30300310001 (Optional)	Seal cover with anti-rotation pin, pos. 42.00
14002150000 (Optional)	Housing seal in FPM, item 14.20
CTM 61/A.	Peripheral pump in block design, 0.33 kW, 230 V, 50 Hz, IP 54, 2900 rpm, Mechanical seal: carbon / ceramic / NBR
EJ 21-N100-250 B/A - NG 7/16/B.	Fire extinguishing system, with two standard pumps N 100-250B / A and a Jokey pump NG 7/16 / B, DN125x250 reductions on the suction side, DN250 check valves, on common Base plate, pre-piped with control systems for Main and jockey pump
TP 100/B.	Peripheral pump, 2.2 kW, 230/400 volts, 50 Hz, IP54, 2900 rpm, mechanical seal: Carbon / ceramic / NBR
MXSM 503	multi-stage submersible pump made of stainless steel, 0.55 kW, 230 volts, 50 Hz, AC, Connection cable 15 m H07RN-F
MXSM 504	multi-stage submersible pump made of stainless steel, 0.9 kW, 230 volts, 50 Hz, AC, Connection cable 15 m H07RN-F and plug
MXHM 202E	62310021000 multi-stage centrifugal pump made of stainless steel, 0.33 kW, 230 V, 50 Hz, IP54, 2900 rpm, Mechanical seal: carbon/ceramic/EPDM

MXHM 204/A	
14002600000	O-ring NBR, item 14.20, (CA80, NCA80, TP 80, TP 78, NTP78), (MXA = Pos. 22.16) CA 80E S/N: 2016036487
NM 25/12B-60/A.	Close-coupled centrifugal pump, 0.55 kW, 254/440 volts, 60 Hz, IP 54, 3,450 rpm, Mechanical seal: carbon/ceramic/NBR
TP 80E	Peripheral wheel pump, 0.75 kW, 230/400 volts, 50 Hz, IP54, 2900 rpm, mechanical seal: Carbon/ceramic/FPM, body seal FPM
70M00431000	NR 50C/B Inline pump, single-stage, close-coupled, 0.75 kW, 230/400 V, 50 Hz, IP 54, 2900 rpm, Mechanical seal: carbon/ceramic/NBR
MXHM 202E	multi-stage centrifugal pump made of stainless steel, 0.25 kW, 230 V, 50 Hz, IP54, 2900 rpm, Mechanical seal: carbon/ceramic/EPDM
MXV-B 40-804/1,5 KW	
CTM61/A	Close-coupled peripheral wheel pump, 0.33 kW, 230 V, 50 Hz, IP 54, 2900 rpm, Mechanical seal: carbon/ceramic/NBR
MXH 805/B	62252051000 horizontal multistage centrifugal pump, in Block design, made of stainless steel AISI-304, 1.8 kW, 230/400 volts, 50 Hz, IP54, IE-3, 2900 rpm, Mechanical seal: carbon/ceramic/EPDM
B-TM 65E-R	71120030001 Bronze peripheral pump, 0.45 kW, 230 volts 50 Hz + 220 volts 60 Hz, iso. class F, 2900/3450 rpm, mechanical seal: silicon carbide/silicon carbide/FPM, Housing seal made of FPM, optimized impeller
Varied Pump PERIPHERAL PUMP,[TM 65E-R	230V,0.48~3.0M3/H,Head:8-44M,0.45kW,2900rpm,FOR GAMMA GAUGE, #3ZRM
NM 50/12A/C.	60400923000 Close-coupled centrifugal pump, 4 kW, 400/690 V, 50 Hz, IP 54, 2900 rpm, mechanical seal: carbon/ceramic/NBR
A 50-125B/A.	60F00862000 self-priming drainage pump open impeller, 1.1 kW, 230/400 V, 50 Hz, IP 54, 2900 rpm, mechanical seal: carbon/ceramic/NBR
MXV 50-1506	53380621000 vertical multistage centrifugal pump made of stainless steel AISI304, hydraulics for 5.5 kW motor, 2900 rpm Mechanical seal: tungsten carbide/carbon/EPDM
14001890000	NBR housing seal, item 14.20
16006080000	Mechanical seal 32 mm, carbon/ceramic/NBR, item 36.00
70220010008	CT61/A, Peripheral wheel pump in block design, 0.33 kW, 230/400 volts, 50 Hz, IP 54, 2900 1/min, Standard version with Mechanical seal: carbon/ceramic/NBR, Switch-on type S3-60%
MXVL 80-4806/D	vertical, multi-stage centrifugal pump AISI-316 stainless steel, in-line design, 15 kW, 400/690 volts, 50 Hz, 2900 1/min, IP55, IE-3, with Mechanical seal: tungsten carbide/carbon/EPDM, with flange connections DN 80 Item number 55450621L00
NCS3 20-70/130	Hot water circulation pump, 230V, 50 Hz, IP 44, insulation class H, bronze housing, 130 mm installation length
A 50-125B/A	60F00862000 self-priming dirty water pump with open impeller, 1.1 kW, 230/400 V, 50 Hz, IP 54, 2900 1/min, mechanical seal: Carbon/ceramic/NBR
T 65E	Peripheral wheel pump, 0.45 kW, 230/400 V, 50 Hz, IP 54, 2900 1/min, mechanical seal: Carbon/ceramic/NBR
	CTM 61/A, Peripheral impeller pump in block design, 0.33 kW, 230 volts,

70320011000	50 Hz, IP54, single phase, IP 54, IE-2, 2900 rpm, standard version with Mechanical seal: carbon/ceramic/NBR
A 65-150 A/C	
72B51040000	NGXM 4/110, self-priming centrifugal pump made of stainless steel, 0.75 kW, 230 volts, 50 Hz, single-phase, 2900 rpm, IP54, mechanical seal: carbon/ceramic/NBR
14002290000	Housing seal, item 14.20
16006670000	Mechanical seal 12 mm, tungsten carbide/carbon/FPM, item 36.00
14003090000	Splash ring Pos. 46.00
14001190000	Rolling bearings, item 73.00, & 81.00
B-CM 22/1/A-R, (71710060054)	Centrifugal pump with open impeller, 0.45 kW, 2900 rpm, 230 volts, 50 Hz, special version with mechanical seal: WC/carbon/FPM and with optimized bronze impeller
NM 40/20B/A	Centrifugal pump in close-coupled design, made of GG, 5.5 kW, 400/690 volts, 50 Hz, IP 54, 2900 1/min, Standard version with mechanical seal: Carbon/Ceramic/NBR
NRC100-160/15	
CTM 61/A	70320011000 Peripheral impeller pump in block design, 0.33 kW, 230 Volt, 50 Hz, IP54, single-phase, IP 54, IE-2, 2900 1/min, standard version with mechanical seal: carbon/ceramic/NBR
70MA0200000	NR 40/125C, single-stage centrifugal pump in block design, Inline design, 0.75 kW, 230/400 Volt, 50 Hz, 2900 1/min., IP54, standard version with Mechanical seal: carbon/ceramic/NBR
14001820000	Housing seal in NBR, Pos. 14.20
14001230000	rolling bearing, item 73.00
14001210000	rolling bearing, item 81.00
61F01643000	BA 65-150A/B Self-priming dirty water pump Bronze with open impeller, 4 kW, 400/690 V, 50 Hz, IP 54, 2900 1/min, mechanical seal: carbon/ceramic/NBR
61F01643000- BA 65-150A/B,	BA 65-150A/B, Self-priming dirty water pump Bronze with open impeller, 4 kW, 400/690 V, 50 Hz, IP 54, 2900 1/min, mechanical seal: carbon/ceramic/NBR
Single Pump Hydrophore (Excluding Panel)	QMax/Min-15/44 m3/h HMax/Min-51/25,5 m 5,5 kw (7,5hp)
Three Pump Hydrophore (Including Panel)	QMax/Min-15/44 m3/h HMax/Min-103/52,5 m 11 kw (15hp)
NM 40/20D/B,	Centrifugal pump in block design, 4.0 kW, 400/690 V, 50 Hz, IP 54, 2900 1/min, standard version with mechanical seal: carbon/ceramic/NBR
NM4 125/25 D/B	horizontal centrifugal pump in block design, made of GG, 7.5 kW, 400/690 volts, 50 Hz, IP54, 1450 1/min, special version with mechanical seal: carbon/ceramic/EPDM
NM4 100/20B/A	horizontal centrifugal pump in block design, made of GG, 4.0 kW, 400/690 volts, 50 Hz, IP54, 1450 1/min, special version with mechanical seal: carbon/ceramic/EPDM
MXHML 204/A	
CTM61	Peripheral impeller pump in block design, 0.33 kW, 230 volts, 50 Hz, IP54, single phase, IP 54, IE-2, 2900 rpm, standard version with Mechanical seal: carbon/ceramic/NBR
	Centrifugal pump in close-coupled design, made of GG, 4.0 kW, 400/690

NM 40/20C/B	volts, 50 Hz, IP 54, 2900 1/min, Special version with mechanical seal: SiC/WC/FPM, housing seal FPM
Housing seal in FPM, item 14.20	
Mechanical seal 24 mm, SiC/WC/FPM, R5H2,	Item 36.00
Impeller nut, item 28.04	
16002500000	Mechanical seal 18 mm, SiC/SiC/FPM, Pos. 36.00
16006060000	Gleitringdichtung 24mm, Kohle/Keramik/NBR, Pos. 36.00
16002200000	Mechanical seal 24mm, SiC/SiC/FPM, item 36.00
Mechanical seal	Mechanical seal 24mm, carbon/ceramic/NBR, Item 36.00
Housing seal in NBR, item 14.20	
BCM 20/A 230/50 Hz IE2 TROPICALIZED R3-XYXRZY	FPM CASING JOINT
BCM 22/1/A 230/50 Hz IE2 TROPICALIZED R3-XYXRZY	
14002140000	Pump
16006060000	Mechanical seal 24mm, carbon/ceramic/NBR, Item 36.00
70MA058200000	NR 50/125A/B with SN 2017085463 NR 50/125A/B, Inline pump in block design, 2.2 kW, 230/400 Volt, 50 Hz, IP 54, 2900 1/min, GLRD: Coal/ceramic/NBR
NM 32/12 S/A,	6040008200019 3 centrifugal pump in block design, 1.5 kW, 230/400 volts, 50 Hz, IP 54, 2900 1/min, Mechanical seal: Silicon carbide/carbon/EPDM
NM 25/12A/B,	Centrifugal pump in block design, 0.75 kW, 230/400 volts, 50 Hz, IP 54, 2900 1/min, Mechanical seal: Silicon carbide/carbon/FPM, with tropicalized insulated motorcycle Article number 6001031100023
798.500.30	A2S XT3 XT3 500 203 300N
MXH 202/A,	multi-stage, horizontal centrifugal pump made of Stainless steel, 0.25 kW, 230/400 V, 50 Hz, IP54, 2900 rpm, mechanical seal: Coal/ceramic/EPDM
70M0043100000	NR 50C/B, Single-stage inline pump in block design, 0.75 kW, 230/400 V, 50 Hz, IP 54, 2900 1/min, Standard version with mechanical seal: Coal/ceramic/NBR
14002300000	Housing seal in NBR, A50-125, C41, Pos. 14.20
16006030000	Mechanical seal 18mm, carbon/ceramic/NBR, Item 36.00
14015910000	Housing seal for A65, item 14.20 Pump: A 50-125B/BS/N 2021349933
MXH 203E,	Multi-stage centrifugal pump in block design, horizontal, made of stainless steel, 0.37 kW, 230/400 V, 50 Hz, three-phase, IP54, 2900 1/min, Mechanical seal: Carbon/ceramic/EPDM
B-C 41/A,	Bronze centrifugal pump with open impeller, 1.1 kW, 230/400 volts, 50 Hz, 2900 1/min, Mechanical seal: Silicon carbide/carbon/FPM, Special version with wheel made of Aluminium bronze, tropicalized insulated motor Article number 7160011200010
NM 32/16A/B,	6040016300000 Centrifugal pump in block design, made of cast iron, 2.2 kW, 230/400 volts, 50 Hz, IP 54, 2900 1/min, Standard version with mechanical seal: Coal/ceramic/NBR
Nm 32/12ae	

Mxhm 204/A	
Mxh 405/C	
Val 30/750	
Nr 50 D/A	
Nmd20/110 A-60/A	
Nm40/16ae-R Xyhyzvy 4kw 2900d/Dk	
Nm 65/25c/A	
Nm 65/16d/B	
34	
Mxh-203e	AUTO PUMP SET 50HZ 0.45KW 220-240V
60900101000 Nm4-40/16 C/A	
Mxh 803/A	
Mxh 805/B	
A 65-150a/B	
Tp100e	
Nm 3/Be	
B-6sds 32/11 + I-6cs 15	
Nm65/12ae	
25.02	
Nm 40/16 ?/B	
Mxh 404/B	
Mxh 406/A	
K0009.Vr00	
40/800 5.5 Kw 2900 D/Dak	
25.01	
Tm61e	PUMP PERIPHERAL CLOSE-COUPLED 230V 60HZ
Tp100/A	
Nm 65/12c/B	
Nmd 20/140e	
Mxh 1605/B	
Nms 65/250a/B	
Nm 32/20 Ce	
?-? 80-170?/?	
Bnm32/16b-60,3450rpm	
Brass Impeller (For Ca 60 Pump)	

Mxhm 203e	
Ng4/A	
Nm50/12ae	
Mxhm 206	
Gmv 80-80/A	
Nm4 80/31c	
B-Nm 25/160 Ae	
Mxh 1602	
C41e	
Tp132r/A	
71710040000 B-Cm 20/A	
Val 65/2500r/A	
Mxh 1602/A	
65/125a/A	
Mxh 1604/A	
Mxh 202e	
Bnm 25/200ae Ref.0506169608	
Nmd 20/140be 230/400/50 Hz	
Mxh 206/C	
Nm 65/16c/C	
Nm2a	
0763 Ns4-Nms4 150/315	
16.00	
Nm 65/16ar	
30200431000	
Nm465/31be	
Mxhm 805	
B-Nm 50/200be	
Nm 65/20a/A	
B-Nmd20-140be	
Pos. 14.20	Housing seal in NBR,
14.20	
M30x2 Uni 5589	
130510601s	
Nmd25/190be	
Mxhm 202e	

64
v3 0200.13rvt
Nm80/16e/A 28.00
42004736
14001840000
Mxh803-60 B
Nmd 40/180b
60401964038
Mxhm 402e
B-Nmd 200/110 A/A.
14,20 - 14002390000
65/125d/A
7073004000
Mxhl 404/A
Nm 65/20c/C
0765
Nm 40/12 A/B
28.04
Mxh 804/A
Nm 65/12a/B
70020021000
Nmd 40/180b/A 400/690/50
Nm4 100/20 A-R2
Nm 50/25be-R
Nm 32/12 Fe-60 380v-60hz R3-X7x72z7
Nm 25/160 Ae - 60
B-6sds 58/10 + I-6cs 18,5
Mxhm 406
60800041000 Nm4 25/200 Ce
Mxh 802/B
70m10060000 Nr4-50a/A
2x120 M3/H
Mxhm 403/A
Nm 3/Be-60hz
Nm 65/16b/C
Mxhm 205/A

Mxh 204/A	
Nm25/20be	
399057954 Type: Bnm65	
70020021003	
Nm 65/12ae	
22,12 - 14009850000	
Nmd20/140a	
B C 41e 0704227160	
Mxhm 802/A	
Mxh 1606/B	
Nms 65/250b/A	
Nmd20/110a	
Im25/4e-230v	
Nm 65/20b/D	
Mxv-25-220/C-Xyxykry-Fpm	VERTICAL MULTI-STAGE IN-LINE PUMP, 415V 3PH 50HZ
Nm 65/20 B/B (18,5kw)	
60401042018 Nm 50/20b-60/B	
Nm 50/20 B/A	
32	
28.00	
A65-150 (Ex A65-150ae)	
28	
Nmd 20/140a/A Tm Xyhy2vy	
Nm480/20be	
Nmd 20/140a	
Xyxyrry	
Nmd 25/190b/A Tm	
316 D75x359	
Nms4 150/315b	
Mxhm 804	
Ctm 61	
Nm 65/16a/C	
Nmd 25/190b-60a	
Nm 65/16c-60/A	
Mxh 1603/B	

Nm32/16ae	
Nr4 65b/A	
Nm 25/12 Be	
6sdx46-12	
Nm 80/16c/C V.400/690/50hz	
62330051000 Mxhm 205/A	
Mxh 402e	
16006030000	Mechanical seal 18mm, carbon/ceramic/NBR, Pos. 36.00
Nm 32/12 Se	
Nm 40/12a-60b 380v-60hz R3-X7x72z7	
Gmv 80-80a/A	
Mxv 25-207-60(G)	
Nm 50/16b/B	
16.17	
Nm4 80/20be	
Mxhm 803	
Art Nr. 16006080000	Mechanical seal 32 mm, carbon / ceramic / NBR, Pos. 36.00
Nm4 65/31ce	
Mxhm 202e 62310021000	
N80-250a	
Mxhm 405	
Nm4125/25e/A	
Nm 40/25c/A	
Nm 3/S No:73091 Pump+motor	
B081sd000340aa2	
B-8sds 70/7 + I-6cs 30	
Nmd 20/140a/A	
65/2500-R/A Hp3	
Nm 25/160 Ae-R 6000033106e	
Mxv 25-220 - 0407142486	
Fpm 414x436x5	
65/125s/A 4 Kw	
Mpcm 31/A	
Nm 65/12e/C	
Nm 65/16d-60/A	
Nmd20/140b	

Bnm 25/200b	
998290628	
Nm4 25/12a/A	
Mxh 403/A	
16006210000	
Mxhm 404/A	
Nm 25/20a/B 230/400/50 Hz	
Nm40/20b/A	Mechanical Seal (ORIGINAL) MEKANİK SALMASTRA (ORIJİNAL) MEKANİK SALMASTRA
22,16 - 14009820000	
Nmd 20/110a-60b	
Nm32/20c/A	
Aisi 316 Ini 6604	
Mxh 205/B	
62242051000 Mxh 805/A	
28.20	
Mxh803-60/B	