



Camlock

Garanti: 12 ay
 Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Camlock Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Camlock T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
FLANGE;A350-LF2 CL.1;#150;RF;2"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 2" x 1 1/2", CL150 , RF , SCH XS, B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1,
FLANGE;A350-LF2 CL.1;#150;RF;2"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 2" x 1 1/2", CL150 , RF , SCH XS, B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1,
FLANGE;A350-LF2 CL.1;#150;RF;2"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 2" x 1 1/2", CL150 , RF , SCH XS, B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1, ----- Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. Material certificate: EN 10204 Type 3.1Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. Material certificate: EN 10204 Type 3.1
FLANGE;A350-LF2 CL.1;#150;RF;4"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 4" x 1 1/2", CL150 , RF , SCH STD., B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1,
FLANGE;A350-LF2 CL.1;#150;RF;4"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 4" x 1 1/2", CL150 , RF , SCH STD., B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1, ---- Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. Material certificate: EN 10204 Type 3.1Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. EN 10204 Type 3.1
	GASKET , 2" , 316L SS-FG , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THK , 316L SS INNER RING , 316L SS OUTER RING , CL150 , B16.5 , B16.20 ---- Commodity Code: PGG153L5315BL01 GASKET , 316L

GASKET;SPIRAL WOUND;2";#150 316L SS;1/8"	STAINLESS STEEL WINDING, FLEXIBLE GRAPHITE FILLED , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THICK , 316L STAINLESS STEEL INNER RING , 316L STAINLESS STEEL OUTER CENTERING RING , CLASS 150 , PER ASME B16.5 , PER ASME B16.20Commodity Code: PGG153L5315BL01
GASKET;SPIRAL WOUND;4";#150 316L SS;1/8"	GASKET , 4" , 316L SS-FG , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THK , 316L SS INNER RING , 316L SS OUTER RING , CL150 , B16.5 , B16.20 ---- Commodity Code: PGG153L5315BL01 GASKET , 316L STAINLESS STEEL WINDING, FLEXIBLE GRAPHITE FILLED , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THICK , 316L STAINLESS STEEL INNER RING , 316L STAINLESS STEEL OUTER CENTERING RING , CLASS 150 , PER ASME B16.5 , PER ASME B16.20Commodity Code: PGG153L5315BL01
FITTINGS;STUD BOLT;A320-L7;5/8"x4"	STUD BOLT (CONT) , 5/8" x 4" , CR-MO A320-L7 , W/ 2 HVY HEX NUTS , A194-7, S3 , B1.1 , Xylan 1424 COATED , DIA (IMP) X LEN (MET)STUD BOLT (CONT) , 5/8" x 4" , CR-MO A320-L7 , W/ 2 HVY HEX NUTS , Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS, PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , Xylan 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS, PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , Xylan 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1
FITTINGS;STUD BOLT;A320-L7;5/8"x7"	STUD BOLT (CONT) , 5/8" x 7" , CR-MO A320-L7 , W/ 2 HVY HEX NUTS , A194-7, S3 , B1.1 , Xylan 1424 COATED , DIA (IMP) X LEN (MET) ---- Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS , PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , Xylan 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS , PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , Xylan 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1
F150-SS-NPT	1 1/2 NPTM SNAPLOCK ADAPTOR SS
B150-SS-NPT	1 1/2 NPTM SNAPLOCK COUPLER SS
DC150-SS	1 1/2 SNAPLOCK DUST CAP SS
2" Ball Valves, Manual Lever	Operations, Full Bore, PN16, Bronze Material, NPTF, RPTFE Seat
4" Ball Valves, Manual Lever	Operations, Full Bore, PN16, Bronze Material, NPTF, RPTFE Seat
2" NPT cap SS316/316L	
4" NPT cap SS316/316L	
4" cam-lock adaptor type F	(male cam-lock / female NPT) Bronze
4" cam-lock adaptor type D	(female cam-lock / female NPT) Bronze
4" hose c/w cam-lock	couplers type C one end, type E other end (male / female), length 10mtr
CAMLOCK 991S01-21-1AGV BOLT (3222346929)	

SMP_S400S_4303	
991S01-21-1AGV BOLT (3222346929)	
991R2-2AZ_3222343802	
F100-SS-NPT	Snaplock Part F 1" Male Adaptor x NPT Male Thread, 316 S/Steel
A100-SS-NPT	Snaplock Part A 1" Male Adaptor x Female NPT Thread, 316 S/Steel
HEX100MN-050FN-SS	Hex 1" Male NPT X 1/2" Female NPT S/Steel
100GSK-BU	1" Buna Gasket
HEX050MN-050MN-SS	1/2" BSPT Male NPT x 1/2" BSPT Male NPT SS
HEX050FN-TEE-SS	1/2" Female NPT Equal TEE SS
F100-SS-NPT-	Snaplock Part F 1" Male Adaptor x NPT Male Thread, 316 S/Steel
PLUG,HEX,2",SS304	
REDUCER,BELL,2"Fx1"F,SS304	
MALE,1",CAMxNPT,SS304	
BUSHING,REDUCER,2"Mx1/2"F,NPT,SS	
991S01-21-1AGV	LOCKING PEN
991R2-2AZ	WELDABLE HOLDING CAMS, GALVANIZED STEEL
C200-AL-MB	CAMLOCK FITTING, 2IN, ALUMINIUM, TYPE C, MULTI SERATED HOSE SHANK
E200-AL-MB	CAMLOCK FITTING, 2IN, ALUMINIUM, TYPE E, MULTISERATED HOSE SHANK
DC200-A	Snaplock Part DC 2" Camlock Dust Cap, Aluminim, Brass Handles, Buna Nitrile Seal
DP200-A	Snaplock Part DP 2" Camlock Dust Plug, Aluminium
200GSK-BU	2" Buna Gasket
V.N.009.1/00.	