

Cavotec

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Cavotec** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Cavotec Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.





Ürün	Açıklama
GSK 50-18/58-18/180/DV/Hz	A00-14-LT0009 Slip ring assembly with housing 17x 25A + PE, 600V - Ms / Cu gap 16x 16A + PE, 24V - Ms / Cu with heating 110V, 20W (mounted in the housing) SRK for use down to -25 ° C Wiring of the rings with special cables - 2.0m Lapp Ölflex FD 855 CP 18x2.5mm ² (power rings) Shield connected to PE Lapp Control TM 18x1.0mm ² (data rings) Wiring of the pantograph - 2.0m from the housing Lapp Ölflex FD 855 CP 18x2.5mm ² (power rings) Shield connected to PE Lapp Control TM 18x1.0mm ² (data rings) Lapp Tray II 5GAWG14 (heating) Housing with cable glands: 1x M32x1.5 1x M25x1.5 1x M20x1.5 (heating cable) Lines potted in the axis Flange without cable gland Total height 414mm . according to Drawing no .: A00-14-LT0009 and wiring diagram index B . !New variant!
40632810UA0305	

A06-B01980-OZ	
40632810UA0305	
FTL 28501820HA4704	313521.15-2
I/O MODULE MC-KB-4 EXi	
FLT 50712812UB0305	A00-01-CFR072 4 x 90A + PE, 500V with direct wiring Trigger direction of rotation: left Winding length: 22 m (load case 8) with the cable mounted on the jacket - 27m Semoflex 5 x 16mm ² (Ø 25.3mm / 1.17 kg / m) with holding stocking type T-25 galv. (A. with thread in the flange M50x1.5 with cable gland in the housing M40x1.5 Hood Ø 205 mm / a = 205 mm
PC4-VX04-0700	
PC4-WX04-0700	
PC5-VX04-1500	SOCKET, X5, 3x420A+E+2p/1kV 120/150mm ²
Type : GSK 58-16/110/DV/So	Cavotec slipring column Type : GSK 58-16/110/DV/So Serial Nr. : S1806576.10-10 No of poles/current/tension : 3X 16A + PE; 230V Year : 1118
001-RE090	
11 SN:442	
1604872.10-1	
1604872.30-1	
331442	
58-06/110/KL/So oem	
AG300K1	
AP300KM1	
Buflex-M 3x120+3G25	
CAB01-03240-000	
Collector(with brushes) for K424/FC V1000/Nr:081957/1	
D 25426 N132M8VC-B5	
FLT 19291420BA4504	
FLT 25330610FA5806 (OEM)	
FLT19361420 DA4605	
GSK 02-04/98-10/205/KL	
GSK 47-04/140/KL/So 11 Kw	
GSK 47-04/140/KL/So 7.5 Kw	
GSK 47-04/140/KL/So oem	
GXO-KMD66-000000	
KK270 CD 1240.3240/253/R + GR2-1	
KP-BRUSH	

M5_1080_3600
M5-1031-3452
M5-1051-3600
M5-1080-3600 the same as M5-1080-3699
M5-1080-3699
M5-2321-4111
M9-1051-3003
M 9-1051-3600
M9-1120-5020
M9-1510-3600
M9-2021-9005
N132M8VC B5
N15_250/28
PC2-EX-SB04-0500/M50S
PC4-SX04-0700 OEM!!
PC4-SX04-0702
PC4-SX37-0025
PC4-WX37-0025
PC5 RX04 S7004P
PC5 SX04 S700R4P
PC5-RX04-S700
PC5-SS05-S0700B
PC5-SX04-S700
PC5-SX04-S700R
PC5-TX04-1850.
PC5-VX04-1500
PC5-VX04-K0500
PC5-VX04-S700
PC5-WX04-1850
PC5-WX04-1850 OEM
PC6-RS04-3000
PCS2-SX01-1500
PCX-11010-051 oem
PCX-12010-048 oem
PCX-16006-038 oem
PCX-21410-0401 oem

RM4D2_032530	
S00SG205601	
S02-00440-010	
S22-00460_110	
S70-00005-100	
A00-14-CFR033	
A00-01-CFR073	
060-SCR_A00-01-CFR073	Spring cable drum according to type plate
DACO-50	
Model: MC-2-3	Specification - IP66 rating, 6 two-step push-buttons, 4 selector switches with LED, emergency stop button, comes with MC-IRX base station unit
A00-14-CFR033	
Spring cable reel 4600	
M5-2152-1209	SWITCH,TOGGLE,0>1
M5-2129-3002	BOOT,SEALING,FOR TOGGLE SWITCH
M5-2121-6700	PUSHBUTTON,BLACK
M5-2129-3105	CAP,NEOPRENE,FOR PUSHBUTTON
M5-2116-1616	SWITCH,ROTARY 21MM,16 POS HEX
M5-2160-0913	ARROW ,FOR 21MM OPERATING HANDLE
M5-2129-3109	BOOT,SEALING BLACK,FOR ROTARY HEX SWITCH
M5-2119-4917	HANDLE,OPEARTING,15MM FOR POT
M5-2117-2002	POTENTIOMETER,W/15MM KNOB
M5-2119-4912	CUP,FOR OPERATING HANDLE
M5-1060-5220	LCD,DISPLAY 2X20
M5-1020-4300	MODULE,PROCESSOR
M5-1040-3306	JOYSTICK,FOR BOARD CONNECTION
M5-2935-3303	LED(LIGHT EMITTING DIOD),YELLOW 3MM
M5-2935-3302	LED(LIGHT EMITTING DIOD),GREEN 3MM
M5-2935-3301	LED(LIGHT EMITTING DIOD),RED 3MM
M5-2211-0100	JOYSTICK,JC-100
M5-2121-6711	PUSHBUTTON,WITH GREEN LED
M5-1510-3314	SUPPORT,STRAP MC-3300
M5-2502-9002	FUSE,AUTO,2-P,6A
M5_2129-3100	
M5_2121-6700	
M5_2121-6710	

M5 2153-1229	
GSK 02-04/98-10/205	KL 3X50A+PE, 10X25A. 500V.
KK270CD1120.3120/440.353R	
GSK 02-04/98-10/205/KL	3X50A+PE, 10X25A. 500V.
PC5 IEC80005-3 version -350 Amper	
Dabico (Cavotec) F-EC-280-3x70-XP4xx	Service Cable 400 Hz 28m, 3x70, Zgv, Mxx, XP-4: MS, LED, (Cable Harness 28 meters 3x70+3x12+6x(4x1.0) with XP4 strain relief)Including copper addendum
PC5-VX04-0950LD	SOCKET X5, 3X300A+E+2P/1kV 95 MM2 LOCK PREPARATION
060-SCR	A00-14-BSC001 - 58-06/110/KL/So
SC-2301412-JB2 Fiber Optic Termination Box Set	
M5-1060-5220 MC Display (MC-LCD)	
M5-1510-3314 Support Strap MC-3300	
M5-2116-1612 Switch, Hex 12-Pos Continuous	
M5-2116-1616 Switch, Hex 16-Pos Continuous	
M5-2116-4004 Switch, Rotary 6-Pos 1x6	
M5-2117-2002 Potentiometer Assembly	
M5-2119-4914 MC CAP for 2119-4913	
M5-2121-0901 MC Switch 40mm ,	
M5-2121-6700 MC Switch Pushbutton 0-1 IP67, Black	
M5-2129-3002 Sealing Boot F/Toggle SW	
M5-2129-3100 Silicone Cap	
M5-2152-1209 Switch, Toggle 0-1 w/loc	
M5-2153-1207 Switch, Toggle 1-0-1	
M5-2153-1215 MC Toggle Switch 1-0-1 w/lock	
M5-2211-0100 Joystick JC100	
M5-2935-3301 MC Diode LED Red 3mm	
M5-2935-3302 MC Diode LED Green 3mm	
M5-2935-3303 MC Diode LED Yellow 3mm	
28461110ha9820	Cable Drum
PC5-SX04-K1852-05	PLUG X5 3x350A+E+3p/7,2kV 185mm2 E=95 BLUE prep FO
GPU-400HZXP4	SILV.PLT EXC.KIT ABCN CAVTC
GPU- 400HZXP4	CON. HALF HOUSING I/O CAVTC
GPU-400HZXP4	CON.HALF HOUS.ON/OFF CAVTC
M5-2129-3101	Sealing boot Black for push button
DAB-750/41CWTHD8WPEAF-FHPAS-4-IF4-PG-	

SS-LS4-SC-GL-1900D	
M5-2129-3002	Sealing boot f/toggle sw. Fluorinated Silicone
S91-H0000-135	Marshalling Panel Locking Mechanism
Terminal Block	
Sc-120414-Afi	
Sr2-00594-000	
Flt40632810ua9820	
Pc5-Vx04-K0350	
Nmb202393	
Sr2-S0116-000	
Sr6-S0217-000	
Pc2-Px01-2400/M50	
N112ml4/1-85	
S01-H1200-003	
22301820dc5826	
Sr2-00598-000	
22361430eb4504	
M5-1042-4100	
Flt50802813ua-0703	
Kv44/8s	
F-Cc-1231016-001	
Pc2-Tx01-2400/M50	
28431820ha5826	
28461110ha9820	
28461110ha-9820	Artikel-Nr.: A00-01-CIT304 Spring line drum of the type Special flange with mounted cable on the jacket - 20m reelable cable 24 x 2,5mm2 (Ø 16,9mm / 0,41kg / m)
Pc5-Sx04-1504	
S01-20t70-341	
Jetcable	
Sr2-01083-000	
Pc5-Tx04-1500	
S1606225.180-8 - Model : Flt 40632820sa0205 / Semoflex 5x10 Mm2	
Mc-2-3	HAND HELD RADIO REMOTE CONTROL
S78-70000-006	
Sr2-00593-000	

[Pc5-Wxo4-1850](#)

[Pc4-Ss05-0700](#)

[Pc5-Tx04-1850](#)

[Sr6-S0325-002](#)

[S17-Ae112-004](#)

[40.6 Vm509-40g K424/7](#)

[S22-40618-9s0](#)