



Cedes

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Cedes Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Cedes Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
445I-P4s1320yd	*** Successor to Safe4-1320-30 *** GuardShield Safe 4 safety light curtain Pair (transmitter and receiver) Hand protection (30 mm resolution), Protective field height 1320mm, Range: 18m Goods tariff no. Country of origin ECCN 8536501990 MX Weight about 5.78
445I-106427	Safe 4 Connection Cap A, Cable Gland Gewicht ca. 58,967 kg 85366990 CH
114 559	Cegard/mini-MOD SY-2000-36 , NB , BCK , CC
Object 100F	
Part no: 104948	
HW 100SW100	
cegard/Mini SY-2000-36, NB, BCK, CC	113 606 Range (m): 0.0-4.0 Elements/beams: 36/174 Length/protection (mm): 2000/1600
Cedes	
safe c3	
GridScan/Mini SY-2030-21 ,SB, N	113 264 With door blanking Resolution: 50 mm at bottom 500 mm, 190 mm at upper part Output: Push-pull Test: Active low Edge length: 2030 mm Protection height: 1800 mm Elements: 21
GridScan/Pro SY-2000-20	114 988 With door blanking Resolution: 50 mm at bottom 500 mm, 185 mm at upper part Output: Push-Pull and FSS Test: Active low Edge length: 2060 mm Protection height: 2000 mm Elements: 20
103 785	ELS 263 receiver NPN/DO, 5m cable
BB 10 - T 33/76B/115-7M	
GridScan/Mini SY-2030-21, SB, N	113 264
	114 988 With door blanking Resolution: 50 mm at bottom

GridScan/Pro SY-2000-20	500 mm, 185 mm at upper part Output: Push-Pull and FSS Test: Active low Edge length: 2060 mm Protection height: 2000 mm Elements: 20
SAFEC 3 V2	
APS – Absolute Positioning System	+ 10meter Streifen
S4L-AEF2N-KH1-LH1F2-ACDA07553	
Swiss mode/ GLS126 slot type sens¼r.	
GridScan/Pro SY-2500-22	includes transmitter and receiver, as well as connection cable
103 311	ELS 263 transmitter, RW 6m, 5m cable
SY-2500-22	
104 569	ELS 263 transmitter, RW 6m, connector M8
104 570	ELS 263 receiver NPN/LO, connector M8
103 716	Receiver cable 5m, connector M8
103 717	transmitter cable 5m, connector M8
GRIDSCAN/PRO, PNP/NPN (PUSH-PULL) UND FSS. 10...30VDC, 50 MA,	SY-2500-22
114 988	GridScan/Pro SY-2000-20 With door blanking Resolution: 50 mm at bottom 500 mm, 185 mm at upper part Output: Push-Pull and FSS Test: Active low Edge length: 2060 mm Protection height: 2000 mm Elements: 20
101 231	cegard/Max
o0100FS-KEF5N-LJ14-BCD33	
GridScan/Pro SY-2320- 21	GridScan/Pro SY-2320- 21
105 239	
1013446	cegard/MiniSY-2000-16 105 245
GridScan/Pro	
Els264	
100688	
Els263npn-D0	
445I-P4s3400yd	
S400s-Kef5n-Lf10-Acd67	
S400s-Kef5n-Lf24-Ccd62	
Cegardmax-74	

Els263nnpn-L0	
100687	
300223	
101397	
103-005-0016r	LIGHT CURTAIN 24VDC .3AMP 500MA 270MM RESOLUTION
S400s-Krf5n-Lf10-Acd70	
100697	
100700	