

Cewe Instrument



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Cewe Instrument Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Cewe Instrument T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
DPT221-401	Programmable transmitter, class accuracy 0.2, 4 programmable analog outputs, 2 digital Outputs, with RS485 Modbus interface, with USB interface for parameterization Input voltage: 3x100-693 V (3-phase system) Input current: 0-1 ... 5 A Frequency: 45-65 Hz Auxiliary voltage: 40-276 V AC / DC
ConfigView-Kit	Parameterization software and USB cable
AKM47877	WINDING TEMPERATURE INDICATOR and OIL TEMPERATURE INDICATOR AKM47877 4-20mA 0-150
12475278	
375011111	
440-447	
AUF SEITE 35 DES KATALOGS M-TECH	
CL48	
CL72.	
CP23 -141	
CP28-U10 T1 DI125	

CQ72	
CQ96 0-0-200-250 V	
DI121	
DI125	
DP14	
DP344	
DPT221- 401	
DPT723-156	
Elite 440-444 (0.2s)	
FQ 96/2	
H100579	
IQ72	
IQ96	
MAK45/14	
MAK62/30	
MAX10Y-028	
NC301	
PI 29-1	
PI 36-5	
PI25-1	
PI25-2	
PI36-1	
PI39-1	
PQ23	
SK613050-2	
Elite 440-447	Multifunction built-in measuring device Frame size 96 x 96 mm, four-line LC display Current transformer connection: 1-2 or 5-10 A Voltage: 57.7 V (100 V)- 240 (415) V, 3 phases, 4 conductor system (3 phases, 3 conductors), Accuracy class 0.5s including RS485 interface for Modbus communication Auxiliary Voltage: 80-300V AC/DC
ELITE 440 MODEL ENERGY ANALYZER	
DPT611-155	Programmable transmitter for current for 1-phase connection Measuring current: 1/ 5 A Frequency: 50/60Hz 2 x outputs:20 mA Auxiliary voltage: 80 - 276 V AC/DC with micro USB port Accuracy class: 0.5 according to IEC 688-2
DPT623-157	Programmable reactive power transmitter for 3-phase connection Measuring current: 1/ 5 A Measuring voltage: 3 x 57.5 - 240 V (conductor-earth) Frequency: 50/60Hz 2 x outputs:20 mA Auxiliary voltage: 80 - 276 V AC/DC with mini USB port Accuracy class: 0.5 according to IEC 688-2
DPT623-156	Programmable transmitter for active power for 3-phase connection Measuring current: 1/ 5 A Measuring voltage: 3 x 57.5 - 240 V (conductor-earth) Frequency: 50/60Hz 2 x outputs:20 mA Auxiliary

	voltage: 80 - 276 V AC/DC with micro USB port Accuracy class: 0.5
PI25-1	Switch position indicator with bar symbol square, front dimensions: 25x25 mm for direct voltage 24-230 V DC including terminal cover
DPT623-157	Programmable reactive power transmitter for 3-phase connection Measuring current: 1/ 5 A Measuring voltage: 3 x 57.5 - 240 V (conductor-earth) Frequency: 50/60Hz 2 x outputs:20 mA Auxiliary voltage: 80 - 276 V AC/DC with mini USB port Accuracy class: 0.5 according to IEC 688-2
CQ96	moving coil meter with quadrant scale, 90° pointer deflection, Front dimensions: 96 x 96 mm Input: 4--20mA DC Scale: 0-150°C Accuracy class 1.5 with terminal cover
4-20mA AKM 47877	
E500C-5101	Multifunctional built-in measuring device Elite 500 Frame size 96 x 96 mm, TFT display Measuring input current: 10mA - 6A Measuring input voltage: 35 V - 500 V (L-L), 20 V - 300V (L-N), Accuracy class 0.5s Harmonic detection up to 15th harmonics including RS485 interface for Modbus RTU and RJ-45 for Ethernet Auxiliary voltage: 48-300V DC or 85-300V AC
Prometer	100-R8 R3E021- 002*452102 6 Advanced Energy Meter Mounting: Rack Accuracy class: 0.2s 3 phase 4 wire Current: 1-10A , User Programmable CT Ratios: User Programmable VT Ratios: User Programmable Frequency: 50 Hz or 60 Hz Double aux supply: 1x selfpowered & 1 x 60-240V AC/DC, 8 pulse outputs, 4 configurable pulse input /outputs Com Options: 1xIEC61850, 1xRS485, 1 x Ethernet Communication Protocol: DLMS / Modbus TCP/ IEC 61850 both available Language in product: English, German, (Selectable)
MAX10Z-257	11" Rack for one meter
PBC000-184-	Configuration kit with optical cable and M cube 100 software (needed one per substation)
Elite 440-447	Multifunctional built-in measuring device Frame size 96 x 96 mm, four-line LC display Current transformer connection: 1-2 or 5-10 A Voltage: 57.7V (100V) - 240 (415)V, 3 phase, 4 Ladder system (3 phases, 3 conductors), Accuracy class 0.5s including RS485 interface for Modbus communication Auxiliary voltage: 80-300V AC/DC
Prometer 100-W5/C1 P3E021-000*4563163	Advanced Energy Meter Mounting: Wall Accuracy class: 0.5s 3 phase 4 wire Current: 1-10A , User Programmable CT Ratios: User Programmable VT Ratios: User Programmable Frequency: 50/60 Hz Double aux supply: selfpowered & 60-240V AC DC 4 configurable pulse input /outputs, 7 pulse outputs Com Options: 1xRS232 & 1xRS485, Ethernet Communication Protocol: DLMS / Modbus / Both available Language in product: English, German, French (Selectable)
MAX10Z-211	Panel mounting kit (needed for flush panel mounting, one per meter)
PBC000-184-001	Configuration kit with optical cable and M cube 100 software (needed one per substation)
PROMETER 100	CEWE X/5 ACTIVE METER CL:0,5S 60 -240 V AC
CQ96	Moving-coil measuring instrument with quadrant scale, 90° pointer deflection, Front dimensions: 96 x 96 mm Input: 4-20 mA, DC Scale: 0-150°C Accuracy class 1.5 with terminal cover
Premier 300	
Nc304 - M By - Pi25-2	
Pi25-1	

Check Energy Meter (2 Shunt, 2 Trf Hi Side) (Promotor100)	
Osr 2e Sk613050-2 48 Vdc , By Pi25-1	
Di63 - , By Dr335	
Du02. - , By Du125	
Mak62/30 200/1 A -	
-5...0...+ 5 Mvar	
Pi25-5	
Configview-Kit Parametriersoftware Und Usb- Kabel	
Dpt623-156	
379891001	
Ceweconfig Kit	
Di125	
Config View Suite	
Iq72 Ammeter	
684.120.0325	
Configview-Kit	
6600/110 V (Iq96)	
Ctc13	POWER TRANSDUCER 60HZ 460VAC IN
Lag -0.5 ...1...+0.5 Lead	
Dq14 - , By - Dq135	
Dv-125	
Dp14 - , By Dp135	
Pi 36-5	
Redline At 154 Kv	
Cewepromet Er W 372843110	
C 563 - Obsolete, Replacement - Dpt521- 401	
Dpt201-401	
Cq96 12475278 The Tropical Version Is Obsolete, Alternative Cq96	
Mak62/30 250/1 A -	
0....15 A Dc	
Pir36-5	
Cq72.	
CI72	
CI96	

Wq 96/2s	
Dpt611-151	
Cl48.	
Pi 36-1	
Nc301 - , By Pi25-1	
Cw0000880043	
Cp28-U10 P2 Cq48	
Akm 47877	
W 371843110	
Pi25-2	
Configview Kit For Dpt521-401	
Dpt521-401	
Dpt-221(201)	
Iq72 Voltmeter	
Dp345	
Dpq 345	
Dr335	
Check Energy Meter (2 Trf Lo Side) (Prometor100)	
Auf Seite 35 Des Katalogs M-Tech	
Cp23 -141 Ceweprometer-R	
Iq 48	
Du02 - , Replased By Du125	
Cq72 0-1400ma	
Qb72	
Cq96	
In: 57/99-120/208v, 1a, Class 0,5	In: 57/99-120/208V, 1A, 50 Hz. Uaux: 85-265 VAC, 100-300 VDC. Class: 0,5S 110V, 5A, 50Hz
Dr135	
Config View	
Cp28-U10 P1 Clr48	
Du01, Nr:15345605 , Dpt611-151	
Elite 440-443 (0,2s))	ALTERNATİF Multifunction installation device Frame size 96 x 96 mm, four-line LC display Current transformer connection: 1-2 or 5-10 A Voltage: 57.7 V (100 V) - 240 (415) V, 3 phases, 4 conductor system (3 phases, 3 conductors), Accuracy class 0.2s including RS485 interface for Modbus communication Auxiliary voltage: 80-300 V AC / DC
Redline At 212 Mw	
Dp135	

Dq135	
W 375243111	
Iq72 0-600/720 A	
Df03-04	
Pi 29	
Pir36-5, (New Serial Number For The Same Product) 211365	
H100579 / By Dp135	
Redline At 800 A	
Cp28-U10 T1 Di125	
Redline At 400 A	
Dpt (Ex.Dpf14)	
Type: Di 122 Input: 5a, 50hz Output: 4-20ma Aux: 184-276vac Range: 0-5a	
Cqr72	
Cq72 0-1600ma	
Akm 47877-2	
Iq72 0-300/360 A	
Check Energy Meter (Prometor100)	
Mak62/30 300/1 A -	
Cp23 T2 Dp135	
Parametriersoftware Und Usb-Kabel	
Du125	
375011111 Obsolete, Alternativ 375243111	
Elite 440-443	Multifunction installation device Frame size 96 x 96 mm, four-line LC display Current transformer connection: 1-2 or 5-10 A Voltage: 57.7 V (100 V) - 240 (415) V, 3 phases, 4 conductor system (3 phases, 3 conductors), Accuracy class 0.5s including RS485 interface for Modbus communication Auxiliary voltage: 80-300 V AC / DC
Akm 47877-3	
Dpt221-401	
Iq 72	
Art. 379891001	
Pi29-1	
Cp23 T1 Dp135	
Di02 - , By Di125	
Osr 2e Sk613050-2 110 Vdc , By Pi25-1	
Check Energy Meter (1 Shunt, 2 Trf Hi Side) (Prometor100)	

[Type: Dp345 , Dpt623-156](#)

[Type: Iq72](#)

[Mak45/14 - , By Typ Tsc 1 150/1a](#)

[Dtp521-401](#)

[Elite 443](#)