Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Columbus Mckinnon

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Columbus Mckinnon Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Columbus Mckinnon Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
HSE 50.1 N-1-2B-H / S-1-Tr	Pfaff-silberblau screw jack Customs tariff number: 84834025 With the following configuration Size: HSE 50.1 N Type: 1 lifting spindle: Tr 40 x 8 RH Gear ratio: 6: 1 Stroke per revolution: 1.33 mm Installation position: M2B Execution: H / S Drive side right: Yes Drive side left: Yes Head design: I Stroke: 370 mm Spindle extension VL (manual): 5 mm Installation dimension v. Screw on the housing: to the end of head I. Installation dimension: 73 mm Lubrication: Gearbox with synthetic oil filling Surface treatment: primed Operating instructions: SHE_HSE_MKR_Ba1_Ba2_de Process code: 0
PN: N00401313	RATCHET DISC ASSEMBLY
PN: N00404732	FRICTION DISC
PN: N04307655	HAND CHAIN (STAINLESS STEEL
PN: N00400668	CONNECTING LINK
SHE 3.1 N-1-1A-A - F / S-2-Tr	CMEP-HBE Pfaff-silberblau screw jack Customs tariff number: 84834025 With the following configuration Size: SHE 3.1 N Type: 1 lifting spindle: Tr 30 x 6 RH

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Offer ZNR_DE: A13_01_105_000_2400BL01 Translation: 6:1 Stroke per revolution: 1.00 mm Installation position: M1A Version: A - F / S Drive Side Right: Yes Drive side left: Yes Head design: II Stroke: 105mm Spindle extension VL (manual): 158 mm installation dimension Housing screwing: up to the end of head II Installation dimension: 309 mm Lubrication: grease Surface treatment: primed Process code: 0
CMEP-MKR	M2-1-1A-5-320-31-N-T20x4 Pfaff-silberblau spindle lifting element With the following configuration Size: M2 N Type: 1 lifting spindle: Tr 20 x 4 RH Offer ZNR_DE: A18_01_002_0000_0100 Translation: 4:1 Stroke per revolution: 1.00 mm Installation position: M1A Version: F / SF Drive side right: Yes Drive side left: Yes Head design: GK (fork head) stroke: 320 mm Spindle extension VL (manual): 31 mm Installation dimension from housing screw: to center hole head GK Installation dimension: 187 mm Lubrication: Grease Process code: 0
Wb	CHAIN HOIST 1/4TON LOAD 16SPD 6.3AMP 110/120/60V
M2-1-1a-5-160-0-L-T20x4	
4233	HOIST
M2248	
R	HOIST
1754626cf8ft	CHAIN HOIST

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.