

Communication Instruments

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Communication Instruments Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Communication Instruments Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
1618092-7	SAFETY RELAY, SPST-NO, 120VAC, 5A, COIL VOLTAGE VAC NOM:120V, COIL VOLTAGE VDC NOM:-, COIL RESISTANCE:-, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC NO
1-1617076-2	3SBH1141A2 = M39016/14-001L, ROHS COMPLIANT: NO
1617085-2	SSAW-6C-24B = SS 6 POLE RELAY
3-1618071-7	250X=WILMAR OVER/UNDERVOLTAGE, ROHS COMPLIANT: NO
3sbc2126a2	3SBC2126A2 = M39016/38-026P
91512-3	CC II HEAD ASSY CMNL 24-18
1-1616109-1	A701D (FAA/PMA)=RELAY
Ls-7105	LS-7105 = LS RELAY
1-1616058-6	A703GC=RELAY
1-1618058-2	VOLTAGE MONITORING RELAY, DPDT, 32VDC, PRODUCT RANGE:WD SERIES, CONTACT CONFIGURATION:DPDT, COIL VOLTAGE:140VAC, CONTACT CURRENT:-, RELAY

	MOUNTING:DIN
1617087-1	CAW-1C-24B = HALF.10A.1 POLE.2
Jps10-2y	JPS10-2Y = M28750/10-002Y
1618058-5	RELAY, SAFETY, DPDT, 30VDC, 5A, PRODUCT RANGE:WD25 SERIES, CONTACT CONFIGURATION:DPDT, COIL VOLTAGE:32VDC, CONTACT CURRENT:5A, RELAY MOUNTING:- , RELAY
Wd5051-001	WD5051-001=RELAY, OVERCURRENT
3-1617343-9	RD6CAH2601=RD 6 POLE RELAY
Sr-7601	SR-7601 = M39016/40-001
4r-2500s-Sil	4R-2500S-SIL=RELAY,ELECTROMAGN
1618058-3	RELAY, SAFETY, DPDT, 240VAC, 30VDC, 5A, PRODUCT RANGE:WD25 SERIES, CONTACT CONFIGURATION:DPDT, COIL VOLTAGE:200VDC, CONTACT CURRENT:5A, RELAY MOUNTING
3sbh1165a2	3SBH1165A2 = M39016/14-008M
1-1616082-0	A885Y=RELAY
3-1618058-4	RELAY, CONTROL, DPDT, 240VAC, 30VDC, 5A, CONTACT CURRENT MAX:5A, CONTACT VOLTAGE AC NOM:240V, CONTACT VOLTAGE DC NOM:30V, CONTACT CONFIGURATION:DPDT
41ro-2500s-Sil	41RO-2500S-SIL = RELAY ELECTR
1-1616126-5	E323E=RELAY