

Cosema

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Cosema Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Cosema Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Magnetic separator new model M500	A strong welded steel housing which is protected by special paint and fitted with a non-magnetic stainless steel base. • Flow rate : ~ 400 l/min max • A rotating drum of permanent sintered ring-type magnets which are fitted to a sturdy shaft supported by two supports complete with bearing. • The drum is operated at a very low speed due to the use of a three phase motor and a reduction gear box 0,18 kW. 400 V 50 Hz – B14 • Inlet 3"
M700	
Distributor box for magnetic separator M500	(OPTIONAL)
Magnetic separator new model M700	A strong welded steel housing which is protected by special paint and fitted with a non-magnetic stainless steel base. • Flow rate : ~ 600 l/min max • A rotating drum of permanent sintered ring-type magnets which are fitted to a sturdy shaft supported by two supports complete with bearing. • The drum is operated at a very low speed due to the use of a three phase motor and a reduction gear box 0,18 kW. 400 V 50 Hz – B14 • Inlet 4"
Distributor box for magnetic separator M700	(optional)
820203	
Tessuto Tipo li	
Adm3-2000	

Ürün	Açıklama
Dmp300	
6aacd905	
250-509294000	
400304d	
Dmp1000-A2	
Mrh250ms1b/D	
Dmp 150 Verteilerbox Für Magnetischen Seperator	SERIE NO:643/96
Paramoll Hiflow 130	
400304	
F12005	
Fb3 2000	
1 Off Magnetic Separator New Model M250	• A strong welded steel housing which is protected by special paint and fitted with a non-magnetic stainless steel base. • Flow rate : ~ 150-200 l/min max • A rotating drum of permanent sintered ring-type magnets which are fitted to a sturdy shaft supported by two supports complete with bearing. • The drum is operated at a very low speed due to the use of a three phase motor and a reduction gear box 0,18 kW. 400 V 50 Hz – B14 • Inlet 3" • COLOUR: Black COLOUR: CATAPHORESIS TREATMENT (BLACK COLOUR) VOLTAGE: 400 V 50 Hz PACKING: PALLET ISPM15 AND THERMORETRAIBLE FILM - not stackable
Paramoll N 927/100p	
I2mh10I1	
F10416iv	
Paramoll N927/50 P	
Paramoll N 968/100	

Ürün	Açıklama
Paramoll N 927/70 P	
Xt00299	
Z4016h24q24000	
Paramoll N 260/100	
Cosematipoi	
Z4013h12q24000	
99-Cilindri New	
Paramoll 927/70 P	
1100mm	
Paraprint Ol50	
Parafil Rt20	
Dmp1000-M	
Paramoll N 334/150	
Dmp 150 Magnetischer Seperator	SERIE NO:643/96
Dmp1000-A1	
Fadm-3000	
Am3-1500	
Pos.8	
Paraprint Ol 20	
Paraprint Ol35	
Paramoll N927/35 P	
Td400/7,5	
M 100	
Dmp 300	
Paramoll Hiflow 180	
Paraprint Ol60	

Ürün	Açıklama
F21213	
F21214	
400304I	
Dmp200-Comp	
Dmp200	
Distributor Box For Magnetic Separator (Optional)	Optional