

A-342



Crosby

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Crosby Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Crosby T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Typ G-417	7013035 Bow rope sleeve type G-417 Diameter 32-35 mm
G-417	7013048 Bow rope sleeve type G-417 Diameter 44-48 mm
7013035	Bow rope sleeve type G-417 Diameter 32-35 mm
7013048	Bow rope sleeve type G-417 Diameter 44-48 mm
Liste 18 Pos.	Bitte um Kontrolle und Angebot
Crane pennant, 2 meters long 6x19 IWRC Galv	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv	. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye(SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
2 legs (Spreaders) 8 ton SWL x 5m long.	22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
2 legs (Spreaders) 5 ton SWL x 5m long.	6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
Green pin standard shckles	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 16mm x 19mm, SWL 3.25 ton
Green pin standard shckles,	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 19mm x 22mm, SWL 4.75 ton
Green pin standard shckles	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 22mm x 25mm, SWL 6.5 ton
	bow shackles with safety bolt, to EN13889, hot dipped

Green pin standard shckles,	galvanized, 25mm x 28mm, SWL 8.5 ton
Green pin standard shckles,	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 32mm x 35mm, SWL 12 ton
1000 kg SWL Chain blocks with certificate	
Crane pennant, 2 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 2 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
Crane pennant, 5 meters long	6x19 IWRC Galv. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
2 legs (Spreaders)	8 ton SWL x 5m long. 22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
2 legs (Spreaders)	5 ton SWL x 5m long. 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
1090125	Crosby safety hook set SS-4055 - 11.5to for old hooks 319, 320 and 322
1093541	Crosby safety hook set SS-4055 - 22to 22 to. - for old hooks 319, 320 and 322
G-450 16 mm	7504530-2 Crosby wire rope clips G-450 Nominal width 16 mm 5/8 "- HOT GALVANIZED"
G-450 9-10 mm	Crosby wire rope clips G-450 Nominal width 9-10 mm 3/8 "- HOT GALVANIZED"
G-429 14 - 16 mm	Crosby wire rope clips G-429 Nominal width 14 - 16 mm 9/16 - 5/8 "
3313042	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 3/4 in., WLL: 25 t EN 13889 Nominal size 1 3/4 in., WLL: 25 t

3313212	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 1/4 in., WLL: 12 t EN 13889 Nominal size 1 1/4 in., WLL: 12 t
3313210	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 in., WLL: 8.5 t EN 13889 Nominal size 1 in., WLL: 8.5 t
25 TON MCKISSICK BLOCK, FOR WIRE SIZE 28.5 MM	M-491G/2032315 MCKISSICK
12 TON MCKISSICK BLOCK, FOR WIRE SIZE 19 MM	M-491G/2021163 MCKISSICK
4 TON MCKISSICK BLOCK, FOR WIRE SIZE 10 MM	M-491G/2020170 MCKISSICK
7504529	Crosby wire rope clips G-450 Nominal size 3 - 4 mm "1/4" "-HOT GALVANIZED" As an alternative to HG223, we offer: Crosby - with fork-fork
3013085	Crosby rigging screw galvanized HG-228 1/4 "x 4" fork - fork
6000000	Crosby rigging screw galvanized HG-228 5/16 "x 4-1 / 2" fork - fork
Range 143-163PSI	
RANGE 131-149PSI	
4100743	IP lifting clamp IPU10 0.5 EN 13155 Load capacity: 0.5 tons Gripping range 0-16MM
4100731	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM
4100733	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM
Crosby S-265 (1290848)	WLL: 3,2
G2130A 4-3/4T 3/4" ALLOY BOLT TYPE SHK	1219516
G2130A 6-1/2T 7/8" ALLOY BOLT TYPE SHK	1219534
S265 1,2TX13MM	Ersetzt Art. 1290740
Rope Terminal Ø10mm	
BEP MBL 90T	Shackle Mooring No 852
1068389	HR1000M M36X130MM 6000000
(S65) CROSBY - 1068389	FAM 02TD2
CROSBY G341 16MM 5/8" WELDLESS SLING LINK GALV.	

CROSBY G209 3/4T 5/16" SCREW PIN ANCHOR SHACKLE	
CROSBY 1208 WEST 4" SHEAVE bb	
CROSBY G341 10MM 3/8" WELDLESS SLING LINK GALV	
CROSBY A336 8-10MM 3/8" GR6 LOK-A-LOY	
A-1337 32-10 (ID: 1015181)	Crosby Lock-a-loy
WLL: 25T (ID: 1262095)	Crosby Bow shackle with safety bolt
1018552	CROSBY G209 9-1/2T 1-1/8" SCREW PN ANCH
1018516	CROSBY G209 6-1/2T 7/8" SCREW PIN ANCH. SHACKLE
1018598	CROSBY G209 13-1/2T 1-3/8" SCREW PIN AN SHACKLE
Crosby HR125 - 1"A, ID: 1016964	
DOUBLE CLEVIS LINK S-247	Material item number : 00013195 Manufacturer : CROSBY Manufacturer part no. : 1013049
ALLOY CHAIN 8MM	Material item number : 00013196 Manufacturer : CROSBY Manufacturer part no. : Gr. 100 - 273729
LEBUS L-140 STANDARD RATCHET	Material item number : 00013197 Manufacturer : CROSBY Manufacturer part no. : 1048404
G-8142 EYE NUT M20 DIN 582	
LIFTING EYE GR8	Material item number : 00013199 Manufacturer : Green Pin Manufacturer part no. : GPAL20
LIFTING EYE LENGTH AS DIN580 GR8	Material item number : 00013200 Manufacturer : Green Pin Manufacturer part no. : GPAL20DIN
4100731	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM 2701663
4100733	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM 2701665
4100745	IP lifting clamp IPU10 2 EN 13155 Load capacity: 2 tons Gripping range 0-35MM 2701677
1.1/2G2.1/1 JLT-J05-15-A	
Crosby G209	1018491
2092120/	CROSBY Wirbelhaken - SHUR-LOC S-1326 10 MM
KLEMENSİ 16 MM G-450 crosby	
KLEMENSİ 28 MM G-450 crosby	
	Crosby Wire Rope Clips G-450 Nominal width 16 mm "5/8 "" -

7504530-2/	HOT GALVANIZED"
7504531/	Crosby Wire Rope Clips G-450 Nominal width 28-30 mm
G-2140	Alloy Bolt type Anchor Shackle WLL: 40T, ID: 1021138
Clip 3/8" Wire G-429 Fist Grip(Gergi Halatı Clamsi	
589714	EGKN-10-10
IPH10--2703297	
5-S-3 Stock No : 297235	
HR 125 M16	
Shackle 1/4" Crosby 2130 Grade6 bolttype	
Shackle 3/8" Crosby 2130 Grade6 bolttype	
Shackle 1/2" Crosby 2130 Grade6 bolttype	
Shackle 5/8" Crosby 2130 Grade6 bolttype	
Shackle 3/4" Crosby 2130 Grade6 bolttype	
Shackle 1" Crosby 2130 Grade6 bolttype	
G-2130	Crosby G-2130 Bolt Type Anchor Shackle WLL: 0,5T, Part No.: 1019466
951111MFA-P:VALVE	~ OMNI 951, 3/4 MNPT X 1 FNPT, 316 SST MATERIALS WITH METAL SEAT, THREADED CAP, PED
HG-228 G-6323 -	1032714 SSGPMBGG191 2 163 403 412 ROPE TENSIONER, JAW-JAW, 3/4" X 12", 2.36 TONS
HG-228 G-6323 -	1032778 SSGPMBGG221 8 163 407 818 ROPE TENSIONER, JAW-JAW, 7/8" X 18", 3.27 TONS
HG-228 G-6323 -	1032830 SSGPMBGG251 8 163 410 018 ROPE TENSIONER, JAW-JAW, 1" X 18", 4.54 TONS
HG-228 G-6323 -	1032894 SSGPMBGG321 8 163 411 418 ROPE TENSIONER, JAW-JAW, 1-1/4" X 18", 6.90 TONS
HG-228 G-6323 -	SSGPMBGG642 4 ROPE TENSIONER, JAW-JAW, 2-1/2" X 24", 27.20 TONS
G-450 G-6240	1010079 CLGRP08 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 8 MM (5/16"), EN 13411-5 TYPE B
G-450 G-6240	1010097 CLGRP10 STEEL ROPE TERMINAL, HOT DIP

G-450 G-6240	GALVANIZED, 10 MM (3/8"), EN 13411-5 TYPE B 1010131 CLGRP12 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 13 MM (1/2"), EN 13411-5 TYPE B
G-450 G-6240	1010195 CLGRP19 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 19 MM (3/4"), EN 13411-5 TYPE B
G-414	G-6120 1037675 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 10 MM (3/8")
G-414	G-6120 1037791 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 22 MM (7/8")
1035018	
1014155	
1048636	
Swivel 3 Te	Swivel No: 3-S-2, Steel, Red Operating Temperature: -40° C to +204° C Onshore Working Load Limit: 3 Tons
Crosby Shackles x 8 ea.	Crosby G 2130, Steel, Galvanized, Operating Temperature: - 40° C to +204° C Onshore Working Load Limit: 2 Tons
98832835	SHACKLE, BOLT TYPE ANCHOR, WLL 1.5T
98871566	SAFETY, SHACKLE, 4 PART ANCHOR, BOW, - G-2130, SWL 3.25T C/W COTTER PINS
END LINK WELDLESS S340 1/2 SUPPLIER CODE: 75535	
SHACKLE ANCHOR S-213 2T SUPPLIER: 75535,	
SHACKLE ANCHOR S-213 3 1/4 TON SUPPLIER: 75535,	
LINK, END WELDLESS S-340 (312) SUPPLIER:	75535
VALVE, RLF, CROSBY, 95114XMFA- SPL, 261PSI	Valves, Relief Type of bonnet/cover CLOSED Type of construction CONVENTIONAL Flow, max 7.327 m³/h Set pressure 17.99 bar 261 psi Temperature, max 38 °C Temperature, min -35 °C Size, inlet 1/2 in Size, outlet 1/2 in Size, orifice, actual 0.545 cm² Mat, body MONEL Service(s) SEAWATER Type of end connection NPT MALE x FEMALE Mat, bonnet MONEL Mat, spring INCONEL X750 Type, cap SCREWED Manufacturer THE CROSBY GROUP Manufacturer Part Number 95114XMFA-SPL
3K4 JOS-E-45-J	
CHAIN HOOK / MODEL:S1317	SHUR-LOC CLEVIS HOOK, 6MM PIN AUTOMATIC LOCKING HOOK, CAPACITY:1450KG, EN 1677-3 (CERTIFICATE INCLUDED) / CROSBY / 1028991 /
Hr125 Hoist Ring 8000# 7/8 X 2.75 -	or equivalent -MPT THREAD

Crosby 1016953	
Hr125 Hoist Ring 5000# 3/4 X 2.25 - Crosby 1016931	or equivalent -MPT THREAD
Hr125 Hoist Ring 4000# 5/8 X 2 - Crosby 1016920 or	or equivalent - MPT THREAD
Hr125 Hoist Ring 2500# 1/2 X 2 - Crosby 1016909 or	equivalent - MPT THREAD
TYPE B, ASME B30.26	56-58 MM (2-1/4"), EN 13411-5 HOT DIP GALVANIZED
TL13N	
3M8HCA	Serial No: 13185990 & 13185991 & 13185972 & 13185973
2,5K2HCA	Serial No: 13185986 & 13185987 & 13185988 & 13185989 & 13185952 & 13185969 & 13185970 & 13185971
10049938	
10050309	
G-4163	WLL: 6,5 ton Bow shackle with safety bolt
Type WLL 6 ½ Ton 7/8	Chackle Bolt
0.2t M6	
G450 2-3/4" 68-72MM	WIRE ROPE CLAMPS 1010435
G277	
1020695	
1014397	
1037719	
1256868	
1014266	
1026695	
1020485	
1014431	
1019515	
1018491	
1014285	
1014266.	
	Sheet metal clamp IPNM 2,000kg -40mm Product description sheet metal clamp Permissible payload 2,000.00 kg Type

25301010015070	designation IPNM max. operating temperature 70 °C minimum temperature range -20 °C Standard number DIN EN 13155 Material steel Surface powder-coated Stop direction horizontal/vertical Application Smooth, polished surfaces Application steel sheets, steel construction Min. gripping range 0.00 mm Max. gripping range 40.00 mm How traction works Minimum load 20.00 kg Type of control Manual Max. load cycles 16,000 load cycles
25301010015067	Sheet metal clamp IPNMN 1,000kg -20mm Product description sheet metal clamp Permissible payload 1,000.00 kg Type designation IPNMN max. operating temperature 70 °C min. temperature range -20 °C Standard number DIN EN 13155 Material steel Surface powder-coated Stop direction horizontal/vertical Application Smooth, polished surfaces Application steel sheets, steel construction Min. gripping range 0.00 mm Max. gripping range 20.00 mm How traction works Minimum load 10.00 kg Type of control Manual Max. load cycles 16,000 load cycles
25301010035985	Sheet metal clamp 6,000kg 0-180mm force connection Product description sheet metal clamp Permissible payload 6,000.00 kg max. operating temperature 70 °C min. temperature range -20 °C Standard number DIN EN 13155 Material steel Surface powder-coated Stop direction horizontal Application steel sheets, steel construction Min. gripping range 0.00 mm Max. gripping range 180.00 mm How traction works Type of control Manual
25301010035089	Sheet metal clamp 2,000 kg Product description sheet metal clamp Permissible payload 2,000.00 kg Max. load cycles 16,000 load cycles Customs tariff number 84314100 Net weight 133.28 KG IPHNM 0 - 30 mm
25301010035765	Sheet metal clamp IPH10E 3,000kg -60mm Product description sheet metal clamp Permissible payload 3,000.00 kg Type designation IPH10E max. temperature use 100 °C min. temperature range -40 °C Standard number DIN EN 13155 Material steel Surface painted Stop direction horizontal Min. gripping range 0.00 mm Max. gripping range 60.00 mm How traction works Type of control Manual Max. load cycles 16,000 load cycles
1-IPNM	STELL LİFTİNG REMOVAL
55320000035180	***G403 5/8" 16mm swivel with fork
Gunnebo UKN 1	
HR-125 1/2-13x2.00	Crosby Swivel Hoist Ring, Cap. 2500LBS HR125 1/2X2.00" 2500LBS
HR-125 1/2-13x2.50	Crosby Swivel Hoist Ring, Cap. 2500LBS HR125 1/2X2.50" 2500LBS
G-4163	WLL 13,5 ton Bow shackles with safety bolt.
A-342	Crosby Alloy Master Link, type A-342, cap. 38.50T, Size 44MM (1-3/4") DNV A342 44MM (1- 3/4") DNV

G-2150	Crosby bolt type chain shackle, type G-2150, cap. 25T, size 1-3/4" G2150 25T 1-3/4"
1.5d2 Jbs-E-55-J/Spl	
961101mfa	
1019579 Hochfeste Sch¼kel	
1019533 Hochfeste Sch¼kel G 2130	
1.5h3 Jbs-E-15x-J -Spl	
G2150 1019953	Shackle straight with nut and split pin
1018516 (G209)	
1019686 Hochfeste Sch¼kel S 2130	
089115 (Obsolete - No Replacement) Nozzle	
G-340	Crosby G-340 1014093 WLL: 2,95 t.
1014365	CROSBY Master Link A-342
1025896-L1327	Eye hooks
1019953 Hochfeste Sch¼kel G 2150	
1.5d2 Jlt-Jos-E-56x-J/Spl-Spl	
G-450	G-450 1/2" 12-13 MM 1010131
P/N:136161	
1.5h3jos-E15c-Pspl	
A-1337	
1019524 Hochfeste Sch¼kel S 2130	
1022923	
1.5h3 Jbs-E-Or-15-L	
1018614	
GP® Bow shackle with screw pin, WLL 0,75 Ton	Crosby anchor shackle with eyelet pin G-209 EN 13889 Nominal size 5/16 in., WLL: 0.75 t Screw Pin Anchor Shackle - 1/3 Ton
G 2150 1019873	Shackle straight with nut and split pin
1022238	
1019677 Hochfeste Sch¼kel G 2130	
123834	

1010015 G450	
1018534.	
L320an-1022457	Eye hooks
Uni1950	
10143604	
04-4749-065	
1022260	
1019613 Hochfeste Sch¼kel G 2130	
S-91740	
1.5g2.5 Jbs-E-45-J	
A-345	Master Link Assembly WLL: 38,5to Crosby-Artikel-Nr.: 1014814
1.5e2 Jos-E-55x-J /Spl-Spl	
1014348 Aufh¼ngeglied	
Z091147b1ra5p1	
1014342-Obsolete-Alternative 1014348 Master Link	
A-342	Alloy Master Links
1014348	
1022293	
Grade 100 Alloy Chain	Nominal thickness: 26mm Crosby Item No .: 1210232
S-91328 / Inconel 625	
1.5g2.5 Jos-E-26-D	
1.5h3 Jos-E-26-D	
1019953	CROSBY Sch¼kel G-2150 - 25 to
1019622 Hochfeste Sch¼kel S 2130	
G2150 1019935	Shackle straight with nut and split pin
1015104	
0.5t Ip10 222.701.674	
951101mfa	
1022246	

Lok-A-Loy 10 Alloy Connection Link	WLL: 41,0to Crosby-Artikel-Nr.: 1015181
320/C	
961111mfa	
1.5f2 Jbs-E-16-L	
G-408	G-408 1/2" 11-13 MM 1037595
1037318	
951101ma	
1014319 Aufhangeglied	
1022932	
101517 2	
1019515 Hochfeste Schakel G 2130	
L320an-1022446	Eye hooks
1019962 Hochfeste Schakel S 2150	
1018570	
1022424	
1019542 Hochfeste Schakel S 2130	
10195794	
Hg-228 1/2x12"	3000000
039973 (Obsolete - No Replacement) Disc Bushing	