

A-342



## Crosby

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Crosby** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Crosby T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">Typ G-417</a>	7013035 Bow rope sleeve type G-417 Diameter 32-35 mm
<a href="#">G-417</a>	7013048 Bow rope sleeve type G-417 Diameter 44-48 mm
<a href="#">7013035</a>	Bow rope sleeve type G-417 Diameter 32-35 mm
<a href="#">7013048</a>	Bow rope sleeve type G-417 Diameter 44-48 mm
<a href="#">Liste 18 Pos.</a>	Bitte um Kontrolle und Angebot
<a href="#">Crane pennant, 2 meters long 6x19 IWRC Galv</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv</a>	. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye(SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
<a href="#">2 legs (Spreaders) 8 ton SWL x 5m long.</a>	22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">2 legs (Spreaders) 5 ton SWL x 5m long.</a>	6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">Green pin standard shckles</a>	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 16mm x 19mm, SWL 3.25 ton
<a href="#">Green pin standard shckles,</a>	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 19mm x 22mm, SWL 4.75 ton
<a href="#">Green pin standard shckles</a>	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 22mm x 25mm, SWL 6.5 ton
	bow shackles with safety bolt, to EN13889, hot dipped

<a href="#">Green pin standard shckles,</a>	galvanized, 25mm x 28mm, SWL 8.5 ton
<a href="#">Green pin standard shckles,</a>	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 32mm x 35mm, SWL 12 ton
<a href="#">1000 kg SWL Chain blocks with certificate</a>	
<a href="#">Crane pennant, 2 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 2 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long</a>	6x19 IWRC Galv. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
<a href="#">2 legs (Spreaders)</a>	8 ton SWL x 5m long. 22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">2 legs (Spreaders)</a>	5 ton SWL x 5m long. 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">1090125</a>	Crosby safety hook set SS-4055 - 11.5to for old hooks 319, 320 and 322
<a href="#">1093541</a>	Crosby safety hook set SS-4055 - 22to 22 to. - for old hooks 319, 320 and 322
<a href="#">G-450 16 mm</a>	7504530-2 Crosby wire rope clips G-450 Nominal width 16 mm 5/8 "- HOT GALVANIZED"
<a href="#">G-450 9-10 mm</a>	Crosby wire rope clips G-450 Nominal width 9-10 mm 3/8 "- HOT GALVANIZED"
<a href="#">G-429 14 - 16 mm</a>	Crosby wire rope clips G-429 Nominal width 14 - 16 mm 9/16 - 5/8 "
<a href="#">3313042</a>	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 3/4 in., WLL: 25 t EN 13889 Nominal size 1 3/4 in., WLL: 25 t

<a href="#">3313212</a>	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 1/4 in., WLL: 12 t EN 13889 Nominal size 1 1/4 in., WLL: 12 t
<a href="#">3313210</a>	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 in., WLL: 8.5 t EN 13889 Nominal size 1 in., WLL: 8.5 t
<a href="#">25 TON MCKISSICK BLOCK, FOR WIRE SIZE 28.5 MM</a>	M-491G/2032315 MCKISSICK
<a href="#">12 TON MCKISSICK BLOCK, FOR WIRE SIZE 19 MM</a>	M-491G/2021163 MCKISSICK
<a href="#">4 TON MCKISSICK BLOCK, FOR WIRE SIZE 10 MM</a>	M-491G/2020170 MCKISSICK
<a href="#">7504529</a>	Crosby wire rope clips G-450 Nominal size 3 - 4 mm "1/4" "-HOT GALVANIZED" As an alternative to HG223, we offer: Crosby - with fork-fork
<a href="#">3013085</a>	Crosby rigging screw galvanized HG-228 1/4 "x 4" fork - fork
<a href="#">6000000</a>	Crosby rigging screw galvanized HG-228 5/16 "x 4-1 / 2" fork - fork
<a href="#">Range 143-163PSI</a>	
<a href="#">RANGE 131-149PSI</a>	
<a href="#">4100743</a>	IP lifting clamp IPU10 0.5 EN 13155 Load capacity: 0.5 tons Gripping range 0-16MM
<a href="#">4100731</a>	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM
<a href="#">4100733</a>	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM
<a href="#">Crosby S-265 (1290848)</a>	WLL: 3,2
<a href="#">G2130A 4-3/4T 3/4" ALLOY BOLT TYPE SHK</a>	1219516
<a href="#">G2130A 6-1/2T 7/8" ALLOY BOLT TYPE SHK</a>	1219534
<a href="#">S265 1,2TX13MM</a>	Ersetzt Art. 1290740
<a href="#">Rope Terminal Ø10mm</a>	
<a href="#">BEP MBL 90T</a>	Shackle Mooring No 852
<a href="#">1068389</a>	HR1000M M36X130MM 6000000
<a href="#">(S65) CROSBY - 1068389</a>	FAM 02TD2
<a href="#">CROSBY G341 16MM 5/8" WELDLESS SLING LINK GALV.</a>	

<a href="#">CROSBY G209 3/4T 5/16" SCREW PIN ANCHOR SHACKLE</a>	
<a href="#">CROSBY 1208 WEST 4" SHEAVE bb</a>	
<a href="#">CROSBY G341 10MM 3/8" WELDLESS SLING LINK GALV</a>	
<a href="#">CROSBY A336 8-10MM 3/8" GR6 LOK-A-LOY</a>	
<a href="#">A-1337 32-10 (ID: 1015181)</a>	Crosby Lock-a-loy
<a href="#">WLL: 25T (ID: 1262095)</a>	Crosby Bow shackle with safety bolt
<a href="#">1018552</a>	CROSBY G209 9-1/2T 1-1/8" SCREW PN ANCH
<a href="#">1018516</a>	CROSBY G209 6-1/2T 7/8" SCREW PIN ANCH. SHACKLE
<a href="#">1018598</a>	CROSBY G209 13-1/2T 1-3/8" SCREW PIN AN SHACKLE
<a href="#">Crosby HR125 - 1"A, ID: 1016964</a>	
<a href="#">DOUBLE CLEVIS LINK S-247</a>	Material item number : 00013195 Manufacturer : CROSBY Manufacturer part no. : 1013049
<a href="#">ALLOY CHAIN 8MM</a>	Material item number : 00013196 Manufacturer : CROSBY Manufacturer part no. : Gr. 100 - 273729
<a href="#">LEBUS L-140 STANDARD RATCHET</a>	Material item number : 00013197 Manufacturer : CROSBY Manufacturer part no. : 1048404
<a href="#">G-8142 EYE NUT M20 DIN 582</a>	
<a href="#">LIFTING EYE GR8</a>	Material item number : 00013199 Manufacturer : Green Pin Manufacturer part no. : GPAL20
<a href="#">LIFTING EYE LENGTH AS DIN580 GR8</a>	Material item number : 00013200 Manufacturer : Green Pin Manufacturer part no. : GPAL20DIN
<a href="#">4100731</a>	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM 2701663
<a href="#">4100733</a>	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM 2701665
<a href="#">4100745</a>	IP lifting clamp IPU10 2 EN 13155 Load capacity: 2 tons Gripping range 0-35MM 2701677
<a href="#">1.1/2G2.1/1 JLT-J05-15-A</a>	
<a href="#">Crosby G209</a>	1018491
<a href="#">2092120/</a>	CROSBY Wirbelhaken - SHUR-LOC S-1326 10 MM
<a href="#">KLEMENSİ 16 MM G-450 crosby</a>	
<a href="#">KLEMENSİ 28 MM G-450 crosby</a>	
	Crosby Wire Rope Clips G-450 Nominal width 16 mm "5/8 "" -

<a href="#">7504530-2/</a>	HOT GALVANIZED"
<a href="#">7504531/</a>	Crosby Wire Rope Clips G-450 Nominal width 28-30 mm
<a href="#">G-2140</a>	Alloy Bolt type Anchor Shackle WLL: 40T, ID: 1021138
<a href="#">Clip 3/8" Wire G-429 Fist Grip(Gergi Halatı Clamsi</a>	
<a href="#">589714</a>	EGKN-10-10
<a href="#">IPH10--2703297</a>	
<a href="#">5-S-3 Stock No : 297235</a>	
<a href="#">HR 125 M16</a>	
<a href="#">Shackle 1/4" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 3/8" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 1/2" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 5/8" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 3/4" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 1" Crosby 2130 Grade6 bolttype</a>	
<a href="#">G-2130</a>	Crosby G-2130 Bolt Type Anchor Shackle WLL: 0,5T, Part No.: 1019466
<a href="#">951111MFA-P:VALVE</a>	~ OMNI 951, 3/4 MNPT X 1 FNPT, 316 SST MATERIALS WITH METAL SEAT, THREADED CAP, PED
<a href="#">HG-228 G-6323 -</a>	1032714 SSGPMBGG191 2 163 403 412 ROPE TENSIONER, JAW-JAW, 3/4" X 12", 2.36 TONS
<a href="#">HG-228 G-6323 -</a>	1032778 SSGPMBGG221 8 163 407 818 ROPE TENSIONER, JAW-JAW, 7/8" X 18", 3.27 TONS
<a href="#">HG-228 G-6323 -</a>	1032830 SSGPMBGG251 8 163 410 018 ROPE TENSIONER, JAW-JAW, 1" X 18", 4.54 TONS
<a href="#">HG-228 G-6323 -</a>	1032894 SSGPMBGG321 8 163 411 418 ROPE TENSIONER, JAW-JAW, 1-1/4" X 18", 6.90 TONS
<a href="#">HG-228 G-6323 -</a>	SSGPMBGG642 4 ROPE TENSIONER, JAW-JAW, 2-1/2" X 24", 27.20 TONS
<a href="#">G-450 G-6240</a>	1010079 CLGRP08 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 8 MM (5/16"), EN 13411-5 TYPE B
<a href="#">G-450 G-6240</a>	1010097 CLGRP10 STEEL ROPE TERMINAL, HOT DIP

<a href="#">G-450 G-6240</a>	GALVANIZED, 10 MM (3/8"), EN 13411-5 TYPE B 1010131 CLGRP12 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 13 MM (1/2"), EN 13411-5 TYPE B
<a href="#">G-450 G-6240</a>	1010195 CLGRP19 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 19 MM (3/4"), EN 13411-5 TYPE B
<a href="#">G-414</a>	G-6120 1037675 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 10 MM (3/8")
<a href="#">G-414</a>	G-6120 1037791 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 22 MM (7/8")
<a href="#">1035018</a>	
<a href="#">1014155</a>	
<a href="#">1048636</a>	
<a href="#">Swivel 3 Te</a>	Swivel No: 3-S-2, Steel, Red Operating Temperature: -40° C to +204° C Onshore Working Load Limit: 3 Tons
<a href="#">Crosby Shackles x 8 ea.</a>	Crosby G 2130, Steel, Galvanized, Operating Temperature: - 40° C to +204° C Onshore Working Load Limit: 2 Tons
<a href="#">98832835</a>	SHACKLE, BOLT TYPE ANCHOR, WLL 1.5T
<a href="#">98871566</a>	SAFETY, SHACKLE, 4 PART ANCHOR, BOW, - G-2130, SWL 3.25T C/W COTTER PINS
<a href="#">END LINK WELDLESS S340 1/2 SUPPLIER CODE: 75535</a>	
<a href="#">SHACKLE ANCHOR S-213 2T SUPPLIER: 75535,</a>	
<a href="#">SHACKLE ANCHOR S-213 3 1/4 TON SUPPLIER: 75535,</a>	
<a href="#">LINK, END WELDLESS S-340 (312) SUPPLIER:</a>	75535
<a href="#">VALVE, RLF, CROSBY, 95114XMFA- SPL, 261PSI</a>	Valves, Relief Type of bonnet/cover CLOSED Type of construction CONVENTIONAL Flow, max 7.327 m <sup>3</sup> /h Set pressure 17.99 bar 261 psi Temperature, max 38 °C Temperature, min -35 °C Size, inlet 1/2 in Size, outlet 1/2 in Size, orifice, actual 0.545 cm <sup>2</sup> Mat, body MONEL Service(s) SEAWATER Type of end connection NPT MALE x FEMALE Mat, bonnet MONEL Mat, spring INCONEL X750 Type, cap SCREWED Manufacturer THE CROSBY GROUP Manufacturer Part Number 95114XMFA-SPL
<a href="#">3K4 JOS-E-45-J</a>	
<a href="#">CHAIN HOOK / MODEL:S1317</a>	SHUR-LOC CLEVIS HOOK, 6MM PIN AUTOMATIC LOCKING HOOK, CAPACITY:1450KG, EN 1677-3 (CERTIFICATE INCLUDED) / CROSBY / 1028991 /
<a href="#">Hr125 Hoist Ring 8000# 7/8 X 2.75 -</a>	or equivalent -MPT THREAD

<a href="#">Crosby 1016953</a>	
<a href="#">Hr125 Hoist Ring 5000# 3/4 X 2.25 - Crosby 1016931</a>	or equivalent -MPT THREAD
<a href="#">Hr125 Hoist Ring 4000# 5/8 X 2 - Crosby 1016920 or</a>	or equivalent - MPT THREAD
<a href="#">Hr125 Hoist Ring 2500# 1/2 X 2 - Crosby 1016909 or</a>	equivalent - MPT THREAD
<a href="#">TYPE B, ASME B30.26</a>	56-58 MM (2-1/4"), EN 13411-5 HOT DIP GALVANIZED
<a href="#">TL13N</a>	
<a href="#">3M8HCA</a>	Serial No: 13185990 & 13185991 & 13185972 & 13185973
<a href="#">2,5K2HCA</a>	Serial No: 13185986 & 13185987 & 13185988 & 13185989 & 13185952 & 13185969 & 13185970 & 13185971
<a href="#">10049938</a>	
<a href="#">10050309</a>	
<a href="#">G-4163</a>	WLL: 6,5 ton Bow shackle with safety bolt
<a href="#">Type WLL 6 ½ Ton 7/8</a>	Chackle Bolt
<a href="#">0.2t M6</a>	
<a href="#">G450 2-3/4" 68-72MM</a>	WIRE ROPE CLAMPS 1010435
<a href="#">G277</a>	
<a href="#">1020695</a>	
<a href="#">1014397</a>	
<a href="#">1037719</a>	
<a href="#">1256868</a>	
<a href="#">1014266</a>	
<a href="#">1026695</a>	
<a href="#">1020485</a>	
<a href="#">1014431</a>	
<a href="#">1019515</a>	
<a href="#">1018491</a>	
<a href="#">1014285</a>	
<a href="#">1014266.</a>	
	Sheet metal clamp IPNM 2,000kg -40mm Product description sheet metal clamp Permissible payload 2,000.00 kg Type

<a href="#">25301010015070</a>	designation IPNM max. operating temperature 70 °C minimum temperature range -20 °C Standard number DIN EN 13155 Material steel Surface powder-coated Stop direction horizontal/vertical Application Smooth, polished surfaces Application steel sheets, steel construction Min. gripping range 0.00 mm Max. gripping range 40.00 mm How traction works Minimum load 20.00 kg Type of control Manual Max. load cycles 16,000 load cycles
<a href="#">25301010015067</a>	Sheet metal clamp IPNMN 1,000kg -20mm Product description sheet metal clamp Permissible payload 1,000.00 kg Type designation IPNMN max. operating temperature 70 °C min. temperature range -20 °C Standard number DIN EN 13155 Material steel Surface powder-coated Stop direction horizontal/vertical Application Smooth, polished surfaces Application steel sheets, steel construction Min. gripping range 0.00 mm Max. gripping range 20.00 mm How traction works Minimum load 10.00 kg Type of control Manual Max. load cycles 16,000 load cycles
<a href="#">25301010035985</a>	Sheet metal clamp 6,000kg 0-180mm force connection Product description sheet metal clamp Permissible payload 6,000.00 kg max. operating temperature 70 °C min. temperature range -20 °C Standard number DIN EN 13155 Material steel Surface powder-coated Stop direction horizontal Application steel sheets, steel construction Min. gripping range 0.00 mm Max. gripping range 180.00 mm How traction works Type of control Manual
<a href="#">25301010035089</a>	Sheet metal clamp 2,000 kg Product description sheet metal clamp Permissible payload 2,000.00 kg Max. load cycles 16,000 load cycles Customs tariff number 84314100 Net weight 133.28 KG IPHNM 0 - 30 mm
<a href="#">25301010035765</a>	Sheet metal clamp IPH10E 3,000kg -60mm Product description sheet metal clamp Permissible payload 3,000.00 kg Type designation IPH10E max. temperature use 100 °C min. temperature range -40 °C Standard number DIN EN 13155 Material steel Surface painted Stop direction horizontal Min. gripping range 0.00 mm Max. gripping range 60.00 mm How traction works Type of control Manual Max. load cycles 16,000 load cycles
<a href="#">1-IPNM</a>	STELL LİFTİNG REMOVAL
<a href="#">55320000035180</a>	***G403 5/8" 16mm swivel with fork
<a href="#">Gunnebo UKN 1</a>	
<a href="#">HR-125 1/2-13x2.00</a>	Crosby Swivel Hoist Ring, Cap. 2500LBS HR125 1/2X2.00" 2500LBS
<a href="#">HR-125 1/2-13x2.50</a>	Crosby Swivel Hoist Ring, Cap. 2500LBS HR125 1/2X2.50" 2500LBS
<a href="#">G-4163</a>	WLL 13,5 ton Bow shackles with safety bolt.
<a href="#">A-342</a>	Crosby Alloy Master Link, type A-342, cap. 38.50T, Size 44MM (1-3/4") DNV A342 44MM (1- 3/4") DNV

<a href="#">G-2150</a>	Crosby bolt type chain shackle, type G-2150, cap. 25T, size 1-3/4" G2150 25T 1-3/4"
<a href="#">RADIOLINK+ 35T</a>	Straightpoint Radiolink Plus load cell, type RLP35T, cap. 35T, includes handheld SW -HHP
<a href="#">1.5d2 Jbs-E-55-J/Spl</a>	
<a href="#">961101mfa</a>	
<a href="#">1019579 Hochfeste Schäkel</a>	
<a href="#">1019533 Hochfeste Schäkel G 2130</a>	
<a href="#">1.5h3 Jbs-E-15x-J -Spl</a>	
<a href="#">G2150 1019953</a>	Shackle straight with nut and split pin
<a href="#">1018516 (G209)</a>	
<a href="#">1019686 Hochfeste Schäkel S 2130</a>	
<a href="#">089115 (Obsolete - No Replacement) Nozzle</a>	
<a href="#">G-340</a>	Crosby G-340 1014093 WLL: 2,95 t.
<a href="#">1014365</a>	CROSBY Master Link A-342
<a href="#">1025896-L1327</a>	Eye hooks
<a href="#">1019953 Hochfeste Schäkel G 2150</a>	
<a href="#">1.5d2 Jlt-Jos-E-56x-J/Spl-Spl</a>	
<a href="#">G-450</a>	G-450 1/2" 12-13 MM 1010131
<a href="#">P/N:136161</a>	
<a href="#">1.5h3jos-E15c-Pspl</a>	
<a href="#">A-1337</a>	
<a href="#">1019524 Hochfeste Schäkel S 2130</a>	
<a href="#">1022923</a>	
<a href="#">1.5h3 Jbs-E-Or-15-L</a>	
<a href="#">1018614</a>	
<a href="#">GP@ Bow shackle with screw pin, WLL 0,75 Ton</a>	Crosby anchor shackle with eyelet pin G-209 EN 13889 Nominal size 5/16 in., WLL: 0.75 t Screw Pin Anchor Shackle - 1/3 Ton
<a href="#">G 2150 1019873</a>	Shackle straight with nut and split pin
<a href="#">1022238</a>	
<a href="#">1019677 Hochfeste Schäkel G 2130</a>	

<a href="#">123834</a>	
<a href="#">1010015 G450</a>	
<a href="#">1018534.</a>	
<a href="#">L320an-1022457</a>	Eye hooks
<a href="#">Uni1950</a>	
<a href="#">10143604</a>	
<a href="#">04-4749-065</a>	
<a href="#">1022260</a>	
<a href="#">1019613 Hochfeste Sch¼kel G 2130</a>	
<a href="#">S-91740</a>	
<a href="#">1.5g2.5 Jbs-E-45-J</a>	
<a href="#">A-345</a>	Master Link Assembly WLL: 38,5to Crosby-Artikel-Nr.: 1014814
<a href="#">1.5e2 Jos-E-55x-J /Spl-Spl</a>	
<a href="#">1014348 Aufh¼ngeglied</a>	
<a href="#">Z091147b1ra5p1</a>	
<a href="#">1014342-Obsolete-Alternative 1014348</a> <a href="#">Master Link</a>	
<a href="#">A-342</a>	Alloy Master Links
<a href="#">1014348</a>	
<a href="#">1022293</a>	
<a href="#">Grade 100 Alloy Chain</a>	Nominal thickness: 26mm Crosby Item No .: 1210232
<a href="#">S-91328 / Inconel 625</a>	
<a href="#">1.5g2.5 Jos-E-26-D</a>	
<a href="#">1.5h3 Jos-E-26-D</a>	
<a href="#">1019953</a>	CROSBY Sch¼kel G-2150 - 25 to
<a href="#">1019622 Hochfeste Sch¼kel S 2130</a>	
<a href="#">G2150 1019935</a>	Shackle straight with nut and split pin
<a href="#">1015104</a>	
<a href="#">0.5t Ip10 222.701.674</a>	
<a href="#">951101mfa</a>	

<a href="#">1022246</a>	
<a href="#">Lok-A-Loy 10 Alloy Connection Link</a>	WLL: 41,0to Crosby-Artikel-Nr.: 1015181
<a href="#">320/C</a>	
<a href="#">961111mfa</a>	
<a href="#">1.5f2 Jbs-E-16-L</a>	
<a href="#">G-408</a>	G-408 1/2" 11-13 MM 1037595
<a href="#">1037318</a>	
<a href="#">951101ma</a>	
<a href="#">1014319 Aufhngeglied</a>	
<a href="#">1022932</a>	
<a href="#">101517 2</a>	
<a href="#">1019515 Hochfeste Schkel G 2130</a>	
<a href="#">L320an-1022446</a>	Eye hooks
<a href="#">1019962 Hochfeste Schkel S 2150</a>	
<a href="#">1018570</a>	
<a href="#">1022424</a>	
<a href="#">1019542 Hochfeste Schkel S 2130</a>	
<a href="#">10195794</a>	
<a href="#">Hg-228 1/2x12"</a>	3000000
<a href="#">039973 (Obsolete - No Replacement) Disc Bushing</a>	