

## Demmel

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Demmel** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Demmel T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">D16-03002-000</a>	DEMMELEER® stop and clamping angle D16 PL 200 cast, right Length: 200mm Width: 138mm Height: 50mm Weight: 1,700 kg - Three fully-fledged clamping sides with system bores and slotted holes for continuous adjustment - Better sliding behavior through the combination of cast iron and steel - With grid lines and fine scaling - Special casting: Highest stability and toughness - Powder coated
<a href="#">D16-03001-004</a>	DEMMELEER® stop and clamping angle D16 PL 90 x 90 mm bore / bore Length: 90mm Width: 25mm Height: 90mm Weight: 0.300kg - Measurements can be set using crack lines on the 3D welding table - Ideal for tight spaces - Fine scaling on both sides - Blued steel
<a href="#">E16-06001-000</a>	DEMMELEER® EcoLINE bolt D16 short Weight: 0.070kg - Limit clamping range: 22 - Connection element for system parts - Simple design without extended clamping range - Connects 2 system parts or 1 system part on the welding table
<a href="#">D16-05015-000</a>	DEMMELEER® sliding stop D16 Steel blued Length: 150mm Width: 12mm Height: 25mm Weight: 0.180kg - Fine scaling on both sides - Continuously adjustable via scale on both

	sides
<a href="#">E16-05001-000</a>	DEMMELE® universal stop D16 PROFIEcoLINE large Length: 115mm Width: 12mm Height: 25mm Weight: 0.200kg - Combination bore / oblong hole - Simple execution - With fine scaling
<a href="#">Dpk-Ekit8048c</a>	EVALUATION BOARD, DPP-CT8048 ILCD MODULE, SILICON MANUFACTURER:DEMMELE PRODUCTS, SILICON CORE NUMBER:-, KIT APPLICATION TYPE:DISPLAY, APPLICATION SUB T
<a href="#">Dpp-Ct1060</a>	LCD MODULE, 10.2, 1024 X 600, BACKLIGHTING COLOUR:WHITE, LCD DISPLAY TYPE:GRAPHIC, PIXEL PITCH (H X W) :0.2192MM X 0.0722MM, DISPLAY MODE:TRANSMISSIV
<a href="#">Dpk-Ekit6448c</a>	EVALUATION BOARD, DPP-CT6448 ILCD MODULE, SILICON MANUFACTURER:DEMMELE PRODUCTS, SILICON CORE NUMBER:-, KIT APPLICATION TYPE:DISPLAY, APPLICATION SUB T
<a href="#">Dpk-Ekit1060c</a>	EVALUATION BOARD, DPP-CT1060 ILCD MODULE, SILICON MANUFACTURER:DEMMELE PRODUCTS, SILICON CORE NUMBER:-, KIT APPLICATION TYPE:DISPLAY, APPLICATION SUB T