Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Deprag

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Deprag Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Deprag Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Vibrator	
140S250 140U/MIN Nr 100207703	
67X-2521	306720F ADVANCED LINE Motor with external parts made of stainless steel. The performance data are based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance in oil-free operation of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX-conform EX II 2D Ex h IIIC T80 ° C Db X EX II 2G Ex h IIC T6 Gb X Nominal power 0.09 kW Direction of rotation reversible Idle speed 100 1 / min Max.permissible torque 5.00 Nm Air consumption at nominal load 0.30 m^3 / min Operating pressure 6.0 bar Min. Supply air hose Ø OD / ID - / 6 Min. Exhaust hose Ø OD / ID - / 6 Working temperature range -20 ° C - 110 ° C ATEX working temperature range -20 ° C - 40 ° C Max. Axial force 340 N Max. Radial force (dimension a) 165 N Dimension a 9.0 mm Output spindle-shaped key
337802	
330255 PZD1X4,6X127	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
331002 PHI2X6,1X27	
325567 PHI1X4,6X127	
324686	
803985	
3269521	Spindel .M3
3270042	Idler pinion M0,5Z9DA6x15,5DI1
406228	Motor housing .346-X38-31U
67X-0225	Motor with external parts made of stainless steel. The performance data are based on the specified operating pressure and lubricated supply air. Please take into account a reduction in performance of approx. 10-20% for oil-free operation. ATEX-conform EX II 2D Ex h IIIC T130 ° C Db X EX II 2G Ex h IIC T4 Gb X Nominal power 0.20 kW Direction of rotation reversible Nominal speed 1200 rpm Idle speed 2400 rpm Nominal torque 1.60 Nm Starting torque 2.40 Nm Stall torque 3.00 Nm Air consumption at nominal load 0.37 m^3 / min Operating pressure 6.0 bar Min. Supply air hose Ø OD / ID - / 10 Min. Exhaust hose Ø OD / ID - / 10 Working temperature range -20 ° C - 110 ° C ATEX working temperature range -20 ° C - 40 ° C Max. Axial force 510 N Max. Radial force (dimension a) 1170 N Dimension a 11.0 mm Output spindle-shaped key Please check the following technical changes for the alternative engine: The motor fulfills the ATEX temperature class T4 (previously: T6). The ATEX marking has changed. The performance data (power, speed, torque or Axial / radial forces) of the motor have changed.
007F05	
100686320	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
103181E	
104-230-S1	
1136636/09	
1202767/12	
202-30	
208001A	
300004B	
300735	
306770B	
310519B	
320E27 0042-D	
320E27-0018-D (416500-H)	
320EGA27-0022	
320EGA36-0120	
323036	
3275961	
341357B	
345-308-31	
345-3258U	
346-328 U	
347-310-31U	
347-328U	
347-520-31UL	
347-528-31	
347Z-328U	
370195	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
370197	
382687B	
384210C	
400373D	
400611E	
400611E	
406282B 346-230-31U	
412799B	
442507	
444550H	
6060836A	
6060891A	
6061104A	
6061107A	
6061275B	
6074512	
63-001F01	
63-018F07	
63X-018F03	
67X-0725	
68-P025F-000-9	
716	
803587	
8037563	
805435	
807427	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
820454A	
826357	
830721	
AST11-1	
DEPRAG PV16BN	
E6,3	
GDS 070-190SXI	
GDS 100-190SXI	
GDS009-1000BY	
HAS/040	
HP101-R25B	
HS 043-H19B	
II 2GDC IIC-TG(80 C)X	
KMO-AST1X-2,5M	
M24 104-230-S1	
P0383X-P00-IFR	
PLU 180D-80X	
SH 150- 180BX	
SMP 140-3/4 ZAEX	
SMP 85	
SN 25	
SS 150- 280BX	
SZG 11022/0.75	
TYP 347-328-31 BEST.-NR. 386369 B	
TYP 67-093	
67X-747	306770I ADVANCED LINE

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	Motor with external parts made of stainless steel. The performance data are based on the stated operating pressure and oiled supply air t. Please take into account a reduction in performance for oil-free operation of approx. 10-20%. You can find more information in our product catalogue: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.90 kW Direction of rotation reversible Rated speed 80 rpm Idle speed 160 rpm Rated torque 107.40 Nm Starting torque 161.10 Nm Stalling torque 204.10 Nm Air consumption at nominal load 1.40 m^3/min Operating pressure 6.0 bar Min. supply air hose Ø OD / ID - / 12 Min. exhaust hose Ø OD / ID - / 12 Working temperature range -20 °C - 110 °C ATEX working temperature range -20 °C - 40 °C Max. axial force 1160 N Max. radial force (dimension a) 3790 N Dimension a 20.0 mm Output spindle shape Key Please check the following technical changes for the alternative engine: The ATEX marking has changed. The overall length of the motor changes by +5 mm The spindle diameter changes from 19 mm to 24 mm. The performance data (power, speed, torque or axial/radial forces) of the motor have changed.
1136493/09	
444785A	spare parts kit .67X-0*25 Spare parts set consisting of fins, sealing rings, O-rings and silencers
104-230-S1	Motor M24
306710E ADVANCED LINE Motor	67X-081 Motor with external parts made of stainless steel. The performance data is based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance when

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Ürün	Açıklama
	operating oil-free of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.08 kW Direction of rotation can be reversed Idle speed 240 1/min Max. permissible torque 2.00 Nm Air TV consumption at nominal load 0.23 m^3/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID 6 / 4 Working temperature range -20°C - 110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 200 N Max. radial force (dimension a) 240 N Dimensions: 7.0 mm Output spindle shape round, flattened on one side
306710G ADVANCED LINE Motor	67X-331 Motor with external parts made of stainless steel. The performance data is based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance when operating oil-free of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.08 kW Direction of rotation can be reversed Idle speed 60 1/min Max. permissible torque 2.00 Nm Air TV consumption at nominal load 0.23 m^3/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID 6 / 4 Working temperature range -20°C - 110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 200 N Max. radial force (dimension a) 240 N Dimensions: 7.0 mm Output spindle shape round, flattened on one side
306710I ADVANCED LINE Motor	67X-581 Motor with external parts made of stainless steel. The performance data is based on the specified operating pressure and oiled supply air t.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Please take into account a reduction in performance when operating oil-free of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.08 kW Direction of rotation can be reversed Idle speed 8 1/min Max. permissible torque 2.00 Nm Air TV consumption at nominal load 0.23 m^3/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID 6 / 4 Working temperature range -20°C - 110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 200 N Max. radial force (dimension a) 240 N Dimensions: 7.0 mm Output spindle shape round, flattened on one side
342EGA-0012	Further information can be found in our product catalog: D3480 Hand screwdriver type Bauf orm straight Bauf orm Electric drive type Start type: pressure start Torque range 0.15 Nm - 1.20 Nm Speed range 700 1/min - 1000 1/min Two-stage speed changeover Direction of rotation can be reversed Switch off mechanical clutch Torque switch-off parameter ESD capable yes Output spindle shape hexagon socket ISO1173 - F6.3 Insertion tool external hexagon ISO1173 - E6.3 Sound pressure level 68.0 dB(A) Vibration value in m/s^2 < 2.5
208005D	BASIC LINE engine 63X-018F05 Motor with robust gray cast iron housing. The performance data is based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance when operating oil-free of approx. 10-20%. Reduced maintenance effort thanks to the QuickVChange slat changing system: slats can be changed in just a few minutes without dismantling the motor

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	minutes. Further information can be found in our product catalog: D6200 ATEX compliant EX II 2D Ex h IIIC T130°C Db X EX II 2G Ex h IIC T4 Gb X Rated power 0.60 kW Direction of rotation can be reversed Rated speed 270 1/min Idle speed 540 1/min Rated torque 21.00 Nm Starting torque 31.50 Nm Stalling torque 39.90 Nm Air TV consumption at nominal load 0.90 m^3/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID - / 13 Min. exhaust hose Ø AD / ID - / 13 Working temperature range -20°C - 110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 70 N Max. radial force (dimension a) 360 N Dimensions: 20.0 mm Output spindle form fitting spring
445700A	140S25U Rated power 0.20 kW Direction of rotation can be reversed Rated speed 70 1/min Idle speed 140 1/min Rated torque 27.00 Nm Starting torque 40.00 Nm Stalling torque 50.00 Nm Air TV consumption at nominal load 0.37 m^3/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID - / 10 Working temperature range -20°C - 110°C Output spindle shape customer-specific The performance data is based on the specified operating pressure and oiled supply air.
Liste amanhang	
396982E	GEARING G4M31
406020D	Clutch bearing .346-3/430-31
802358	BEARING NEEDLE 2x11,8 NRB -2/-4

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
406112	VALVE PIN 1,5x57
396030A	K3AF50RH0
802368	BEARING NEEDLE 2x15,8 NRB 0/-5
1272703/16	104-230 S1 2500 U/Min 6.3 bar max
445700A / 140S25U	140S25U rated power 0.20 kW direction of rotation reversible nominal speed 70 rpm idle speed 140 rpm nominal torque 27.00 Nm starting torque 40.00 Nm stalling torque 50.00 Nm Air consumption at nominal load 0.37 m^3/min operating pressure 6.0 bar Min. supply hose Ø AD / ID - / 10 Working temperature range -20 °C - 110 °C Output spindle shape customer-specific The performance data is based on the specified operating pressure and oiled supply air.
408010A	linear tripod LS20 ESD-capable no total height 1,225 mm swivel range 360 degrees Max. permissible torque 20.00 Nm Mounting type table mounting
3227941	compression spring 0.5x7.0x9.5x11
803561	Blade E6.3 TX8x3.1x89 Torx output Output size TX8 Drive E6.3 Blade length 89.00 mm Diameter 3.10 mm
8035631	Blade E6.3 TX10x3.9x89

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Torx output Output size TX10 Drive E6.3 Blade length 89.00 mm Diameter 3.90 mm
208001E BASIC LINE Motor	63X-029F01 For further information, please see our product catalogue: D6200 ATEX compliant EX II 2D Ex h IIIC T130°C Db X EX II 2G Ex h IIC T4 Gb X Rated power 0.20 kW Direction of rotation can be reversed Rated speed 170 rpm Idle speed 340 rpm Nominal torque 11.20 Nm Starting torque 16.80 Nm Stalling torque 21.30 Nm Air consumption at nominal load 0.30 m^3/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID - / 10 Min. exhaust hose Ø AD / ID - / 10 Working temperature range -20 °C - 110 °C ATEX working temperature range -20 °C - 40 °C Max. axial force 70 N Max. radial force (dimension a) 360 N Dimension a 20.0 mm Output spindle shape keyway Motor with robust cast iron housing. The performance data is based on the specified operating pressure and oiled supply air. Please consider a Performance reduction of approx. 10-20%. Reduced maintenance effort through QuickVChange Slat changing system: Slat changing without dismantling the Engine in just a few minutes.
406252	Ring .346-X38-31U
406015	valve housing .346-X38-31
802522	O-ring 22x2 NBR 70/80
140-230-S1	
406020-D	CLUTCH BEARING
Gds009-1000by Schleif-Maschine	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
386360a	
833790	
1236618/14 Luftmotor 344-740-31u	
6060875a	
444570f	
Has/040 Schlauch Antistatisch Mit Verbindungen	
Gds 100-190sxi	
365996	
Hr105-R60v	
Gda 070-190bx	
5933 140s25u	
Dreb 13/15	
383143a	
67-058? Deprag Pneumatic Motor	
3659192	
365997	
339269?	
444500g Motor 67-04251 Advanced Line (P=100 W,N=90 U/Min,T=10,5 Nm)	
310519b Schleifmaschine Gat 812-221bx	
2100716717	
326949/2	
208003b	
3658543	
Baf60090	
Pv 16bn Pneumatische Bohrmaschine	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Klasse Explosionsschutz 1exibii Bt6	
63x-124 F01 208001h	
6061275b Winkelschleifmaschine Ga815-190bx Mit Gewinkeltem Antrieb Ga 815-190bx	
Kmo-Ast30-5m	MOTOR CABLE 5METER FOR AST30
4065661	
Hs 043-H19?	
3660053	
323035	
344859/3	
802511	
6060836? Pneumatische Bohrmaschine	
6074508	
343428	
802092	
385777a	
406282 B 346-230-31u - Deprag Tornavida Motoru	
440015a	
63x-007f07	
386363c	
833780	
388730a	
6078615	
63-001f01 Pneumomotor	
388721a	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
3217253	
802063	
445538e	
3658694	
326947	
Pbo100	
67-093	
414010 B	
802452	
Gd070-153wyi	
388730-A	MOTOR CABLE 5METER FOR AST30
1254724	
802435	
007f05 Luftmotor Leistung 0,6 Kw, Leerlaufdrehzahl 1460 U/Min, Drehmoment 7.8 Nm	
782175 Pneumatic Motor 101-030-2	
Pv16bn Bohrmaschine	
388731a	
353657c	
444550h Motor67-012	
444500g	
802292	
445251a (Oem)	
6060874a	
Pv16bn	
377521uf	DRIVER

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
63x-124 F01 208001h Elektromotor	
6060874a Lubricator 6060874a D = 3/4 "p = 8 Bar	
820454?	
830721 Drill Chuck	
100686320 Luftmotor	
344862/3	
Pv16bn Pneumatic Drill	
63x-001f01	
388720-A	DRIVE 230V
347-428u	
1202767/12 Pneumatikantrieb347-328-7	
342 Ega-019	
347-520-31	
386460 B	
385778a	
6060836?	
B257-50mdw-Sz	
446227b	
347z-238	
833783	
Pv 16bn Pneumatische Bohrmaschine	
P 0383x-P00-Ife	
310519b Winkelschleifmaschine Gat812-221bx	
Deprag Pv16bn Pneumatische Bohrmaschine	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
63-018f07 Luftmotor	
802430	
63x-007f07 Air Motor	
335637	
6061107a Pneumatische Bohrmaschine Dp Eigensichere 220-011 Bxoex 6061107a Deprag (Atex)	
48-381-3fsr - Obsolete, Replacement P0383x-P00-Ifr	
345-308u	
1611-Es / 0,75-1	
Gds 070-190sxi	
Pv16bn Pneumatische Bohrmaschine Mit Schlauch Komplett Mit Verbindungen Zu 30m	
3217265	
1255417	
Ast30-1-230v	DRIVE 230V
6061104?	
444550e	
Pv16bn Pneumatische Bohrmaschine	
Sn 25 Pneumatisches Nadel-Abbruchhammer	
67x-2521	
326950/4	
Pv16bn Pneumatikbohrer Pv16bn	
812915	Blade E6.3 TX20x4.5x70 Drive 6-point E6.3 (1/4") ISO 1173 Output Torx Output size TX20 Blade length 70.00 mm Diameter 4.50 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.