



Det Tronics

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Det Tronics Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Det Tronics Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
GT3000	H2S 50PPM Det-Tronics GT3000
Flexview UD-10	
x3301 ir exproof	+Mounting Feet
U5015-A-2-M-13-A	Explosion-Proof Smoke Detector
028258-001	X3301A4N13T1
007168-2005	Pirecla1B1T2 3/4,4-20W
DETECTOR:GAS;IR,	METHNE,24VDC,SS316 GAS DETECTOR TYPE: GAS ANALYZER OF HYDROCARBON GASES STATIONARY INFRARED MODEL MODEL: PIRECLB1A1SK2 GAS DETECTOR CALIBRATION GAS: METHANE OUTPUT SIGNALS: 4 - 20 MA; HART HYDROPHOBIC FILTER POWER SUPPLY: 24 VDC BODY MATERIAL: STAINLESS STEEL 316 CABLE PORT: 2 X M25*1.5MM ISO IP66/IP67 EX D IIC T4-T5 GB FIXING BOLTS, STAINLESS STEEL ADDITIONAL CERTIFICATE: MIN SIL-1 REQUIRED MODEL - DET-TRONICS
	,IR,24VDC,SS316 DETECTOR:FLAME TYPE: MULTISPECTRUM TRIPLE IR SENSITIVE: VERY HIGH CONE OF VISION: 90

DETECTOR:FLME;TRPL	HORIZONTAL, 75 VERTICAL RESPONSE TIME: 3 SEC FOR HEPTANE&METHANE TRANSMISSION SIGNAL: 4-20 m; FIRE, FAULT & AUX RELAYS MATERIAL BODY: SS316, RED CONNECTION: 4xM25*1.5mm ADDITIONAL CERTIFICATE: SIL CERTIFICATE-MIN SIL-1 REQUIRED MODEL - DET-TRONICS
CGSS1C6V2R1X M20,6LW,CV	COMBUSTIBLE GAS SENSOR 006824-004
CGSS1C6C2R1X	
CGSS1C6V2R1X M20,6LW,CV	006824-004
U7698E	Operating Voltage: 18-30 VDC Nominal Power: 2 W Maximum Power: 4.5 W Output Signal: 4-20 mA Methane Flame Length: 76 cm Field of View: 80° Explosion Protection Ratings: Class I, Division 1, Groups B, C & D Class I, Division 2, Groups A, B, C & D (T4) Class II/III, Division 1, Groups E, F, & G Class II/III, Division 2, Groups F & G (T4) Enclosure: Type 4X CENELEC Certification: EEx d IIC T6 (Tamb = -40°C to +70°C) EEx d IIC T5 (Tamb = -40°C to +75°C) EEx d IIC T4 (Tamb = -55°C to +125°C) Ingress Protection: IP66 Gosstandart Certification: 1 Ex d IIC T6 (Tamb = -40°C to +70°C) 1 Ex d IIC T5 (Tamb = -40°C to +75°C) 1 Ex d IIC T4 (Tamb = -55°C to +125°C)
CTX10A3F2T	CTX10 replacement for 505 transmitter 014394-002
PIRECLA1A1W1 GAS DETECTOR	
X33301a	flame detector
007371-003	EQ3700DW DCIO
Eq2453ne 3/4npt 5p Fm/Csa/Atex	006941-009
028128-001	X3301A4N14W2 FLAME DETECTOR
027752-001	X3301,HEAD, AL, EX D E